

R - Vectors

Vectors are the most basic R data objects and there are six types of atomic vectors. They are logical, integer, double, complex, character and raw.

Vector Creation

Single Element Vector

Even when you write just one value in R, it becomes a vector of length 1 and belongs to one of the above vector types.

```
# Atomic vector of type character.
```

```
print("abc");
```

[Live Demo](#)

```
# Atomic vector of type double.
```

```
print(12.5)
```

```
# Atomic vector of type integer.
```

```
print(63L)
```

```
# Atomic vector of type logical.
```

```
print(TRUE)
```

```
# Atomic vector of type complex.
```

```
print(2+3i)
```

```
# Atomic vector of type raw.
```

```
print(charToRaw('hello'))
```

When we execute the above code, it produces the following result –

```
[1] "abc"
```

```
[1] 12.5
```

```
[1] 63  
[1] TRUE  
[1] 2+3i  
[1] 68 65 6c 6c 6f
```

Multiple Elements Vector

Using colon operator with numeric data

Creating a sequence from 5 to 13.

```
v <- 5:13  
print(v)
```

[Live Demo](#)

Creating a sequence from 6.6 to 12.6.

```
v <- 6.6:12.6  
print(v)
```

If the final element specified does not belong to the sequence then it is dis

```
v <- 3.8:11.4  
print(v)
```

When we execute the above code, it produces the following result –

```
[1] 5 6 7 8 9 10 11 12 13  
[1] 6.6 7.6 8.6 9.6 10.6 11.6 12.6  
[1] 3.8 4.8 5.8 6.8 7.8 8.8 9.8 10.8
```

Using sequence (Seq.) operator

Create vector with elements from 5 to 9 incrementing by 0.4.

```
print(seq(5, 9, by = 0.4))
```

[Live Demo](#)

When we execute the above code, it produces the following result –

```
[1] 5.0 5.4 5.8 6.2 6.6 7.0 7.4 7.8 8.2 8.6 9.0
```

Using the c() function

The non-character values are coerced to character type if one of the elements is a character.

```
# The Logical and numeric values are converted to characters.  
s <- c('apple','red',5,TRUE)  
print(s)
```

[Live Demo](#)

When we execute the above code, it produces the following result –

```
[1] "apple" "red"   "5"     "TRUE"
```

Accessing Vector Elements

Elements of a Vector are accessed using indexing. The **[] brackets** are used for indexing. Indexing starts with position 1. Giving a negative value in the index drops that element from result. **TRUE**, **FALSE** or **0** and **1** can also be used for indexing.

```
# Accessing vector elements using position.  
t <- c("Sun","Mon","Tue","Wed","Thurs","Fri","Sat")  
u <- t[c(2,3,6)]  
print(u)
```

[Live Demo](#)

```
# Accessing vector elements using logical indexing.  
v <- t[c(TRUE,FALSE,FALSE,FALSE,FALSE,TRUE,FALSE)]  
print(v)
```

```
# Accessing vector elements using negative indexing.  
x <- t[c(-2,-5)]  
print(x)
```

```
# Accessing vector elements using 0/1 indexing.
```

```
y <- t[c(0,0,0,0,0,0,1)]  
print(y)
```

When we execute the above code, it produces the following result –

```
[1] "Mon" "Tue" "Fri"  
[1] "Sun" "Fri"  
[1] "Sun" "Tue" "Wed" "Fri" "Sat"  
[1] "Sun"
```

Vector Manipulation

Vector arithmetic

Two vectors of same length can be added, subtracted, multiplied or divided giving the result as a vector output.

```
# Create two vectors.  
v1 <- c(3,8,4,5,0,11)  
v2 <- c(4,11,0,8,1,2)
```

[Live Demo](#)

```
# Vector addition.  
add.result <- v1+v2  
print(add.result)
```

```
# Vector subtraction.  
sub.result <- v1-v2  
print(sub.result)
```

```
# Vector multiplication.  
multi.result <- v1*v2  
print(multi.result)
```

```
# Vector division.  
divi.result <- v1/v2  
print(divi.result)
```

When we execute the above code, it produces the following result –

```
[1] 7 19 4 13 1 13
[1] -1 -3 4 -3 -1 9
[1] 12 88 0 40 0 22
[1] 0.7500000 0.7272727      Inf 0.6250000 0.0000000 5.5000000
```

Vector Element Recycling

If we apply arithmetic operations to two vectors of unequal length, then the elements of the shorter vector are recycled to complete the operations.

```
v1 <- c(3,8,4,5,0,11)
v2 <- c(4,11)
# V2 becomes c(4,11,4,11,4,11)

add.result <- v1+v2
print(add.result)

sub.result <- v1-v2
print(sub.result)
```

[Live Demo](#)

When we execute the above code, it produces the following result –

```
[1] 7 19 8 16 4 22
[1] -1 -3 0 -6 -4 0
```

Vector Element Sorting

Elements in a vector can be sorted using the **sort()** function.

```
v <- c(3,8,4,5,0,11, -9, 304)

# Sort the elements of the vector.
sort.result <- sort(v)
print(sort.result)
```

[Live Demo](#)

```
# Sort the elements in the reverse order.
revsort.result <- sort(v, decreasing = TRUE)
print(revsort.result)

# Sorting character vectors.
v <- c("Red","Blue","yellow","violet")
sort.result <- sort(v)
print(sort.result)

# Sorting character vectors in reverse order.
revsort.result <- sort(v, decreasing = TRUE)
print(revsort.result)
```

When we execute the above code, it produces the following result –

```
[1] -9  0  3  4  5  8 11 304
[1] 304 11  8  5  4  3  0 -9
[1] "Blue" "Red"  "violet" "yellow"
[1] "yellow" "violet" "Red"    "Blue"
```