

R - Factors

Factors are the data objects which are used to categorize the data and store it as levels. They can store both strings and integers. They are useful in the columns which have a limited number of unique values. Like "Male", "Female" and True, False etc. They are useful in data analysis for statistical modeling.

Factors are created using the **factor ()** function by taking a vector as input.

Example

```
# Create a vector as input.
data <- c("East","West","East","North","North","East","West","West","West","East","North")

print(data)
print(is.factor(data))

# Apply the factor function.
factor_data <- factor(data)

print(factor_data)
print(is.factor(factor_data))
```

Live Demo

When we execute the above code, it produces the following result –

```
[1] "East" "West" "East" "North" "North" "East" "West" "West" "West" "East" "North"
[1] FALSE
[1] East West East North North East West West West East North
Levels: East North West
[1] TRUE
```

Factors in Data Frame

On creating any data frame with a column of text data, R treats the text column as categorical data and creates factors on it.

Live Demo

```
# Create the vectors for data frame.
height <- c(132,151,162,139,166,147,122)
weight <- c(48,49,66,53,67,52,40)
gender <- c("male","male","female","female","male","female","male")

# Create the data frame.
input_data <- data.frame(height,weight,gender)
print(input_data)

# Test if the gender column is a factor.
print(is.factor(input_data$gender))

# Print the gender column so see the levels.
print(input_data$gender)
```

When we execute the above code, it produces the following result –

```
height weight gender
1  132    48  male
2  151    49  male
3  162    66 female
4  139    53 female
5  166    67  male
6  147    52 female
7  122    40  male
[1] TRUE
[1] male  male  female female male  female male
Levels: female male
```

Explore our **latest online courses** and learn new skills at your own pace. Enroll and become a certified expert to boost your career.

Changing the Order of Levels

The order of the levels in a factor can be changed by applying the factor function again with new order of the levels.

```
data <- c("East","West","East","North","North","East","West",
         "West","West","East","North")
# Create the factors
factor_data <- factor(data)
print(factor_data)
```

[Live Demo](#)

```
# Apply the factor function with required order of the Level.
new_order_data <- factor(factor_data, levels = c("East", "West", "North"))
print(new_order_data)
```

When we execute the above code, it produces the following result –

```
[1] East West East North North East West West West East North
Levels: East North West
[1] East West East North North East West West West East North
Levels: East West North
```

Generating Factor Levels

We can generate factor levels by using the **gl()** function. It takes two integers as input which indicates how many levels and how many times each level.

Syntax

```
gl(n, k, labels)
```

Following is the description of the parameters used –

- **n** is a integer giving the number of levels.
- **k** is a integer giving the number of replications.
- **labels** is a vector of labels for the resulting factor levels.

Example

```
v <- gl(3, 4, labels = c("Tampa", "Seattle", "Boston"))
print(v)
```

Live Demo

When we execute the above code, it produces the following result –

Tampa Tampa Tampa Tampa Seattle Seattle Seattle Seattle Boston
[10] Boston Boston Boston
Levels: Tampa Seattle Boston