

# R - Operators

An operator is a symbol that tells the compiler to perform specific mathematical or logical manipulations. R language is rich in built-in operators and provides following types of operators.

## Types of Operators

We have the following types of operators in R programming –

- Arithmetic Operators
- Relational Operators
- Logical Operators
- Assignment Operators
- Miscellaneous Operators

## Arithmetic Operators

Following table shows the arithmetic operators supported by R language. The operators act on each element of the vector.

Operator	Description	Example
+	Adds two vectors	<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v+t)</pre> <div>Live Demo</div> <p>it produces the following result –</p> <pre>[1] 10.0 8.5 10.0</pre>
-	Subtracts second vector from the first	<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v-t)</pre> <div>Live Demo</div> <p>it produces the following result –</p> <pre>[1] -6.0 2.5 2.0</pre>

*	Multiplies both vectors	<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v*t)</pre> <div data-bbox="1257 165 1430 232">Live Demo</div> <p>it produces the following result –</p> <pre>[1] 16.0 16.5 24.0</pre>
/	Divide the first vector with the second	<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v/t)</pre> <div data-bbox="1257 584 1430 651">Live Demo</div> <p>When we execute the above code, it produces the following result –</p> <pre>[1] 0.250000 1.833333 1.500000</pre>
%%	Give the remainder of the first vector with the second	<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v%%t)</pre> <div data-bbox="1257 1043 1430 1111">Live Demo</div> <p>it produces the following result –</p> <pre>[1] 2.0 2.5 2.0</pre>
%/%	The result of division of first vector with second (quotient)	<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v%/%t)</pre> <div data-bbox="1257 1460 1430 1527">Live Demo</div> <p>it produces the following result –</p> <pre>[1] 0 1 1</pre>
^	The first vector raised to the exponent of second vector	<pre>v &lt;- c( 2,5.5,6) t &lt;- c(8, 3, 4) print(v^t)</pre> <div data-bbox="1257 1877 1430 1944">Live Demo</div> <p>it produces the following result –</p>

```
[1] 256.000 166.375 1296.000
```

Explore our **latest online courses** and learn new skills at your own pace. Enroll and become a certified expert to boost your career.

## Relational Operators

Following table shows the relational operators supported by R language. Each element of the first vector is compared with the corresponding element of the second vector. The result of comparison is a Boolean value.

Operator	Description	Example
>	Checks if each element of the first vector is greater than the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v&gt;t)</pre> <div>Live Demo</div> <p>it produces the following result –</p> <pre>[1] FALSE TRUE FALSE FALSE</pre>
<	Checks if each element of the first vector is less than the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v &lt; t)</pre> <div>Live Demo</div> <p>it produces the following result –</p> <pre>[1] TRUE FALSE TRUE FALSE</pre>
==	Checks if each element of the first vector is equal to the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v == t)</pre> <div>Live Demo</div> <p>it produces the following result –</p> <pre>[1] FALSE FALSE FALSE TRUE</pre>

<=	Checks if each element of the first vector is less than or equal to the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v&lt;=t)</pre> <a href="#">Live Demo</a> it produces the following result – <pre>[1] TRUE FALSE TRUE TRUE</pre>
>=	Checks if each element of the first vector is greater than or equal to the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v&gt;=t)</pre> <a href="#">Live Demo</a> it produces the following result – <pre>[1] FALSE TRUE FALSE TRUE</pre>
!=	Checks if each element of the first vector is unequal to the corresponding element of the second vector.	<pre>v &lt;- c(2,5.5,6,9) t &lt;- c(8,2.5,14,9) print(v!=t)</pre> <a href="#">Live Demo</a> it produces the following result – <pre>[1] TRUE TRUE TRUE FALSE</pre>

## Logical Operators

Following table shows the logical operators supported by R language. It is applicable only to vectors of type logical, numeric or complex. All numbers greater than 1 are considered as logical value TRUE.

Each element of the first vector is compared with the corresponding element of the second vector. The result of comparison is a Boolean value.

Operator	Description	Example
----------	-------------	---------

&	It is called Element-wise Logical AND operator. It combines each element of the first vector with the corresponding element of the second vector and gives a output TRUE if both the elements are TRUE.	<pre>v &lt;- c(3,1,TRUE,2) t &lt;- c(4,1,FALSE,2) print(v&amp;t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE TRUE FALSE TRUE</pre>
	It is called Element-wise Logical OR operator. It combines each element of the first vector with the corresponding element of the second vector and gives a output TRUE if one the elements is TRUE.	<pre>v &lt;- c(3,0,TRUE,2) t &lt;- c(4,0,FALSE,2) print(v t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE FALSE TRUE TRUE</pre>
!	It is called Logical NOT operator. Takes each element of the vector and gives the opposite logical value.	<pre>v &lt;- c(3,0,TRUE,2) print(!v)</pre> <p>it produces the following result –</p> <pre>[1] FALSE TRUE FALSE FALSE</pre>

The logical operator && and || considers only the first element of the vectors and give a vector of single element as output.

Operator	Description	Example
&&	Called Logical AND operator. Takes first element of both the vectors and gives the TRUE only if both are TRUE.	<pre>v &lt;- c(3,0,TRUE,2) t &lt;- c(1,3,TRUE,2) print(v&amp;&amp; t)</pre> <p>it produces the following result –</p> <pre>[1] TRUE</pre>
	Called Logical OR operator. Takes first element of both the vectors and gives the TRUE if one of them is TRUE.	<pre>v &lt;- c(0,0,TRUE,2) t &lt;- c(0,3,TRUE,2) print(v   t)</pre>

```
print(v||t)
```

it produces the following result –

```
[1] FALSE
```

## Assignment Operators

These operators are used to assign values to vectors.

Operator	Description	Example
<code>&lt;-</code> or <code>=</code> or <code>&lt;&lt;-</code>	Called Left Assignment	<pre>v1 &lt;- c(3,1,TRUE,2+3i) v2 &lt;&lt;- c(3,1,TRUE,2+3i) v3 = c(3,1,TRUE,2+3i) print(v1) print(v2) print(v3)</pre> <div>Live Demo</div> <p>it produces the following result –</p> <pre>[1] 3+0i 1+0i 1+0i 2+3i [1] 3+0i 1+0i 1+0i 2+3i [1] 3+0i 1+0i 1+0i 2+3i</pre>
<code>-&gt;</code> or <code>-&gt;&gt;</code>	Called Right Assignment	<pre>c(3,1,TRUE,2+3i) -&gt; v1 c(3,1,TRUE,2+3i) -&gt;&gt; v2 print(v1) print(v2)</pre> <div>Live Demo</div> <p>it produces the following result –</p> <pre>[1] 3+0i 1+0i 1+0i 2+3i [1] 3+0i 1+0i 1+0i 2+3i</pre>

## Miscellaneous Operators

These operators are used to for specific purpose and not general mathematical or logical computation.

Operator	Description	Example
----------	-------------	---------

:	Colon operator. It creates the series of numbers in sequence for a vector.	<pre>v &lt;- 2:8 print(v)</pre> <div>Live</div> <p>it produces the following result –</p> <pre>[1] 2 3 4 5 6 7 8</pre>
%in%	This operator is used to identify if an element belongs to a vector.	<pre>v1 &lt;- 8 v2 &lt;- 12 t &lt;- 1:10 print(v1 %in% t) print(v2 %in% t)</pre> <div>Live</div> <p>it produces the following result –</p> <pre>[1] TRUE [1] FALSE</pre>
%*%	This operator is used to multiply a matrix with its transpose.	<pre>M = matrix( c(2,6,5,1,10,4), nrow = 2, ncol = 3, byrow = TRUE) t = M %*% t(M) print(t)</pre> <div>Live</div> <p>it produces the following result –</p> <pre>      [,1] [,2] [1,]  65  82 [2,]  82 117</pre>