

WorkItemInterfaceProxy, interface specification

Table of contents

1 Overview.....	2
1.1 Background.....	2
1.2 References.....	2
1.3 Revisions	2
2 General information	3
2.1 Format	3
2.2 Resources.....	3
2.3 Responses.....	3
2.4 Requests.....	4
3 Request descriptions	4
3.1 AddWorkItem	4
3.2 AddWorkItemAutoClose	6
3.3 AddThreadWorkItem	6
3.4 CloseWorkItem	9
3.5 UpdateContactData.....	10
3.6 GetContactData	10
3.7 GetContactId	11
3.8 KeepAlive.....	12
4 Request examples	12
4.1 AddWorkItem	13
4.2 AddThreadWorkItem	14
4.3 CloseWorkItem	17
4.4 UpdateContactData.....	18
4.5 GetContactData	19
4.6 GetContactId	20
4.7 KeepAlive.....	21
5 Error Response object examples	22
5.1 Json	22
5.2 XML	22
6 Error codes	23
7 Test tools	24

1 Overview

The document describes the REST interface for the CallGuide WorkItem interface.

1.1 Background

The Rest interface implements all the workitem commands that exist in the CallGuide Workitem Interface, see Ref [1].

For this Rest interface to work, the CallGuide WorkItem Server needs to be installed, license acquired and the WorkItem interface needs to be enabled, see Ref [1].

1.2 References

Ref [1] CallGuide Interface specification Work Item Interface, PRO-26343

1.3 Revisions

Version	Date	Signature	Comment
4.0	2018-09-12	AnWä	Removed fixed URL's
4.1	2018-12-12	JoHo	Added Basic Auth for authentication.
5.0	2019-05-03	JoHo	Added new production URL.
6.0	2019-12-04	JoHo	Added AddWorkItemAutoClose
6.1	2019-12-12	JoHo	Added Api-version header and description for the error response object.
6.1	2020-01-10	JoHo	Changed the Telia logo
7.0	2020-10-19	AnWä	Option of sending queryparameters removed since API does not support that any longer.
7.1	2020-11-05	JoHo	Fixed ref to error codes in responses.
8.0	2020-11-05	AnWä	Approved

2 General information

2.1 Format

All requests respond with application/json or application/xml format. This is decided by the HTTP header "Accept".

Requests that supplies data in the body must set the HTTP header "Content-Type" to application/json or application/xml.

The requests shall be authenticated with Basic Authentication.

The body data must be UTF-8 encoded.

The header "Api-Version" can be set to "2" or higher to get an error response in json or xml format otherwise all error responses contains plain text.

2.2 Resources

Base URI for all Rest requests is <https://wiproxy.ccs.teliacompany.net/wi-interface-proxy/rest/{system}>

Parameter needed by all requests:

Parameter	Parameter type	Description
system	Path	The id for the CallGuide system.

2.3 Responses

If the request succeeds, http status code 200 is responded.

If the request fails, http status code not equal to 200 is responded and an error message is set in the message body. The error message contains plain text or an error response object. To get the error response object an additional header "Api-Version" must be set to "2" or higher.

ErrorResponse object

Field	Type	Description
service	String	Name of the service
errorType	String	CONNECTION, INTERNAL, EXTERNAL
status	Integer	Http status code
errorCode	String	See Error codes page 23. Ex. wiErrorCode-1.
details	String	Error description
incidentId	String	Tag used in the server log files

If the request fails due to authentication error, http status code 401 is responded.

Temporary errors respond with http status code 502 or 503.

All response objects have a requestId that can be used to trace the request in the CallGuide logs.

When a workitem is created both a contactId and an emailUid will be returned in the response.

Since the contactId is changed when the CallGuide server is restarted it's most safe to use the emailUid for updating or closing the workitem.

2.4 Requests

The Rest requests are named in the same way as the commands used in the CallGuide Workitem Interface, see Ref [1].

Request	Resource (appended to Base URI)	Method	Description
AddWorkItem	workitem	POST	Create a workitem
AddWorkItemAutoClose	workitem/autoclose	POST	Create a workitem and close it automatic
AddThreadWorkItem	workitem/thread	POST	Create a thread workitem
CloseWorkItem	workitem	DELETE	Close a workitem
UpdateContactData	workitem/{contactId} workitem/emailUid/{emailUid}	PUT	Update a contact data key value
GetContactData	workitem/{contactId} workitem/emailUid/{emailUid}	GET	Get the value of a contact data key
GetContactId	workitem/emailUid/{emailUid}	GET	Get the contactId for a workitem
KeepAlive	workitem/ keepalive	GET	Test the connection to CallGuide

3 Request descriptions

See the examples in chapter 4 for more detailed information about the requests.

3.1 AddWorkItem

Description

Creates a workitem in CallGuide.

Note: Parameters that requires CallGuide version 10 should be omitted when using a lower CallGuide version.

Resource

workitem

Method

POST

Http headers

Accept: Application/json or Application/xml
Content-Type: Application/json or Application/xml

Request body properties

Property	Description
from	Identify who create this contact. Update contact data key with name emailHdrFrom.
subject	Show subject for this workitem. Update contact data key with name emailHdrSubject.
entrance	Name of entrance in CallGuide. The given entrance must be defined as a workitem account in CallGuide Admin. Update contact data key with name Entrance.
menuchoice	Could be used for routing of contact. Update contact data key with name menuChoice. Optional if not used.
errand	Define type of errand in CallGuide. Important to group statistics. Update contact data key with name Errand.
workitem	The workitem text. Describe what to do for the agent. Update contact data key with name workItem.
workitemSource	Used to identify type of workitem, e.g. voicemail, facebook or twitter. Optional. CallGuide version 10 required
contentUrl	Link to content, used by workitem source facebook. Optional. CallGuide version 10 required
workitemContent	Data attached to the workitem, e.g. a voicemail. Optional. CallGuide version 10 required
workitemContentEncoding	Encoding of workItemContent. e.g. base64 is used for voicemail. Optional. CallGuide version 10 required
workitemContentType	Content type of workItemContent. e.g. audio/mp3 is used for voicemail. Optional. CallGuide version 10 required
customKeys	Key value map for custom or system contact data keys. Optional if no customKeys are used. Key name is case sensitive and must match the name given in CallGuide.

Response body properties

Property	Description
requestId	Id for this request.
contactId	Identify the new contact in CallGuide
emailUid	Identify the new contact in CallGuide

3.2 AddWorkItemAutoClose

Description

Creates a workitem in CallGuide and closes it automatic.

Note: Parameters that requires CallGuide version 10 should be omitted when using a lower CallGuide version.

Resource

workitem/autoclose

Method

POST

Request and response body properties

Same as for AddWorkItem

3.3 AddThreadWorkItem

Description

Creates a workitem in CallGuide.

Note: CallGuide version 9.1 or higher is required.

Note: Parameters that requires CallGuide version 10 should be omitted when using a lower CallGuide version.

Resource

workitem/thread

Method

POST

Http headers

Accept: Application/json or Application/xml
Content-Type: Application/json or Application/xml

Request body properties

Property	Description
----------	-------------

from	Identify who create this contact. Update contact data key with name emailHdrFrom.
createWhenDelivered	If set to true a new workItem is created if the main workItem of a thread is delivered to an agent. If set to false, the delivered workItem is instead updated. Note: The value is inverted before sending to CallGuide to get the correct behavior in CallGuide.
threadId	Name to identify thread
createKeys	If thread does not exist these keys will be used to create a new work item. See 3.3.1
updateKeys	The values of these keys will overwrite previous set values. Note If thread does not exist these keys will not be used. If the thread exists updateKeys will be applied before appendKeys. Optional. See 3.3.2
appendKeys	The values of these keys will be appended to previous value. Note If thread does not exist these keys will not be used. If the thread exists updateKeys will be applied before appendKeys. Optional. See 3.3.3

3.3.1 createKeys

Keys used when creating a workitem.

Property	Description
subject	Show subject for this workitem. Update contact data key with name emailHdrSubject
entrance	Name of entrance in CallGuide. The given entrance must be defined as a workitem account in CallGuide Admin. Update contact data key with the same name.
menuchoice	Could be used for routing of contact. Update contact data key with the same name.
errand	Define type of errand in CallGuide. Important to group statistics. Update contact data key with the same name.
workitem	The workitem text. Describe what to do for the agent. Update contact data key with the same name.
workitemSource	Used to identify type of workitem, e.g. voicemail, facebook or twitter. CallGuide version 10 required
contentUrl	Link to content, used by workitem source facebook. CallGuide version 10 required
workitemContent	Data attached to the workitem, e.g. a voicemail. CallGuide version 10 required
workitemContentEncoding	Encoding of workItemContent. e.g. base64 is used for voicemail. CallGuide version 10 required
workitemContentType	Content type of workItemContent. e.g. audio/mp3 is used for voicemail. CallGuide version 10 required
customKeys	Key value map for custom or system contact data keys. Optional if no customKeys are used.

	Key name is case sensitive and must match the name given in CallGuide.
--	--

3.3.2 updateKeys

Keys used to overwrite previous value for a workitem.

Property	Description
subject	Show subject for this workitem. Update contact data key with name emailHdrSubject
workitem	The workitem text. Describe what to do for the agent. Update contact data key with the same name.
contentUrl	Link to content, used by workitem source facebook. CallGuide version 10 required
workitemContent	Data attached to the workitem, e.g. a voicemail. CallGuide version 10 required
workitemContentEncoding	Encoding of workItemContent. e.g. base64 is used for voicemail. CallGuide version 10 required
workitemContentType	Content type of workItemContent. e.g. audio/mp3 is used for voicemail. CallGuide version 10 required
customKeys	Key value map for custom or system contact data keys. Optional if no customKeys are used. Key name is case sensitive and must match the name given in CallGuide.

3.3.3 appendKeys

Keys used to append data a previous value for to a workitem.

Property	Description
subject	Show subject for this workitem. Update contact data key with name emailHdrSubject
workitem	The workitem text. Describe what to do for the agent. Update contact data key with the same name.
contentUrl	Link to content, used by workitem source facebook. CallGuide version 10 required
workitemContent	Data attached to the workitem, e.g. a voicemail. CallGuide version 10 required
workitemContentEncoding	Encoding of workItemContent. e.g. base64 is used for voicemail. CallGuide version 10 required
workitemContentType	Content type of workItemContent. e.g. audio/mp3 is used for voicemail. CallGuide version 10 required
customKeys	Key value map for custom or system contact data keys. Optional if no customKeys are used.

	Key name is case sensitive and must match the name given in CallGuide.
--	--

Response body properties

Property	Description
requestId	Id for this request.
contactId	Identify the new contact in CallGuide
emailUid	Identify the new contact in CallGuide

3.4 CloseWorkItem**Description**

Closes a workitem by contactId or emailUid.

The workitem must be in state 'created' or 'queue' to be closed.

Resource

workitem/{contactId}

or

workitem/emailUid/{emailUid}

Method

DELETE

Http headers

Accept: Application/json or Application/xml

Parameters

Parameter	Parameter type	Description
contactId	Path	The contactId for the workitem to close
emailUid	Path	The emailUid for the workitem to close

No request body properties**Response body properties**

Property	Description
requestId	Id for this request.
contactId	Set if closed by contactId
emailUid	Set if closed by emailUid

3.5 UpdateContactData

Description

Updates contact data key values for a workitem by contactId or emailUid.

Resource

workitem/{contactId}

or

workitem/emailUid/{emailUid}

Method

PUT

Http headers

Accept: Application/json or Application/xml

Content-Type: Application/json or Application/xml

Parameters

Parameter	Parameter type	Description
contactId	Path	The contactId for the workitem to update
emailUid	Path	The emailUid for the workitem to update

Request body properties

Property	Description
customKeys	Key value map for custom or system contact data keys. Key name is case sensitive and must match the name given in CallGuide.

Response body properties

Property	Description
requestId	Id for this request.
contactId	Set if updated by contactId
emailUid	Set if updated by emailUid

3.6 GetContactData

Description

Gets the value for a contact data key by contactId or emailUid.

Resource

workitem/{contactId}?contactDataKey={contactDataKey}

or

workitem/emailUid/{emailUid}?contactDataKey={contactDataKey}

Method

GET

Http headers

Accept: Application/json or Application/xml

Parameters

Parameter	Parameter type	Description
contactId	Path	The contactId for the workitem to get contact data from
emailUid	Path	The emailUid for the workitem to get contact data from
contactDataKey	Query	The name of the contact data key. The key name is case sensitive and must match the name of the contact data key given in CallGuide.

No request body properties**Response body properties**

Property	Description
requestId	Id for this request.
contactId	Set if get by contactId
emailUid	Set if get by emailUid
contactDataKey	The name of the contact data key.
contactDataValue	The value of the contact data key.

3.7 GetContactId**Description**

Gets the contactId for a given emailUid.

Resource

workitem/emailUid/{emailUid}/contactId

Method

GET

Http headers

Accept: Application/json or Application/xml

Parameters

Parameter	Parameter type	Description
emailUid	Path	The emailUid for the workitem

No request body properties**Response body properties**

Property	Description
requestId	Id for this request.
contactId	The contactId for the workitem
emailUid	The emailUid

3.8 KeepAlive**Description**

Tests the CallGuide server connection.

The request is not needed to keep any session alive as the name might imply.

Resource

workitem/keepalive

Method

GET

Http headers

Accept: Application/json or Application/xml

Parameters

No parameters

No request body properties**Response body properties**

Property	Description
requestId	Id for this request.

4 Request examples

In the example [URL:s](#) the path parameter "{system}" should be replaced to the actual CallGuide system key.

The request shall have the Basic Auth header set to a system specific username and password.

The hostname should be replaced with "wiproxy.ccs.teliacompany.net".

Example:

The example header below has a base64 encoded username (testuser) and password (pwd123).

Header: Authorization: Basic dGVzdHVzZXI6cHdkMTIz

<https://hostname/wi-interface-proxy/rest/Test/workitem/keepalive>

4.1 AddWorkItem

4.1.1 URL

Create a workitem.

<https://hostname/wi-interface-proxy/rest/{system}/workitem>

Http method POST

4.1.2 Json

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/json

Content-Type: Application/json

Request body

```
{
  "from" : "callguide@teliasonera.com",
  "subject" : "Test ärende",
  "entrance" : "Privat",
  "menuchoice" : "menuchoice",
  "errand" : "ärende",
  "workitem": "http://teliasonera.se",
  "customKeys" : {
    "custKey1" : "ett",
    "custKey2" : "två"
  },
  "workitemSource" : "voicemail",
  "contentUrl" : "http://host/test.com",
  "workitemContent" : "data",
  "workitemContentEncoding" : "base64",
  "workitemContentType" : "audio/mp3"
}
```

Reponse body

```
{
  "requestId": "12",
  "contactId": "42",
  "emailUid": "42.CallGuideWorkItem@computer"
}
```

}

4.1.3 XML

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml

Content-Type: Application/xml

Request body

```
<AddWorkItemRequest>
  <from>callguide@teliasonera.com</from>
  <subject>Test ärende</subject>
  <entrance>Privat</entrance>
  <menuchoice>menuchoice</menuchoice>
  <errand>Ärende</errand>
  <workitem>http://teliasonera.se/workitem>

  <workitemSource>voicemail</workitemSource>
  <contentUrl>http://host/test.com</contentUrl>
  <workitemContent>data</workitemContent>
  <workitemContentEncoding>base64</workitemContentEncoding>
  <workitemContentType>audio/mp3</workitemContentType>

  <customKeys>
    <entry>
      <key>custKey1</key>
      <value>ett</value>
    </entry>
    <entry>
      <key>custKey2</key>
      <value>två</value>
    </entry>
  </customKeys>
</AddWorkItemRequest>
```

Response body

```
<AddWorkItemResponse>
  <requestId>14</requestId>
  <contactId>42</contactId>
  <emailUid>42.CallGuideWorkItem@computer</emailUid>
</AddWorkItemResponse>
```

4.2 AddThreadWorkItem

4.2.1 URL

Create a workitem.

<https://hostname/wi-interface-proxy/rest/{system}/workitem/thread>

Http method POST

4.2.2 Json

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/json

Content-Type: Application/json

Request body

```
{
  "from": "Test",
  "createWhenDelivered": true,
  "threadId": "threadId",
  "createKeys": {
    "subject": "subject",
    "workitem": "workitem",
    "contentUrl": "http://host/test.com",
    "workitemContent": "data",
    "workitemContentEncoding": "base64",
    "workitemContentType": "audio/mp3",
    "customKeys": {
      "custKey1": "ett",
      "value": "två"
    },
    "entrance": "entrance",
    "menuchoice": "menuchoice",
    "workitemSource": "voicemail",
    "errand": "123"
  },
  "updateKeys": {
    "subject": "subject",
    "workitem": "workitem",
    "contentUrl": "http://host/test.com",
    "workitemContent": "data",
    "workitemContentEncoding": "base64",
    "workitemContentType": "audio/mp3",
    "customKeys": {
      "custKey1": "ett",
      "value": "två"
    }
  },
  "appendKeys": {
    "subject": "subject",
    "workitem": "workitem",
    "contentUrl": "http://host/test.com",
    "workitemContent": "data",
    "workitemContentEncoding": "base64",
    "workitemContentType": "audio/mp3",
    "customKeys": {
      "custKey1": "ett",
      "value": "två"
    }
  }
}
```

Creator
Jonas Holmgren**Relation**
CC 5564300142/02

```
}  
}
```

Reponse body

```
{  
  "requestId": "12",  
  "contactId": "42",  
  "emailUid": "42.CallGuideWorkItem@computer"  
}
```

4.2.3 XML

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml

Content-Type: Application/xml

Request body

```
<AddThreadWorkItemRequest>  
  <from>Test</from>  
  <createWhenDelivered>true</createWhenDelivered>  
  <threadId>threadId</threadId>  
  <createKeys>  
    <subject>subject</subject>  
    <workitem>workitem</workitem>  
    <contentUrl>http://host/test.com</contentUrl>  
    <workitemContent>data</workitemContent>  
    <workitemContentEncoding>base64</workitemContentEncoding>  
    <workitemContentType>audio/mp3</workitemContentType>  
    <customKeys>  
      <entry>  
        <key>custKey1</key>  
        <value>ett</value>  
      </entry>  
      <entry>  
        <key>custKey2</key>  
        <value>två</value>  
      </entry>  
    </customKeys>  
    <entrance>entrance</entrance>  
    <menuchoice>menuchoice</menuchoice>  
    <workitemSource>voicemail</workitemSource>  
    <errand>123</errand>  
  </createKeys>  
  <updateKeys>  
    <subject>subject</subject>  
    <workitem>workitem</workitem>  
    <contentUrl>http://host/test.com</contentUrl>  
    <workitemContent>data</workitemContent>  
    <workitemContentEncoding>base64</workitemContentEncoding>  
    <workitemContentType>audio/mp3</workitemContentType>
```

```
<customKeys>
  <entry>
    <key>custKey1</key>
    <value>ett</value>
  </entry>
  <entry>
    <key>custKey2</key>
    <value>två</value>
  </entry>
</customKeys>
</updateKeys>
<appendKeys>
  <subject>subject</subject>
  <workitem>workitem</workitem>
  <contentUrl>http://host/test.com</contentUrl>
  <workitemContent>data</workitemContent>
  <workitemContentEncoding>base64</workitemContentEncoding>
  <workitemContentType>audio/mp3</workitemContentType>
  <customKeys>
    <entry>
      <key>custKey1</key>
      <value>ett</value>
    </entry>
    <entry>
      <key>custKey2</key>
      <value>två</value>
    </entry>
  </customKeys>
</appendKeys>
</AddThreadWorkItemRequest>
```

Response body

```
<AddWorkItemResponse>
  <requestId>14</requestId>
  <contactId>42</contactId>
  <emailUid>42.CallGuideWorkItem@computer</emailUid>
</AddWorkItemResponse>
```

4.3 CloseWorkItem

4.3.1 URL:s

Close the workitem identified by contactId 1.

<https://hostname/wi-interface-proxy/rest/{system}/workitem/1>

Close the workitem identified by emailUid "42.CallGuideWorkItem@computer".

<https://hostname/wi-interface-proxy/rest/{system}/workitem/emailUid/42.CallGuideWorkItem@computer>

Creator
Jonas Holmgren**Relation**
CC 5564300142/02

Http method DELETE

4.3.2 Json

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/json

No request body**Response body**

```
{  
  "requestId": "5",  
  "contactId": null,  
  "emailUid": "42.CallGuideWorkItem@computer"  
}
```

4.3.3 XML

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml

No request body**Response body**

```
<CloseWorkItemResponse>  
  <requestId>16</requestId>  
  <emailUid>42.CallGuideWorkItem@computer</emailUid>  
</CloseWorkItemResponse>
```

4.4 UpdateContactData

4.4.1 URL:s

Update contact data for the workitem identified by contactId 1.

<https://hostname/wi-interface-proxy/rest/{system}/workitem/1>Update contact data for the workitem identified by emailUid
"42.CallGuideWorkItem@computer".[https://hostname/wi-interface-proxy/rest/{system}/workitem/emailUid/
42.CallGuideWorkItem@computer](https://hostname/wi-interface-proxy/rest/{system}/workitem/emailUid/42.CallGuideWorkItem@computer)

Http method PUT

4.4.2 Json

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Creator
Jonas Holmgren**Relation**
CC 5564300142/02

Accept: Application/json
Content-Type: Application/json

Request body

```
{
  "customKeys" : {
    "custKey1" : "ett",
    "custKey2" : "två"
  }
}
```

Response body

```
{
  "requestId": "18",
  "contactId": null,
  "emailUid": "42.CallGuideWorkItem@computer"
}
```

4.4.3 XML**Http headers**

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml
Content-Type: Application/xml

Request body

```
<UpdateContactDataRequest>
  <customKeys>
    <entry>
      <key>custKey1</key>
      <value>ett</value>
    </entry>
    <entry>
      <key>custKey2</key>
      <value>två</value>
    </entry>
  </customKeys>
</UpdateContactDataRequest>
```

Response body

```
<UpdateContactDataResponse>
  <requestId>27</requestId>
  <emailUid>42.CallGuideWorkItem@computer</emailUid>
</UpdateContactDataResponse>
```

4.5 GetContactData**4.5.1 URL:s**

Get the contact data key value (in this example contact data key "workItem") for a workitem identified by contactId 1.

https://hostname/wi-interface-proxy/rest/{system}/workitem/1?contactDataKey=workItem

Get the contact data key value for a workitem identified by emailUid
"42.CallGuideWorkItem@computer".

https://hostname/wi-interface-
proxy/rest/{system}/workitem/emailUid/42.CallGuideWorkItem@computer?contactDataKey=workItem

Http method GET

4.5.2 Json

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/json

No request body

Response body

```
{  
  "requestId": "25",  
  "contactId": null,  
  "emailUid": "42.CallGuideWorkItem@computer",  
  "contactDataKey": "workItem",  
  "contactDataValue": "4242 <>&"  
}
```

4.5.3 XML

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml

No request body

Response body

```
<GetContactDataResponse>  
  <requestId>29</requestId>  
  <contactDataKey>workItem</contactDataKey>  
  <contactDataValue>4242 &lt;&gt;&amp;</contactDataValue>  
  <contactId>12345</contactId>  
</GetContactDataResponse>
```

4.6 GetContactId

4.6.1 URL

Get the contactId for a workitem identified by emailUid "42.CallGuideWorkItem@computer".

https://hostname/wi-interface-
proxy/rest/{system}/workitem/emailUid/42.CallGuideWorkItem@computer/contactId

Http method GET

Creator
Jonas Holmgren**Relation**
CC 5564300142/02

4.6.2 Json

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/json

No request body**Response body**

```
{  
  "requestId": "13",  
  "contactId": "42",  
  "emailUid": "42.CallGuideWorkItem@computer"  
}
```

4.6.3 XML

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml

No request body**Response body**

```
<GetContactIdResponse>  
  <requestId>31</requestId>  
  <contactId>42</contactId>  
  <emailUid>42.CallGuideWorkItem@computer</emailUid>  
</GetContactIdResponse>
```

4.7 KeepAlive

4.7.1 URL

<https://hostname/wi-interface-proxy/rest/{system}/workitem/keepalive>

Http method GET

4.7.2 Json

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/json

No request body**Response body**

```
{  
  "requestId": "32"  
}
```

4.7.3 XML

Http headers

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml

No request body

Response body

```
<KeepAliveResponse>  
  <requestId>32</requestId>  
</KeepAliveResponse>
```

5 Error Response object examples

5.1 Json

Http headers for request

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/json

Api-version : 2

The application must check of the “Content-type” for the response to see if the message body contains an error response object (application/json) or plain text.

```
{  
  "service": "wi-proxy",  
  "errorType": "EXTERNAL",  
  "status": 400,  
  "errorCode": "wiErrorCode-1",  
  "details": "Mandatory field missing",  
  "incidentId": "wi-proxy-191212-272424186"  
}
```

5.2 XML

Http headers for request

Authorization: Basic dGVzdHVzZXI6cHdkMTIz

Accept: Application/xml

Api-version : 2

The application must check of the “Content-type” for the response to see if the message body contains an error response object (application/xml) or plain text.

```
<errorResponseData>  
  <details>Mandatory field missing</details>  
  <errorCode>wiErrorCode-1</errorCode>  
  <errorType>EXTERNAL</errorType>  
  <incidentId>wi-proxy-191212-365549706</incidentId>  
  <service>wi-proxy</service>
```

```
<status>400</status>
</errorResponseData>
```

6 Error codes

The error response object field `errorCode` is set to additional information about the reason of the error. ErrorCodes starting with “wiErrorCode” are generated by the ACE server.

errorCode	Description
wiErrorCode-1	A mandatory field is missing or is empty. Field name is given in <code>errorText</code> .
wiErrorCode-2	Field value is of wrong data type. Field is given in <code>errorText</code> .
wiErrorCode-3	Unknown command. Check for incorrect spelling.
wiErrorCode-4	Connection has timed out because no valid command have been received by the server in a period of time.
wiErrorCode-5	ACE Main Server could not be contacted by Work Item Server.
wiErrorCode-6	Unknown Entrance key. The value in field “Entrance” has to match with what is defined in Telia ACE.
wiErrorCode-7	Field (name or value) length error. Max length is 512 characters for all field except <code>workItemContent</code> which has a max length of 1 MB.
wiErrorCode-8	Max size. Too much data have been received by the server without a valid command found in the request. Connection will close.
wiErrorCode-9	Contact with that <code>contactId</code> or <code>emailUid</code> doesn’t exist in ACE Main Server.
wiErrorCode-10	No value was returned for the specified contact and contact data key.
wiErrorCode-11	Update of contact data failed.
wiErrorCode-12	Contact is routed to an agent or placed in a agents personal queue, operation failed
wiErrorCode-99	An unknown error has occurred.
<code>communicationError</code>	Error connecting to ACE workitem server
<code>operationTimeout</code>	Timeout waiting for an operation to complete
<code>internalError</code>	An internal error has occurred

7 Test tools

To explore the REST interface a test tool for REST can be used to execute the requests manually.

For simple GET requests without any body parameters a web browser can be used. But to execute more complex requests you need a tool.

Links to some useful tools:

<https://addons.mozilla.org/sv-se/firefox/addon/restclient/>

<http://www.soapui.org/>