



Maritime &
Coastguard
Agency

Guidance

Annex 3 - Class IX(A) requirements for Life Saving Appliances, and Fire Fighting Equipment

Published 24 November 2023

Contents

1. Life Saving Appliances (LSA)
2. Fire Fighting Equipment for Class IX(A) vessels of up to 500 GT



© Crown copyright 2023

This publication is licensed under the terms of the Open Government Licence v3.0 except where otherwise stated. To view this licence, visit nationalarchives.gov.uk/doc/open-government-licence/version/3 or write to the Information Policy Team, The National Archives, Kew, London TW9 4DU, or email: psi@nationalarchives.gov.uk.

Where we have identified any third party copyright information you will need to obtain permission from the copyright holders concerned.

This publication is available at <https://www.gov.uk/government/publications/mgn-469-m-amendment-1-safety-standards-for-non-passenger-vessels/annex-3-class-ixa-requirements-for-life-saving-appliances-and-fire-fighting-equipment>

1. Life Saving Appliances (LSA)

Vessels constructed before 1 July 1986

Equipment	Category ABC			Category D	
	<12.2m	12.2m to 21.3m	21.3m and over	<12.2m	12.2m to 21.3m
Liferaft or boat	-	-	-	-	1
Lifebuoy	Persons on board/2 ¹	Persons on board/2 ^{1&2} (min 2)	Persons on board/2 ³ (min 4)	-	2
Life jacket	-	1 per persons on board	1 per persons on board	-	1 per persons on board

Vessels constructed on or after 1 July 1986 and before 1 July 1998

Equipment	Category ABC			Category D	
	< 12m	12m to 20m	> 20m	< 12m	12m to 20m

Equipment	Category ABC				Category D
Liferaft	-	-	-	-	1 ⁵
Lifebuoy	Persons on board/2 ^{1&2} (min 2)	Persons on board/2 ² (min 2)	Persons on board/2 ³ (min 4)	Persons on board/2 ² (min 2)	2 ²
Life jacket 32kg +	-	1 per persons of board	1 per persons of board	-	1 per persons c board
Life jacket <32kg	-	1 per persons of board	1 per persons of board	-	1 per persons c board
Rocket flares	-	-	-	6	6

Vessels constructed on or after 1 July 1998

Equipment	Category ABC				Category D
	< 12m	12m to 20m	> 20m	< 12m	12m to 20m
Liferaft	-	-	-	-	1 ⁵
Lifebuoy	Persons on board/2 ^{1&2} (min 2)	Persons on board/2 ² (min 2)	Persons on board/2 ³ (min 4)	Persons on board/2 ² (min 2)	2 ²
Life jacket 32kg +	-	1 per persons on board	1 per persons on board	-	1 per persons c board

Equipment		Category ABC			Category D
Life jacket <32kg	-	1 per persons on board	1 per persons on board	-	1 per persons on board
Rocket flares	-	-	-	6	6

Note: In addition to the above, every tug and tender shall carry buoyant apparatus sufficient to support the total of persons on board.

¹ Unless non-SOLAS type used then one per persons on board member.

² One with buoyant line (18m) and one with smoke signal and light (on tankers light to be battery type).

³ Two with buoyant line (18m) and two with smoke signal and light (on tankers light to be battery type), one of each on each side.

⁴ With light.

⁵ With associated lighting, posters and training manual.

2. Fire Fighting Equipment for Class IX(A) vessels of up to 500 GT

Equipment	<150 GT	<150 GT	150 GT to <500 GT
	< 21.34m	≥ 21.34 m	-
Fire Pump (power)	-	Yes ¹	Yes
Fire Main – to provide a jet of water	-	Yes	Yes

Equipment	<150 GT	<150 GT	150 GT to <500 GT
Fire pump – outside engine room	Yes ²	Yes ³	Yes ³
Hoses and nozzles	Yes ⁴	3	3
Portable fire extinguisher – accommodation & service spaces	2 ⁵	3 ⁵	3
Fireman's outfit and BA	-	-	Yes ⁶
Fireman's axe	-	Yes	See note ⁶
Boiler room (& room with oil fuel installation):			
Fixed system	See note ⁷	See note ⁷	Yes
Portable fire extinguisher	-	-	2 ⁸
Sand box	-	-	1 ⁹
Engine room:			
Portable fire extinguisher (suitable for oil fires)	1 (< 6 m) or 2 (≥ 6m)	2	1 per 74.6 kW ¹⁰ or 2 plus a 45 litre foam (or 16kg CO ₂)

¹ Power may be off main engine.

² May be power or hand operated.

³ Can be manually operated.

⁴ Able to produce a jet 6m of water which can be directed at any part of the ship, with a 10mm and spray nozzle. Although in any ship <9m and any open ship less <21.34m this requirement may be substituted with two fire buckets, one of which must have a lanyard. These fire buckets need not be additional to those mentioned in note 5

⁵ May be substituted with buckets, one of which must have a lanyard.

-

⁶ As per reg. 37 of SI 1998/1011, i.e. including fire axe, torch etc.

⁷ For wooden boats see regs. 20 (5) and 21 (2) of SI 1998/1011.

⁸ Two in each space containing any part of any oil fuel instillation.

⁹ Alternatively, an additional portable extinguisher suitable for oil fires.

¹⁰ Up to a maximum of seven.



OGI

All content is available under the [Open Government Licence v3.0](#), except where otherwise stated



© Crown copyright