Bill of Materials

Sunflare Solar Team

Drachten, The Netherlands

Project: 001-H-01 CAN to Bluetooth.PrjPCB

Revision: 1.00 Date: 11/4/2020

Designator C1, C4, C7, C8, C13, C14, C15, C16, C17, C18, C20, C21, C24	Comment 100nF	Description Capacitor	Dielectric X7R	VoltageRating Tolerance 100V	Footprint CAP0805	Manufacturer -	Manufacturer Part Nc Farnell Orderc Price			Quantity	Total price
							-	-	0.00	13	0
C2	4.7uF	Capacitor Pol	ELCO	63V	CAPPOL5MM	WURTH ELEKTRONIK		2837323	0.33	1	0.33
C3, C5, C6, C9, C19	10uF	Capacitor	X7R, X5R	16V	CAP1210	TDK, Multicomp	C3225X7R1C106K2	200/ 2112722, 17	594 1.35, 0.50	5	#VALUE!
C11, C12	33pF	Capacitor	C0G	100V	CAP0805	-	-	-	0.00	2	0
C22, C23	47pF	Capacitor	C0G	50V	CAP0805	-	-	-	0.00	2	
D1	SMA2	Diode			DIODEDO-214AC	Multicomp	S2MA	2675071	0.13	1	0.13
D2	HTA5U100	Diode Schottky			DIODEDO-214AC	Multicomp	HTA5U100	2750942	0.46	1	0.46
D3, D6	Green	Led			LEDTHT	Multicomp	MCL034GT	1581123	0.08	2	0.16
D4	PESD1CAN	ESD Protection Device, TVS, 70 V, SOT-23, 3 Pins	3		SOT23-3N	NXP	PESD1CAN	1510703	0.13	1	0.13
D5	RED	Led			LEDTHT	Multicomp	MCL034PT	1581121	0.06	1	0.06
F1	250mA PTC	Fuse			Fuse 1206	EATON BUSSMANN S	PTS120660V010	2929345	0.26	1	0.26
H1	Hardware	Generaric hardware				IMO PRECISION CON	121.950M/2-E	2575233	0.37	1	0.37
H2	001-H-01	PCB				-	-	-	2.00	1	2
H3	001-H-02	Casing bottom				-	-	-	2.50	1	2.5
H4	001-H-03	Casing top				-	-	-	2.50	1	2.5
L1	220uH	Inductor			INDWE-PD	WE	744777222	2761710	0.971	1	0.971
L3	51uH	Choke common mode			IND200P450X300-4N	Bourns	SRF4532-510Y	2859108	0.47	1	0.47
P2	Header 2 way	Header 2 way			21.95MH/2-E	IMO PRECISION CON	21.95MH/2-E	2517885	0.15	1	0.15
P3, P4	Header 1X8 G	Connector 1X8 with Ground			TECO-1-406541-5	-	-	-	0.00	2	0
R1	100K	Resistor		1%	RES0603	-	-	-	0.00	1	0
R2	39K	Resistor		1%	RES0603	-	-	-	0.00	1	0
R3	1M0	Resistor		1%	RES0603	-	-	-	0.00	1	0
R4. R17	10K	Resistor		1%	RES0603	-	-	-	0.00	2	0
R5, R6, R8, R9, R13, R14, R18, R19, R20, R21, R22	470R	Resistor		1%	RES0603	-	-	-	0.00	11	0
R7. R11	15K	Resistor		1%	RES0603	-	-		0.00	2	0
R10. R16	330R	Resistor		1%	RES0603			-	0.00	2	
R15	2K	Resistor		1%	RES0603	-	-	-	0.00	1	0
S1	Switch	Tactile Switch		170		TE CONNECTIVITY	FSMRA4JH	1555988	0.15	1	0.15
S2	Switch	Tactile Switch			JS202011AQN	C&K COMPONENTS		2435145	0.31	1	0.31
U1	MAX5035B	5V 1A, 76V, High-Efficiency MAXPower Step- Down DC-DC Converter	:		SOIC-8N	Maxim Integrated Prod		2799102	3.26	1	3.26
U2	NCP1117DT33G	Fixed LDO Voltage Regulator, 20V in, 1.07V Dropout, 3.3V/1A out, DPAK-3			DPAK-3	ON SEMICONDUCTO	NCP1117DT33G	1652364	0.37	1	0.37
U3	DSPIC33EP128GS804	16-Bit Digital Signal Controllers fo r Digital Power Applications with Interconnected High Speed PWM, ADC, PGA and Comparators	1-		TQFP80P1200X1200X	(1 Microchip	DSPIC33EP128GS	804 2706170	4.44		4.44
114	MCP2562	CAN Bus. Transceiver, CAN, LIN, 1, 1, 4,5 V.			SOIC-8N	Microchip	MCP2562-E/SN	2362839	0.79	1	0.79
		5.5 V, SOIC				'				· · · · · · · · · · · · · · · · · · ·	
_U5	HC-05	Bluetooth Module			HC-05	N/A	HC-05	N/A	4.00	1	4
Y1	16MHz	Crystal			XT49M-2016M	Multicomp	MCRSD16000F183	NNN 2305058	0.19	1	0.19

Altium Limited Confidential Page 1