

Nurix Campaign Manager — CRM Lead Ingestion API

Ingest leads into a specific Campaign in Nurix Campaign Manager with a single HTTPS call.

Base URL

US Region: `https://campaign-manager-us.nurixlabs.tech`

Endpoint: `POST /crm-webhook`

This guide uses the US base URL. If your account is provisioned in a different region, use the region-specific base URL provided by your Nurix contact.

Authentication

Use an **API key** in the `Authorization` header.

Authorization: YOUR_API_KEY

Keep your key secret. Rotate it immediately if exposed.

Required Headers

Header	Type	Required	Example	Notes
<code>Authorization</code>	string	✓	<code>2654dcf8-****-****-****-9c9dc99233f6</code>	Your API key.
<code>X-Campaign-Id</code>	string	✓	<code>15</code>	Should match the <code>campaign_id</code> in the body.
<code>Content-Type</code>	string	✓	<code>application/json</code>	Only JSON is accepted.

HTTP Method

POST /crm-webhook

Request Body (JSON)

Top-level fields:

Field	Type	Required	Description
<code>campaign_id</code>	string	✓	The target Campaign ID in Nurix Campaign Manager. Must match <code>X-Campaign-Id</code> header.
<code>leads</code>	array of Lead	✓	One or more lead objects (see below).

Lead object

Field	Type	Required	Example	Notes
<code>country_code</code>	string	✓	+1	E.164 country calling code.
<code>phone_number</code>	string	✓	750354XXXX or +1750354XX XX	Accepts local number (with <code>country_code</code>) or full E.164. Non-digits/spaces are ignored.
<code>time_zone</code>	string	✓	America/Chicago	IANA time zone (e.g., America/Los_Angeles, Asia/Kolkata).
<code>custom_dynamic_variables_config</code>	object	✓	See below	Arbitrary key/value pairs used in your campaign templates and routing.

custom_dynamic_variables_config

Common keys you may send (your workspace may support additional keys):

Key	Type	Example
candidate_id	string	a8dsy7f98
first_name	string	John
last_name	string	Smith
req_id	string	asd8f0sdas98d

Tip: Unknown keys are accepted and can be referenced in message templates if configured in your campaign.

Example: cURL

```
curl --location 'https://campaign-manager-us.nurixlabs.tech/crm-webhook' \
--header 'Authorization: YOUR_API_KEY' \
--header 'X-Campaign-Id: CAMPAIGN_ID' \
--header 'Content-Type: application/json' \
--data-raw '{
  "campaign_id": "CAMPAIGN_ID",
  "leads": [
    {
      "country_code": "+1",
      "phone_number": "750354XXXX",
      "time_zone": "America/Chicago",
      "custom_dynamic_variables_config": {
        "candidate_id": "a8dsy7f98",
        "first_name": "John",
        "last_name": "Smith",
        "req_id": "asd8f0sdas98d"
      }
    }
  ]
}'
```

Validation Rules & Recommendations

- **Campaign matching:** `X-Campaign-Id` must equal body `campaign_id`.
- **Phone numbers:**
 - Send either local number **with** `country_code` (e.g., `+1 + 750354XXXX`) **or** full E.164 (e.g., `+1750354XXXX`).
 - Avoid extensions; do not include letters. Spaces and dashes are tolerated but stripped.
- **Time zone:** Must be a valid **IANA** time zone (e.g., `America/New_York`, `Europe/London`).
- **Email:** If provided, must be syntactically valid.
- **Sizes:** We recommend batching up to **100 leads** per request for best performance. (Contact Nurix Support to increase limits.)

Unless otherwise configured, the API responds with `200 OK` and a receipt summarizing processing results.

Common HTTP status codes

Status	Meaning	Example causes
<code>200</code>	OK	Request accepted; see body for per-lead outcomes.
<code>400</code>	Bad Request	Missing fields, invalid time zone, malformed JSON, campaign/header mismatch.
<code>401</code>	Unauthorized	Missing/invalid API key.
<code>403</code>	Forbidden	API key lacks access to the specified campaign.
<code>404</code>	Not Found	Campaign does not exist or is disabled.
<code>415</code>	Unsupported Media Type	<code>Content-Type</code> not <code>application/json</code> .

Status	Meaning	Example causes
429	Too Many Requests	Rate limit exceeded.
5xx	Server Error	Temporary server-side problem. Retry with backoff.

Idempotency & Retries

Duplicates are not detected downstream.

When retrying 5xx or network errors, use **exponential backoff**.

Security Best Practices

- Always use **HTTPS**.
 - Store API keys in a secure secret manager; **do not hardcode** in source code or share keys publicly.
 - Rotate keys periodically and immediately if exposed.
-

FAQ

Q: Can I send both local and E.164 phone formats?

A: Yes. Provide either (**country_code + local number**) or a single E.164 number in **phone_number**.

Q: Do I have to include every key under **custom_dynamic_variables_config?**

A: No. Only include keys you need for your campaign's personalization and usecase.

Q: What is the maximum batch size?

A: We recommend up to 100 leads per call by default. Contact Nurix Support if you need higher throughput.