DSA

#### 1.3sum closet

```
import java.util.Arrays;
import java.util.Scanner;
public class Problem1 {
  public int threeSumClosest(int[] nums, int target) {
     Arrays.sort(nums);
     int closestSum = Integer.MAX VALUE / 2;
     for (int i = 0; i < nums.length - 2; i++) {
       int left = i + 1, right = nums.length - 1;
       while (left < right) {
          int currentSum = nums[i] + nums[left] + nums[right];
          if (Math.abs(target - currentSum) < Math.abs(target - closestSum)) {
            closestSum = currentSum;
          if (currentSum < target) {</pre>
            left++;
          } else if (currentSum > target) {
            right--;
          } else {
            return currentSum;
     return closestSum;
```

```
public static void main(String[] args) {
   Scanner scanner = new Scanner(System.in);
   System.out.println("Enter the array size:");
   int n = scanner.nextInt();
   int[] nums = new int[n];
   System.out.println("Enter the elements of the array:");
   for (int i = 0; i < n; i++) {
      nums[i] = scanner.nextInt();
   }
   System.out.println("Enter the target integer:");
   int target = scanner.nextInt();
   Problem1 solver = new Problem1();
   int result = solver.threeSumClosest(nums, target);
   System.out.println("Output: " + result);
   scanner.close();
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem1.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem1
Enter the array size:
Enter the elements of the array:
-1 1 2 -1
Enter the target integer:
Output: 2
```

# 2.Jump Game 2

```
import java.util.Scanner;
public class Problem2 {
  public int jump(int[] nums) {
    int jumps = 0;
     int currentEnd = 0;
     int farthest = 0;
     for (int i = 0; i < nums.length - 1; i++) {
       farthest = Math.max(farthest, i + nums[i]);
       if (i == currentEnd) {
         jumps++;
          currentEnd = farthest;
    return jumps;
  public static void main(String[] args) {
     Scanner scanner = new Scanner(System.in);
     System.out.println("Enter the array size:");
     int n = scanner.nextInt();
```

```
System.out.println("Enter the elements of the array:");
for (int i = 0; i < n; i++) {
    nums[i] = scanner.nextInt();
}

Problem2 solver = new Problem2();
int result = solver.jump(nums);
System.out.println("Output: " + result);

scanner.close();
}

C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem2.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem2
Enter the array size:
5
Enter the elements of the array:
2 3 1 1 4
Output: 2
```

## 3. Group Anagrams

int[] nums = new int[n];

```
import java.util.*;

public class Problem3 {
   public List<List<String>> groupAnagrams(String[] strs) {
      Map<String, List<String>> anagramMap = new HashMap<>();
      for (String str : strs) {
```

```
char[] charArray = str.toCharArray();
     Arrays.sort(charArray);
     String sortedStr = new String(charArray);
     if (!anagramMap.containsKey(sortedStr)) {
       anagramMap.put(sortedStr, new ArrayList<>());
     }
     anagramMap.get(sortedStr).add(str);
  return new ArrayList<>(anagramMap.values());
}
public static void main(String[] args) {
  Scanner scanner = new Scanner(System.in);
  System.out.println("Enter the number of strings:");
  int n = scanner.nextInt();
  scanner.nextLine(); // consume the newline
  String[] strs = new String[n];
  System.out.println("Enter the strings:");
  for (int i = 0; i < n; i++) {
     strs[i] = scanner.nextLine();
  Problem3 solver = new Problem3();
  List<List<String>> result = solver.groupAnagrams(strs);
```

```
System.out.println("Grouped Anagrams:");
   System.out.println(result);
   scanner.close();
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem3.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem3
Enter the number of strings:
Enter the strings:
Grouped Anagrams:
[[a]]
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem3
Enter the number of strings:
Enter the strings:
eat
ate
nat
tan
Grouped Anagrams:
[[eat, ate], [nat, tan]]
```

## 4.Decode ways

```
import java.util.Scanner;

public class Problem4 {
   public int numDecodings(String s) {
      if (s == null || s.length() == 0 || s.charAt(0) == '0') {
        return 0;
      }

   int n = s.length();
   int[] dp = new int[n + 1];
```

```
dp[0] = 1;
  dp[1] = 1;
  for (int i = 2; i \le n; i++) {
     if (s.charAt(i - 1) != '0') {
       dp[i] += dp[i - 1];
     }
     int twoDigit = Integer.parseInt(s.substring(i - 2, i));
     if (twoDigit >= 10 && twoDigit <= 26) {
       dp[i] += dp[i - 2];
  return dp[n];
public static void main(String[] args) {
  Scanner scanner = new Scanner(System.in);
  System.out.println("Enter the encoded string:");
  String s = scanner.next();
  Problem4 solver = new Problem4();
  int result = solver.numDecodings(s);
  System.out.println("Number of ways to decode: " + result);
  scanner.close();
```

```
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem4.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem4
Enter the encoded string:
12
Number of ways to decode: 2
```

## 5.Best time to buy and sell stock 2

```
import java.util.Scanner;
public class Problem5 {
  public int maxProfit(int[] prices) {
     int profit = 0;
     for (int i = 1; i < prices.length; i++) {
       if (prices[i] > prices[i - 1]) {
          profit += prices[i] - prices[i - 1];
     return profit;
  public static void main(String[] args) {
     Scanner scanner = new Scanner(System.in);
     System.out.println("Enter the number of days:");
     int n = scanner.nextInt();
     int[] prices = new int[n];
```

```
for (int i = 0; i < n; i++) {
    prices[i] = scanner.nextInt();
}

Problem5 solver = new Problem5();
int result = solver.maxProfit(prices);

System.out.println("Maximum profit: " + result);

scanner.close();
}
}

C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem5.java

C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem5
Enter the number of days:
5
Enter the stock prices:
1 2 3 4 5
Maximum profit: 4
```

#### 6. Number of Islands

```
import java.util.Scanner;

public class Problem6 {
   public int numIslands(char[][] grid) {
     if (grid == null || grid.length == 0) {
        return 0;
     }
}
```

System.out.println("Enter the stock prices:");

```
int m = grid.length;
  int n = grid[0].length;
  int islandCount = 0;
  for (int i = 0; i < m; i++) {
     for (int j = 0; j < n; j++) {
        if (grid[i][j] == '1') {
           islandCount++;
           dfs(grid, i, j, m, n);
  return islandCount;
}
private void dfs(char[][] grid, int i, int j, int m, int n) {
  if (i < 0 \parallel j < 0 \parallel i >= m \parallel j >= n \parallel grid[i][j] == '0') {
     return;
  grid[i][j] = '0';
  dfs(grid, i + 1, j, m, n); // down
  dfs(grid, i - 1, j, m, n); // up
  dfs(grid, i, j + 1, m, n); // right
  dfs(grid, i, j - 1, m, n); // left
}
public static void main(String[] args) {
```

```
Scanner scanner = new Scanner(System.in);
    System.out.println("Enter the number of rows:");
    int m = scanner.nextInt();
    System.out.println("Enter the number of columns:");
    int n = scanner.nextInt();
    char[][] grid = new char[m][n];
    System.out.println("Enter the grid (use '1' for land and '0' for water):");
    for (int i = 0; i < m; i++) {
      String row = scanner.next();
      grid[i] = row.toCharArray();
    }
    Problem6 solver = new Problem6();
    int result = solver.numIslands(grid);
    System.out.println("Number of islands: " + result);
    scanner.close();
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem6.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem6
Enter the number of rows:
Enter the number of columns:
Enter the grid (use '1' for land and '0' for water):
11000
00100
Number of islands: 3
```

# 7.QuickSort

```
import java.util.Scanner;
public class Problem7 {
  public void quickSort(int[] arr, int low, int high) {
     if (low < high) {
       int pi = partition(arr, low, high);
       quickSort(arr, low, pi - 1);
       quickSort(arr, pi + 1, high);
  private int partition(int[] arr, int low, int high) {
     int pivot = arr[high];
     int i = (low - 1);
     for (int j = low; j < high; j++) {
       if (arr[j] < pivot) {
          i++;
          int temp = arr[i];
          arr[i] = arr[j];
          arr[j] = temp;
     int temp = arr[i + 1];
     arr[i+1] = arr[high];
     arr[high] = temp;
     return i + 1;
```

```
public static void main(String[] args) {
    Scanner scanner = new Scanner(System.in);
    System.out.println("Enter the number of elements:");
    int n = scanner.nextInt();
    int[] arr = new int[n];
    System.out.println("Enter the elements:");
    for (int i = 0; i < n; i++) {
      arr[i] = scanner.nextInt();
    }
    Problem7 sorter = new Problem7();
    sorter.quickSort(arr, 0, arr.length - 1);
    System.out.println("Sorted array:");
    for (int num : arr) {
      System.out.print(num + " ");
    scanner.close();
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem7.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem7
Enter the number of elements:
Enter the elements:
5 3 8 1 2
Sorted array:
```

# 8.Merge Sort

```
import java.util.Scanner;
public class Problem8 {
  public void mergeSort(int[] arr, int left, int right) {
     if (left < right) {
        int mid = left + (right - left) / 2;
        mergeSort(arr, left, mid);
        mergeSort(arr, mid + 1, right);
        merge(arr, left, mid, right);
     }
   }
  private void merge(int[] arr, int left, int mid, int right) {
     int n1 = mid - left + 1;
     int n2 = right - mid;
     int[] leftArr = new int[n1];
     int[] rightArr = new int[n2];
     for (int i = 0; i < n1; ++i) leftArr[i] = arr[left +i];
     for (int i = 0; i < n2; ++i) rightArr[i] = arr[mid + 1 + i];
     int i = 0, j = 0;
     int k = left;
     while (i \le n1 \&\& j \le n2) {
        if (leftArr[i] <= rightArr[j]) {</pre>
           arr[k] = leftArr[i];
          i++;
        } else {
```

```
arr[k] = rightArr[j];
       j++;
     k++;
  while (i \le n1) {
     arr[k] = leftArr[i];
     i++;
     k++;
  while (j \le n2) {
     arr[k] = rightArr[j];
     j++;
     k++;
public static void main(String[] args) {
  Scanner scanner = new Scanner(System.in);
  System.out.println("Enter the number of elements:");
  int n = scanner.nextInt();
  int[] arr = new int[n];
  System.out.println("Enter the elements:");
  for (int i = 0; i < n; i++) {
     arr[i] = scanner.nextInt();
```

```
Problem8 sorter = new Problem8();
sorter.mergeSort(arr, 0, arr.length - 1);

System.out.println("Sorted array:");
for (int num : arr) {
    System.out.print(num + " ");
}
scanner.close();
}

C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem8.java

C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem8
Enter the number of elements:

6
Enter the elements:
12 3 4 5 8 6
Sorted array:
3 4 5 6 8 12
```

## 9.Ternary Search

```
import java.util.Scanner;

public class Problem9 {
   public int ternarySearch(int[] arr, int left, int right, int target) {
     if (right >= left) {
        int mid1 = left + (right - left) / 3;
        int mid2 = right - (right - left) / 3;
        if (arr[mid1] == target) return mid1;
```

```
if (arr[mid2] == target) return mid2;
     if (target < arr[mid1]) return ternarySearch(arr, left, mid1 - 1, target);
     if (target > arr[mid2]) return ternarySearch(arr, mid2 + 1, right, target);
     return ternarySearch(arr, mid1 + 1, mid2 - 1, target);
  return -1;
}
public static void main(String[] args) {
  Scanner scanner = new Scanner(System.in);
  System.out.println("Enter the number of elements:");
  int n = scanner.nextInt();
  int[] arr = new int[n];
  System.out.println("Enter the elements:");
  for (int i = 0; i < n; i++) {
     arr[i] = scanner.nextInt();
  System.out.println("Enter the target value:");
  int target = scanner.nextInt();
  Problem9 searcher = new Problem9();
  int result = searcher.ternarySearch(arr, 0, arr.length - 1, target);
  System.out.println("Element found at index: " + result);
  scanner.close();
```

```
}
```

```
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem9.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem9
Enter the number of elements:
6
Enter the elements:
1 2 3 4 5 6
Enter the target value:
4
Element found at index: 3
```

## 10.Interpolation Search

```
public class Problem10 {
    public int interpolationSearch(int[] arr, int left, int right, int target) {
        if (left <= right && target >= arr[left] && target <= arr[right]) {
            int pos = left + ((right - left) / (arr[right] - arr[left])) * (target - arr[left]);
            if (arr[pos] == target) return pos;
            if (arr[pos] < target) return interpolationSearch(arr, pos + 1, right, target);
            if (arr[pos] > target) return interpolationSearch(arr, left, pos - 1, target);
        }
        return -1;
    }
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        System.out.println("Enter the number of elements:");
        int n = scanner.nextInt();
    }
}
```

```
int[] arr = new int[n];
   System.out.println("Enter the elements:");
   for (int i = 0; i < n; i++) {
      arr[i] = scanner.nextInt();
   }
   System.out.println("Enter the target value:");
   int target = scanner.nextInt();
   Problem10 searcher = new Problem10();
   int result = searcher.interpolationSearch(arr, 0, arr.length - 1, target);
   System.out.println("Element found at index: " + result);
   scanner.close();
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>javac Problem10.java
C:\Users\SUNITHARAJ\Downloads\DSA-CODING-PROBLEMS\Day 7>java Problem10
Enter the number of elements:
Enter the elements:
10 20 30 40 50
Enter the target value:
Element found at index: 3
```