

MAGUS:

Machine learning And Graph theory assisted Universal structure Searcher

Hao Gao, Junjie Wang, Yu Han, Qiuhan Jia, Shuning Pan, Jian Sun

National Laboratory of Solid State Microstructures, School of Physics and Collaborative
Innovation Center of Advanced Microstructures, Nanjing University, Nanjing, 210093,
China

Manual

Version 1.6.0, February 21, 2023.

<https://gitlab.com/bigd4/magus>

Contents

1	Installation	3
1.1	Dependency	3
1.2	Preparation	4
1.2.1	Set up the ASE API with Vasp	4
1.2.2	Set up Job System	4
1.2.3	Machine Learning Package Installation (Optional)	5
1.2.4	Build a Virtual Environment (Optional)	5
1.3	Install with pip	5
1.4	Install with Source Code	6
1.4.1	Download Code	6
1.4.1.1	Use git	6
1.4.1.2	From Website	6
1.4.2	Use pip to Install the Source Code	6
1.5	Install Offline	7
1.6	Other Settings	7
1.6.1	Set up Environment Variables	7
1.6.2	Set up Auto Completion (Optional)	7
1.7	Check Installation	7
2	Examples	9
2.1	Example List	9
2.2	Example Introductions	9
2.2.1	Generate structures	9
2.2.2	Relax structures	9

2.2.3	3D bulk search	10
2.2.4	Molecule crystal search	10
2.2.5	Cluster search	10
2.2.6	Surface reconstruct	10
2.2.7	Machine learning search	10
2.2.8	2D bulk search	10
3	Input parameters	11
3.1	Command lines	11
3.1.1	search	12
3.1.2	summary	13
3.1.3	clean	14
3.1.4	prepare	15
3.1.5	calculate	15
3.1.6	generate	16
3.1.7	checkpack	17
3.1.8	test	17
3.1.9	update	18
3.1.10	getslabtool	18
3.1.11	mutate	18
3.2	Parameter inputs	20

Chapter 1

Installation

1.1 Dependency

MAGUS needs python \geq 3.6 and gcc \geq 4.8. You should install pip before using it to install other packages. The following python packages are required:

```
numpy
scipy
scikit-learn
pyyaml $\geq$ 6.0
ase $\geq$ 3.18
networkx
spglib
pandas
prettytable
packaging
```

The following python packages are optional:

```
beautifulreport
plotly
dscribe
networkx
pymatgen
```

If you want to use MTP, you need to install mlip.

1.2 Preparation

1.2.1 Set up the ASE API with Vasp

MAGUS does VASP calculation based on ASE API. Hence, you need to do the following preparations first.

- 1) Make a new file **run_vasp.py**:

```
import subprocess
exitcode = subprocess.call("mpiexec.hydra vasp_std",
shell=True)
```

ase manual.

- 2) Make a new **mypps** dir to store vasp pseudopotentials. You can also use soft links:

```
mypps/
├── potpaw
├── potpaw_GGA
└── potpaw_PBE
```

```
$ ln -s /your/path/PBE-5.4 mypps/potpaw_PBE
```

Three sub directories correspond to LDA, PW91 and PBE, respectively. It is allowed to leave some of them nonexistent if you do use these potentials. It is also allowed to add other pseudopotentials.

- 3) Set environment variables:

```
$ export VASP_SCRIPT=/your/path/run_vasp.py
$ export VASP_PP_PATH=/your/path/mypps
```

More information in: [ase manual for vasp calculator](#).

Notice: **run_vasp.py** and **mypps** should not be under **magus** dir.

1.2.2 Set up Job System

MAGUS is developed under [LSF](#) job system, which is the default setting. But we also add support to [SLURM](#) and [PBS](#) job systems. You need to set an environment variable if you are not using the default LSF job system:

```
$ export JOB_SYSTEM=<your-job-system>
```

Add this line into your **bashrc** to make the setting work every time you log in.

1.2.3 Machine Learning Package Installation (Optional)

MLIP is a software for Machine Learning Interatomic Potentials. It has been developed at Skoltech (Moscow) by Alexander Shapeev, Evgeny Podryabinkin, Konstantin Gubaev, and Ivan Novikov.* According to the license, MLIP is not allowed to be published and otherwise distributed. You need to register in **<https://mlip.skoltech.ru/download/>** and follow the instructions.

1.2.4 Build a Virtual Environment (Optional)

And we highly recommend that you use [Anaconda](#) to build a virtual environment and install MAGUS in an isolated environment to avoid conflicts. After installing anaconda, it will automatically write several lines in your **bashrc** which is used to initialize anaconda environment. You should source **bashrc** or re-login to make anaconda activated. If you do the jobs correctly, your shell prompt should be modified to be started as **(base)**, which means you are now in base environment of anaconda. Then, create a new virtual environment with

```
$ conda create -n <your-env-name> python=<python-version>
```

<your-env-name> is the name of the environment that you can define as you will, and <python-version> should be not less than 3.6. When you want to activate this environment, use

```
$ conda activate <your-env-name>
```

1.3 Install with pip

It is convenient to install with pip. It will automatically download the source code and install the required python packages. The install command is

*Novikov, Ivan S., et al. "The MLIP package: moment tensor potentials with MPI and active learning." Machine Learning: Science and Technology 2.2 (2020): 025002.

```
$ pip install git+https://gitlab.com/bigd4/magus.git
```

You may need to type in your username and password of your gitlab account because the project is not public. If you want to install in a virtual environment, do not forget to activate the environment first. If you works in a cluster and do not have permission to install in the default location, you may add **--user** parameter.

1.4 Install with Source Code

1.4.1 Download Code

1.4.1.1 Use git

Clone the project and submodules to local file system:

```
$ git clone --recursive https://gitlab.com:bigd4/magus.git
```

1.4.1.2 From Website

If you have problem downloading with git, you have the alternative choose to download the zipped package on our [gitlab website](#). Notice that the submodules such as pybind11 will not be downloaded at the same time. You should download and extract them and replace the empty folders in the source code, respectively.

1.4.2 Use pip to Install the Source Code

After downloading the code, go into the directory and install with:

```
$ pip install -e .
```

pip will read **setup.py** in your current directory and install. The **-e** option means python will import the module from the current path, but not copy the codes to the default lib path and import the module there, which is convenient for modifying in the future. If you do not have the need, you can remove the option.

1.5 Install Offline

If you have no access to Internet and your cluster does not have a python pypi mirror, which means you cannot use pip to install packages. You have the alternative choose to download with our pre-built offline installation package. You can download it from [here](#). Install with

```
$ ./magus-<version-number>.sh
```

Follow the instructions. It will build an isolated conda environment with all required packages. You should go into your install path. Then, add **bin** into PATH and add conda into PYTHONPATH. Notice that this method will build a new conda. If have already installed a conda in your system, the new one will not merge into the old one, which may cause difficulties to switch conda environments. As a result, it is not recommended to install with this method if your pip works normally.

1.6 Other Settings

1.6.1 Set up Environment Variables

To run MAGUS in your console, you need to add PATH in **bashrc**.

```
$ export PATH=$PATH:/your_path_to_magus
$ export PYTHONPATH=$PYTHONPATH:/your_path_to_magus
```

1.6.2 Set up Auto Completion (Optional)

We have prepared a shell completion script for MAGUS. Add the following line into **bashrc**:

```
$ source your_path_to_magus/auto_complete.sh
```

1.7 Check Installation

If MAGUS is properly installed, you can see the version number by the following command in console:


```
$ magus -v
```

```
1.0.5
```

If you have installed other optional packages, you can check if they are properly installed using:

```
$ magus checkpack
```

Chapter 2

Examples

2.1 Example List

number	target
01	Generate structures
02	Relax structures
03	3D bulk search
04	Molecule crystal search
05	Cluster search
06	Surface reconstruct
07	Machine learning search
08	2D bulk search

2.2 Example Introductions

2.2.1 Generate structures

- **01--1-B12**: Generate 3d periodic crystal structures of boron with 12 atoms per unit cell by symmetry.
- **01--2-NH4NO3**: Generate 3d periodic crystal structures of molecule crystal with 8 NH4 and NO3 molecules per unit cell by symmetry Pccn (56).

2.2.2 Relax structures

- **02--1-C8-VASP**: Structure relaxation of diamond by vasp interface.
- **02--2-B12-MTP**: Relax 2000 structures with MTP and VASP.

2.2.3 3D bulk search

- **03--1-Al-fix-EMT**: GAssearch of fixed composition Al (12 atoms per cell) by EMT.
- **03--2-Al-fix-VASP**: GAssearch of fixed composition Al (12 atoms per cell) by VASP.
- **03--3-TiO2-fix-VASP**: GAssearch of fixed composition TiO_2 (12 atoms per cell).
- **03--4-MgAlO-fix-GULP**: GAssearch of fixed composition MgAlO under high pressure by GULP.
- **03--5-Si-fix-Castep**: GAssearch of fixed composition Si by Castep.
- **03--6-ZnOH-var-GULP**: GAssearch of variable composition $\text{Zn}_x(\text{OH})_y$.

2.2.4 Molecule crystal search

- **04--1-CH4-fix-VASP**: GAssearch of molecule crystal CH_4 with 4 molecules per unit cell.

2.2.5 Cluster search

- **05--1-LJ26**: Ground state of Lennard-Jones cluster of 26 atoms.

2.2.6 Surface reconstruct

- **06--1-C_2x1_100**: Surface reconstruction of diamond (100)- 2×1 .
- **06--2-SnO2_4x1_110**: Surface reconstruction of SnO_2 (110)- 4×1 .

2.2.7 Machine learning search

- **07--1-MgSiO3-MTP**: Use mtp to search MgSiO_3 under high pressure.
- **07--2-Na-NEP**: A toy example for use NEP to search sodium.

2.2.8 2D bulk search

- **08--1-graphene**: GAssearch of 2D carbon (graphene) by VASP.

Chapter 3

Input parameters

In magus we use inputs including command lines and parameter input file (in yaml format) to control programs.

If you are a new user of MAGUS (AND SINCERELY THANKS VERY MUCH FOR USING OUR PROGRAM!), before you read the full description about all inputs below, we recommend first taking a look at examples which are easier to follow.

3.1 Command lines

You can simply type

```
$ magus -h
```

to see which commands are supported for magus. You will see

```
usage: magus [-h] [-v]
           {search,summary,clean,prepare,calculate,
           generate,checkpack,test,update,getslabtool,
           mutate,parmhelp}
           ...
```

```
Magus: Machine learning And Graph theory assisted
Universal structure Searcher
```

```
optional arguments:
```

```
-h, --help          show this help message and exit
-v, --version        print version
```

Valid subcommands:

{search,summary,clean,prepare,calculate,generate,checkpack,test,update,getslabtool,mutate,parmhelp}	
search	search structures
summary	summary the results
clean	clean the path
prepare	generate InputFold etc to prepare
for the search	
calculate	calculate many structures
generate	generate many structures
checkpack	check full
test	do unit test of magus
update	update magus
getslabtool	tools to getslab in surface search
mode	
mutate	mutation test

which prints valid subcommands. You can also helps for each command line:

3.1.1 search

```
$ magus search -h
```

```
usage: magus search [-h] [-ll {DEBUG,INFO,WARNING,ERROR}]
                 [-lp LOG_PATH]
                 [-i INPUT_FILE] [-m] [-r]
```

optional arguments:

```
-h, --help                show this help message and exit
-ll {DEBUG,INFO,WARNING,ERROR}, --log-level
{DEBUG,INFO,WARNING,ERROR}
                           set verbosity level by strings:
                           ERROR, WARNING, INFO
                           and DEBUG (default: INFO)
-lp LOG_PATH, --log-path LOG_PATH
                           set log file to log messages to
                           disk (default:
                           log.txt)
-i INPUT_FILE, --input-file INPUT_FILE
```

-m, --use-ml (default: False)	the input parameter file in yaml format (default: input.yaml)
-r, --restart False)	use ml to accelerate(?) the search
	Restart the searching. (default: False)

3.1.2 summary

```
$ magus summary -h
```

```
usage: magus summary [-h] [-p PREC] [-r] [-s]
[--need-sort] [-o OUTDIR]
                        [-n SHOW_NUMBER] [-sb SORTED_BY
                        [SORTED_BY ...]]
                        [-rm REMOVE_FEATURES [REMOVE_FEATURES
                        ...]]
                        [-a ADD_FEATURES [ADD_FEATURES ...]]
                        [-v]
                        [-b BOUNDARY [BOUNDARY ...]] [-t
                        {bulk,cluster}]
                        filenames [filenames ...]
```

positional arguments:

filenames file (or files) to summary

optional arguments:

-h, --help	show this help message and exit
-p PREC, --prec PREC (default: 0.1)	tolerance for symmetry finding
-r, --reverse False)	whether to reverse sort (default: False)
-s, --save False)	whether to save POSCARS (default: False)
--need-sort	whether to sort (default: False)
-o OUTDIR, --outdir OUTDIR	where to save POSCARS (default: .)
-n SHOW_NUMBER, --show-number SHOW_NUMBER	

```

                                number of show in screen (default:
                                100)
-sb SORTED_BY [SORTED_BY ...], --sorted-by SORTED_BY
[SORTED_BY ...]
                                sorted by which arg (default:
                                Default)
-rm REMOVE_FEATURES [REMOVE_FEATURES ...],
--remove-features REMOVE_FEATURES [REMOVE_FEATURES ...]
                                the features to be removed from
                                the show features
                                (default: [])
-a ADD_FEATURES [ADD_FEATURES ...], --add-features
ADD_FEATURES [ADD_FEATURES ...]
                                the features to be added to the
                                show features
                                (default: [])
-v, --var
                                use variable composition mode
                                (default: False)
-b BOUNDARY [BOUNDARY ...], --boundary BOUNDARY
[BOUNDARY ...]
                                in variable composition mode: add
                                boundary (default:
                                [])
-t {bulk,cluster}, --atoms-type {bulk,cluster}

```

3.1.3 clean

```
$ magus clean -h
```

```
usage: magus clean [-h] [-f]
```

```
optional arguments:
```

```

  -h, --help    show this help message and exit
  -f, --force   rua!!!! (default: False)

```

3.1.4 prepare

```
$ magus prepare -h
usage: magus prepare [-h] [-v] [-m]

optional arguments:
  -h, --help      show this help message and exit
  -v, --var        variable composition search (default: False)
  -m, --mol        molecule crystal search (default: False)
```

3.1.5 calculate

```
$ magus calculate -h

usage: magus calculate [-h] [-ll {DEBUG,INFO,WARNING,ERROR}] [-lp LOG_PATH]
                        [-m {scf,relax}] [-i INPUT_FILE]
                        [-o OUTPUT_FILE]
                        [-p PRESSURE]
                        filename

positional arguments:
  filename              structures to relax

optional arguments:
  -h, --help            show this help message and exit
  -ll {DEBUG,INFO,WARNING,ERROR}, --log-level {DEBUG,INFO,WARNING,ERROR}
                        set verbosity level by strings:
                        ERROR, WARNING, INFO
                        and DEBUG (default: INFO)
  -lp LOG_PATH, --log-path LOG_PATH
                        set log file to log messages to
                        disk (default:
                        log.txt)
  -m {scf,relax}, --mode {scf,relax}
                        scf or relax (default: relax)
  -i INPUT_FILE, --input-file INPUT_FILE
```



```

        the input parameter file in yaml
        format (default:
        input.yaml)
-o OUTPUT_FILE, --output-file OUTPUT_FILE
        output traj file (default:
        out.traj)
-p PRESSURE, --pressure PRESSURE
        add pressure (default: None)

```

3.1.6 generate

```
$ magus generate -h
```

```

usage: magus generate [-h] [-ll
{DEBUG,INFO,WARNING,ERROR}] [-lp LOG_PATH]
                        [-i INPUT_FILE] [-o OUTPUT_FILE] [-n
                        NUMBER]

```

optional arguments:

```

-h, --help            show this help message and exit
-ll {DEBUG,INFO,WARNING,ERROR}, --log-level
{DEBUG,INFO,WARNING,ERROR}
                        set verbosity level by strings:
                        ERROR, WARNING, INFO
                        and DEBUG (default: INFO)
-lp LOG_PATH, --log-path LOG_PATH
                        set log file to log messages to
                        disk (default:
                        log.txt)
-i INPUT_FILE, --input-file INPUT_FILE
                        the input parameter file in yaml
                        format (default:
                        input.yaml)
-o OUTPUT_FILE, --output-file OUTPUT_FILE
                        where to save generated traj
                        (default: gen.traj)
-n NUMBER, --number NUMBER
                        generate number (default: 10)

```

3.1.7 checkpack

```
$ magus checkpack -h
```

```
usage: magus checkpack [-h] [-ll  
{DEBUG,INFO,WARNING,ERROR}] [-lp LOG_PATH]  
  
                                [{all,calculators,comparators,fingerprints}]  
  
positional arguments:  
    {all,calculators,comparators,fingerprints}  
                                the package to check (default:  
                                all)  
  
optional arguments:  
    -h, --help                show this help message and exit  
    -ll {DEBUG,INFO,WARNING,ERROR}, --log-level  
    {DEBUG,INFO,WARNING,ERROR}  
                                set verbosity level by strings:  
                                ERROR, WARNING, INFO  
                                and DEBUG (default: INFO)  
    -lp LOG_PATH, --log-path LOG_PATH  
                                set log file to log messages to  
                                disk (default:  
                                log.txt)
```

3.1.8 test

```
$ magus test -h
```

```
usage: magus test [-h] [totest]  
  
positional arguments:  
    totest                the package to test (default: *)  
  
optional arguments:  
    -h, --help            show this help message and exit
```

3.1.9 update

```
$ magus update -h
```

```
usage: magus update [-h] [-u] [-f]
optional arguments:
  -h, --help      show this help message and exit
  -u, --user      add --user to pip install (default: False)
  -f, --force     add --force-reinstall to pip install
                  (default: False)
```

3.1.10 getslabtool

```
$ magus getslabtool -h
```

```
usage: magus getslabtool [-h] [-f FILENAME] [-s SLABFILE]

optional arguments:
  -h, --help            show this help message and exit
  -f FILENAME, --filename FILENAME
                        defaults is
                        './Ref/layerslices.traj' of slab
                        model and
                        'results' for analyze results.
                        (default: )
  -s SLABFILE, --slabfile SLABFILE
                        slab file (default: slab.vasp)
```

3.1.11 mutate

```
$ magus mutate -h
```

```
usage: magus mutate [-h] [-i INPUT_FILE] [-s SEED_FILE]
                  [-o OUTPUT_FILE]
                  [--cutandsplice] [--replaceball]
                  [--soft] [--perm]
```

```
    [--lattice] [--ripple] [--slip]
    [--rotate] [--rattle]
    [--formula] [--lyrslip] [--shell]
    [--lyrsym] [--clusym]
```

optional arguments:

```
-h, --help            show this help message and exit
-i INPUT_FILE, --input_file INPUT_FILE
                        input_file (default: input.yaml)
-s SEED_FILE, --seed_file SEED_FILE
                        seed_file (default: seed.traj)
-o OUTPUT_FILE, --output_file OUTPUT_FILE
                        output_file (default: result)
--cutandsplice        add option to use operation!
(default: False)
--replaceball         add option to use operation!
(default: False)
--soft               add option to use operation!
(default: False)
--perm              add option to use operation!
(default: False)
--lattice           add option to use operation!
(default: False)
--ripple           add option to use operation!
(default: False)
--slip             add option to use operation!
(default: False)
--rotate           add option to use operation!
(default: False)
--rattle           add option to use operation!
(default: False)
--formula          add option to use operation!
(default: False)
--lyrslip          add option to use operation!
(default: False)
--shell            add option to use operation!
(default: False)
--lyrsym           add option to use operation!
(default: False)
--clusym           add option to use operation!
(default: False)
```

3.2 Parameter inputs

A yaml format parameter file is also necessary. By default is 'input.yaml'. IN THE FUTURE we will add command line to easily export notes and default values by

```
$ magus parmhelp
```

to see help for which parameters you can set in 'input.yaml'. For current version they are:

```
parameter information for <class
'magus.parameters.magusParameters'>
+++++ Default parameters +++++
formulaType      : type of formula, choose from fix or var
                  default value: fix
structureType    : structure type, choose from bulk, layer,
confined_bulk, cluster, surface
                  default value: bulk
spacegroup       : spacegroup to generate random structures
                  default value: [1-230]
DFTRelax        : DFTRelax
                  default value: False
initSize         : size of first population
                  default value: =popSize
goodSize         : number of good indivials per generation
                  default value: =popSize
molMode         : search molecule clusters
                  default value: False
mlRelax         : use Machine learning relaxation
                  default value: False
symprec         : tolerance for symmetry finding
                  default value: 0.1
bondRatio        : limitation to detect clusters
                  default value: 1.15
eleSize         : used in variable composition mode,
control how many boundary structures are generated
                  default value: 0
volRatio         : cell_volume/SUM(atom_ball_volume) when
generating structures (around this number)
                  default value: 2
dRatio          : distance between each pair of two atoms
in the structure is
```

```

                                not less than (radius1+radius2)*d_ratio
                                default value: 0.7
molDetector      : methods to detect mol, choose from 1 and
2. See
                                Hao Gao, Junjie Wang, Zhaopeng Guo, Jian
                                Sun, "Determining dimensionalities and
                                multiplicities
                                of crystal nets" npj Comput. Mater. 6,
                                143 (2020)
                                [doi.org/10.1016/j.fmre.2021.06.005]
                                for more details.
                                default value: 0
addSym           : whether to add symmetry before crossover
and mutation
                                default value: True
randRatio        : ratio of new generated random structures
in next generation
                                default value: 0.2
chkMol           : use mol dectector
                                default value: False
chkSeed          : check seeds
                                default value: True
diffE            : energy difference to determin structure
duplicates
                                default value: 0.01
diffV            : volume difference to determin structure
duplicates
                                default value: 0.05
comparator       : comparator, type magus checkpack to see
which comparators you have.
                                default value: nepdes
fp_calc          : fingerprints, type magus checkpack to see
which fingerprint method you have.
                                default value: nepdes
n_cluster        : number of good individuals per generation
                                default value: =saveGood
autoOpRatio      : automantic GA operation ratio
                                default value: False
autoRandomRatio : automantic random structure generation
ratio
                                default value: False

```

```

-----
parameter information for <class
'magus.generators.random.MoleculeSPGGenerator'>
+++++ Requirement parameters +++++
input_mols      : input molecules
formula_type    : type of formula, choose from fix or var
symbols         : atom symbols
formula         : formula
min_n_atoms     : minimum number of atoms per unit cell
max_n_atoms     : maximum number of atoms per unit cell
+++++ Default parameters +++++
symprec         : tolerance for symmetry finding for
molucule

                    default value: 0.1
threshold_mol   : distance between each pair of two
molecules in the structure is
                    not less than
                    (mol_radius1+mol_radius2)*threshold_mol
                    default value: 1.0
max_attempts    : max attempts to generate a random
structure

                    default value: 50
p_pri           : probability of generate primitive cell
                    default value: 0.0
volume_ratio    : cell_volume/SUM(atom_ball_volume) when
generating structures (around this number)
                    default value: 1.5
n_split         : split cell into n_split parts
                    default value: [1]
dimension       : dimension
                    default value: 3
ele_size        : number of single component structures to
generate to decide hull boundaries in
variable composition mode
                    default value: 0
min_lattice     : min lattice
                    default value: [-1, -1, -1, -1, -1, -1]
max_lattice     : max lattice
                    default value: [-1, -1, -1, -1, -1, -1]
min_volume      : min volume
                    default value: -1

```

```

max_volume      : max volume
                  default value: -1
min_n_formula   : minimum formula
                  default value: None
max_n_formula   : maximum formula
                  default value: None
d_ratio         : distance between each pair of two atoms
in the structure is
                  not less than (radius1+radius2)*d_ratio
                  default value: 1.0
distance_matrix: distance between each pair of two atoms
in the structure is
                  not less than
                  (radius1+radius2)*distance_matrix[1][2]
                  default value: None
spacegroup      : spacegroup to generate random structures
                  default value: [1-230]
max_ratio       : max formula ratio in variable
composition mode, for example set 10 and Zn11(OH) is not
allowed
                  default value: 1000
full_ele        : only generate structures with full
elements
                  default value: True

```

```

-----
parameter information for <class
'magus.generators.random.LayerSPGGenerator'>
+++++ Requirement parameters +++++
min_thickness   : minimum thickness
max_thickness   : maximum thickness
formula_type    : type of formula, choose from fix or var
symbols         : atom symbols
formula         : formula
min_n_atoms     : minimum number of atoms per unit cell
max_n_atoms     : maximum number of atoms per unit cell
+++++ Default parameters +++++
symprec         : symprec
                  default value: 0.1
threshold_mol   : threshold_mol
                  default value: 1.0
spg_type        : spg_type

```



```

                                default value: layer
vacuum_thickness: vacuum_thickness
                                default value: 10
max_attempts    : max attempts to generate a random
structure
                                default value: 50
p_pri           : probability of generate primitive cell
                                default value: 0.0
volume_ratio    : cell_volume/SUM(atom_ball_volume) when
generating structures (around this number)
                                default value: 1.5
n_split         : split cell into n_split parts
                                default value: [1]
dimension       : dimension
                                default value: 3
ele_size        : number of single component structures to
generate to decide hull boundaries in
variable composition mode
                                default value: 0
min_lattice     : min lattice
                                default value: [-1, -1, -1, -1, -1, -1]
max_lattice     : max lattice
                                default value: [-1, -1, -1, -1, -1, -1]
min_volume      : min volume
                                default value: -1
max_volume      : max volume
                                default value: -1
min_n_formula   : minimum formula
                                default value: None
max_n_formula   : maximum formula
                                default value: None
d_ratio        : distance between each pair of two atoms
in the structure is
                                not less than (radius1+radius2)*d_ratio
                                default value: 1.0
distance_matrix: distance between each pair of two atoms
in the structure is
                                not less than
                                (radius1+radius2)*distance_matrix[1][2]
                                default value: None
spacegroup      : spacegroup to generate random structures

```

```

                                default value: [1-230]
max_ratio      : max formula ratio in variable
composition mode, for example set 10 and Zn11(OH) is not
allowed

                                default value: 1000
full_ele       : only generate structures with full
elements

                                default value: True

```

```

-----
parameter information for <class
'magus.reconstruct.generator.ClusterSPGGenerator'>
+++++ Requirement parameters +++++
formula_type   : type of formula, choose from fix or var
symbols        : atom symbols
formula        : formula
min_n_atoms    : minimum number of atoms per unit cell
max_n_atoms    : maximum number of atoms per unit cell
+++++ Default parameters +++++
vacuum_thickness: vacuum thickness
                                default value: 10

```

```

-----
parameter information for <class
'magus.generators.random.SPGGenerator'>
+++++ Requirement parameters +++++
formula_type   : type of formula, choose from fix or var
symbols        : atom symbols
formula        : formula
min_n_atoms    : minimum number of atoms per unit cell
max_n_atoms    : maximum number of atoms per unit cell
+++++ Default parameters +++++
max_attempts   : max attempts to generate a random
structure

                                default value: 50
p_pri          : probability of generate primitive cell
                                default value: 0.0
volume_ratio   : cell_volume/SUM(atom_ball_volume) when
generating structures (around this number)
                                default value: 1.5
n_split        : split cell into n_split parts
                                default value: [1]
dimension      : dimension

```

```

                                default value: 3
ele_size      : number of single component structures to
                                generate to decide hull boundarys in
                                variable composition mode
                                default value: 0
min_lattice   : min lattice
                                default value: [-1, -1, -1, -1, -1, -1]
max_lattice   : max lattice
                                default value: [-1, -1, -1, -1, -1, -1]
min_volume    : min volume
                                default value: -1
max_volume    : max volume
                                default value: -1
min_n_formula : minimum formula
                                default value: None
max_n_formula : maximum formula
                                default value: None
d_ratio       : distance between each pair of two atoms
in the structure is
                                not less than (radius1+radius2)*d_ratio
                                default value: 1.0
distance_matrix: distance between each pair of two atoms
in the structure is
                                not less than
                                (radius1+radius2)*distance_matrix[1][2]
                                default value: None
spacegroup    : spacegroup to generate random structures
                                default value: [1-230]
max_ratio     : max formula ratio in variable
composition mode, for example set 10 and Zn11(OH) is not
allowed
                                default value: 1000
full_ele      : only generate structures with full
elements
                                default value: True

```

```

-----
parameter information for <class
'magus.reconstruct.generator.SurfaceGenerator'>
+++++ Requirement parameters +++++
formula_type   : type of formula, choose from fix or var
symbols        : atom symbols

```

```

formula           : formula
min_n_atoms      : minimum number of atoms per unit cell
max_n_atoms      : maximum number of atoms per unit cell
+++++ Default parameters +++++
randwalk_range   : maximum range of random walk
                     default value: 0.5
randwalk_ratio   : ratio of random walk atoms
                     default value: 0.3
rsc_x            : size[x] of reconstruction
                     default value: [1]
rsc_y            : size[y] of reconstruction
                     default value: [1]
buffer           : use buffer layer
                     default value: True
rsc_formula      : formula of surface region
                     default value: None
spg_type         : generate with planegroup/layergroup
                     default value: plane
+++++ slabinfo parameters +++++
bulk_file        : file of bulk structure
                     default value: None
cutslices       : bulk_file contains how many atom layers
                     default value: 2
bulk_layernum    : number of atom layers in substrate region
                     default value: 3
buffer_layernum  : number of atom layers in buffer region
                     default value: 3
rsc_layernum     : number of atom layers in top surface
region
                     default value: 2
direction       : Miller indices of surface direction,
i.e.[1,0,0]
                     default value: None
rotate          : R
                     default value: 0
matrix          : matrix notation
                     default value: None
addH            : passivate bottom surface with H
                     default value: False
pcell           : use primitive cell
                     default value: True

```

```

+++++ modification parameters +++++
adsorb      : adsorb atoms to cleaved surface
              default value: {}
clean       : clean cleaved surface
              default value: {}
defect      : add defect to cleaved surface
              default value: {}

-----

parameter information for <class
'magus.populations.individuals.Bulk'>
+++++ Requirement parameters +++++
symprec     : tolerance for symmetry finding
+++++ Default parameters +++++
mol_detector : methods to detect mol, choose from 1 and
2. See

              Hao Gao, Junjie Wang, Zhaopeng Guo, Jian
              Sun, "Determining dimensionalities and
              multiplicities
              of crystal nets" npj Comput. Mater. 6,
              143 (2020)
              [doi.org/10.1016/j.fmre.2021.06.005]
              for more details.
              default value: 0
n_repair_try : attempts to repair structures when doing
GA operation
              default value: 5
max_attempts : maximum attempts
              default value: 50
check_seed   : if check seeds
              default value: False
min_lattice  : min_lattice
              default value: [0.0, 0.0, 0.0, 45.0,
              45.0, 45.0]
max_lattice  : max_lattice
              default value: [99, 99, 99, 135, 135,
              135]
d_ratio      : distance between each pair of two atoms
in the structure is
              not less than (radius1+radius2)*d_ratio
              default value: 1.0

```

```

distance_matrix: distance between each pair of two atoms
in the structure is
                    not less than
                    (radius1+radius2)*distance_matrix[1][2]
                    default value: None
radius           : radius
                    default value: None
max_forces       : if forces of a structure larger is than
this number it will be deleted.
                    default value: 50.0
max_enthalpy     : if enthalpy of a structure is larger than
this number it will be deleted.
                    default value: 100.0
full_ele        : full_ele
                    default value: True
max_length_ratio: if max-cell-length/min-cell-length of a
structure is larger than this number it will be deleted.
                    default value: 8

```

```

-----
parameter information for <class
'magus.populations.individuals.Layer'>
+++++ Requirement parameters +++++
symprec         : tolerance for symmetry finding
+++++ Default parameters +++++
vacuum_thickness: vacuum_thickness
                    default value: 10
bond_ratio      : bond_ratio
                    default value: 1.1
n_repair_try    : attempts to repair structures when doing
GA operation
                    default value: 5
max_attempts    : maximum attempts
                    default value: 50
check_seed      : if check seeds
                    default value: False
min_lattice     : min_lattice
                    default value: [0.0, 0.0, 0.0, 45.0,
45.0, 45.0]
max_lattice     : max_lattice
                    default value: [99, 99, 99, 135, 135,
135]

```

```

d_ratio          : distance between each pair of two atoms
in the structure is
                    not less than (radius1+radius2)*d_ratio
                    default value: 1.0
distance_matrix: distance between each pair of two atoms
in the structure is
                    not less than
                    (radius1+radius2)*distance_matrix[1][2]
                    default value: None
radius          : radius
                    default value: None
max_forces      : if forces of a structure larger is than
this number it will be deleted.
                    default value: 50.0
max_enthalpy   : if enthalpy of a structure is larger than
this number it will be deleted.
                    default value: 100.0
full_ele       : full_ele
                    default value: True
max_length_ratio: if max-cell-length/min-cell-length of a
structure is larger than this number it will be deleted.
                    default value: 8

```

```

-----
parameter information for <class
'magus.populations.individuals.ConfinedBulk'>
+++++ Requirement parameters +++++
symprec        : tolerance for symmetry finding
+++++ Default parameters +++++
vacuum_thickness: vacuum thickness
                    default value: 10
n_repair_try   : attempts to repair structures when doing
GA operation
                    default value: 5
max_attempts   : maximum attempts
                    default value: 50
check_seed     : if check seeds
                    default value: False
min_lattice    : min_lattice
                    default value: [0.0, 0.0, 0.0, 45.0,
45.0, 45.0]
max_lattice    : max_lattice

```

```

                                default value: [99, 99, 99, 135, 135,
                                135]
d_ratio      : distance between each pair of two atoms
in the structure is
                                not less than (radius1+radius2)*d_ratio
                                default value: 1.0
distance_matrix: distance between each pair of two atoms
in the structure is
                                not less than
                                (radius1+radius2)*distance_matrix[1][2]
                                default value: None
radius       : radius
                                default value: None
max_forces   : if forces of a structure larger is than
this number it will be deleted.
                                default value: 50.0
max_enthalpy : if enthalpy of a structure is larger than
this number it will be deleted.
                                default value: 100.0
full_ele     : full_ele
                                default value: True
max_length_ratio: if max-cell-length/min-cell-length of a
structure is larger than this number it will be deleted.
                                default value: 8

```

```

-----
parameter information for <class
'magus.reconstruct.individuals.Surface'>
+++++ Requirement parameters +++++
symprec      : tolerance for symmetry finding
+++++ Default parameters +++++
vacuum_thickness: vacuum thickness
                                default value: 10
buffer       : use buffer region
                                default value: True
fixbulk      : fix atom positions in substrate
                                default value: True
slices_file  : file name for slices_file
                                default value: Ref/layerslices.traj
n_repair_try : attempts to repair structures when doing
GA operation
                                default value: 5

```



```

max_attempts      : maximum attempts
                    default value: 50
check_seed        : if check seeds
                    default value: False
min_lattice       : min_lattice
                    default value: [0.0, 0.0, 0.0, 45.0,
                                     45.0, 45.0]
max_lattice       : max_lattice
                    default value: [99, 99, 99, 135, 135,
                                     135]
d_ratio           : distance between each pair of two atoms
in the structure is
                    not less than (radius1+radius2)*d_ratio
                    default value: 1.0
distance_matrix   : distance between each pair of two atoms
in the structure is
                    not less than
                    (radius1+radius2)*distance_matrix[1][2]
                    default value: None
radius            : radius
                    default value: None
max_forces        : if forces of a structure larger is than
this number it will be deleted.
                    default value: 50.0
max_enthalpy      : if enthalpy of a structure is larger than
this number it will be deleted.
                    default value: 100.0
full_ele          : full_ele
                    default value: True
max_length_ratio  : if max-cell-length/min-cell-length of a
structure is larger than this number it will be deleted.
                    default value: 8

```

```

-----
parameter information for <class
'magus.reconstruct.individuals.Cluster'>
+++++ Requirement parameters +++++
symprec           : tolerance for symmetry finding
+++++ Default parameters +++++
vacuum_thickness  : vacuum thickness surrounding cluster to
break pbc when runing calculation
                    default value: 10

```

```
cutoff : two atoms are "connected" if their
distance < cutoff*radius.
           default value: 1.0
weighten : use weighten atoms when appending or
removing atoms
           default value: True
n_repair_try : attempts to repair structures when doing
GA operation
           default value: 5
max_attempts : maximum attempts
           default value: 50
check_seed : if check seeds
           default value: False
min_lattice : min_lattice
           default value: [0.0, 0.0, 0.0, 45.0,
                           45.0, 45.0]
max_lattice : max_lattice
           default value: [99, 99, 99, 135, 135,
                           135]
d_ratio : distance between each pair of two atoms
in the structure is
           not less than (radius1+radius2)*d_ratio
           default value: 1.0
distance_matrix: distance between each pair of two atoms
in the structure is
           not less than
           (radius1+radius2)*distance_matrix[1][2]
           default value: None
radius : radius
           default value: None
max_forces : if forces of a structure larger is than
this number it will be deleted.
           default value: 50.0
max_enthalpy : if enthalpy of a structure is larger than
this number it will be deleted.
           default value: 100.0
full_ele : full_ele
           default value: True
max_length_ratio: if max-cell-length/min-cell-length of a
structure is larger than this number it will be deleted.
           default value: 8
```

```

-----
parameter information for <class
'magus.reconstruct.individuals.AdClus'>
+++++ Requirement parameters +++++
symprec      : tolerance for symmetry finding
+++++ Default parameters +++++
substrate    : substrate file name
               default value: substrate.vasp
dist_clus2surface: distance from cluster to surface
               default value: 2
size         : size
               default value: [1, 1]
vacuum_thickness: vacuum thickness surrounding cluster to
break pbc when runing calculation
               default value: 10
cutoff       : two atoms are "connected" if their
distance < cutoff*radius.
               default value: 1.0
weighten     : use weighten atoms when appending or
removing atoms
               default value: True
n_repair_try  : attempts to repair structures when doing
GA operation
               default value: 5
max_attempts  : maximum attempts
               default value: 50
check_seed   : if check seeds
               default value: False
min_lattice  : min_lattice
               default value: [0.0, 0.0, 0.0, 45.0,
45.0, 45.0]
max_lattice  : max_lattice
               default value: [99, 99, 99, 135, 135,
135]
d_ratio      : distance between each pair of two atoms
in the structure is
               not less than (radius1+radius2)*d_ratio
               default value: 1.0
distance_matrix: distance between each pair of two atoms
in the structure is

```

```

                                not less than
                                (radius1+radius2)*distance_matrix[1][2]
                                default value: None
radius      : radius
              default value: None
max_forces  : if forces of a structure larger is than
this number it will be deleted.
              default value: 50.0
max_enthalpy : if enthalpy of a structure is larger than
this number it will be deleted.
              default value: 100.0
full_ele    : full_ele
              default value: True
max_length_ratio: if max-cell-length/min-cell-length of a
structure is larger than this number it will be deleted.
              default value: 8

```

```

-----
parameter information for <class
'magus.populations.populations.FixPopulation'>
+++++ Requirement parameters +++++
results_dir  : path for results
pop_size     : population size
symbols      : symbols
formula      : formula
+++++ Default parameters +++++
check_seed   : if check seed is turned on, we will check
your seeds and delete those donot meet requirements
              default value: False

```

```

-----
parameter information for <class
'magus.populations.populations.VarPopulation'>
+++++ Requirement parameters +++++
results_dir  : path for results
pop_size     : population size
symbols      : symbols
formula      : formula
+++++ Default parameters +++++
check_seed   : if check seed is turned on, we will check
your seeds and delete those donot meet requirements
              default value: False

```

```
parameter information for <class  
'magus.reconstruct.individuals.RcsPopulation'>  
+++++ Requirement parameters +++++  
results_dir      : path for results  
pop_size         : population size  
symbols          : symbols  
formula          : formula  
+++++ Default parameters +++++  
check_seed       : if check seed is turned on, we will check  
your seeds and delete those donot meet requirements  
                   default value: False
```

```
-----  
parameter information for <class  
'magus.operations.crossovers.CutAndSplicePairing'>  
+++++ Default parameters +++++  
tryNum           : try attempts  
                   default value: 50  
cut_disp         : cut displacement  
                   default value: 0  
best_match       : choose best match  
                   default value: False
```

```
-----  
parameter information for <class  
'magus.operations.crossovers.ReplaceBallPairing'>  
+++++ Default parameters +++++  
tryNum           : try attempts  
                   default value: 50  
cut_range        : cut range  
                   default value: [1, 2]
```

```
-----  
parameter information for <class  
'magus.operations.mutations.SoftMutation'>  
+++++ Default parameters +++++  
tryNum           : tryNum  
                   default value: 50
```

```
-----  
parameter information for <class  
'magus.operations.mutations.PermMutation'>  
+++++ Default parameters +++++  
tryNum           : try attempts  
                   default value: 50
```

```
frac_swaps      : possibility to swap
                  default value: 0.5
```

```
-----
parameter information for <class
'magus.operations.mutations.LatticeMutation'>
```

```
+++++ Default parameters +++++
```

```
tryNum          : try attempts
                  default value: 50
sigma           : Gauss distribution standard deviation
                  default value: 0.1
cell_cut        : coefficient of gauss distribution in cell
mutation
                  default value: 1
keep_volume      : whether to keep the volume unchange
                  default value: True
```

```
-----
parameter information for <class
'magus.operations.mutations.RippleMutation'>
```

```
+++++ Default parameters +++++
```

```
tryNum          : try attempts
                  default value: 50
rho             : rho
                  default value: 0.3
mu             : mu
                  default value: 2
eta            : eta
                  default value: 1
```

```
-----
parameter information for <class
'magus.operations.mutations.SlipMutation'>
```

```
+++++ Default parameters +++++
```

```
tryNum          : try attempts
                  default value: 50
cut             : cut position
                  default value: 0.5
randRange       : range of movement
                  default value: [0.5, 2]
```

```
-----
parameter information for <class
'magus.operations.mutations.RotateMutation'>
```

```
+++++ Default parameters +++++
```

```

tryNum      : try attempts
                default value: 50
p          : possibility
                default value: 1

```

```

-----
parameter information for <class
'magus.operations.mutations.RattleMutation'>
+++++ Default parameters +++++

```

```

tryNum      : try attempts
                default value: 50
p          : possibility
                default value: 0.25
rattle_range : range of rattle
                default value: 4
d_ratio     : d_ratio
                default value: 0.7
keep_sym    : if keeps symmetry when rattles
                default value: None
symprec     : tolerance for symmetry finding
                default value: 0.1

```

```

-----
parameter information for <class
'magus.operations.mutations.FormulaMutation'>
+++++ Default parameters +++++

```

```

tryNum      : try attempts
                default value: 10
n_candidate : number of candidates
                default value: 5

```

```

-----
parameter information for <class
'magus.reconstruct.ga.LyrSlipMutation'>
+++++ Default parameters +++++

```

```

tryNum      : tryNum
                default value: 10
cut         : cut
                default value: 0.2
randRange   : randRange
                default value: [0, 1]

```

```

-----
parameter information for <class
'magus.reconstruct.ga.ShellMutation'>

```

```

+++++ Default parameters +++++
tryNum      : tryNum
              default value: 10
d           : d
              default value: 0.23
-----

parameter information for <class
'magus.reconstruct.ga.LyrSymMutation'>
+++++ Default parameters +++++
tryNum      : tryNum
              default value: 10
symprec     : symprec
              default value: 0.0001
-----

parameter information for <class
'magus.reconstruct.ga.CluSymMutation'>
+++++ Default parameters +++++
tryNum      : tryNum
              default value: 10
symprec     : symprec
              default value: 0.0001
-----

parameter information for <class
'magus.calculators.emt.EMTCalculator'>
+++++ Requirement parameters +++++
work_dir    : work dictionary
job_prefix  : calculation dictionary
+++++ Default parameters +++++
eps         : convergence energy
              default value: 0.05
max_step    : maximum number of relax steps
              default value: 100
optimizer   : optimizer method, choose from bfgs, fire,
lbfgs
              default value: bfgs
max_move    : max range of movement
              default value: 0.1
relax_lattice : if to relax lattice
              default value: True
pressure    : pressure
              default value: 0.0

```



```

-----
parameter information for <class
'magus.calculators.lammps.LammpsCalculator'>
+++++ Default parameters +++++
mode           : choose from parallel or serial
                  default value: parallel
pressure       : pressure
                  default value: 0.0
exe_cmd        : command line to run lammps
                  default value:
save_traj      : save_traj
                  default value: False
atomStyle      : atomStyle
                  default value: atomic
job_prefix     : job_prefix
                  default value: Lammps
+++++ Requirement_parallel parameters +++++
queue_name     : queue name
num_core       : num_core
work_dir       : work dictionary
job_prefix     : calculation dictionary
+++++ Default_parallel parameters +++++
pre_processing : serves to add any sentence you wish when
submitting the job to change system variables, load modules
etc.
                  default value:
wait_time      : wait_time
                  default value: 200
verbose        : verbose
                  default value: False
kill_time      : kill_time
                  default value: 100000
num_parallel   : num_parallel
                  default value: 1
pressure       : pressure
                  default value: 0.0
-----

parameter information for <class
'magus.calculators.mtp.MTPNoSelectCalculator'>
+++++ Default parameters +++++
mode           : choose from parallel or serial

```

```

                                default value: parallel
pressure      : pressure
                                default value: 0.0
force_tolerance: force_tolerance
                                default value: 0.05
stress_tolerance: stress_tolerance
                                default value: 1.0
min_dist      : min_dist
                                default value: 0.5
n_epoch       : n_epoch
                                default value: 200
job_prefix    : job_prefix
                                default value: MTP
+++++ Requirement_parallel parameters +++++
queue_name    : queue name
num_core      : num_core
work_dir      : work dictionary
job_prefix    : calculation dictionary
+++++ Default_parallel parameters +++++
pre_processing : serves to add any sentence you wish when
submitting the job to change system variables, load modules
etc.

                                default value:
wait_time     : wait_time
                                default value: 200
verbose       : verbose
                                default value: False
kill_time     : kill_time
                                default value: 100000
num_parallel  : num_parallel
                                default value: 1
pressure      : pressure
                                default value: 0.0

-----
parameter information for <class
'magus.calculators.mtp.MTPSelectCalculator'>
+++++ Default parameters +++++
mode          : choose from parallel or serial
                                default value: parallel
pressure      : pressure
                                default value: 0.0

```

```

xc                : xc
                  default value: PBE
weights           : weights
                  default value: [1.0, 0.01, 0.001]
scaled_by_force   : scaled_by_force
                  default value: 0.0
force_tolerance   : force_tolerance
                  default value: 0.05
stress_tolerance   : stress_tolerance
                  default value: 1.0
min_dist          : min_dist
                  default value: 0.5
n_epoch           : n_epoch
                  default value: 200
ignore_weights    : ignore_weights
                  default value: True
job_prefix        : job_prefix
                  default value: MTP
n_fail            : n_fail
                  default value: 0
+++++ Requirement_parallel parameters +++++
queue_name        : queue name
num_core          : num_core
work_dir          : work dictionary
job_prefix        : calculation dictionary
+++++ Default_parallel parameters +++++
pre_processing    : serves to add any sentence you wish when
submitting the job to change system variables, load modules
etc.

                  default value:
wait_time         : wait_time
                  default value: 200
verbose           : verbose
                  default value: False
kill_time         : kill_time
                  default value: 100000
num_parallel      : num_parallel
                  default value: 1
pressure          : pressure
                  default value: 0.0
-----

```

```

parameter information for <class
'magus.calculators.mtp.MTPLammpsCalculator'>
+++++ Default parameters +++++
mode           : choose from parallel or serial
                  default value: parallel
pressure       : pressure
                  default value: 0.0
xc             : xc
                  default value: PBE
weights        : weights
                  default value: [1.0, 0.01, 0.001]
scaled_by_force: scaled_by_force
                  default value: 0.0
force_tolerance: force_tolerance
                  default value: 0.05
stress_tolerance: stress_tolerance
                  default value: 1.0
min_dist       : min_dist
                  default value: 0.5
n_epoch        : n_epoch
                  default value: 200
ignore_weights : ignore_weights
                  default value: True
job_prefix     : job_prefix
                  default value: MTP
n_fail         : n_fail
                  default value: 0
+++++ Requirement_parallel parameters +++++
queue_name     : queue name
num_core       : num_core
work_dir       : work dictionary
job_prefix     : calculation dictionary
+++++ Default_parallel parameters +++++
pre_processing : serves to add any sentence you wish when
submitting the job to change system variables, load modules
etc.
                  default value:
wait_time      : wait_time
                  default value: 200
verbose        : verbose
                  default value: False

```

```

kill_time      : kill_time
                  default value: 100000
num_parallel   : num_parallel
                  default value: 1
pressure       : pressure
                  default value: 0.0
-----
parameter information for <class
'magus.calculators.quip.QUIPCalculator'>
+++++ Requirement parameters +++++
work_dir       : work dictionary
job_prefix     : calculation dictionary
+++++ Default parameters +++++
eps            : convergence energy
                  default value: 0.05
max_step       : maximum number of relax steps
                  default value: 100
optimizer      : optimizer method, choose from bfgs, fire,
lbfgs
                  default value: bfgs
max_move       : max range of movement
                  default value: 0.1
relax_lattice  : if to relax lattice
                  default value: True
pressure       : pressure
                  default value: 0.0
-----
parameter information for <class
'magus.calculators.vasp.VaspCalculator'>
+++++ Default parameters +++++
mode           : choose from parallel or serial
                  default value: parallel
pressure       : pressure
                  default value: 0.0
xc             : xc
                  default value: PBE
pp_label       : pp_label
                  default value: None
job_prefix     : job_prefix
                  default value: Vasp
+++++ Requirement_parallel parameters +++++

```

```

queue_name      : quene name
num_core        : num_core
work_dir        : work dictionary
job_prefix      : calculation dictionary
+++++ Default_parallel parameters +++++
pre_processing  : serves to add any sentence you wish when
submitting the job to change system variables, load modules
etc.

                        default value:
wait_time       : wait_time
                        default value: 200
verbose         : verbose
                        default value: False
kill_time       : kill_time
                        default value: 100000
num_parallel    : num_parallel
                        default value: 1
pressure        : pressure
                        default value: 0.0

-----
parameter information for <class
'magus.calculators.castep.CastepCalculator'>
+++++ Default parameters +++++
mode            : choose from parallel or serial
                        default value: parallel
pressure        : pressure
                        default value: 0.0
xc_functional   : xc_functional
                        default value: PBE
pspot           : pspot
                        default value: 00PBE
suffix          : suffix
                        default value: usp
job_prefix      : job_prefix
                        default value: Castep
kpts            : kpts
                        default value: {'density': 10, 'gamma':
True, 'even': False}
castep_command  : castep_command
                        default value: castep
castep_pp_path  : castep_pp_path

```

```

                                default value: None
+++++ Requirement_parallel parameters +++++
queue_name      : queue name
num_core        : num_core
work_dir        : work dictionary
job_prefix      : calculation dictionary
+++++ Default_parallel parameters +++++
pre_processing  : serves to add any sentence you wish when
submitting the job to change system variables, load modules
etc.

                                default value:
wait_time       : wait_time
                                default value: 200
verbose         : verbose
                                default value: False
kill_time       : kill_time
                                default value: 100000
num_parallel    : num_parallel
                                default value: 1
pressure        : pressure
                                default value: 0.0

-----
parameter information for <class
'magus.calculators.lj.LJCalculator'>
+++++ Requirement parameters +++++
work_dir        : work dictionary
job_prefix      : calculation dictionary
+++++ Default parameters +++++
eps             : convergence energy
                                default value: 0.05
max_step        : maximum number of relax steps
                                default value: 100
optimizer       : optimizer method, choose from bfgs, fire,
lbfgs
                                default value: bfgs
max_move        : max range of movement
                                default value: 0.1
relax_lattice   : if to relax lattice
                                default value: True
pressure        : pressure
                                default value: 0.0

```

```

-----
parameter information for <class
'magus.calculators.gulp.GulpCalculator'>
+++++ Default parameters +++++
mode           : choose from parallel or serial
                  default value: parallel
pressure       : pressure
                  default value: 0.0
exe_cmd        : command line to run gulp
                  default value: gulp < input > output
job_prefix     : job_prefix
                  default value: Gulp
+++++ Requirement_parallel parameters +++++
queue_name     : queue name
num_core       : num_core
work_dir       : work dictionary
job_prefix     : calculation dictionary
+++++ Default_parallel parameters +++++
pre_processing : serves to add any sentence you wish when
submitting the job to change system variables, load modules
etc.
                  default value:
wait_time      : wait_time
                  default value: 200
verbose        : verbose
                  default value: False
kill_time      : kill_time
                  default value: 100000
num_parallel   : num_parallel
                  default value: 1
pressure       : pressure
                  default value: 0.0
-----

parameter information for <class
'magus.calculators.base.AdjointCalculator'>
+++++ Requirement parameters +++++
work_dir       : work dictionary
job_prefix     : calculation dictionary
+++++ Default parameters +++++
pressure       : pressure
                  default value: 0.0

```



```
-----  
parameter information for <class  
'magus.calculators.mtp.TwoShareMTPCalculator'>  
+++++ Requirement parameters +++++  
work_dir      : work dictionary  
job_prefix    : calculation dictionary  
+++++ Default parameters +++++  
pressure      : pressure  
                default value: 0.0  
-----
```