

BBO on trade (TBBO)

BBO on trade (TBBO) provides every trade event alongside the BBO immediately *before* the effect of each trade. This is a subset of [MBP-1](#).

Databento groups this under [top of book \(L1\)](#).

Fields (`tbbo`)

Field	Type	Description
<code>ts_recv</code>	uint64_t	The capture-server-received timestamp expressed as the number of nanoseconds since the UNIX epoch. See ts_recv .
<code>ts_event</code>	uint64_t	The matching-engine-received timestamp expressed as the number of nanoseconds since the UNIX epoch. See ts_event .
<code>rtype</code>	uint8_t	A sentinel value indicating the record type. Always 1 in the TBBO schema. See Rtype .
<code>publisher_id</code>	uint16_t	The publisher ID assigned by Databento, which denotes the dataset and venue. See Publishers .
<code>instrument_id</code>	uint32_t	The numeric instrument ID. See Instrument identifiers .
<code>action</code>	char	The event action. Always Trade in the TBBO schema. See Action .
<code>side</code>	char	The side that initiates the trade. Can be Ask for a sell aggressor in a trade, Bid for a buy aggressor in a trade, or None where no side is specified. See Side .
<code>depth</code>	uint8_t	The book level where the update event occurred.
<code>price</code>	int64_t	The order price where every 1 unit corresponds to 1e-9, i.e. 1/1,000,000,000 or 0.000000001. See Prices .
<code>size</code>	uint32_t	The order quantity.
<code>flags</code>	uint8_t	A bit field indicating event end, message characteristics, and data quality. See Flags .
<code>ts_in_delta</code>	int32_t	The matching-engine-sending timestamp expressed as the number of nanoseconds before <code>ts_recv</code> . See ts_in_delta .
<code>sequence</code>	uint32_t	The message sequence number assigned at the venue.
<code>bid_px_00</code>	int64_t	The bid price at the top level where every 1 unit corresponds to 1e-9, i.e. 1/1,000,000,000 or 0.000000001. See Prices .
<code>ask_px_00</code>	int64_t	The ask price at the top level where every 1 unit corresponds to 1e-9, i.e. 1/1,000,000,000 or 0.000000001. See Prices .
<code>bid_sz_00</code>	uint32_t	The bid size at the top level.
<code>ask_sz_00</code>	uint32_t	The ask size at the top level.
<code>bid_ct_00</code>	uint32_t	The bid order count at the top level.
<code>ask_ct_00</code>	uint32_t	The ask order count at the top level.

Implementation differences between clients and encodings

Bid and ask depth messages (fields starting with `bid_` and `ask_`) are structured differently in the **C++ and Rust clients**, the **Python record interface**, and **JSON data**. Instead of using the `_N` suffix, they're stored in an array of structures named `levels`, with the top-of-book at index `0`.

For example, in C++, `levels[5].bid_px` corresponds to `bid_px_05` in the Python DataFrame API and CSV format.

 See also

TBBO has many similarities to the MBP-1 and BBO schemas. The main distinction is that TBBO is in trade space, while MBP-1 is in book update space, and BBO is in time space. In particular, the `action` type of TBBO is always Trade. Learn about the differences between each in our [MBP-1 vs. TBBO vs. BBO schemas guide](#).

Consolidated BBO on trade (TCBBO)

Consolidated BBO on trade (TCBBO) provides every trade event alongside the consolidated BBO immediately *before* the effect of each trade. This is a subset of [CMBP-1](#).