

Paramètres de l'API

A. User roads

A.1 create user

A.2 get user

A.3 edit user

B. Recipe roads

B.1 create recipe

B.2 get all recipes

B.3 get one recipe

B.4 edit recipe

A. User roads

http://localhost:3000/api/user

| | verb | endpoint | body | response |
|-----|------|----------|---|--|
| A.1 | POST | /create | { "username": string, "email": string, "password": string, "lastname": string, "firstname": string } | |
| A.2 | GET | / | | { "username": string, "email": string, "password": string, "lastname": string, "firstname": string } |
| A.3 | PUT | /edit | { "username": string (optional), "email": string (optional), "lastname": string (optional), "firstname" : string (optional), "oldPassword": string, "newPassword": string (optional) } | |

B. Recipe roads

http://localhost:3000/api/recipe

| | verb | endpoint | body | response |
|-----|------|----------|--|---|
| B.1 | POST | / | <pre>{ "recipe": { "title": string, "duration": string, "preparation": [string, string, ...], "img": string, "category": string }, "ingredients": [[string , int, string], [string , int, string], ...] }</pre> | |
| B.2 | GET | / | | <pre>[{ "id": int, "id_user": int, "created_at": string, "img": string, "duration": string, "title": string, "ingredients": [string, string...] }, { ... }</pre> |

| | | | | |
|-----|-----|------|--|--|
| B.3 | GET | /:id | | <pre> { "id": int, "author": string, "date": string, "duration": string, "title": string, "preparation": [string, string...], "img": string, "category": string, "ingredients": [{ "name": string, "quantity": int, "unit": string }, { ...], } </pre> |
| B.4 | PUT | /:id | <pre> { "editedRecipe": { "title": string, "duration": string, "preparation": [string, string, ...], "img": string, "category": string, "editedIngredients": [[string , int, string], [string , int, string], ...] } } </pre> | |