AN EVALUATION OF RESERVATION-BASED SERVING FOR LONG-HORIZON AGENTIC WORKLOADS

Sumit P. Ahuja [1]

ABSTRACT

We specify a serving-layer discipline for long-horizon agentic workloads, a completion-oriented resource contract transferring four lessons packet networking paid for, rationed per-flow guarantees, early probabilistic class-aware shedding, fate-independent supervision, and provenance-bound authority, and we evaluate its central economic claim under a pre-registered protocol: the metric, the kill thresholds, and the baseline tuning discipline were frozen and committed before any evaluation system existed, and every subsequent change is a numbered amendment released with the paper. The claim is that per-flow completion guarantees, jointly covering compute, a cumulative cross-invocation token budget, and pinned cache, with a hard non-preemption guarantee, buy more completed work per provisioned GPU-hour than they strand. Across 108 cells against six equally tuned baselines at identical simulated hardware, the answer is no: a median 10.3 percent loss to the best per-cell baseline, 0 of 108 cells supporting, and the graceful-degradation hypothesis reversed at the corrected horizon. The cost is structural: agentic flows idle in tool time at roughly a 5 percent duty cycle, so reserved capacity is stranded at least 88 percent regardless of configuration, and the deficit peaks exactly at nominal provisioning. What guarantees buy is also measured: 63.3 to 97.1 percent interactive tail-latency isolation across most of the region, bounded containment of runaway flows where the strongest request-oriented schedulers starve compliant agentic work to zero, and a sign flip in the mechanism's favor past saturation. The discipline's enforcement properties, admission where policy binds, a budget that fixes any runaway's worst case in advance, an audit ledger, and a kill authority outside the model's reach, were never throughput claims; two are measured here in the mechanism's favor and the rest hold by construction. We additionally report a measurement lesson: evaluation horizons shorter than the workload's flow lifetimes silently corrupt both completion metrics and baseline tuning, and we give the structural fix. All code, generators, seeds, manifests, the amendment history, and the superseded preliminary readouts are released.

1 INTRODUCTION

Serving systems for large language models schedule work as preemptible requests. A growing class of workloads arrives in a different shape: long-horizon agentic flows, units of work with stable identity across many model invocations, accumulating cache and tool state whose loss destroys progress, idling between invocations while tools and humans respond, and delivering value only at completion. This paper specifies a serving discipline built for such flows, a completion-oriented resource contract granted at admission, and evaluates it under a specification frozen before the evaluation system existed, with published thresholds under which the proposal's central claim dies. The discipline is not invented from first principles: each element transfers a lesson packet networking paid for, rationed per-flow guarantees over aggregate classes, early probabilistic class-aware shedding, fate-independent supervision, and provenance-bound authority at the edge. One transfer is deliberately incomplete, since the discipline keys shedding to a ledger of forward commitments rather than to queue depth, and Appendix D gives the four lessons in full with the expanded transfer table.

The evaluation begins somewhere unexpected. Under a mixed workload at moderate overload, the two strongest request-oriented baselines in our set complete zero compliant agentic flows, scheduling 1 of 107 and preempting none: admission starvation, not preemption churn. That failure is also invisible to the audit mechanisms being specified for agentic systems, because those mechanisms record events and this failure consists of their absence. Investigating it exposed a measurement artifact in our own campaign, a horizon shorter than the workload's flow lifetimes, which right-censors completion metrics and, less obviously, corrupts baseline tuning. Correcting it changed what the primary comparison measured.

The corrected comparison kills the proposal. Across 108 pre-

[1]Main Labs. Correspondence to: Sumit P. Ahuja <sumit@mainlabs.ai>.

Preprint. Licensed CC BY 4.0.

registered cells against six equally tuned baselines at identical simulated hardware, reservation-based serving loses a median 10.3 percent of goodput per provisioned GPU-hour and supports the hypothesis in 0 of 108 cells; the secondary graceful-degradation hypothesis is likewise killed, reversing sign once the horizon was corrected. The cost is structural rather than configurational. An agentic flow runs a short invocation and then waits in tool time, a duty cycle of roughly 5 percent by construction, so reserved capacity is stranded 88 to 95 percent regardless of configuration, and the deficit peaks exactly at nominal provisioning where work-conserving schedulers are at their best.

What the guarantees buy is measured rather than argued away: interactive tail latency improves by 63.3 to 97.1 percent across most of the region, an isolation operators currently purchase by overprovisioning and that the discipline prices in stranded capacity instead; runaway flows are contained to a bounded degradation; and past saturation the sign of the primary comparison flips. The mechanism's enforcement properties were never throughput claims, and two of them are measured here: the budget contains a runaway to a bound fixed at admission, and the distinction between a priority and a contract shows up as 106 of 107 compliant flows starved under the former and half completed under the latter. What the evaluation removes is the ability to sell any of it as free. This paper contributes: a serving-layer discipline for long-horizon agentic flows, specified to the depth required to judge its evaluation (Section 3, with the full specification in Appendix A); the first controlled comparison of completion-oriented against preemption-oriented scheduling for such workloads, seven policies on identical hardware with byte-identical workload realizations per cell under an equal-budget tuning protocol enforced by test (Sections 4 to 6); a measured starvation result for request-oriented scheduling under agentic load, with its observability consequence (Section 6.1); a measurement-methodology finding with a structural fix, quantified (Section 6.2); and a quantified decomposition of what completion guarantees cost and what they buy (Sections 6.3 to 6.6). The pre-registration machinery, frozen thresholds, a numbered amendment log, an input-domain guard on the verdict path, and the release of every artifact including superseded readouts, is described as method, because for a paper whose headline is its own proposal's death the method is the product.

2 FLOWS, NOT REQUESTS

The reorganization of the serving stack is not a proposal anyone needs to make; it is happening. Mozilla.ai's articulation of an LLM control plane names the three-plane split explicitly and maps it onto LLM infrastructure (Gupta, 2026); NVIDIA's Dynamo separates scheduling and placement from execution in a disaggregated runtime (NVIDIA Corporation, 2025); AIBrix builds control-plane machinery as a first-class system layer (Shan et al., 2025); and external control planes with explicit admission control are appearing for agentic workloads specifically (Wang et al., 2026). What the new layer provides, across these systems and the commercial gateways around them, is a consistent portfolio: authentication and routing, rate limits, per-request and per-session budget caps (LiteLLM, 2026; Wang, 2026), priority scheduling with preemption (Kwon et al., 2023), and reserved throughput sold at the account level (Amazon Web Services, 2026; Microsoft Corporation, 2026). Each mechanism is useful. Together they constitute a control plane built on one implicit assumption: that the unit of work is a request, that any request may be delayed, preempted, migrated, or dropped under pressure, and that fairness and efficiency are properties of request streams.

The workload violates the assumption. A flow, an agent executing a task, a multi-step job with a declared objective, has five properties that defeat specific mechanisms of the request-oriented portfolio. It spans tens of invocations whose count is unknown at start, so per-invocation latency optimization compounds queueing delay across the flow and tail completion is governed by the worst episode. It accumulates key-value cache and tool state that are its progress, so preemption with recompute-on-resume or swap-and-requeue does not delay the work but destroys it. It idles between invocations for seconds to minutes while tools and humans respond, and under request accounting an idle flow's resources are fair game, so resumption becomes randomized restart; the idle gap is also, we note at the outset, the strongest argument against the discipline this paper proposes and prices. Its value is concentrated at completion, so a flow abandoned at ninety-five percent of its invocations delivers nothing at ninety-five percent of its cost, inverting the economics that make preemption cheap for divisible work. And its consumption is unbounded by default, an agent in a defective or adversarial loop drawing tokens across invocations that per-request caps structurally cannot see, while session-level budget ceilings (LiteLLM, 2026; Wang, 2026) answer the accumulation with rejection, converting the entire prior spend into waste at the moment of enforcement.

The portfolio, taken together, provides caps that see flows but cannot feed them, schedulers that feed work but cannot promise it anything, and account-level floors that promise capacity but cannot see flows. Nothing guarantees that a specific task, admitted deliberately, will finish or be deliberately stopped; and because no mechanism binds authority to a specific flow, the portfolio offers no enforcement point for governing one. The missing object is a completion-oriented resource contract: resources sufficient to finish, granted at admission and not silently withdrawn; a bound enforced as part of the same contract rather than as an ambush at a ceiling; and a designated authority, outside the flow, entitled

to stop it. Section 3 specifies a discipline providing exactly these clauses. Whether the contract is worth its price is the question the rest of the paper answers.

3 THE RESERVATION DISCIPLINE

The discipline adds one object and one decision to the serving stack. The object is the reservation: a ledger entry binding a flow to a guaranteed resource vector for a lifetime. The decision is admission: whether a flow enters the small reserved subset, enters an aggregate service class, or is declined early. Everything else in this section is the precise semantics of those two things, together with the supervisory and trust elements that complete the contract. We emphasize at the outset what the discipline keeps: the gateway accounting of Section 2 remains the identity and metering substrate, and the scheduling engines of Section 2 remain the execution machinery. The discipline sits at admission and constrains what those layers may do to an admitted flow; it replaces neither.

A flow arrives with a descriptor: an estimated invocation count, a requested cumulative output-token budget, an estimated cache footprint, a service class, and a provenance class. Admission to the reserved subset requires five conditions jointly, of which the load-bearing ones are that the subset holds fewer than K flows, that projected commitment over a forecast window stays under a configured ceiling, and that some device set can hold the flow's cache footprint under the pinning rules. A flow failing any condition is served in an aggregate class or declined early, which is the cheapest moment in a flow's life to say no.

An admitted reservation covers three resources jointly, and the jointness is the point, because a flow starved on any one of them fails entirely: a compute share sufficient for its class latency budget, a cumulative output-token budget metered at decode across every invocation of the flow, and key-value cache pinned against eviction and migration for the reservation lifetime, including across the idle gaps between invocations. The budget is simultaneously a floor and a bound. Budgeted capacity is committed, so the flow cannot be silently starved out of it, and the flow cannot exceed it, so a runaway is a contained event rather than a discovered one. Pinning has two embodiments, strict and tiered, the latter spilling to a guaranteed restore path between invocations; the evaluation prices both without favour.

The guarantee is stated negatively, and the reason is a claim about auditability rather than style: for the reservation lifetime, no resource-motivated action of the serving stack may preempt the flow's invocations, evict or migrate its pinned cache, or reclaim its committed budget. A prohibition can be audited for violations; a permission cannot be audited for its non-occurrence. The sole override is a halt issued by the management plane, which is a safety revocation under designated authority and definitionally not scheduler preemption, since no capacity condition can trigger it. A guarantee with a capacity-triggered escape clause is a priority, and priorities are what the schedulers of Section 2 already have.

All other traffic runs in aggregate service classes with latency budgets and scheduling weights, degraded under pressure by a probabilistic ladder whose probability is keyed to committed headroom computed from the reservation ledger rather than to observed queue depth. That keying is a design claim the evaluation tests directly, not an assumption it rests on.

Two elements complete the contract and were never economic claims. A management plane holds pre-authorized halt, steer, and escalate authority in a failure and trust domain separate from the inference stack, which yields four properties that hold by construction: admission is where organizational policy binds to a flow, the budget fixes any runaway's worst case in advance rather than in an incident review, the reservation ledger is the audit record, and the halt does not route through the model being doubted. Two of the four are measured here rather than asserted: Section 6 reports what the budget does under adversarial injection, and what the difference between a priority and a contract costs the flows subject to it. Trust-keyed admission gates reservation eligibility on the provenance of the content driving a flow, fixed before that content is interpreted. Appendix A carries the full specification: the admission test, the ledger invariants, the budget-exhaustion vocabulary, lease and multi-tenant semantics, and the survivability embodiment.

4 PRE-REGISTERED DESIGN

The evaluation specification was frozen on 2026-07-06, before any simulator code existed, and committed to an append-only repository; the frozen text with its complete amendment log is released with this paper (EvalSpec). This section restates its commitments; the specification governs where they differ.

Primary metric. Task-level goodput per provisioned GPU-hour: value-weighted completed flows per hour, normalized by provisioned capacity. The normalization is the honesty mechanism: capacity a reservation holds idle lowers the discipline's own score arithmetically, so stranding, the mechanism's known cost, is priced inside the headline number rather than negotiated beside it. Value weights are fixed in the specification and varied only in a declared sensitivity sweep. Related serving metrics score completed requests against latency targets (Wang et al., 2026); ours differs in unit and denominator, flow completions valued per provisioned GPU-hour, so that held-but-idle guarantees are

charged to the discipline that holds them.

Thresholds, fixed before data. Support required a median improvement of at least 10 percent over the best baseline, selected per cell as the strongest tuned opponent in that cell (deliberately conservative against the mechanism), across at least 60 percent of the core region, with interactive-traffic p95 time-to-first-token degradation held under 5 percent. Below 5 percent median improvement, or on guardrail violation across the region: kill. Between: a weak result. The verdict is computed mechanically by released code as a pure function of the run manifests.

Region. The core region spans interactive-to-agentic traffic mixes (90/10, 70/30, 50/50 by token volume), offered loads 0.7 to 1.5 times measured capacity, idle-gap distributions with medians of 20, 60, and 300 seconds, and cluster sizes of 8 to 32 devices (Amendment 3, below). Corner cells were pre-declared excluded; none required exclusion in the final grid.

Baselines and fairness. Six baselines: vLLM-style priority scheduling with preemption and paged cache (Kwon et al., 2023); FastServe-style multi-level feedback queues (Wu et al., 2023); Niyama-style deadline-aware class scheduling, implemented here with a deterministic demotion ladder (Goel et al., 2026); CONCUR-style AIMD admission with pause/resume (Chen et al., 2026); a MARS-style external admission controller with cost-benefit cache retention (Wang et al., 2026), added by Amendment 1; and FCFS continuous batching as the no-control floor. Every tunable policy, including ours, received an identical tuning budget: an 8-point pre-registered grid, tuned per workload family on validation seeds and scored on disjoint held-out seeds, with a build-failing test asserting no policy's grid is larger than any other's. Each baseline is a policy-family abstraction rather than a reimplementation of any single system: the families are named for the work that characterises them, and the comparison is against the scheduling discipline each represents. The tuned parameters and both scores are released (Table 1, in Appendix G).

The registration carries three numbered amendments and one integrity ruling, each dated, reasoned, and adopted before the final grid ran: a baseline added because a negative headline makes baseline completeness load-bearing, a measurement horizon corrected, and the grid's device axis reduced after measured infeasibility. All were adopted under a one-fix clause barring any further measurement correction in either direction, which is why the verdict below stands as computed; Appendix E gives the log in full.

5 Simulator and integrity

The evaluation runs on a discrete-event simulator at invocation granularity with token-rate service models: cluster of devices with per-device memory, batch-size-dependent decode throughput, prefill cost, and modeled host spill; validated against closed form (Little's law holds to 0.00 percent on a degenerate configuration, utilization tracks offered load within 1 percent, and these sanity numbers remained bit-identical through every subsequent engine change).

Two design rules carry the comparison's fairness. First, strict policy/engine separation: the engine owns all physics, what preemption costs in both recompute and swap variants, how pinning constrains paging, how budgets are metered at decode, and the physics are identical for every policy; policies are pure decision modules behind one interface, and the reservation ledger's invariants (no over-commitment of compute, memory, or budget under any event interleaving; no capacity condition in any release path) are engine-enforced hard test failures. Second, paired comparison: within a cell, every policy runs against byte-identical workload realizations from shared seeds, verified by test, so cross-policy deltas are not workload noise.

Service-model constants (single-stream decode rate, peak decode, cache bytes per token, spill bandwidth) are literature-anchored and marked low confidence; Section 6.6 reports their measured sensitivity, including which constants bind in which regimes and why. No hardware phase was run: the program gated hardware confirmation on this evaluation supporting the mechanism, and the gate closed.

Three construction defects were caught by the engine's own invariants before the campaign ran, and one of them was depressing the work-conserving baselines that go on to win the final comparison, so leaving it unfixed would have made the mechanism's loss look smaller for a reason unrelated to scheduling. Two further interventions occurred during the campaign and are disclosed in the released readouts: 189 pre-amendment manifests were quarantined behind a new input-domain guard, and two baseline runs that reached congestion collapse were excluded with their selection effect stated, a bias that favours the affected baselines and therefore runs against the mechanism this evaluation killed. Appendix F records all five.

6 Results

All numbers are from the final campaign: 2,268 H1 runs over 108 cells at the Amendment 2 horizon, 252 H2 runs, 84 H3 runs, and 162 ablation runs over two operating points, with full manifests released. Figures and tables supporting each result beyond the two carried inline are in Appendix G, and the full per-cell table is Appendix H. Two baseline runs reached congestion collapse at the wall-clock cap and are excluded with their selection effect disclosed in the readout; the exclusion flatters the affected baselines and therefore runs against the mechanism.




Figure 1. Compliant-flow completion under adversarial runaway injection, absolute rates. The reservation discipline holds near 0.5 with a worst-case degradation of 3.1 points; FCFS completes 0.33 with no containment; the two strongest request-oriented baselines complete zero compliant flows at every level including no injection, instrumented admission starvation (one of 107 compliant flows ever scheduled, zero preemptions; Section 6.1). Deltas against zero are undefined, which is why rates are absolute.

6.1 Request-oriented schedulers starve agentic flows

The campaign's first result is not about reservations. Under a mixed workload at 1.2x offered capacity, the two strongest request-oriented baselines in the set, vLLM-style priority scheduling with preemption and Niyama-style deadline-aware class scheduling, complete 0.000 of compliant agentic flows. Not a degraded fraction: zero, at every level of adversarial injection including no injection at all (Figure 1).

This is not a missing measurement. Instrumentation of the cell shows those policies schedule 1 of 107 compliant agentic flows, with zero preemptions. Under interactive-class priority, long flows never receive a device slot while interactive traffic saturates the cluster. The failure is admission starvation rather than preemption churn, and the result is locked by a regression test. A delta against zero is undefined, which is why this section reports absolute completion rates throughout.

The starvation is also invisible to the audit mechanisms being specified for agentic systems, and that consequence is worth stating separately because it generalizes beyond scheduling. Those mechanisms are event-based: they record what a flow did, which tools it called, what it returned. A flow that is admitted, never scheduled, and still live at the horizon produces no events to record, and a conformant audit trail for such a flow is an honest and indefinitely long sequence of nothing having happened. The failure consists of the absence of events, so event-triggered analysis cannot surface it without a liveness test: the record is complete, and the fault is invisible inside it.

Against that baseline, the discipline's cross-invocation budget does what it was specified to do. Compliant-flow completion holds at 0.503, 0.475, 0.499 and 0.471 across injection levels, a worst-case degradation of 3.1 points, and every runaway is cut off at exactly its budget. FCFS, blind to class, completes 0.332 and degrades 5.0 points under injection: no isolation and no containment, but no starvation either. The discipline is the only policy in the set that is simultaneously above 0.3 absolute and below 3.5 points of adversarial degradation. Section 3 distinguished a priority from a contract as a matter of kind; this is that distinction as a matter of record. Appendix G tabulates every policy's rate at every injection level.

6.2 The horizon lesson

Investigating those zeros produced the campaign's most generalizable finding, and it concerns measurement rather than scheduling. The diagnostic that established the starvation as genuine also showed that every sweep in the campaign was running a measurement horizon far shorter than the workload's own timescale.

The median agentic flow requires roughly 711 seconds to complete with no queueing at all, tool-time gaps plus decode service; the figure was first measured at roughly 863 seconds on the diagnostic realization that surfaced the problem, and the released generator derivation, which any reader can run, gives 711. The build's default horizons ran 150 to 300 seconds, and at a 200-second window only about a quarter of agentic flows could complete on an idle cluster. The primary metric counts completed flows. A window shorter than the unit of value does not measure the metric; it measures truncation.

The bias is not symmetric, and it points at completion-guaranteeing policies specifically. A reservation pays its stranding cost during the flow and collects its payoff at completion; a horizon that ends before completion charges the full cost against zero payoff, the mechanism's worst case by construction, while policies that never schedule long flows at all are barely touched. Quantified on one core cell (Figure 2), the discipline's deficit against the best baseline was 22.3 percent at a 300-second horizon and 7.8 percent at 1500 seconds, stable through 6000 seconds; at the longest horizon the discipline completed more flows in absolute terms than its comparator while still losing on value-weighted goodput, a real loss, but half the reported one.




Figure 2. Horizon censoring on one core cell. The population median agentic flow lifetime, derived from the released workload generators, is roughly 711 seconds (first measured at 863 seconds on the diagnostic realization that surfaced the artifact, open markers); at a 200-second window only about a quarter of agentic flows can complete even on an idle cluster (24.5 percent of the population; 21.5 percent of the diagnostic realization), while the campaign's default horizons ran 150 to 300 seconds. The measured deficit is 22.3 percent at a 300-second horizon and halves to 7.8 percent at adequate horizons, stable through 6000 seconds. Horizons shorter than the workload's completable lifetimes charge guarantee-holders full stranding cost against zero completion payoff (Section 6.2).

Censoring corrupts tuning as well as measurement. Retuning every policy at the corrected horizon flipped selected parameters across the board, most cleanly for the multi-level feedback baseline, whose chosen quantum moved from the shortest value in its grid to the longest in every workload family: under a censored horizon aggressive demotion looks good because long flows are truncated before their cost lands. An evaluation that had tuned at 300 seconds and measured at 1500 would have compared the mechanism against baselines mis-tuned in its favour. Both tuning campaigns are released, and the fix is structural rather than vigilant: the released code asserts before any sweep runs that the configured horizon exceeds the workload's derivable median flow lifetime, and the verdict path independently rejects any manifest whose horizon disagrees with the grid it claims to report. The correction was adopted as a numbered amendment before the final grid ran, under a one-fix clause barring further measurement changes in either direction, and its full history, including that it improved the mechanism's number on the probe cell and worsened it on the served-value comparison, is in the released amendment log. The rule generalizes to any completion-metric evaluation of long-horizon agents: horizons must exceed the completable-lifetime distribution of the workload, or the benchmark measures its own window. We found the cost of honouring it to be severe, superlinear in the horizon under sustained overload, and it forced a disclosed reduction of our own grid; we suspect the rule is widely violated for exactly that reason.

6.3 What completion guarantees cost

Correcting the horizon changed what the primary comparison measured, and the corrected comparison is the verdict. Computed mechanically against the frozen thresholds, reservation-based serving loses a median 10.3 percent of goodput per provisioned GPU-hour to the best per-cell tuned baseline, supports the hypothesis in 0 of 108 cells against a 60 percent requirement, and holds the interactive guardrail in 96 percent of cells. Under the specification's thresholds, the hypothesis is killed. The per-cell improvements are plotted in Appendix G.

The loss has structure worth more than its median. Across offered load it is U-shaped: at 0.7x capacity the deficit runs 6.6 to 16.1 percent; at 1.0x it is deepest, 22.4 to 23.6 percent in every cell; at 1.3x it recovers to 9.5 to 11.5 percent; and at 1.5x the sign flips, with reservation ahead by 0.8 to 3.2 percent in all 24 non-guardrail-failing cells. The deficit peaks exactly where the cluster is well-provisioned: at nominal load the work-conserving baselines run at maximum efficiency while reservations strand capacity across idle gaps, and as load rises past saturation the baselines begin to thrash while stranding matters relatively less, until the ordering inverts at the top of the region. Completion guarantees, on this evidence, are most expensive precisely when the fleet is

sized correctly.

The other axes are quieter. Cluster size is nearly flat: 8-, 16- and 32-device cells agree within roughly a point throughout, which bears on the amendment that reduced the device axis, since nothing in the measured trend suggests the removed 64-device axis behaves categorically differently. Idle-gap distribution has a mild, consistent effect: longer gap medians shrink the deficit at low load, because they favour the tiered-pin embodiment's spill-and-restore over holding hot capacity. At three seeds the paired bootstrap intervals are tight and solidly negative in the load 1.0 band, wider at 0.7x where several upper bounds cross zero. The verdict does not depend on how those intervals are read: taking every cell at its most favourable bound, 33 of 108 would reach the support threshold, against the 65 the criterion requires. Both the cluster-size agreement and the per-cell intervals are read from the full table in Appendix H.

6.4 What they buy, and where it inverts

The guardrail was pre-registered as a constraint, interactive p95 time-to-first-token degraded no more than 5 percent, and the mechanism did not merely satisfy it: in most of the region it inverted it. At and above nominal load, reservations improve interactive tail latency by 63.3 to 97.1 percent relative to the best baseline, above 90 percent in most such cells, while reserved-idle fraction runs 93 to 100 percent in 77 of 81 such cells. Three load-1.5 cells sit at 88.9 percent, admission having granted few reservations there, and one cell is degenerate at zero, admission having granted none. Read together with Section 6.3, this is the ledger's purchase side made precise: the 9.5 to 23.6 percent goodput deficit buys near-order-of-magnitude tail-latency protection for interactive traffic, by structurally keeping long flows off the shared pool. Operators who price interactive tail latency highly are buying exactly this, and today they buy it by overprovisioning; the discipline prices the same isolation in stranded capacity instead. Both per-cell series, tail latency and reserved-idle fraction, are plotted in Appendix G.

The purchase fails in one measured corner. At heavy agentic mix, overload, and short gaps, the guardrail fails spectacularly, interactive p95 time-to-first-token worse by 468.6 to 526.5 percent across all three cluster sizes. The mechanism is legible: with half the token volume agentic, gaps short enough that reserved flows cycle almost continuously, and offered load half again over capacity, the reserved subset occupies the machine and interactive traffic starves on the residue. Isolation is a property of the regime rather than of the mechanism, and it reverses exactly where reservations are densest and the machine is most oversubscribed. One further isolated failure, at low agentic mix and nominal load against a FastServe baseline, does not repeat at any neighbouring cell.

6.5 Secondary hypotheses and ablations

The second pre-registered hypothesis held that degradation keyed to committed headroom yields a better served-value curve under overload than deterministic demotion and preempt-and-requeue. It does not. Over the full load sweep from 0.5x to 3.0x, the discipline's served-value area under curve is 0.626 against the best baseline's 0.648, a 3.4 percent deficit, with two further baselines ahead of it. The comparison carries only corrected-horizon data: an earlier censored-horizon reading was ruled unverified and excluded from the released record, and Section 6.2 explains why censored-horizon comparisons mislead. Two baselines collapse under overload on this metric, both of which protect the system by throttling intake and pay for it in served value. The full sweep, with every policy's curve and area, is in Appendix G. One characterisation requires care. Our implementation of the deadline-ordered family uses a demotion ladder, while the work it is named for relegates violating requests to an opportunistic queue rather than demoting them, so the comparison here is against the deadline discipline rather than against that system's degradation mechanism. The distinction does not enter the number: under the equal-budget protocol the tuner drove that policy's demotion threshold to its maximum in every workload family, so demotion never fires at the tuned point and the comparison is effectively against deadline-ordered scheduling with preemption. A second divergence is not neutralised that way: the published scheduler interpolates between deadline order and remaining-work order, while ours orders by class and then deadline alone.

The ablation campaign removes one element at a time from the tuned discipline at two operating points: an uncontended nominal-load cell, and a contended cell with four times the decode slots, elevated load, and the grid's shortest gaps. Across both, no element shows an effect on the primary metric distinguishable from seed noise. At the contended cell the total goodput spread across all nine variants is 0.68 percent against a within-variant seed spread whose median is 29 percent. One apparent effect appeared and did not survive: at the nominal cell, replacing headroom-keyed degradation with queue-depth keying improved goodput by 20.9 percent, but the effect vanished at the contended cell and sits within the nominal cell's own seed spread; an earlier internal readout called it corroborating evidence, and that reading is withdrawn in the released, corrected document. With three seeds a per-element median is a draw from a distribution wider than the effects being measured, and this design cannot separate an inert element from an unexercised one. That noise floor is a property of the ablation design rather than of the primary comparison: the per-cell deltas of Section 6.3 are paired, every policy scoring byte-identical workload realizations, which cancels the workload draw that dominates the unpaired spread here.

What the campaign does establish is robust because it is large and consistent rather than a difference between near-identical numbers. Reserved capacity sits 88 to 95 percent idle across both ablation operating points, a wider and lower band than Section 6.4's because it includes the contended cell rather than only the at-or-above-nominal grid cells, despite the contended cell's quadrupled slots, elevated load and minimal gaps. An agentic flow runs a short invocation and then waits in tool time, a duty cycle of roughly 5 percent by construction, so capacity reserved for such flows is stranded nine parts in ten regardless of configuration. The mechanism's cost is not located in any single element; it is located in the duty cycle of the workload the mechanism reserves for. The tuning campaign's independent result points the same way at larger scale: under the equal-budget protocol the tuner drove the reserved-subset bound to its grid floor, 5 percent, in every workload family at both horizons; the tuned-parameter table in Appendix G shows the corrected-horizon campaign, and both campaigns are released. Optimized truthfully, the mechanism minimizes itself.

6.6 Fidelity: what the numbers are conditioned on

Every number above is conditioned on the simulator's service model, so the evaluation measured which of that model's constants the result actually depends on rather than asserting that it does not depend on them.

One constant binds and it is material. The single-stream decode rate sets service time: at 0.7x the anchored value, the representative cell's deficit compresses from 21.5 to 4.4 percent; at 1.3x it is 13.0 percent. The sign of the verdict is robust across the tested range while the magnitude is uncertain at roughly the factor the anchor itself is uncertain. That is the paper's principal fidelity caveat, and it is unresolvable here because the hardware phase was gated on this evaluation supporting the mechanism and the gate closed. Appendix G tabulates the per-constant figures.

Two further constants, peak decode rate and cache bytes per token, do not move the representative cell's result at all, and the released binding analysis shows why with instrumentation rather than assertion. At 16 decode slots the batch is capped below the size at which peak decode can bind, and it was the binding term in 0 of 19,342 decode calls; peak memory occupancy stays near 39 percent of capacity, so a 30 percent perturbation changes no placement decision. The same instrumentation was then run at a deliberately memory-bound configuration, 64 slots with an agentic-heavy mix at elevated load, where both constants demonstrably bind: peak decode governs 43 percent of decode calls and memory saturates. The harness therefore detects binding where binding exists, and the main grid's device configuration sits in the compute-bound regime. Regression tests pin all three properties.

7 Discussion

The ledger, in one place. Completion guarantees cost a median 10.3 percent of goodput per provisioned GPU-hour in the tested region, and the cost is U-shaped in load: deepest, 22.4 to 23.6 percent, exactly at nominal provisioning, recovering toward saturation, inverting past it. They buy three measured things: interactive tail-latency isolation of 63.3 to 97.1 percent across most of the region, with one identified inversion corner; containment of adversarial runaways to a 3.1-point degradation where the strongest request-oriented schedulers starve compliant agentic work to zero; and a regime boundary at 1.5x load beyond which the guarantee begins to pay for itself. The efficiency thesis, that the purchases outweigh the cost on a single hardware-normalized metric, is dead on its own pre-registered terms. What survives is a price list.

The honest reading of the mechanism, then, is not "efficiency technique that failed" but "insurance product whose premium is now known." Fleets that are well-provisioned and run nominal load sit at the bottom of the U and should not reserve: the premium is maximal there, and the starvation pathology, while real, is avoidable with cheaper instruments at low agentic share. The case for reservations concentrates where the purchases concentrate: fleets that price interactive tail latency highly and currently buy isolation through overprovisioning; fleets with adversarial or untrusted agentic exposure, where containment is not replicable by per-request caps; and fleets that run hot, past saturation, where the sign has already flipped. Even there, the K-to-floor result disciplines enthusiasm: reserve for the few flows whose completion is worth a known premium, and for nothing else, which is what the rationed-guarantee transfer prescribed before the evaluation priced it. An operator who prices tail latency or adversarial robustness as a first-class objective is solving a different optimization, and Section 6's decomposition is written to let them price it. What cannot move the verdict is re-measurement under this registration: the one-fix clause spent its fix, and the number stands.

8 Limitations

Simulation only. The hardware phase was pre-gated on this evaluation supporting the mechanism, and the gate closed; every number here is conditioned on the simulator's service model. The model's constants are literature-anchored, marked low confidence, and their measured sensitivity is the paper's principal caveat: the binding constant moves the representative deficit between 4.4 and 21.5 percent, sign-stable throughout. Synthetic workloads: no public traces of long-horizon agentic serving existed at specification freeze;

generators, anchors, and seeds are released, and the adversarial family is constructed, not observed. Three seeds per cell (Amendment 3): intervals are wider at low load, and several 0.7x cells have upper bounds crossing zero individually, though the verdict is invariant to how they are read, since taking every cell at its most favourable bound yields 33 of 108 reaching the support threshold against the 65 required. Cluster sizes 8 to 32: the 64-device axis was removed for measured infeasibility at the corrected horizon; the trend across measured sizes is flat, and the memory-bound regime is probed at one configuration rather than swept. Value weights are operator-supplied, fixed at registration, and swept in sensitivity. H2 and H3 are measured on representative configurations, not crossed with the full grid. The two-cell ablation design cannot separate any element's effect from its measured seed-noise floor at three replications; the campaign attributes the mechanism's cost to the workload's structural duty cycle, and finer per-element attribution requires swept axes and more seeds (data released). The comparison also sets a single completion-oriented policy against six request-oriented ones, so it prices this contract rather than the class of contracts; a differently designed completion guarantee is untested here. One boundary is a non-goal rather than a limitation: this layer enforces decisions about flows, their admission, their bounds and their termination, and makes no content-level judgement about what a flow says or does. The service model does not represent chunked prefill, so one mechanism of the deadline-ordered family is unmodelled.

Four gaps in the specification were surfaced by readers after the paper was frozen and are named here rather than quietly repaired. The discipline specifies when a reservation ends, by expiry, exhaustion, renegotiation or halt, and never specifies what becomes of the accumulated pinned state on any of those paths, although Section 3 makes that state load-bearing. The guarantee is scoped to resource-motivated action and the halt to safety revocation, so an erasure obligation arriving from outside the serving stack is neither, and the layer has no correct move when a reservation lifetime exceeds an erasure deadline. The disposition vocabulary cannot hold a non-terminating state, yet Section 6.1 measured one: flows admitted, never scheduled, still live at the horizon, in none of the four categories. And the workload's idle-gap distribution is uncertain in both directions at once. Deployments interposing a human confirmation step, as information-flow control layers for agents do, carry a tail longer than we modelled, which would deepen the stranding; production measurement of tool-call latency share (Biswas et al., 2026) suggests our tool-time anchors may instead be long, which would shorten it. The sensitivity axis contains no arm below its own anchor. The verdict is robust to the anchor in either direction, since Section 6.3 measures that shorter gaps produce larger deficits, but the attribution of the cost to a roughly 5 percent duty cycle is conditional on it.

Finally, the registration's one-fix clause means any residual measurement artifact, in either direction, stands uncorrected in these numbers by design; the amendment log is the complete record of what was corrected and when.

9 Related work

The serving-layer families were treated in Section 2; here we fix the distinctions. Four of the six baselines implement the scheduling family this paper evaluates against directly: priority preemption with paged cache (Kwon et al., 2023), multi-level feedback (Wu et al., 2023), deadline-ordered class scheduling (Goel et al., 2026), and AIMD admission with pause/resume (Chen et al., 2026); migration and chunked-prefill scheduling (Sun et al., 2024; Agrawal et al., 2024) are compatible mechanics not separately evaluated. The MARS-style baseline (Wang et al., 2026) represents external admission control for agentic serving; its dynamic SLO goodput is the nearest metric relative, differing in unit and denominator as Section 4 states, and its cost-benefit cache retention is the advisory counterpart of the contractual pinning evaluated here, alongside time-to-live and estimate-driven retention (Li et al., 2025; Abhyankar et al., 2024). Goodput-oriented routing for agentic inference over heterogeneous pools (Du et al., 2026) pursues the same completion-timeliness objective by placement and migration, within the preemption-family philosophy this evaluation tests against, and reports gains orthogonal to the admission question studied here. Program-level schedulers order agentic work without resource contracts and compose beneath either approach (Luo et al., 2025); workflow-aware serving (Wadlom et al., 2026), OS-inspired agent process management (Agyemang et al., 2026), and client-side cost-ladder overload control (Yuan et al., 2026) are likewise compatible and orthogonal. Gateway budget enforcement (LiteLLM, 2026; Wang, 2026) supplies the cumulative accounting the discipline's budgets extend from ceiling to contract; account-level provisioned throughput (Amazon Web Services, 2026; Microsoft Corporation, 2026) reserves at a granularity that cannot see flows, and composes as the tenant envelope of Appendix A. Batch-system advance reservations, quality-of-service classes, and gang scheduling (SchedMD LLC, 2026; The Kubernetes Authors, 2026; Ousterhout, 1982) are the structural ancestors; what is new here is what was tested, jointly guaranteed cache-and-budget reservations across idle gaps at flow granularity, and the finding is that the ancestors' economics survive the transfer better than the guarantees do. The network lineage of Section 1 and Appendix D (Braden et al., 1997; Blake et al., 1998; Floyd & Jacobson, 1993; Heinanen et al., 1999; Ferguson & Senie, 2000; Baker & Savola, 2004; Intel Corporation et al.,

2013) is inheritance, not reargued here. Production measurement of tool-based agentic inference reports tool calls accounting for 30 to 85 percent of end-to-end first-token latency (Biswas et al., 2026), a workload shape convergent with the one modelled here and measured rather than constructed.

Two adjacent literatures bound the discipline's trust and supervision elements, both of which now sit in Appendix A: content-level defences that govern what a piece of content may cause an agent to do (Debenedetti et al., 2025; Costa et al., 2025; Zhong et al., 2025; Wallace et al., 2024; Fan et al., 2026; Maloyan & Namiot, 2026; Santos-Grueiro, 2026; Wu et al., 2026), and in-pipeline or execution-time monitoring that supplies verdicts about agent behaviour (Inan et al., 2023; Zou et al., 2024; Dobrin & Chmiel, 2026; Lee et al., 2025). Both act downstream of admission on content or actions; the discipline's elements act upstream on capacity and standing, and Appendix A states the distinction. The plane-separation convergence (Gupta, 2026; NVIDIA Corporation, 2025; Shan et al., 2025; Wang et al., 2026) is this paper's premise. On method, pre-registration with published kill criteria remains rare in systems evaluation; the horizon result of Section 6.2 relates to right-censoring in survival analysis and to warmup discipline in queueing simulation, applied to a benchmark category, completion-metric agent evaluation, that is currently multiplying.

10 Conclusion

This paper proposed a completion-oriented resource contract for the serving layer, built it from four lessons packet networking paid for, stated in advance and in public the numbers that would prove its economics wrong, and then measured them. The economics are wrong: a median 10.3 percent loss, no supporting cell in 108, the graceful-degradation hypothesis reversed, and the cause structural, a workload whose 5 percent duty cycle strands whatever is reserved for it. What the contract provides regardless, isolation, containment, an audit record, and a stop that the computation being stopped cannot reach, is measured or holds by construction, and is now priced rather than free. The starvation of compliant agentic work by request-oriented schedulers is no longer an argument but a table. The evaluation leaves one rule for the benchmarks being built around long-horizon agents: the horizon must exceed the workload's completable lifetimes, or the benchmark measures its own window. Every artifact required to check, retune, or overturn these numbers is released.

Artifacts

The release contains: the evaluation specification frozen 2026-07-06 with its complete amendment log and integrity rulings; the simulator (engine, seven policies behind one interface, workload generators, 141 tests); the tuning harness with both tuning campaigns (censored and corrected horizons, all tuned parameters and scores); all run manifests including the quarantined pre-amendment set and the collapsed-run records; the preliminary readouts with superseded banners intact; the final readout and the analysis code that computes the verdict as a pure function of the manifest set; figure-generation code with one command per figure; and per-figure reproduction commands. The release is archived under 10.5281/zenodo.22759004, with the working repository at https://github.com/Sup3rn0vaN0w/mainlabs-reservation-discipline. Nothing reported in this paper depends on an unreleased artifact.

References

Abhyankar, R., He, Z., Srivatsa, V., Zhang, H., and Zhang, Y. InferCept: Efficient intercept support for augmented large language model inference. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235 of *Proceedings of Machine Learning Research*, pp. 81–95, 2024.

Agrawal, A., Kedia, N., Panwar, A., Mohan, J., Kwatra, N., Gulavani, B. S., Tumanov, A., and Ramjee, R. Taming throughput-latency tradeoff in LLM inference with Sarathi-Serve. arXiv preprint arXiv:2403.02310, 2024.

Agyemang, J. O., Kponyo, J. J., Somuah, O. K., Amponsah, E., Boakye, G. M. A., and Agyekum, K. O.-B. O. HiveMind: OS-inspired scheduling for concurrent LLM agent workloads. arXiv preprint arXiv:2604.17111, 2026.

Amazon Web Services. Increase model invocation capacity with provisioned throughput in Amazon Bedrock. Amazon Bedrock User Guide, 2026. URL https://docs.aws.amazon.com/bedrock/latest/userguide/prov-throughput.html. Accessed 2026-07-24.

Baker, F. and Savola, P. Ingress filtering for multihomed networks. RFC 3704, BCP 84, RFC Editor, March 2004. URL https://www.rfc-editor.org/info/rfc3704.

Biswas, A., Goel, K., S, S., Mohan, J., Khare, A., Parayil, A., Ramjee, R., and Bansal, C. Sutradhara: An intelligent orchestrator-engine co-design for tool-based agentic inference. arXiv preprint arXiv:2601.12967, 2026.

Blake, S., Black, D., Carlson, M., Davies, E., Wang, Z., and Weiss, W. An architecture for differentiated services. RFC 2475, Informational, RFC Editor, December 1998. URL https://www.rfc-editor.org/info/rfc2475.

Braden, R., Zhang, L., Berson, S., Herzog, S., and Jamin, S. Resource ReSerVation protocol (RSVP) – version 1 functional specification. RFC 2205, Proposed Standard, RFC Editor, September 1997. URL https://www.rfc-editor.org/info/rfc2205.

Chen, Q., Ye, Z., Tang, T., Sun, P., Tian, B., Wang, G., Li, S., Wen, Y., Han, Z., and Zhang, T. CONCUR: High-throughput agentic batch inference of LLM via congestion-based concurrency control. arXiv preprint arXiv:2601.22705, 2026.

Costa, M., Köpf, B., Kolluri, A., Paverd, A., Russinovich, M., Salem, A., Tople, S., Wutschitz, L., and Zanella-Béguelin, S. Securing AI agents with information-flow control. arXiv preprint arXiv:2505.23643, 2025.

Debenedetti, E., Shumailov, I., Fan, T., Hayes, J., Carlini, N., Fabian, D., Kern, C., Shi, C., Terzis, A., and Tramèr, F. Defeating prompt injections by design. arXiv preprint arXiv:2503.18813, 2025.

Dobrin, S. and Chmiel, Ł. The unfireable safety kernel: Execution-time AI alignment for AI agents and other escapable AI systems. arXiv preprint arXiv:2606.26057, 2026.

Du, B., Huangfu, B., Luo, Y., Chen, C., Li, Z., Yu, M., Fan, X., and Guo, M. GoodServe: Towards high-goodput serving of agentic LLM inferences over heterogeneous resources. arXiv preprint arXiv:2605.16867, 2026.

European Parliament and Council of the European Union. Regulation (EU) 2024/1689 laying down harmonised rules on artificial intelligence (Artificial Intelligence Act), article 14. Official Journal of the European Union, OJ L, 2024/1689, 12.7.2024, CELEX 32024R1689, 2024. URL https://eur-lex.europa.eu/eli/reg/2024/1689/oj.

EvalSpec. Pre-registered evaluation specification and amendment log for reservation-based serving. https://github.com/Sup3rn0vaN0w/mainlabs-reservation-discipline, 2026. Frozen 2026-07-06.

Fan, L., Li, Z., Tian, Y., Wang, Y., Li, R., and Wang, X. The granularity mismatch in agent security: Argument-level provenance solves enforcement and isolates the LLM reasoning bottleneck. arXiv preprint arXiv:2605.11039, 2026.

Ferguson, P. and Senie, D. Network ingress filtering: Defeating denial of service attacks which employ IP source address spoofing. RFC 2827, BCP 38, RFC Editor, May 2000. URL https://www.rfc-editor.org/info/rfc2827.

Floyd, S. and Jacobson, V. Random early detection gateways for congestion avoidance. *IEEE/ACM Transactions on Networking*, 1(4):397–413, August 1993.

Goel, K., Mohan, J., Kwatra, N., Anupindi, R. S., and Ramjee, R. QoServe: Breaking the silos of LLM inference serving. In *Proceedings of the ACM International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS)*, Pittsburgh, PA, USA, 2026.

Gupta, A. What is an LLM control plane? Mozilla.ai Blog, June 2026. URL https://blog.mozilla.ai/what-is-an-llm-control-plane/. Published 2026-06-12.

Heinanen, J., Baker, F., Weiss, W., and Wroclawski, J. Assured forwarding PHB group. RFC 2597, Proposed Standard, RFC Editor, June 1999. URL https://www.rfc-editor.org/info/rfc2597.

Inan, H., Upasani, K., Chi, J., Rungta, R., Iyer, K., Mao, Y., Tontchev, M., Hu, Q., Fuller, B., Testuggine, D., and Khabsa, M. Llama guard: LLM-based input-output safeguard for human-AI conversations. arXiv preprint arXiv:2312.06674, 2023.

Intel Corporation, Hewlett-Packard Company, NEC Corporation, and Dell Inc. Intelligent platform management interface specification, second generation, v2.0, revision 1.1. Industry specification, 2013. URL https://www.intel.com/content/dam/www/public/us/en/documents/product-briefs/ipmi-second-gen-interface-spec-v2-rev1-1.pdf.

Kwon, W., Li, Z., Zhuang, S., Sheng, Y., Zheng, L., Yu, C. H., Gonzalez, J. E., Zhang, H., and Stoica, I. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP)*, 2023.

Lee, S., Kim, H., and Park, S. Can we stop malicious AI? KILLBENCH: A benchmark for external AI kill switch feasibility. arXiv preprint arXiv:2511.13725, 2025.

Li, H., He, R., Mang, Q., Zhang, Q., Mao, H., Chen, X., Zhou, H., Cheung, A., Gonzalez, J., and Stoica, I. Continuum: Efficient and robust multi-turn LLM agent scheduling with KV cache time-to-live. arXiv preprint arXiv:2511.02230, 2025.

LiteLLM. Agent iteration budgets. LiteLLM documentation, 2026. URL https://docs.litellm.ai/docs/a2a_iteration_budgets. Accessed 2026-07-24; per-session iteration and dollar budgets enforced at the gateway.

Luo, M., Shi, X., Cai, C., Zhang, T., Wong, J., Wang, Y., Wang, C., Huang, Y., Chen, Z., Gonzalez, J. E., and Stoica, I. Autellix: An efficient serving engine for LLM agents as general programs. arXiv preprint arXiv:2502.13965, 2025.

Maloyan, N. and Namiot, D. Sleeper channels and provenance gates: Persistent prompt injection in always-on autonomous AI agents. arXiv preprint arXiv:2605.13471, 2026.

Microsoft Corporation. Provisioned throughput for foundry models. Microsoft Learn documentation, 2026. URL https://learn.microsoft.com/en-us/azure/foundry/openai/concepts/provisioned-throughput. Accessed 2026-07-24; provisioned throughput units (PTUs).

NVIDIA Corporation. NVIDIA Dynamo: Overall architecture. Dynamo documentation, v1.3.0, 2025. URL https://docs.dynamo.nvidia.com/dynamo/design-docs/overall-architecture. Accessed 2026-07-24.

Ousterhout, J. K. Scheduling techniques for concurrent systems. In *Proceedings of the Third International Conference on Distributed Computing Systems (ICDCS)*, pp. 22–30, 1982.

Santos-Grueiro, I. Context-to-execution integrity for LLM agents. arXiv preprint arXiv:2607.06000, 2026.

SchedMD LLC. Slurm workload manager: Advanced resource reservation guide. Slurm documentation, version 26.05, 2026. URL https://slurm.schedmd.com/reservations.html. Accessed 2026-07-24.

Shan, J., Gupta, V., Xu, L., Shi, H., Zhang, J., Wang, N., Xu, L., Kang, R., Liu, T., Zhang, Y., Zhu, Y., Jin, S., Lim, G., Chen, B., Chen, Z., Liu, X., Chen, X., Yin, K., Chung, C.-P., Jiang, C., Lu, Y., Chen, J., Lin, C., Xiang, W., Shi, R., and Xie, L. AIBrix: Towards scalable, cost-effective large language model inference infrastructure. arXiv preprint arXiv:2504.03648, 2025.

Su, Z., Zhang, Z., Lan, T., Wang, Z., Shen, H., Yang, J., and Cheng, Y. MorphServe: Efficient and workload-aware LLM serving via runtime quantized layer swapping and KV cache resizing. arXiv preprint arXiv:2506.02006, 2025.

Sun, B., Huang, Z., Zhao, H., Xiao, W., Zhang, X., Li, Y., and Lin, W. Llumnix: Dynamic scheduling for large language model serving. In *18th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, 2024.

The Kubernetes Authors. Pod quality of service classes. Kubernetes documentation, 2026. URL https://kubernetes.io/docs/concepts/workloads/pods/pod-qos/. Accessed 2026-07-24.

Wadlom, N., Shen, J., and Lu, Y. Efficient LLM serving for agentic workflows: A data systems perspective. arXiv preprint arXiv:2603.16104, 2026.

Wallace, E., Xiao, K., Leike, R., Weng, L., Heidecke, J., and Beutel, A. The instruction hierarchy: Training LLMs to prioritize privileged instructions. arXiv preprint arXiv:2404.13208, 2024.

Wang, B. Governing multi-agent systems: Agent identity, A2A, and the agent gateway. TrueFoundry Blog, June 2026. URL https://www.truefoundry.com/blog/multi-agent-a2a-governance-gateway. Published 2026-06-19.

Wang, Y., Ye, H., Xu, Y., Guo, C., Wei, C., Wang, Q., Li, D., Chen, T., Li, H., Zhuo, D., and Chen, Y. MARS: Efficient, adaptive co-scheduling for heterogeneous agentic systems. arXiv preprint arXiv:2604.26963, 2026.

Wu, B., Zhong, Y., Zhang, Z., Liu, S., Liu, F., Sun, Y., Huang, G., Liu, X., and Jin, X. Fast distributed inference serving for large language models. arXiv preprint arXiv:2305.05920, 2023.

Wu, B., Ding, Z., Huang, J., and Zhao, Y. Forget to improve: On-device LLM-agent continual learning via budget-curated memory. arXiv preprint arXiv:2606.25115, 2026.

Yuan, R., Zeng, Y., Gao, X., Yu, L., Liao, H., and Wang, H. Scheduling the unschedulable: Taming black-box LLM inference at scale. arXiv preprint arXiv:2604.06970, 2026.

Zhong, P. Y., Chen, S., Wang, R., McCall, M., Titzer, B. L., Miller, H., and Gibbons, P. B. RTBAS: Defending LLM agents against prompt injection and privacy leakage. arXiv preprint arXiv:2502.08966, 2025.

Zou, A., Phan, L., Wang, J., Duenas, D., Lin, M., Andriushchenko, M., Wang, R., Kolter, Z., Fredrikson, M., and Hendrycks, D. Improving alignment and robustness with circuit breakers. arXiv preprint arXiv:2406.04313, 2024.

A THE RESERVATION DISCIPLINE: FULL SPECIFICATION

A.1 Admission and the reservation vector

A flow arrives with a descriptor: an estimated invocation count or duration, a requested cumulative output-token bud-

get, an estimated cache footprint, a service class, a provenance class (below), and optionally a deadline. Estimates may be wrong; the semantics below are defined so that wrong estimates degrade a flow's own outcome, never the guarantee already granted to another.

Admission to the reserved subset requires five conditions jointly. First, the reserved subset on the target pool holds fewer than K flows, where K is a deliberately small bound relative to concurrent traffic: the discipline rations per-flow state to the flows whose requirements justify it, and class-serves the rest, which is the surviving shape of Appendix D's first lesson. Second, the pool's projected commitment, the sum over active and admitted-but-idle reservations of their remaining resource claims over a forecast window, remains under a configured ceiling after adding this flow. Third, a device set exists that can hold the flow's cache footprint under the pinning rules below; this is an affinity feasibility test, not a best-effort placement. Fourth, the requested token budget fits within the flow's class quota. Fifth, the flow's provenance class is reservation-eligible (below). A flow failing any condition is admitted to an aggregate class, or receives an early decline, optionally with a time quote for when admission would succeed. Declining at the door is a feature: it is the cheapest moment in a flow's life to say no.

Projecting compute commitment for autoregressive work is estimation, not measurement: output lengths are unknown at admission, and the forecast inherits that uncertainty. The discipline absorbs estimation error structurally rather than pretending precision: the commitment ceiling is set with margin, misestimation is charged to the misestimating flow's own disposition (below), and the forecast window's construction is an evaluation variable, not a claimed contribution.

An admitted reservation jointly covers three resources, and the jointness is the point: a flow starved on any one of them fails entirely, so a guarantee over a subset is not a guarantee. The first is compute: a share sufficient to meet the flow's class latency budget at each invocation start. The second is a cumulative output-token budget metered at decode across every invocation of the flow. The budget has a dual character that single-purpose mechanisms lack: it is a floor, in that budgeted capacity is committed and the flow cannot be silently starved out of it, and simultaneously a bound, in that the flow cannot exceed it, which makes the runaway loop of Section 2 a contained event rather than a discovered one. The third is key-value cache: the flow's accumulated cache is pinned, exempt from eviction and migration for the reservation lifetime; pinning applies to the flow's private suffix blocks, while prefix blocks shared across flows under paged cache management remain governed by reference counting, which never reclaims a block a pinned flow still references. The pin holds across inter-invocation idle gaps up to a per-reservation idle bound.

A.2 The guarantee, its cost surfaces, and ordinary traffic

The guarantee is stated negatively, because that is what makes it checkable: for the reservation lifetime, no resource-motivated action of the serving stack may preempt the flow's invocations, evict or migrate its pinned cache, or reclaim its committed budget. The sole override is a halt issued by the management plane (below), which is a safety revocation under a designated authority, and definitionally not scheduler preemption: no capacity condition can trigger it. This distinction is load-bearing. A guarantee with a capacity-triggered escape clause is a priority, and Section 2's schedulers already have priorities; the discipline exists because priorities are not contracts.

Pinning across idle gaps is where the guarantee meets its cost, and we give two embodiments. Under strict pinning the cache stays resident in accelerator memory throughout, idle gaps included: maximal simplicity, maximal stranding, appropriate when gaps are short or the reserved subset is tiny. Under tiered pinning the cache is resident during active invocations, and between invocations it may be moved to a guaranteed spill tier, host memory with a reserved restore path, under a contractual bound on restore latency and with restore capacity itself reserved. The guarantee survives the movement: the flow observes at most the restore bound as added start latency, and nothing it has accumulated is ever lost. Tiered pinning is the engineering answer to the idle-gap objection of Section 2, and the evaluation of Sections 4 through 6 prices both embodiments without favor.

Budget exhaustion is a defined event, not an ambush. Policies are configured per class from a small vocabulary: warn at a threshold fraction and continue; hard-stop generation at the bound; escalate to the management plane for a disposition; or renegotiate, which is a fresh admission test at current headroom for an extended budget, with no privilege carried over from the original grant. The contrast with the gateway ceiling of Section 2 is the timing and the contract: a flow under this discipline knows its bound at admission, progresses under a guarantee toward it, and reaches exhaustion as a planned disposition, rather than spending freely until a rejection converts the entire prior spend into waste.

All other traffic runs in aggregate service classes: a small set, each with a latency budget and a scheduling weight, imposing no per-flow state on the serving core. Classes are where the discipline meets ordinary traffic, and deliberately nothing here is novel: weighted scheduling against class latency budgets is Section 2's scheduling family doing what it does well.

Degradation is the discipline's pressure-release surface, and

its signal is the departure from precedent flagged in Appendix D's second lesson. Define committed headroom H on a pool as one minus the ratio of forward commitments, from the reservation ledger over a forecast window, to capacity. As H shrinks, best-effort traffic experiences actions drawn from a configured ladder, each applied with probability p(H), monotone increasing as H falls, beginning well before exhaustion: early admission decline, model-tier downgrade, context truncation, token-budget haircut, cache spill, reduced generation effort, including runtime quality adaptation of the model itself (Su et al., 2025). The curve is class-differentiated, lower classes degrading earlier and harder, and trust-keyed admission below adds provenance to the keying. The signal choice is a design claim the evaluation tests directly: queue depth reports congestion that has already arrived; the ledger reports congestion that has been promised; whether the forward signal is worth anything is answered, against this design's expectation, in Sections 6.5 and 7.

Reservations are leases. Each carries a lifetime; renewal is an admission test, not an entitlement; expiry returns the resources to the pool with a grace disposition for the flow. In multi-tenant deployments the structure nests: K, commitment ceilings, and class quotas are set per tenant against tenant-level allocations, and the account-level provisioned throughput of Section 2 composes naturally as the tenant's envelope within which flow-level contracts are written. Appendix B states the admission test and the ledger invariants at pseudocode level; the invariants, no over-commitment of compute, memory, or budget under any interleaving of admissions, renewals, expiries, and halts, are the correctness core of the discipline, and the evaluation's engine enforces them as hard test failures (Section 5).

A.3 The management plane

Every oversight mechanism deployed inside today's serving stacks shares a structural property with the thing it oversees: it runs in the same pipeline. Guard models classify the token stream in-line (Inan et al., 2023); critique and reflection execute as part of the very computation they are meant to check; representation-level monitors and intervention methods, however promising, run in the process they observe (Zou et al., 2024), and halt mechanisms reachable through the model's own input channel inherit that channel's attack surface (Lee et al., 2025). Execution-time safety kernels that treat the agent runtime as untrusted and hold an out-of-reach stop (Dobrin & Chmiel, 2026) apply the same doctrine at the action layer; the management plane applies it at the layer beneath, the resource contracts every action layer depends on. The in-pipeline property is not an implementation accident, it is a fate: whatever compromises, overloads, or wedges the inference stack is positioned to compromise its oversight in the same stroke, and the scenarios in which oversight matters most, a manipulated agent, a saturated cluster, a defective rollout, are precisely the scenarios in which the stack is least trustworthy about itself. Appendix D's third lesson states the doctrine networks derived from the same observation.

The discipline therefore places supervision in a management plane with two independence properties, named exactly. The first is authority independence: the plane holds pre-authorized rights over flows, and the validation and audit of those rights occur outside the inference stack, so no state of the model or the serving engine can expand, contract, or forge them. The second is availability independence: the plane runs in a separate failure domain, a distinct process and host at minimum, distinct credentials and control network in the strong embodiment, with a heartbeat between the planes; if the management plane becomes unreachable, the serving layer enters a configured fail-safe, admitting no new reservations while honoring existing guarantees, so that supervision failure degrades the system toward caution rather than toward the unsupervised open. We do not claim, and the design does not require, signal independence: the plane's inputs, telemetry, ledger state, and activation taps exported one-way from the data plane, originate in the stack it watches, and a sufficiently compromised stack can starve or distort them. What the compromised stack cannot do is revoke the watcher's authority or take it offline with itself, and that is the property the doctrine actually needs.

The plane's action vocabulary is small and maps onto the discipline's objects. Halt revokes a reservation and stops a flow: the one override of the guarantee above, triggerable only by this authority and never by a capacity condition. Steer forces a degradation action from the ladder above onto a specific flow, a bounded intervention short of termination. Escalate routes a flow's disposition to an external policy engine or a human. Each action is pre-authorized at admission time, logged against the ledger, and executable without the cooperation of the flow, the model, or the scheduler that serves them.

The control plane as an enforcement point. It is worth stating plainly what this machinery amounts to for the governance of deployed agents, because the question of who can stop a misbehaving agent is today answered mostly inside the model, through training, prompting, and in-line classification, which is to say inside the thing being doubted. The discipline gives an organization four primitives that require no trust in the model at all. Admission is where policy binds: an organization can require that flows touching designated systems present an attested identity, a bounded budget, and an eligible provenance class before any capacity is granted. The budget is containment: the worst case of a rogue or looping agent is its remaining budget, a number fixed at admission rather than discovered in an incident review, and

Section 6's adversarial results measure exactly this property. The management plane is the stop: a pre-authorized, audited, out-of-band kill that does not route through the agent's own reasoning. And the reservation ledger is the record: for every admitted flow, who authorized it, under what identity and provenance, bounded to what, degraded or halted when and by whom. Regulatory frameworks are beginning to require exactly this shape of control: the EU AI Act's human-oversight article mandates an intervention or stop capability for high-risk systems (European Parliament and Council of the European Union, 2024), and a reservation-holding control plane is where such a stop can be implemented as a deterministic property of infrastructure rather than a request to the model. These are the questions compliance functions actually ask, and identity-layer controls can already revoke an agent's credentials and tool permissions without the model's cooperation; the serving layer adds the answer those controls lack, revocation of the computation itself, since an agent with revoked credentials but live compute continues reasoning toward its next attempt, while an agent with a revoked reservation stops. The boundary of the claim is equally plain, and Section 8 fixes it as a non-goal: this layer enforces decisions about flows; it does not judge content. Detection, whether a flow's outputs are harmful, deceptive, or noncompliant, is a model-layer problem with its own literature and its own tools, and those tools gain rather than lose value here: a verdict from any of them, or from a human, becomes actionable through an authority that the misbehaving computation cannot reach.

A.4 Trust-keyed admission

The discipline's final element keys the admission decision above to provenance, the transfer of Appendix D's fourth lesson. Every flow carries a trust class assigned at admission from the provenance of the content that drives it: an instruction typed by an authenticated operator; a request from an authenticated service principal; a task derived from tool output; a task derived from open-web content. The classes order naturally, and the rule is structural: flows at or below a configured threshold are ineligible for the reserved subset regardless of their content, receive capped budgets, and sit lowest in the class-differentiated degradation curves above, shedding first under pressure.

The qualifier regardless of their content is the design. Content-level defenses against prompt injection and instruction subversion are an active field with real mechanisms: control-flow and data-flow separation with capability policies over tool access (Debenedetti et al., 2025), information-flow labels propagated through agent pipelines (Costa et al., 2025), runtime policies gating tool invocation on taint (Zhong et al., 2025), and trained instruction hierarchies (Wallace et al., 2024). These systems, with argument-level and formally enforced descendants (Fan et al., 2026; Maloyan & Namiot, 2026), answer the question of what a piece of content may cause an agent to do, and they answer it downstream of admission, in the agent's execution; integrity layers that verify authority at the moment of execution extend the same family (Santos-Grueiro, 2026). Trust-thresholded admission itself has appeared for one resource, entries into an agent's memory store (Wu et al., 2026). The discipline's object is different: serving-layer capacity and standing. What provenance gates here is whether a flow may hold a guaranteed reservation, at what budget scale, and where it stands in the degradation order, fixed at admission before the flow's content is ever interpreted. Composed with the management plane above, the enforcement reading is direct: untrusted provenance is served, at best-effort and under bound, but it cannot occupy the infrastructure's promises.

Reservation survivability. A guarantee that dies with a serving instance is a guarantee against everything except the most common failure. The discipline extends the contract across unplanned instance failure by replicating the reservation record itself, the budget counter and service class, deliberately exclusive of cache contents and generation progress, to a standby. On failure, the standby resumes the admitted flow without re-entering admission and without enqueueing behind its own intake, and it makes room for the inherited guarantee under load the same way the discipline makes room for anything: by degrading its best-effort traffic through the headroom-keyed ladder. The flow loses unpinned progress; it does not lose its contract.

B ADMISSION TEST AND LEDGER INVARIANTS

```
State, per pool p: reserved set R_p with bound K_p; capacity vector Cap_p
(compute, device memory, spill-tier memory and restore bandwidth); forecast
window W; committed(p, t) = sum over r in R_p of r's remaining claim
profile over [t, t+W]; per-class budget quotas Q_c; per-tenant envelopes
E_g.

ADMIT(f) for flow f with descriptor (class c, tenant g, budget b, footprint
m, profile est):
  1. |R_p| < K_p
  2. committed(p, t) + claim(est) <= ceiling(p) for all t in window
  3. exists device set D: pinnable(m, D) under embodiment (strict: resident
     throughout; tiered: resident-active plus reserved spill and reserved
     restore within bound L_restore)
  4. spent(c) + b <= Q_c and within E_g
  5. trust(f) >= eligibility threshold for reservation
  All pass: grant r(f), append to ledger, R_p += {f}.
  Any fail: route to class c best-effort, or decline with optional quote.

Events: RENEW is ADMIT at current state with no carried privilege. EXPIRE
and EXHAUST release r(f) with the class's disposition. HALT(authority)
releases r(f) immediately; it is the only release not initiated by the
flow's own lifecycle.

Invariants (any interleaving of admit, renew, expire, exhaust, halt):
  I1 Compute: committed(p, t) <= ceiling(p) <= Cap_p at all t.
  I2 Memory: pinned bytes + reserved spill/restore never exceed their
     tiers; a tiered-pin flow always has a reserved restore path.
  I3 Budget conservation: metered decode tokens of f never exceed b; quota
     accounting is exact under renegotiation.
  I4 Guarantee monotonicity: once granted, r(f) is removed only by expire,
     exhaust, or halt; no capacity condition appears in any release path.
```

C DEGRADATION PROBABILITY FAMILIES

p(H) requirements: p monotone non-increasing in H; p(H) = 0 for H >= H_max; p(H) = p_ceiling for H <= H_min. Families: piecewise-linear between (H_max, 0) and (H_min, p_ceiling); exponential p = p_ceiling * ((H_max - H)/(H_max - H_min))^k for shaping early gentleness; per-class and per-provenance parameterization as a matrix {H_max, H_min, p_ceiling, action ladder}_c,tr with lower classes and lower trust assigned earlier H_max and higher p_ceiling. H computed from the ledger over forecast window W; W trades responsiveness against stability and is swept in the evaluation.

D NETWORKING TRANSFERS: THE FOUR LESSONS AND THE EXPANDED TRANSFER TABLE

D.1 The four lessons

Resource management under the tension between per-unit guarantees and aggregate efficiency is the central design problem of packet networking's middle decades, and the field's resolutions were expensive: standardized architectures were built, deployed at scale, and abandoned before the surviving doctrine settled. Four of those lessons transfer to the serving layer, and the discipline of Section 3 is their deliberate transfer. We state each in its original setting, because the failure modes that produced them are already visible, in miniature, in the systems of Section 2.

Lesson one: per-flow guarantees do not scale to all flows, so guarantee few and aggregate the rest. The Integrated Services architecture offered end-to-end per-flow reservations, signaled by RSVP, to any flow that asked (Braden et al., 1997); it failed in deployment substantially because per-flow state in every element of the path could not scale. Its successor inverted the design: Differentiated Services keeps per-flow complexity at the edge and gives the core only a small set of aggregate classes (Blake et al., 1998). The surviving doctrine is neither "no guarantees" nor "guarantees for all"; it is guarantees rationed to the few flows whose requirements justify per-flow state, with class-based service for the remainder. Section 3 adopts this shape directly: a deliberately bounded reserved subset, and aggregate classes for everything else.

Lesson two: load shedding is a design surface, and it should act early, probabilistically, and per class. Random Early Detection drops packets with a probability that rises as smoothed queue occupancy grows, before the queue is full, precisely so that overload is signaled gradually rather than discovered at exhaustion (Floyd & Jacobson, 1993); its class-differentiated descendants shed lower-precedence traffic first within the same discipline (Heinanen et al., 1999). The alternative, tail drop at a full buffer, produces synchronized collapse and serves the most recent arrival as badly as the most important one. Section 2's schedulers shed load today, but deterministically and at the cliff: demotion at a deadline, rejection at a ceiling, preemption at exhaustion. Section 3 transfers the early-probabilistic-per-class shape, with one deliberate change of signal: the serving layer possesses a quantity networks lack, a ledger of forward commitments, and Section 3 keys the shedding probability to committed headroom rather than to observed queue state.

Lesson three: the plane that supervises a system must not share fate with the system it supervises. Operators reach a wedged or compromised machine through a management path that is powered, connected, and authenticated independently of the machine's own stack: the baseboard management controller and its descendants (Intel Corporation et al., 2013). The design premise is unconditional: the moment supervision runs inside the thing supervised, every failure of the thing is potentially a failure of its supervision, and the cases where supervision matters most are exactly the cases where the system is least trustworthy. Today's model-level oversight, guard models in the pipeline, self-critique in the context, probes in the process, sits inside the supervised stack. Section 3 transfers the doctrine: a management plane whose authority and availability are independent of the inference infrastructure, whatever signals it consumes from within.

Lesson four: bind authority to provenance at the edge, not to content downstream. Networks learned to discard traffic whose claimed origin does not match the path it arrived by, at the ingress edge, before that traffic can spend the network's resources or authority (Ferguson & Senie, 2000; Baker & Savola, 2004). The alternative, judging packets by their payloads deeper in the network, loses to any adversary who can forge plausible content, which is every adversary. The serving-layer analog is stated carefully in Section 3, because content-level defenses for language models are an active field with real results; the transfer claims only the resource half: whatever a flow's content says, the provenance class assigned at admission should bound what capacity and authority the flow can hold.

One table summarizes the mapping: rationed per-flow guarantees over aggregate classes $\rightarrow$ the bounded reserved subset; early probabilistic class-aware shedding $\rightarrow$ headroom-keyed degradation; fate-independent supervision $\rightarrow$ the management plane; provenance-bound authority at the edge $\rightarrow$ trust-keyed admission. The transfers hold at the granularity where they are claimed, the flow, where a control decision is cheap relative to the minutes or hours of work it governs; they fail at per-token or per-layer granularity, where the decision rivals the work; and flows are not packets, since a flow's accumulated state entangles it with the machinery serving it in ways a datagram never is. The lessons are a design inheritance, bought at someone else's expense, and the discipline that follows spends it. The evaluation that follows the discipline then tests whether the inheritance survives the transfer: the first lesson's economics, this paper finds, largely do not (Sections 6.5 and 7), the second lesson's transferred signal proves untenable in its transferred form, and the third and fourth lessons' properties were never economic claims and are examined on their own terms in Section 7.

D.2 The transfer table, expanded

1. Rationed guarantees. Origin: per-flow reservations failed at scale; edge-complexity with core aggregates survived

(Braden et al., 1997; Blake et al., 1998). Serving gap: no per-task guarantee exists at any scale. Element: bounded reserved subset K over aggregate classes (Section 3). Leak: K's right size is workload-dependent and swept, not derived; the evaluation's tuner chose the smallest offered (Section 6.5). 2. Early probabilistic class-aware shedding. Origin: (Floyd & Jacobson, 1993; Heinanen et al., 1999). Serving gap: deterministic cliffs (demotion at deadline, rejection at ceiling). Element: p(H) ladder (Appendix A). Departure, not transfer: the signal is ledger commitments, a forward quantity networks lacked. Leak: forecast quality bounds the signal's advantage, and the evaluation found no advantage attributable above its noise floor (Section 6.5). 3. Fate-independent supervision. Origin: out-of-band management (Intel Corporation et al., 2013). Serving gap: oversight in the supervised pipeline. Element: management plane with authority-and-availability independence (Appendix A). Leak: signal dependence is retained and conceded. 4. Provenance-bound authority at the edge. Origin: ingress source validation (Ferguson & Senie, 2000; Baker & Savola, 2004). Serving gap: content adjudicated downstream can command capacity. Element: trust-keyed reservation eligibility (Appendix A). Leak: provenance classes are coarser than network paths, and class assignment itself must be trustworthy.

E PRE-REGISTRATION: THE COMPLETE AMENDMENT LOG

The amendment log, in full. Pre-registration without a change log is theater; ours has three amendments and one integrity ruling, each numbered, dated, reasoned, and adopted before the final grid ran. Amendment 1 (2026-07-14): the MARS-style baseline added, because a negative headline makes baseline completeness load-bearing. Amendment 2 (2026-07-15): all measurement horizons raised to at least 1500 seconds after a diagnostic showed the build default (300 seconds) was shorter than the workload's median flow lifetime (roughly 863 seconds as measured on the diagnostic realization; the released population derivation gives roughly 711), right-censoring the large majority of agentic flows (78.5 percent of the diagnostic realization, roughly 75 percent of the population, incompletable within a 200-second window) and biasing the primary metric against reservation-holding policies; adopted with a one-fix clause, no further measurement correction in either direction, Section 6.2 reports the finding in full. Amendment 3 (2026-07-20): the device axis reduced to 8/16/32 and replications to three seeds after direct measurement showed the frozen grid infeasible at the corrected horizon (projected 39,600 to 49,700 cpu-hours, a single 64-device run estimated at 24 to 32 wall-clock hours, unparallelizable); direction of effect unknown for the device axis, neutral for seeds, and the paper states the narrowed scope. Integrity ruling (2026-07-20): 189 pre-amendment manifests found in the verdict path's evidence directory were quarantined and an input-domain guard added that hard-errors on any manifest outside the grid it claims to report; measurement semantics unchanged.

F SIMULATOR INTEGRITY RECORD

Integrity record. We report the evaluation's own caught defects, because for a negative result the reader's question is whether the loss is real. Three defects were caught by the engine's invariants during construction, each fixed and regression-tested, and one of them was flattering the mechanism: an O(n squared) scheduling path under overload was silently depressing the work-conserving baselines, the exact policies that win the final comparison; left unfixed, the mechanism's loss would have looked smaller for a reason that had nothing to do with scheduling. A second defect would have violated the tiered-pin restore guarantee; a third let oversized flows pin most of a device. During the final campaign, two further interventions occurred, both disclosed in the readout: 189 manifests from a pre-amendment pilot were found in the verdict path's evidence directory and quarantined behind a new input-domain guard (the contamination, censored-horizon cells at an excluded cluster size, biased against the mechanism; it was removed on domain logic, not direction), and two baseline runs that reached congestion collapse at the wall-clock cap were excluded with the selection effect stated, a bias that favors the affected baselines and therefore runs against the mechanism the evaluation killed. The full test suite (141 tests), the quarantine directory, and the collapsed-run manifests are released.

G SUPPLEMENTARY RESULTS AND FIGURES

Table 1. Policy roster and tuned parameters per workload family (corrected-horizon tuning campaign; 8-point equal-budget grids).

policy	workload family	tuned parameters
concur_style	mix_10	`additive_increase=1.0, congestion_queue_threshold=0.25, multiplicative_decrease=0.5`
concur_style	mix_30	`additive_increase=1.0, congestion_queue_threshold=0.25, multiplicative_decrease=0.5`
concur_style	mix_50	`additive_increase=1.0, congestion_queue_threshold=0.25, multiplicative_decrease=0.5`
fastserve_mlfq	mix_10	`num_levels=4, preempt_mode=swap, quantum_scale=2.0`
fastserve_mlfq	mix_30	`num_levels=4, preempt_mode=swap, quantum_scale=2.0`
fastserve_mlfq	mix_50	`num_levels=4, preempt_mode=swap, quantum_scale=2.0`
fcfs	mix_10	`(no parameters)`
fcfs	mix_30	`(no parameters)`
fcfs	mix_50	`(no parameters)`
mars_style	mix_10	`additive_increase=2.0, multiplicative_decrease=0.75, retain_threshold_tokens=500`
mars_style	mix_30	`additive_increase=2.0, multiplicative_decrease=0.75, retain_threshold_tokens=500`
mars_style	mix_50	`additive_increase=2.0, multiplicative_decrease=0.5, retain_threshold_tokens=500`
niyama_style	mix_10	`demote_after_fraction=1.0, preempt_mode=swap`
niyama_style	mix_30	`demote_after_fraction=1.0, preempt_mode=swap`
niyama_style	mix_50	`demote_after_fraction=1.0, preempt_mode=swap`
reservation	mix_10	`degradation.action=shorten, pin_mode=tiered, reserved_subset_fraction=0.05`
reservation	mix_30	`degradation.action=shorten, pin_mode=tiered, reserved_subset_fraction=0.05`
reservation	mix_50	`degradation.action=shorten, pin_mode=strict, reserved_subset_fraction=0.05`
vllm_style	mix_10	`max_batch_fraction=1.0, preempt_mode=swap`
vllm_style	mix_30	`max_batch_fraction=1.0, preempt_mode=swap`
vllm_style	mix_50	`max_batch_fraction=1.0, preempt_mode=swap`

Table 2. Pre-registered verdict summary (thresholds fixed 2026-07-06).

threshold	required	measured	outcome
median improvement	$\geq$ +10% (support) / $\geq$ +5% (weak)	-10.3%	KILL
supporting cells	$\geq$ 60% of core cells	0 of 108 (0%)	KILL
interactive guardrail	p95 TTFT degradation $\leq$ 5%	intact in 96% of cells	holds (4 cells fail)

Table 3. H3 absolute compliant-flow completion rates at each runaway-injection level, with the worst delta versus the no-injection condition (percentage points).

policy	inj 0%	inj 1%	inj 5%	inj 10%	worst delta
reservation	0.503	0.475	0.499	0.471	-3.1
fcfs	0.332	0.295	0.306	0.282	-5.0
mars_style	0.249	0.223	0.245	0.227	-2.6
fastserve_mlfq	0.102	0.100	0.114	0.116	-0.3
concur_style	0.082	0.082	0.070	0.063	-1.9
vllm_style	0.000	0.000	0.000	0.000	+0.0
niyama_style	0.000	0.000	0.000	0.000	+0.0

Table 4. Service-model sensitivity: measured effect and binding classification per constant.

constant	perturbation	representative-cell delta	binding
single-stream decode rate	0.7x / 1.3x	deficit 21.5% $\rightarrow$ 4.4% / 13.0%	binding
peak decode rate	$\pm$30%	none (0 of 19,342 decode calls bound)	non-binding
cache bytes per token	$\pm$30%	none (peak HBM near 39% of capacity)	non-binding




Figure 3. Per-cell improvement of the reservation discipline over the best per-cell tuned baseline, across offered load. Each point is one of 108 pre-registered core cells; the heavy line traces the per-load median. The deficit is U-shaped, deepest at nominal provisioning (22.4 to 23.6 percent at 1.0x), and the sign flips past saturation (+0.8 to +3.2 percent at 1.5x). Dashed lines mark the pre-registered WEAK (+5 percent) and SUPPORT (+10 percent) thresholds; no cell reaches SUPPORT. Open symbols mark the four cells failing the interactive guardrail (Section 6.4).




Figure 4. Served value across the load sweep. The reservation discipline's area under curve (0.626) trails deadline-ordered class scheduling (0.648), killing the graceful-degradation hypothesis; the admission-throttling baselines collapse under overload (Section 6.5).




Figure 5. Interactive tail latency under reservations. Per-cell p95 time-to-first-token change versus the best baseline: at and above nominal load, reservations improve interactive tail latency by 63.3 to 97.1 percent by keeping agentic flows off the shared pool. The effect inverts in the heavy-agentic, overloaded, short-gap corner, where the guardrail fails by 468.6 to 526.5 percent (Section 6.4).




Figure 6. What that isolation costs. Reserved-idle fraction per cell: the protection of Figure 5 is priced in capacity held idle, 93 to 100 percent of the reserved pool in 77 of 81 cells, with three load-1.5 cells at 88.9 percent and one cell granted no reservations (marked). This is the structural duty-cycle cost of Section 6.5.

H PER-CELL H1 RESULTS

Per-cell H1 results, machine-generated from the FINAL readout (cell, best baseline, improvement, 95 percent CI, guardrail; all 108 cells).

cell	best baseline	improvement	95% CI	guardrail
mix0.1_load0.7_dev16_gap20.0	fcfs	-7.8%	[-7.8%, +9.6%]	ok
mix0.1_load0.7_dev16_gap300.0	fcfs	-6.9%	[-6.9%, +9.1%]	ok
mix0.1_load0.7_dev16_gap60.0	fcfs	-7.3%	[-7.3%, +9.3%]	ok
mix0.1_load0.7_dev32_gap20.0	fcfs	-7.3%	[-7.7%, +9.9%]	ok
mix0.1_load0.7_dev32_gap300.0	fcfs	-6.6%	[-6.7%, +9.2%]	ok
mix0.1_load0.7_dev32_gap60.0	fcfs	-7.0%	[-7.2%, +9.5%]	ok
mix0.1_load0.7_dev8_gap20.0	fcfs	-8.5%	[-8.5%, +8.5%]	ok
mix0.1_load0.7_dev8_gap300.0	fcfs	-7.8%	[-7.8%, +7.9%]	ok
mix0.1_load0.7_dev8_gap60.0	fcfs	-8.1%	[-8.1%, +8.0%]	ok
mix0.1_load1.0_dev16_gap20.0	vllm_style	-23.2%	[-23.2%, -3.7%]	ok
mix0.1_load1.0_dev16_gap300.0	vllm_style	-23.2%	[-23.2%, -3.3%]	ok
mix0.1_load1.0_dev16_gap60.0	vllm_style	-23.2%	[-23.2%, -3.6%]	ok
mix0.1_load1.0_dev32_gap20.0	vllm_style	-23.5%	[-23.5%, -4.1%]	ok
mix0.1_load1.0_dev32_gap300.0	vllm_style	-23.5%	[-23.5%, -3.4%]	ok
mix0.1_load1.0_dev32_gap60.0	vllm_style	-23.5%	[-23.5%, -3.6%]	ok
mix0.1_load1.0_dev8_gap20.0	vllm_style	-22.5%	[-22.7%, -3.3%]	ok
mix0.1_load1.0_dev8_gap300.0	fastserve_mlfq	-22.6%	[-22.7%, -5.0%]	FAIL (+77.2%)
mix0.1_load1.0_dev8_gap60.0	vllm_style	-22.6%	[-22.7%, -3.0%]	ok
mix0.1_load1.3_dev16_gap20.0	niyama_style	-10.6%	[-10.9%, +9.2%]	ok
mix0.1_load1.3_dev16_gap300.0	niyama_style	-10.7%	[-11.1%, +9.5%]	ok
mix0.1_load1.3_dev16_gap60.0	niyama_style	-10.7%	[-11.0%, +9.7%]	ok
mix0.1_load1.3_dev32_gap20.0	niyama_style	-10.6%	[-10.7%, +9.1%]	ok
mix0.1_load1.3_dev32_gap300.0	niyama_style	-10.8%	[-10.9%, +10.1%]	ok
mix0.1_load1.3_dev32_gap60.0	niyama_style	-10.7%	[-10.8%, +9.9%]	ok
mix0.1_load1.3_dev8_gap20.0	niyama_style	-10.0%	[-10.7%, +9.1%]	ok
mix0.1_load1.3_dev8_gap300.0	niyama_style	-10.2%	[-10.8%, +9.2%]	ok
mix0.1_load1.3_dev8_gap60.0	niyama_style	-10.1%	[-10.7%, +8.8%]	ok
mix0.1_load1.5_dev16_gap20.0	niyama_style	+2.2%	[+1.5%, +19.7%]	ok
mix0.1_load1.5_dev16_gap300.0	niyama_style	+2.0%	[+1.3%, +20.3%]	ok
mix0.1_load1.5_dev16_gap60.0	niyama_style	+2.1%	[+1.4%, +20.3%]	ok
mix0.1_load1.5_dev32_gap20.0	niyama_style	+1.8%	[+1.6%, +19.5%]	ok
mix0.1_load1.5_dev32_gap300.0	niyama_style	+1.7%	[+1.5%, +20.5%]	ok
mix0.1_load1.5_dev32_gap60.0	niyama_style	+1.7%	[+1.6%, +20.2%]	ok
mix0.1_load1.5_dev8_gap20.0	niyama_style	+2.5%	[+1.9%, +20.0%]	ok
mix0.1_load1.5_dev8_gap300.0	niyama_style	+2.3%	[+1.8%, +20.9%]	ok
mix0.1_load1.5_dev8_gap60.0	niyama_style	+2.4%	[+1.8%, +20.6%]	ok
mix0.3_load0.7_dev16_gap20.0	fcfs	-10.9%	[-11.2%, +10.9%]	ok
mix0.3_load0.7_dev16_gap300.0	fcfs	-7.9%	[-8.0%, +9.7%]	ok
mix0.3_load0.7_dev16_gap60.0	fcfs	-9.2%	[-9.4%, +10.7%]	ok
mix0.3_load0.7_dev32_gap20.0	fcfs	-10.5%	[-11.0%, +11.0%]	ok
mix0.3_load0.7_dev32_gap300.0	fcfs	-7.4%	[-7.7%, +9.4%]	ok
mix0.3_load0.7_dev32_gap60.0	fcfs	-8.9%	[-9.2%, +10.6%]	ok
mix0.3_load0.7_dev8_gap20.0	fcfs	-11.0%	[-11.6%, +10.4%]	ok
mix0.3_load0.7_dev8_gap300.0	fcfs	-8.6%	[-8.7%, +8.7%]	ok
mix0.3_load0.7_dev8_gap60.0	fcfs	-9.7%	[-10.1%, +10.1%]	ok
mix0.3_load1.0_dev16_gap20.0	vllm_style	-23.3%	[-23.3%, -7.9%]	ok
mix0.3_load1.0_dev16_gap300.0	vllm_style	-23.3%	[-23.3%, -4.1%]	ok
mix0.3_load1.0_dev16_gap60.0	vllm_style	-23.3%	[-23.3%, -5.3%]	ok
mix0.3_load1.0_dev32_gap20.0	vllm_style	-23.4%	[-23.5%, -7.8%]	ok
mix0.3_load1.0_dev32_gap300.0	vllm_style	-23.5%	[-23.6%, -4.6%]	ok
mix0.3_load1.0_dev32_gap60.0	vllm_style	-23.5%	[-23.6%, -5.7%]	ok
mix0.3_load1.0_dev8_gap20.0	vllm_style	-22.4%	[-22.9%, -7.8%]	ok
mix0.3_load1.0_dev8_gap300.0	vllm_style	-22.4%	[-22.9%, -3.9%]	ok
mix0.3_load1.0_dev8_gap60.0	vllm_style	-22.4%	[-22.9%, -5.0%]	ok
mix0.3_load1.3_dev16_gap20.0	niyama_style	-10.5%	[-10.8%, +4.9%]	ok
mix0.3_load1.3_dev16_gap300.0	niyama_style	-11.0%	[-11.3%, +7.0%]	ok
mix0.3_load1.3_dev16_gap60.0	niyama_style	-10.8%	[-11.0%, +6.3%]	ok

cell	best baseline	improvement	95% CI	guardrail
mix0.3_load1.3_dev32_gap20.0	niyama_style	-10.5%	[-10.7%, +4.6%]	ok
mix0.3_load1.3_dev32_gap300.0	niyama_style	-11.1%	[-11.2%, +8.2%]	ok
mix0.3_load1.3_dev32_gap60.0	niyama_style	-10.8%	[-10.9%, +7.0%]	ok
mix0.3_load1.3_dev8_gap20.0	niyama_style	-9.9%	[-10.5%, +4.1%]	ok
mix0.3_load1.3_dev8_gap300.0	niyama_style	-10.4%	[-11.0%, +7.1%]	ok
mix0.3_load1.3_dev8_gap60.0	niyama_style	-10.1%	[-10.8%, +5.8%]	ok
mix0.3_load1.5_dev16_gap20.0	niyama_style	+2.3%	[+1.8%, +15.4%]	ok
mix0.3_load1.5_dev16_gap300.0	niyama_style	+1.7%	[+1.1%, +19.1%]	ok
mix0.3_load1.5_dev16_gap60.0	niyama_style	+2.0%	[+1.4%, +17.6%]	ok
mix0.3_load1.5_dev32_gap20.0	niyama_style	+2.0%	[+2.0%, +14.9%]	ok
mix0.3_load1.5_dev32_gap300.0	niyama_style	+1.4%	[+1.3%, +18.9%]	ok
mix0.3_load1.5_dev32_gap60.0	niyama_style	+1.7%	[+1.6%, +17.4%]	ok
mix0.3_load1.5_dev8_gap20.0	niyama_style	+3.2%	[+2.1%, +15.1%]	ok
mix0.3_load1.5_dev8_gap300.0	niyama_style	+2.6%	[+1.5%, +19.1%]	ok
mix0.3_load1.5_dev8_gap60.0	niyama_style	+2.9%	[+1.7%, +17.1%]	ok
mix0.5_load0.7_dev16_gap20.0	fastserve_mlfq	-16.0%	[-16.3%, -5.4%]	ok
mix0.5_load0.7_dev16_gap300.0	fcfs	-9.5%	[-9.8%, +10.3%]	ok
mix0.5_load0.7_dev16_gap60.0	vllm_style	-12.5%	[-12.9%, +1.5%]	ok
mix0.5_load0.7_dev32_gap20.0	fastserve_mlfq	-16.1%	[-16.3%, -5.2%]	ok
mix0.5_load0.7_dev32_gap300.0	fcfs	-9.4%	[-9.4%, +10.4%]	ok
mix0.5_load0.7_dev32_gap60.0	fcfs	-12.5%	[-12.5%, +9.7%]	ok
mix0.5_load0.7_dev8_gap20.0	vllm_style	-10.0%	[-15.9%, -4.7%]	ok
mix0.5_load0.7_dev8_gap300.0	fcfs	-9.8%	[-9.8%, +8.8%]	ok
mix0.5_load0.7_dev8_gap60.0	fcfs	-12.8%	[-12.8%, +9.2%]	ok
mix0.5_load1.0_dev16_gap20.0	vllm_style	-22.8%	[-23.0%, -13.2%]	ok
mix0.5_load1.0_dev16_gap300.0	vllm_style	-23.3%	[-23.5%, -6.6%]	ok
mix0.5_load1.0_dev16_gap60.0	vllm_style	-23.2%	[-23.3%, -10.1%]	ok
mix0.5_load1.0_dev32_gap20.0	vllm_style	-23.0%	[-23.1%, -13.4%]	ok
mix0.5_load1.0_dev32_gap300.0	vllm_style	-23.6%	[-23.7%, -6.6%]	ok
mix0.5_load1.0_dev32_gap60.0	vllm_style	-23.4%	[-23.5%, -10.0%]	ok
mix0.5_load1.0_dev8_gap20.0	vllm_style	-22.6%	[-22.6%, -13.5%]	ok
mix0.5_load1.0_dev8_gap300.0	vllm_style	-23.0%	[-23.0%, -6.2%]	ok
mix0.5_load1.0_dev8_gap60.0	vllm_style	-22.9%	[-22.9%, -9.3%]	ok
mix0.5_load1.3_dev16_gap20.0	niyama_style	-10.1%	[-10.4%, -2.7%]	ok
mix0.5_load1.3_dev16_gap300.0	niyama_style	-11.4%	[-11.6%, +4.0%]	ok
mix0.5_load1.3_dev16_gap60.0	niyama_style	-10.8%	[-11.1%, +0.8%]	ok
mix0.5_load1.3_dev32_gap20.0	niyama_style	-10.2%	[-10.4%, -2.2%]	ok
mix0.5_load1.3_dev32_gap300.0	niyama_style	-11.5%	[-11.7%, +5.2%]	ok
mix0.5_load1.3_dev32_gap60.0	niyama_style	-11.0%	[-11.1%, +1.5%]	ok
mix0.5_load1.3_dev8_gap20.0	niyama_style	-9.5%	[-10.0%, -3.5%]	ok
mix0.5_load1.3_dev8_gap300.0	niyama_style	-10.8%	[-11.4%, +4.5%]	ok
mix0.5_load1.3_dev8_gap60.0	niyama_style	-10.3%	[-10.8%, +1.0%]	ok
mix0.5_load1.5_dev16_gap20.0	niyama_style	-1.5%	[-2.2%, +6.2%]	FAIL (+501.7%)
mix0.5_load1.5_dev16_gap300.0	niyama_style	+1.1%	[+0.6%, +15.6%]	ok
mix0.5_load1.5_dev16_gap60.0	niyama_style	+1.9%	[+1.2%, +11.7%]	ok
mix0.5_load1.5_dev32_gap20.0	niyama_style	-1.4%	[-1.9%, +6.9%]	FAIL (+468.6%)
mix0.5_load1.5_dev32_gap300.0	niyama_style	+0.8%	[+0.7%, +15.9%]	ok
mix0.5_load1.5_dev32_gap60.0	niyama_style	+1.5%	[+1.4%, +11.9%]	ok
mix0.5_load1.5_dev8_gap20.0	niyama_style	-1.7%	[-1.9%, +6.1%]	FAIL (+526.5%)
mix0.5_load1.5_dev8_gap300.0	niyama_style	+1.5%	[+1.0%, +14.7%]	ok
mix0.5_load1.5_dev8_gap60.0	niyama_style	+2.2%	[+1.7%, +11.5%]	ok