



Parallel Computing - Others

OpenMP, MPI, R, and GPU

Parallel Automation Levels

Explicit control: Fast but hard

Implicit control: Restrictive but easy



Threads
Processes
MPI
ZeroMQ


OpenMP

Parallel Computing
Libraries on Python

Hadoop
Spark

SQL:
Hive
Pig
Impala

HPC and Big Data K-Means Examples



Dr. Geoffrey Fox, Indiana University. (<http://arxiv.org/pdf/1403.1528.pdf>)


Comparing Spark vs MPI/OpenMP On Word Count MapReduce

Junhao Li

Department of Physics, Cornell University

<https://arxiv.org/abs/1811.04875>

Spark provides an in-memory implementation of MapReduce that is widely used in the big data industry. MPI/OpenMP is a popular framework for high performance parallel computing. This paper presents a high performance MapReduce design in MPI/OpenMP and uses that to compare with Spark on the classic word count MapReduce task. My result shows that the MPI/OpenMP MapReduce is an order of magnitude faster than Apache Spark.



Outline

Classical Paradigm

- OpenMP
- MPI


Modern Paradigm

- ~~Python~~
 - (already covered in lab)
- R

GPU Acceleration


Message Passing vs. Shared Memory

MPI



- Message Passing model: exchange data explicitly via inter-process communication (IPC)
- Application developers define protocol and exchanging format, number of participants, and each exchange

OpenMP



- Shared Memory model: all multiple processes to share data via memory
- Applications must locate and and map shared memory regions to exchange data

message (msg)

OpenMP

- What is OpenMP?
 - Open specification for Multi-Processing
 - “Standard” API for defining multi-threaded shared-memory programs
 - www.openmp.org – Talks, examples, forums, etc.
- High-level API
 - Preprocessor (compiler) directives (~ 80%)
 - Library Calls (~ 19%)
 - Environment Variables (~ 1%)

Who's Involved

OpenMP Architecture Review Board (ARB)

- ARM
- AMD
- Fujitsu
- HP
- IBM
- Intel
- NEC
- Nvidia
- PGI
- Oracle
- Microsoft
- NASA
- Texas Instruments
- (Many Universities)
- (Many Research Labs)
-

<https://www.openmp.org/about/members/>

Why choose OpenMP ?

- Portable
 - **standardized** for shared memory architectures
- Simple and Quick
 - **incremental** parallelization
 - supports both fine-grained and coarse-grained parallelism
 - scalable algorithms without message passing
- Compact API
 - simple and limited set of directives

Traditional Threading in C

```
void* SayHello(void *foo) {
    printf( "Hello, world!\n" );
    return NULL;
}


int main() {
    pthread_attr_t attr;
    pthread_t threads[16];
    int tn;
    pthread_attr_init(&attr);
    pthread_attr_setscope(&attr, PTHREAD_SCOPE_SYSTEM);
    for(tn=0; tn<16; tn++) {
        pthread_create(&threads[tn], &attr, SayHello, NULL);
    }
    for(tn=0; tn<16 ; tn++) {
        pthread_join(threads[tn], NULL);
    }
    return 0;
}
```

OpenMP

- Traditional Threading libraries are hard to use
 - P-Threads/Solaris threads have many library calls for initialization, synchronization, thread creation, condition variables, etc.
 - Programmer must code with multiple threads in mind
- Synchronization between threads introduces a new dimension of program correctness

OpenMP execution model

- Fork and Join: Master thread spawns a team of threads as needed



OpenMP Example in C

```
#include <stdio.h>
#include <omp.h>

int main() {


    omp_set_num_threads(16);

    // Do this part in parallel
    #pragma omp parallel
    {
        printf( "Hello, World!\n" );
    }

    return 0;
}
```

OpenMP


- **Serial regions by default, annotate to create *parallel regions***
 - Generic parallel regions
 - Parallelized loops
 - Sectioned parallel regions
- **Thread-like Fork/Join model**
 - Arbitrary number of *logical* thread creation/ destruction events



OpenMP

```
#include <stdio.h>
#include <omp.h>


int main() {
    // serial region
    printf("Hello...");
    omp_set_num_threads(4)
    // parallel region
    #pragma omp parallel
    {
        printf("World");
    }
    // serial region
    printf("!");
}
```



Hello...WorldWorldWorldWorld!


OpenMP

- Fork/Join can be nested
 - Nesting complication is handled “automatically” at compile-time
 - Independent of the number of threads actually running



OpenMP

```
#include <omp.h>
#include <stdio.h>
void report_num_threads(int level)
{
    #pragma omp single
    {
        printf("Level %d: number of threads in the team - %d\n",
            level, omp_get_num_threads());
    }
}
int main()
{
    omp_set_dynamic(0);
    #pragma omp parallel num_threads(4)
    {
        report_num_threads(1);
        #pragma omp parallel num_threads(8)
        {
            report_num_threads(2);
        }
    }
    return(0);
}
```



OpenMP

- Parallel programs often employ two types of data
 - **Shared** data, visible to all threads.
(often heap-allocated)
 - **Private** data, visible to a single thread.
(often stack-allocated)
- PThreads:
 - Global-scoped variables are **shared**.
 - Stack-allocated variables are **private**.
- OpenMP:
 - **shared** variables are shared.
 - **private** variables are private.

```
int bigdata[1024];

void* foo(void* bar) {
    int tid;

    #pragma omp parallel \
        shared ( bigdata ) \
        private ( tid )
    {
        /* Calculations here */
    }
}
```

OpenMP

#pragma omp reduction

```
#include <stdio.h>
#include <omp.h>

float dot_prod(float* a, float* b, int N)
{
    float sum = 0.0;
    #pragma omp parallel for reduction(+:sum)
    for(int i = 0; i < N; i++) {
        sum += a[i] * b[i];
    }
    return sum;
}
```

OpenMP



C / C++ - sections Directive Example

```
1  #include <omp.h>
2  #define N 1000
3
4  main(int argc, char *argv[]) {
5
6      int i;
7      float a[N], b[N], c[N], d[N];
8
9      /* Some initializations */
10     for (i=0; i < N; i++) {
11         a[i] = i * 1.5;
12         b[i] = i + 22.35;
13     }
14
15     #pragma omp parallel shared(a,b,c,d) private(i)
16     {
17
18         #pragma omp sections nowait
19         {
20
21             #pragma omp section
22             for (i=0; i < N; i++)
23                 c[i] = a[i] + b[i];
24
25             #pragma omp section
26             for (i=0; i < N; i++)
27                 d[i] = a[i] * b[i];
28
29         } /* end of sections */
30
31     } /* end of parallel region */
32
33 }
```

OpenMP

Table 2: OpenMP Functions

Function	Explanation
<i>int omp_get_num_threads()</i>	Gets the number of threads.
<i>int omp_get_thread_num()</i>	Gets the current thread number.
<i>void omp_set_num_threads(int)</i>	Sets the number of threads to be used in future parallel regions.
Locking Functions	
<i>void omp_init_lock(omp_lock_t*)</i>	Initializes a lock.
<i>void omp_set_lock(omp_lock_t*)</i>	Waits and then sets a lock; blocks if the lock is not available.
<i>int omp_test_lock(omp_lock_t*)</i>	Waits and then sets a lock; does not block if the lock is not available.
<i>void omp_unset_lock(omp_lock_t*)</i>	Removes a lock.
<i>void omp_destroy_lock(omp_lock_t*)</i>	Destroys a lock.

Specifications

Home > Specifications



OpenMP 5.0 Specifications

- [OpenMP 5.0 Specification \(PDF\) – Nov 2018 – HTML Version](#)
- [Softcover Version – Purchase from Amazon](#)
- [OpenMP 5.0 Discussion Forum](#)
- [OpenMP 5.0 Reference Guides](#)
- [OpenMP 5.0 Context Definitions Public Comment Draft](#)
- [Supplementary Source Code – \(GitHub Repository\)](#)




OpenMP 4.5 Specifications

- [OpenMP 4.5 Complete Specifications \(Nov 2015\) pdf](#)
- [OpenMP 4.5 Discussion Forum](#)
- [OpenMP 4.5 Reference Guide – C/C++ \(Nov 2015\) pdf](#)
- [OpenMP 4.5 Reference Guide – Fortran \(Nov 2015\) pdf](#)
- [OpenMP 4.5 Examples \(Nov 2016\) pdf](#)
- [OpenMP 4.5 Examples Discussion Forum](#)

<https://www.openmp.org/>


MPI

Distributed



OpenMP

Shared




MPI


- MPI - Message Passing Interface
 - Library standard defined by a committee of vendors, implementers, and parallel programmers
 - Used to create parallel programs based on message passing
 - <https://www.mpi-forum.org/docs/>
- Portable: one standard, many implementations
 - Available on almost all parallel machines in C and Fortran
 - De facto standard platform for the HPC community

MPI

Library functions as the only interface to the communication system!



HPC and Big Data K-Means example



Dr. Geoffrey Fox, Indiana University. (<http://arxiv.org/pdf/1403.1528.pdf>)





Fig. 9. MDS execution time with 32000 points on varying number of nodes. Each node runs 20 parallel tasks.

Parallel Automation Levels

Explicit control: Fast but hard

Implicit control: Restrictive but easy



MPI

- Many parallel programs can be written using just these six functions, only two of which are non-trivial;
 - MPI_INIT
 - MPI_FINALIZE
 - MPI_COMM_SIZE
 - MPI_COMM_RANK
 - MPI_SEND
 - MPI_RECV

MPI

```
#include "mpi.h"
#include <stdio.h>
int main(int argc, char *argv[])
{
    MPI_Init(&argc, &argv);
    printf("Hello, world!\n");
    MPI_Finalize();
    return 0;
}
```

`#include "mpi.h"` provides basic MPI definitions and types.

`MPI_Init` starts MPI

`MPI_Finalize` exits MPI

Notes:

Non-MPI routines are local; this "printf" run on each process

MPI functions return error codes or `MPI_SUCCESS`

Point-to-Point Communication

Four types of point-to-point send operations, each of them available in a blocking and a non-blocking variant

	blocking	Non-blocking
Standard	<code>MPI_Send</code>	<code>MPI_Isend</code>
Buffered	<code>MPI_Bsend</code>	<code>MPI_Ibsend</code>
Synchronous	<code>MPI_Ssend</code>	<code>MPI_Issend</code>
Ready	<code>MPI_Rsend</code>	<code>MPI_Irsend</code>



Standard (regular) send: Asynchronous; the system decides whether or not to buffer messages to be sent

Buffered send: Asynchronous, but buffering of messages to be sent by the system is enforced

Synchronous send: Synchronous, i.e. the send operation is not completed before the receiver has started to receive the message

Ready send: Immediate send is enforced: if no corresponding receive operation is available, the result is undefined

Synchronous Vs. Asynchronous



Point-to-Point Communication

- Meaning of blocking or non-blocking communication (variants with 'l'):
 - Blocking:** the program will not return from the subroutine call until the copy to/from the system buffer has finished.
 - Non-blocking:** the program immediately returns from the subroutine call. It is not assured that the copy to/from the system buffer has completed so that user has to make sure of the completion of the copy.

In MPI,

- Blocking variant: **MPI_Recv**
 - Receive operation is completed when the message has been completely written into the receive buffer
- Non-blocking variant: **MPI_Irecv**
 - Continuation immediately after the receiving has begun
- Can be combined with each of the four send modes
- Non-blocking communications are primarily used to overlap computation with communication and exploit possible performance gains.

Point-to-Point Communication

- Syntax:
`MPI_Send(buf, count, datatype, dest, tag, comm)`
`MPI_Recv(buf, count, datatype, source, tag, comm, status)`
- where
 - `int *buf` pointer to the buffer's begin
 - `int count` number of data objects
 - `int source` process ID of the sending process
 - `int dest` process ID of the destination process
 - `int tag` ID of the message
 - `MPI_Datatype datatype` type of the data objects
 - `MPI_Comm comm` communicator space
 - `MPI_Status *status` object containing message information
- In the non-blocking versions, there's one additional argument request for checking the completion of the communication.

MPI Full Example 1

MPI include file

Declarations, prototypes, etc.

Program Begins

Serial code

Initialize MPI environment

Parallel code begins

Do work & make message passing calls

Terminate MPI environment

Parallel code ends

Program Ends

```
#include "mpi.h"
#include <stdio.h>
#include <stdlib.h>

int main (int argc, char *argv[])
{
    int numtasks, rank, dest, source, rc, count, tag=1;
    char inmsg, outmsg='x';
    MPI_Status Stat;

    MPI_Init(&argc,&argv);
    MPI_Comm_size(MPI_COMM_WORLD, &numtasks);
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);

    if (rank == 0) {
        dest = 1;
        source = 1;
        rc = MPI_Send(&outmsg, 1, MPI_CHAR, dest, tag, MPI_COMM_WORLD);
        rc = MPI_Recv(&inmsg, 1, MPI_CHAR, source, tag, MPI_COMM_WORLD, &Stat);
    }

    else if (rank == 1) {
        dest = 0;
        source = 0;
        rc = MPI_Recv(&inmsg, 1, MPI_CHAR, source, tag, MPI_COMM_WORLD, &Stat);
        rc = MPI_Send(&outmsg, 1, MPI_CHAR, dest, tag, MPI_COMM_WORLD);
    }

    MPI_Finalize();
}
```

MPI Full Example 2

```
#include <stdio.h>
#include <mpi.h>

int main(int argc, char *argv[])
{
    const int tag = 42;          /* Message tag */
    int id, ntasks, source_id, dest_id, err, i;
    MPI_Status status;
    int msg[2]; /* Message array */

    err = MPI_Init(&argc, &argv); /* Initialize
MPI */
    if (err != MPI_SUCCESS) {
        printf("MPI initialization failed!\n");
        exit(1);
    }
    err = MPI_Comm_size(MPI_COMM_WORLD, &ntasks);
    /* Get nr of tasks */
    err = MPI_Comm_rank(MPI_COMM_WORLD, &id); /*
Get id of this process */
    if (ntasks < 2) {
        printf("You have to use at least 2
processors to run this program\n");
        MPI_Finalize(); /* Quit if there is only
one processor */
        exit(0);
    }
}
```

```
if (id == 0) { /* Process 0 (the receiver) does this */
    for (i=1; i<ntasks; i++) {
        err = MPI_Recv(msg, 2, MPI_INT, MPI_ANY_SOURCE,
            tag, MPI_COMM_WORLD, \
                &status); /* Receive a
message */
        source_id = status.MPI_SOURCE; /* Get id of sender
*/
        printf("Received message %d %d from process %d\n",
            msg[0], msg[1], \
                source_id);
    }
}
else { /* Processes 1 to N-1 (the senders) do this */
    msg[0] = id; /* Put own identifier in the message */
    msg[1] = ntasks; /* and total number of
processes */
    dest_id = 0; /* Destination address */
    err = MPI_Send(msg, 2, MPI_INT, dest_id, tag,
        MPI_COMM_WORLD);
}

err = MPI_Finalize(); /* Terminate MPI */
if (id==0) printf("Ready\n");
exit(0);
return 0;
}
```

MPI

- o Collective operations are called by all processes in a communicator
- o **MPI_Bcast** distributes data from one process (the root) to all others in a communicator.

Syntax:

```
MPI_Bcast(void *message, int count, MPI_Datatype  
datatype, int root, MPI_Comm comm)
```

- o **MPI_Reduce** combines data from all processes in communicator or and returns it to one process

Syntax:

```
MPI_Reduce(void *message, void *recvbuf, int count,  
MPI_Datatype datatype, MPI_Op op, int root, MPI_Comm  
comm)
```

- o In many numerical algorithm, send/receive can be replaced by Bcast/Reduce, improving both simplicity and efficiency.

MPI

Function	MPI Call	Type	Purpose
Initialization	<i>MPI_Init</i>	Setup	Prepares system for message-passing functions.
Communication Rank	<i>MPI_Comm_rank</i>	Setup	Provides a unique node number for each node.
Communication Size	<i>MPI_Comm_size</i>	Setup	Provides the number of nodes in the system.
Finalize	<i>MPI_Finalize</i>	Setup	Disable communication services.
Send	<i>MPI_Send</i>	P2P	Send data to a matching receive.
Receive	<i>MPI_Recv</i>	P2P	Receive data from a matching send.
Send-Receive	<i>MPI_Sendrecv</i>	P2P	Simultaneous send and receive between two nodes i.e. send, receive using the same buffer.
Barrier Synchronization	<i>MPI_Barrier</i>	Collective	Synchronize all the nodes together.
Broadcast	<i>MPI_Bcast</i>	Collective	“Root” node sends same data to all other nodes.

Subramaniyan, R., Aggarwal, V., Jacobs, A. and George, A.D., 2006, May. FEMPI: A Lightweight Fault-tolerant MPI for Embedded Cluster Systems. In *ESA* (pp. 3-9).

MPI Forum

This website contains information about the activities of the MPI Forum, which is the standardization forum for the Message Passing Interface (MPI). You may find standard documents, information about the activities of the MPI forum, and links to comment on the MPI Document using the navigation at the top of the page.

[Link to the central MPI-Forum GitHub Presence](#)

MPI 4.0 Standard

The MPI Forum has released a new version of MPI on June 9, 2021. This version is available here:

[MPI 4.0 Standard](#)

Comments on the MPI 4.0 should be sent to the [MPI Comments mailing list](#).

Updates

BoF at SC 20, Nov. 18, 2020

The MPI Forum BoF took place on Wednesday November 18th, 2020 at 10am Eastern US time.

<https://www.mpi-forum.org/>

Lecture Break

R

- There are many parallel computing packages.
- We focus on the following packages:
 - SNOW
 - parallel, foreach, doParallel

R

- SNOW
 - Simple Network Of Workstations

Starting and Stopping clusters

The way to Initialize slave R processes depends on your system configuration. If MPI is installed and there are two computation nodes, then:

```
> cl <- makeCluster(2, type = "MPI")
```

Shut down the cluster and clean up any remaining connections

```
> stopCluster(cl)
```

R

- SNOW

```
> cl <- makeCluster(2, type = "MPI")  
> myfunc <- function(x){x+1}  
> myfunc_argument <- 5  
> clusterCall(cl, function(x){x+1}, 5)  
> stopCluster(cl)
```

```
[[1]]  
[1] 6
```

```
[[2]]  
[1] 6
```

clusterCall(cl, fun, ...)

cl: the computer cluster created with makeCluster.

fun: the function to be applied.

clusterCall calls a specified function with identical arguments on each node in the cluster.

The arguments to clusterCall are evaluated on the master, their values transmitted to the slave nodes which execute the function call.

R

- SNOW

clusterApply(cl, seq, fun, ...)

clusterApply takes a cluster, a sequence of arguments (can be a vector or a list), and a function, and calls the function with the first element of the list on the first node, with the second element of the list on the second node, and so on. The list of arguments must have at most as many elements as there are nodes in the cluster.

```
> cl <- makeCluster(2, type = "MPI")
```

```
> clusterApply(cl, 1:2, sum, 3)
```

```
[[1]]
```

```
[1] 4
```

```
[[2]]
```

```
[1] 5
```

```
> stopCluster(cl)
```

clusterApplyLB is a load balancing version of **clusterApply**. It hands in a balanced work load to slave nodes when the length of **seq** is greater than the number of cluster nodes.

R

- SNOW

```
> A<-matrix(1:10, 5, 2)
```

```
> A
```

```
  [,1] [,2]
```

```
[1,]  1  6
```

```
[2,]  2  7
```

```
[3,]  3  8
```

```
[4,]  4  9
```

```
[5,]  5 10
```

```
> cl <- makeCluster(2, type = "MPI")
```

```
> parApply(cl, A, 1, sum)
```

```
[1]  7  9 11 13 15
```

```
> stopCluster(cl)
```

parApply(cl, X, MARGIN, fun, ...)

X: the array to be used.

MARGIN: a vector giving the subscripts which the function will be applied over. '1' indicates rows, '2' indicates columns, 'c(1,2)' indicates rows and columns.

fun: the function to be applied.

parApply is the parallel version of the R function apply.

R

- SNOW

- <https://cran.r-project.org/web/packages/snow/index.html>

clusterSplit(cl, seq)
clusterCall(cl, fun, ...)
clusterApply(cl, x, fun, ...)
clusterApplyLB(cl, x, fun, ...)
clusterEvalQ(cl, expr)
clusterExport(cl, list, envir = .GlobalEnv)
clusterMap(cl, fun, ..., MoreArgs =
NULL, RECYCLE = TRUE)

parLapply(cl, x, fun, ...)
parSapply(cl, X, FUN, ..., simplify = TRUE,
USE.NAMES = TRUE)
parApply(cl, X, MARGIN, FUN, ...)
parRapply(cl, x, fun, ...)
parCapply(cl, x, fun, ...)
parMM(cl, A, B)

R

- Packages: parallel, foreach, doParallel

```
library(parallel)
```

```
inputs <- 1:10
```

```
processInput <- function(i) {  
  i * i  
}
```

```
numCores <- detectCores()
```

```
results = mclapply(inputs, processInput, mc.cores = numCores)
```

```
# the above won't work on Windows, but this will:
```

```
cl <- makeCluster(numCores)
```

```
results = parLapply(cl, inputs, processInput)
```

```
stopCluster(cl)
```

R

- parallel, foreach, doParallel

```
library(parallel)
library(foreach)
library(doParallel)
numCores <- detectCores()
cl <- makeCluster(numCores)
registerDoParallel(cl)
inputs <- 1:10
processInput <- function(i) {
  i * i
}
results <- foreach(i=inputs) %dopar% {
  processInput(i)
}
```


R

- parallel, foreach, doParallel

```
> x <- iris[which(iris[,5] != "setosa"), c(1,5)]
> trials <- 10000
> ptime <- system.time({
+     r <- foreach(icount(trials), .combine=cbind) %dopar% {
+         ind <- sample(100, 100, replace=TRUE)
+         result1 <- glm(x[ind,2]~x[ind,1], family=binomial(logit))
+         coefficients(result1)
+     }
+ })[3]
> ptime
elapsed
18.693
```

With 2 cores, it took 18.693 sec.
It can take 30.515 sec on 1 core.

R

- SparkR

SparkR is an R package that provides a light-weight frontend to use Apache Spark from R. In Spark 3.2.0, SparkR provides a distributed data frame implementation that supports operations like selection, filtering, aggregation etc. (similar to R data frames, [dplyr](#)) but on large datasets. SparkR also supports distributed machine learning using MLlib.

```
library(SparkR)
```

```
if (nchar(Sys.getenv("SPARK_HOME")) < 1) {  
  Sys.setenv(SPARK_HOME = "/home/spark")  
}  
library(SparkR, lib.loc = c(file.path(Sys.getenv("SPARK_HOME"), "R", "lib")))  
sparkR.session(master = "local[*]", sparkConfig = list(spark.driver.memory = "2g"))
```

<https://spark.apache.org/docs/latest/sparkr.html>

R

- SparkR

A SparkDataFrame is a distributed collection of data organized into named columns. It is conceptually equivalent to a table in a relational database or a data frame in R, but with richer optimizations under the hood. It can be constructed from a wide array of sources such as: structured data files, tables in Hive, external databases, or existing local R data frames.

```
people <- read.df("./examples/src/main/resources/people.json", "json")
head(people)
##   age    name
##1  NA Michael
##2  30    Andy
##3  19   Justin
```

```
df <- read.df(csvPath, "csv", header = "true", inferSchema = "true", na.strings = "NA")
```

```
write.df(people, path = "people.parquet", source = "parquet", mode = "overwrite")
```

GPU Acceleration

- GPU – Graphics Processing Unit
- Originally designed as a graphics processor
 - single-chip processor for mathematically-intensive tasks
 - transformation of vertices and polygons
 - lighting
 - polygon clipping
 - texture mapping
 - polygon rendering



GPU Acceleration

- Since 1999, computer scientists from various fields started using GPUs to accelerate a range of scientific applications.
- GPU programming required the use of graphics APIs such as OpenGL and Cg.
- 2002 James Fung (University of Toronto) developed OpenVIDIA.
- NVIDIA greatly invested in GPGPU movement and offered a number of options and libraries, providing seamless user experience for C, C++ and Fortran programmers.

GPU Acceleration

In November 2006, Nvidia launched CUDA, an API that allows to code algorithms for executions on Geforce GPUs using C programming language.


Khronus Group defined OpenCL in 2008 supported on AMD, Nvidia and ARM platforms.

In 2012, Nvidia presented and demonstrated OpenACC - a set of directives that greatly simplify parallel programming of heterogeneous systems.

After 2015, the explosive advances in artificial intelligence (e.g. deep learning) has sparked people interests in the wide adoption of GPU accelerations such as “tensorflow-gpu” (a python library for deep learning on GPU).


GPU Acceleration

CPU



CPUs consist of a few cores
optimized for serial processing


GPU



GPUs consist of hundreds or
thousands of smaller, efficient cores
designed for parallel performance

GPU Acceleration

CPU




Intel Xeon X5650:

Clock speed: **2.66** GHz
4 instructions per cycle
CPU - **6** cores

$2.66 \times 4 \times 6 =$

63.84 GigaFlops double precision

GPU



NVIDIA Tesla M2070:

Core clock: **1.15**GHz
Single instruction
448 CUDA cores

$1.15 \times 1 \times 448 =$

515 GigaFlops double precision

GPU Acceleration

- GEMM (General Matrix Multiplication) is the fundamental building block for many operations in machine learning (e.g. deep neural networks), for example fully-connected layers, recurrent layers such as RNNs, LSTMs or GRUs, and convolutional layers.
- GEMM is defined as the operation:

$$C = \alpha AB + \beta C$$

with A and B as matrix inputs, α and β as scalar inputs, and C as a pre-existing matrix which is overwritten by the output. A plain matrix product AB is a GEMM with α equal to one and β equal to zero.


- For example, in the forward pass of a fully-connected layer, the weight matrix would be argument A, incoming activations would be argument B, and α and β would typically be 1 and 0, respectively. β can be 1 in some cases, for example, if we're combining the addition of a skip-connection with a linear operation.

GPU Acceleration

GPUs implement GEMMs by partitioning the output matrix into tiles, which are then assigned to thread blocks. Tile size usually refers to the dimensions of these tiles ($M_{tile} \times N_{tile}$ in [Figure 1](#)).

Each thread block computes its output tile by stepping through the K dimension in tiles, loading the required values from the A and B matrices, and multiplying and accumulating them into the output.

Figure 1. Tiled outer product approach to GEMMs



GPU Acceleration

Applications

GPU-accelerated libraries

Seamless linking to GPU-enabled libraries.

tensorflow-gpu, cuFFT, cuBLAS, Thrust, NPP, IMSL, CULA, cuRAND, etc.

OpenACC Directives

Simple directives for easy GPU-acceleration of new and existing applications

PGI Accelerator

Programming Languages

Most powerful and flexible way to design GPU accelerated applications

C/C++, Fortran, Python, Java, etc.


GPU Acceleration

GPU Accelerated Libraries



CUDA is a [parallel computing](#) platform and [application programming interface](#) (API) model created by [Nvidia](#).

The CUDA platform is designed to work with programming languages such as [C](#), [C++](#), and [Fortran](#).



GPU Acceleration

GPU Accelerated Libraries



CUDA is a [parallel computing](#) platform and [application programming interface](#) (API) model created by [Nvidia](#).

The CUDA platform is designed to work with programming languages such as [C](#), [C++](#), and [Fortran](#).

SIMD Programming Model

```
__global__ void kernel(float* x, float* y, float* z, int n){
    int idx= blockIdx.x * blockDim.x + threadIdx.x;
    if(idx < n) z[idx] = x[idx] * y[idx];
}

int main() {
    ...
    cudaMalloc(...);
    cudaMemcpy(...);
    kernel <<<num_blocks, block_size>>> (...);
    cudaMemcpy(...);
    cudaFree(...);
    ...
}
```

GPU Acceleration

GPU Accelerated Libraries



A powerful library of parallel algorithms and data structures;

It provides a flexible, high-level interface for GPU programming;

For example, the `thrust::sort` algorithm delivers 5x to 100x faster sorting performance than STL and TBB

```
// generate 32M random numbers on host
thrust::host_vector<int> h_vec(32 << 20);
thrust::generate(h_vec.begin(),
                 h_vec.end(),
                 rand);

// transfer data to device (GPU)
thrust::device_vector<int> d_vec = h_vec;

// sort data on device (GPU)
thrust::sort(d_vec.begin(), d_vec.end());

// transfer data back to host (Main Memory)
thrust::copy(d_vec.begin(),
             d_vec.end(),
             h_vec.begin());
```

GPU Acceleration

GPU Accelerated Libraries



cuBLAS

- A GPU-accelerated version of the complete standard BLAS library*;
- 6x to 17x faster performance than the latest MKL BLAS
- Complete support for all 152 standard BLAS routines
- Single, double, complex, and double complex data types

```
1 int main() {
2     // Allocate 3 arrays on CPU
3     int nr_rows_A, nr_cols_A, nr_rows_B, nr_cols_B, nr_rows_C, nr_cols_C;
4
5     // for simplicity we are going to use square arrays
6     nr_rows_A = nr_cols_A = nr_rows_B = nr_cols_B = nr_rows_C = nr_cols_C = 3;
7
8     thrust::device_vector<float> d_A(nr_rows_A * nr_cols_A), d_B(nr_rows_B * nr_cols_B), d_C(nr_rows_C * nr_cols_C);
9
10    // Fill the arrays A and B on GPU with random numbers
11    GPU_fill_rand(thrust::raw_pointer_cast(&d_A[0]), nr_rows_A, nr_cols_A);
12    GPU_fill_rand(thrust::raw_pointer_cast(&d_B[0]), nr_rows_B, nr_cols_B);
13
14    // Optionally we can print the data
15    std::cout << "A =" << std::endl;
16    print_matrix(d_A, nr_rows_A, nr_cols_A);
17    std::cout << "B =" << std::endl;
18    print_matrix(d_B, nr_rows_B, nr_cols_B);
19
20    // Multiply A and B on GPU
21    gpu_blas_mmul(thrust::raw_pointer_cast(&d_A[0]), thrust::raw_pointer_cast(&d_B[0]), thrust::raw_pointer_cast(&d_C[0]), nr_rows_A, nr_cols_A, nr_rows_B, nr_cols_B, nr_rows_C, nr_cols_C);
22
23    //Print the result
24    std::cout << "C =" << std::endl;
25    print_matrix(d_C, nr_rows_C, nr_cols_C);
26
27    return 0;
28 }
```

*Basic Linear Algebra Subprograms (BLAS)

<https://solarianprogrammer.com/2012/05/31/matrix-multiplication-cuda-cublas-curand-thrust/>

© "GPU Programming" by Scientific Computing and Visualization at Boston University

GPU Acceleration

Deep Learning Libraries



GPU-accelerated library of primitives for deep neural networks



GPU-accelerated neural network inference library for building deep learning applications




Advanced GPU-accelerated video inference library

Linear Algebra and Math Libraries




cuBLAS

GPU-accelerated standard BLAS library




CUDA Math Library

GPU-accelerated standard mathematical function library



cuSPARSE

GPU-accelerated BLAS for sparse matrices



cuRAND

GPU-accelerated random number generation (RNG)



cuSOLVER

Dense and sparse direct solvers for Computer Vision, CFD, Computational Chemistry, and Linear Optimization applications




AmgX

GPU accelerated linear solvers for simulations and implicit unstructured methods

GPU Acceleration

Signal, Image and Video Libraries



cuFFT

GPU-accelerated library for Fast Fourier Transforms



NVIDIA Performance Primitives


GPU-accelerated library for image and signal processing



NVIDIA Codec SDK

High-performance APIs and tools for hardware accelerated video encode and decode

Parallel Algorithm Libraries



NCCL

Collective Communications Library for scaling apps across multiple GPUs and nodes



nvGRAPH

GPU-accelerated library for graph analytics



Thrust

GPU-accelerated library of parallel algorithms and data structures

Partner Libraries



GPU-accelerated open-source library for computer vision, image processing and machine learning, now supporting real-time operation




Open-source multi-media framework with a library of plugins for audio and video processing



GPU-accelerated open source library for matrix, signal, and image processing

GPU Acceleration



GPU Acceleration

□ Example: Compute $a*x + y$, where x and y are vectors, and a is a scalar.

C (saxpy_array.c)

```
int main(int argc, char **argv){
    int N=1000;
    float a = 3.0f;
    float x[N], y[N];
    for (int i = 0; i < N; ++i) {
        x[i] = 2.0f;
        y[i] = 1.0f;
    }
    #pragma acc kernels
    for (int i = 0; i < N; ++i) {
        y[i] = a * x[i] + y[i];
    }
}
```

Fortran

```
program main
    integer :: n=1000, i
    real :: a=3.0
    real, allocatable :: x(:), y(:)
    allocate(x(n),y(n))
    x(1:n)=2.0
    y(1:n)=1.0
    !$acc kernels
    do i=1,n
        y(i) = a * x(i) + y(i)
    enddo
    !$acc end kernels
end program main
```

GPU Acceleration

```
$ pgcc -acc -Minfo=accel saxpy_array.c -o saxpy_array
```

main:

```
17, Generating copyin(x[:1000])
```

```
Generating copy(y[:1000])
```

```
19, Loop is parallelizable
```

```
Accelerator kernel generated
```

```
Generating Tesla code
```

```
19, #pragma acc loop gang, vector(128) /* blockIdx.x threadIdx.x */
```

https://www.pgroup.com/doc/openacc14_gs.pdf

Li, Xuechao, and Po-Chou Shih. "An Early Performance Comparison of CUDA and OpenACC." *MATEC Web of Conferences*. Vol. 208. EDP Sciences, 2018

GPU Acceleration

- ❑ The loop is not parallelized if there is data dependency. For example,

```
#pragma acc kernels
for (int i = 0; i < N-1; i++) {
    x[i] = a * x[i+1] ;
}
```

- ❑ The compiling output:

```
.....
14, Loop carried dependence of x-> prevents parallelization
    Loop carried backward dependence of x-> prevents vectorization
Accelerator scalar kernel generated
    Loop carried backward dependence of x-> prevents vectorization
```

- ❑ The compiler creates a serial program, which runs slower on GPU than on CPU!

GPU Acceleration

MATLAB with GPU-acceleration

Use GPUs with MATLAB through Parallel Computing Toolbox

- GPU-enabled MATLAB functions such as `fft`, `filter`, and several linear algebra operations
- GPU-enabled functions in toolboxes: Communications System Toolbox, Neural Network Toolbox, Phased Array Systems Toolbox and Signal Processing Toolbox
- CUDA kernel integration in MATLAB applications, using only a single line of MATLAB code

```
A=rand(2^16,1);
```

```
B=fft(A);
```

```
A=gpuArray(rand(2^16,1));
```

```
B=fft(A);
```

GPU Acceleration

Deep Learning (Python Tensorflow) with GPU

```
.....
def matpow(M, n):
    if n < 1: #Abstract cases where n < 1
        return M
    else:
        return tf.matmul(M, matpow(M, n-1))

with tf.device('/gpu:0'):
    a = tf.placeholder(tf.float32, [10000, 10000])
    b = tf.placeholder(tf.float32, [10000, 10000])
    # Compute A^n and B^n and store results in c1
    c1.append(matpow(a, n))
    c1.append(matpow(b, n))

with tf.device('/cpu:0'):
    sum = tf.add_n(c1) #Addition of all elements in c1, i.e. A^n + B^n
.....
```

<https://gist.github.com/j-min/baae1aa56e861cab9831b3722755ae6d>

GPU Acceleration

Programming Languages

Numerical analytics ►

MATLAB, Mathematica, LabVIEW

Fortran ►

OpenACC, CUDA Fortran,

C ►

OpenACC, CUDA C, Thrust,

C++ ►

OpenACC, CUDA C++, Thrust,

Python ►

PyCUDA, Copperhead, Tensorflow, ...

GPU Acceleration

- When should GPU Acceleration be used?
 - **Computationally intensive scenario**
 - The time spent on computation significantly exceeds the time spent on transferring data to and from GPU memory.
 - Single precision performance is better than double precision.
 - Algorithms that require little communication between threads.
 - **Massively parallel scenario**
 - The computations can be broken down into hundreds or thousands of independent units of work.
 - Doing the same calculation with many pieces of input data.
 - The number of processing steps should be at least an order of magnitude greater than the number of pieces of input/output data.
 - Algorithms where most of the cores will follow the same branch paths most of the time.

Summary

- Classical Paradigm
 - OpenMP
 - MPI
- Modern Paradigm
 - ~~Python~~ (already covered in lab)
 - R
- GPU Acceleration

Reference

OpenMP

Table 1: Clauses

Clause	Meaning
<i>shared(variable_list)</i>	Only one version of the variable exists, and all parallel program sections access it. All threads have read and write access. If a thread changes a variable, this also affects the other threads. Default: All variables are <i>shared()</i> except the loop variables in <i>#pragma omp for</i> .
<i>private(variable_list)</i>	Each thread has a private, non initialized copy of the variable. Default: Only loop variables are private.
<i>default(shared private none)</i>	Defines the default behavior of the variables: <i>none</i> means that you must explicitly declare each variable as <i>shared()</i> or <i>private()</i> .
<i>firstprivate(variable_list)</i>	Just like <i>private()</i> ; however, in this case, all copies are initialized with the value of the variable before the parallel loop/region.
<i>lastprivate(variable_list)</i>	The variable is assigned the value from the last thread to change the variable in sequential processing after the parallel loop/region has been completed.

```
a = 0 ; b = 0 ;  
#pragma omp parallel for private(i) shared(x, y, n) reduction(+:a, b)  
for (i=0; i<n; i++) {  
    a = a + x[i] ;  
    b = b + y[i] ;  
}
```