

API Java

- Con API (Application Programming Interface) si indicano tutta una serie di procedure che sono a disposizione del programmatore.
- In particolare le API Java mostrano tutte le classi offerte dal linguaggio e descrivono i metodi a disposizione in ogni classe.
 - Anche dette le librerie Java
- Le API per Java 8 sono disponibili all'URL <https://docs.oracle.com/javase/8/docs/api/>

API Java

- Per ogni classe le API riportano e descrivono in dettaglio superclassi, sottoclassi, funzionalità ad alto livello della classe, campi, costruttori, metodi.
- In questa esercitazione ci concentreremo soprattutto sui metodi

API Java

Browser address bar: <https://docs.oracle.com/javase/7/docs/api/> Search: api java

Java™ Platform Standard Ed. 7

Overview Package Class Use Tree Deprecated Index Help

Prev Next Frames No Frames

Java™ Platform, Standard Edition 7 API Specification

This document is the API specification for the Java™ Platform, Standard Edition.

See: Description

Packages

Package	Description
java.applet	Provides the classes necessary to create an applet and the classes an applet uses to communicate with its applet context.
java.awt	Contains all of the classes for creating user interfaces and for painting graphics and images.
java.awt.color	Provides classes for color spaces.
java.awt.datatransfer	Provides interfaces and classes for transferring data between and within applications.
java.awt.dnd	Drag and Drop is a direct manipulation gesture found in many Graphical User Interface systems that provides a mechanism to transfer information between two entities logically associated with presentation elements in the GUI.
java.awt.event	Provides interfaces and classes for dealing with different types of events fired by AWT components.
java.awt.font	Provides classes and interface relating to fonts.
java.awt.geom	Provides the Java 2D classes for defining and performing operations on objects related to two-dimensional geometry.
java.awt.im	Provides classes and interfaces for the input method framework.
java.awt.im.spi	Provides interfaces that enable the development of input methods that can be used with any Java runtime environment.
java.awt.image	Provides classes for creating and modifying images.
java.awt.image.renderable	Provides classes and interfaces for producing rendering-independent images.
java.awt.print	Provides classes and interfaces for a general printing API.
java.beans	Contains classes related to developing <i>beans</i> -- components based on the JavaBeans™ architecture.
java.beans.beancontext	Provides classes and interfaces relating to bean context.
java.io	Provides for system input and output through data streams, serialization and the file system.
java.lang	Provides classes that are fundamental to the design of the Java programming language.
java.lang.annotation	Provides library support for the Java programming language annotation facility.
java.lang.instrument	Provides services that allow Java programming language agents to instrument programs running on the JVM.

Left sidebar (All Classes):

- AbstractAction
- AbstractAnnotationValueVisitor6
- AbstractAnnotationValueVisitor7
- AbstractBorder
- AbstractButton
- AbstractCellEditor
- AbstractCollection
- AbstractColorChooserPanel
- AbstractDocument
- AbstractDocument.AttributeContext
- AbstractDocument.Content
- AbstractDocument.ElementEdit
- AbstractElementVisitor6
- AbstractElementVisitor7
- AbstractExecutorService
- AbstractInterruptibleChannel
- AbstractLayoutCache
- AbstractLayoutCache.NodeDimensions
- AbstractList
- AbstractListModel
- AbstractMap
- AbstractMap.SimpleEntry
- AbstractMap.SimpleImmutableEntry
- AbstractMarshallerImpl
- AbstractMethodError
- AbstractOwnableSynchronizer
- AbstractPreferences
- AbstractProcessor
- AbstractQueue
- AbstractQueuedLongSynchronizer
- AbstractQueuedSynchronizer

API Java

Esempio: la classe String

The screenshot shows the Oracle Java API documentation for the `String` class. The browser address bar shows `https://docs.oracle.com/javase/7/docs/api/` and the search bar contains `api java`. The left sidebar lists various Java packages, with `String` highlighted under the `java.lang` package. The main content area displays the `String` class details, including its inheritance hierarchy, implemented interfaces, and source code.

Overview Package **Class** Use Tree Deprecated Index Help

Prev Class Next Class Frames No Frames

Summary: Nested | Field | Constr | Method Detail: Field | Constr | Method

java.lang

Class String

java.lang.Object
java.lang.String

All Implemented Interfaces:

Serializable, CharSequence, Comparable<String>

```
public final class String
extends Object
implements Serializable, Comparable<String>, CharSequence
```

The `String` class represents character strings. All string literals in Java programs, such as `"abc"`, are implemented as instances of this class.

Strings are constant; their values cannot be changed after they are created. String buffers support mutable strings. Because String objects are immutable they can be shared. For example:

```
String str = "abc";
```

is equivalent to:

```
char data[] = {'a', 'b', 'c'};
String str = new String(data);
```

Here are some more examples of how strings can be used:

```
System.out.println("abc");
String cde = "cde";
System.out.println("abc" + cde);
String c = "abc".substring(2,3);
String d = cde.substring(1, 2);
```

The class `String` includes methods for examining individual characters of the sequence, for comparing strings, for searching strings, for extracting substrings, and for creating a copy of a string with all characters translated to uppercase or to lowercase. Case mapping is based on the Unicode Standard version specified by the `Character` class.

The Java language provides special support for the string concatenation operator (`+`), and for conversion of other objects to strings. String concatenation is implemented through the `StringBuilder` (or `StringBuffer`) class and its `append` method. String conversions are implemented through the method `toString`, defined by `Object` and inherited by all classes in Java. For additional information on string concatenation and conversion, see Gosling, Joy, and Steele, *The Java Language Specification*.

API Java

Esempio: la classe String

https://docs.oracle.com/javase/7/docs/api/

java.awt.image.renderable
java.awt.print
java.beans
java.beans.beancontext
java.io
java.lang
java.lang.annotation
java.lang.instrument
java.lang.invoke
java.lang.management
java.lang.ref
java.lang.reflect
java.math
java.net
java.nio
StatementEvent
StatementEventListener
StAXResult
StAXSource
Streamable
StreamableValue
StreamCorruptedException
StreamFilter
StreamHandler
StreamPrintService
StreamPrintServiceFactory
StreamReaderDelegate
StreamResult
StreamSource
StreamTokenizer
StrictMath
String
StringBuffer
StringBufferInputStream
StringBuilder
StringCharacterIterator
StringContent
StringHolder
StringIndexOutOfBoundsException
StringMonitor
StringMonitorMBean
StringNameHelper
StringReader
StringRefAddr
StringSelection
StringSeqHelper
StringSeqHolder
StringTokenizer
StringValueExp

Field Summary

Fields	
Modifier and Type	Field and Description
static Comparator<String>	CASE_INSENSITIVE_ORDER A Comparator that orders String objects as by compareToIgnoreCase.

Constructor Summary

Constructors	
Constructor and Description	
String()	Initializes a newly created String object so that it represents an empty character sequence.
String(byte[] bytes)	Constructs a new String by decoding the specified array of bytes using the platform's default charset.
String(byte[] bytes, Charset charset)	Constructs a new String by decoding the specified array of bytes using the specified charset.
String(byte[] ascii, int hibyte)	Deprecated. This method does not properly convert bytes into characters. As of JDK 1.1, the preferred way to do this is via the String constructors that take a Charset, charset name, or that use the platform's default charset.
String(byte[] bytes, int offset, int length)	Constructs a new String by decoding the specified subarray of bytes using the platform's default charset.
String(byte[] bytes, int offset, int length, Charset charset)	Constructs a new String by decoding the specified subarray of bytes using the specified charset.
String(byte[] ascii, int hibyte, int offset, int count)	Deprecated. This method does not properly convert bytes into characters. As of JDK 1.1, the preferred way to do this is via the String constructors that take a Charset, charset name, or that use the platform's default charset.
String(byte[] bytes, int offset, int length, String charsetName)	Constructs a new String by decoding the specified subarray of bytes using the specified charset.
String(byte[] bytes, String charsetName)	Constructs a new String by decoding the specified array of bytes using the specified charset.
String(char[] value)	Allocates a new String so that it represents the sequence of characters currently contained in the character array argument.
String(char[] value, int offset, int count)	

Intro

Nel risolvere gli esercizi

si faccia riferimento ai seguenti metodi della classe String:

- *toUpperCase()* per trasformare tutti i caratteri di una stringa in maiuscolo
- *substring(i,j)* per estrarre una sottostringa
- *contains(x)* per verificare che una stringa contenga la stringa x
- *length()* per ottenere la lunghezza della stringa
- *charAt(i)* per ottenere l'i-esimo carattere della stringa

Per utilizzare i metodi della classe JOptionPane, questa va importata dal package javax.swing

Per utilizzare i metodi della classe Scanner, questa va importata dal package java.util

Esercizio 1

Scrivere un programma Java che date due stringhe in input stampi *true* se una stringa è contenuta nell'altra, *false* altrimenti.

Implementare due varianti in cui le stringhe sono:

- Lette in input dalla console
- Lette in input da finestra di dialogo (JOptionPane)

Esercizio 2

Scrivere un programma Java che data una stringa interamente in minuscolo, stampi la stringa stessa con le lettere nelle posizioni dispari in maiuscolo.

Esempio: input = programmazione ; output= PrOgRaMmAzIoNe

Esercizio 3

Scrivere un programma Java che dato un intero rappresentante un anno, indichi se questo è bisestile.

Un anno è bisestile se è divisibile per 4 ma non per 100, oppure per 400.

Esercizio 4

Scrivere un programma Java che date due stringhe, stampi il rapporto tra le lunghezze delle stringhe stesse.

*Esempio: input1 = "lessie", input2 = "rex" il risultato deve essere 2,
input1 = "rex", input2 = "lessie" il risultato deve essere 0.5*

Esercizio 5

Scrivere un programma Java che chieda in input all'utente due stringhe, e stampi solo la stringa che abbia la somma dei codici ASCII delle proprie lettere maggiore e il valore di tale somma.

Esempio: se le stringhe passate sono "aaa" e "aab" il programma deve stampare "aab 292"

Esercizio 6

Scrivere un programma Java che calcoli l'area di triangoli. Iterativamente il programma deve chiedere in input all'utente due valori numerici rappresentanti la base e l'altezza del triangolo corrente (leggendolo o da console o da JOptionPane) e deve scrivere il risultato in una finestra di output.

Il programma continua a chiedere valori e ad eseguire il calcolo finché non viene inserito un numero negativo.

API Java

Esempio: la classe String

← ⓘ 🔒 https://docs.oracle.com/javase/7/docs/api/ ↻ 🔍 api java ☆ 📁 📄 ⬇ 🏠 🚫

java.awt.image.renderable

java.awt.print

java.beans

java.beans.beancontext

java.io

java.lang

java.lang.annotation

java.lang.instrument

java.lang.invoke

java.lang.management

java.lang.ref

java.lang.reflect

java.math

java.net

java.nio

StatementEvent

StatementEventListener

StAXResult

StAXSource

Streamable

StreamableValue

StreamCorruptedException

StreamFilter

StreamHandler

StreamPrintService

StreamPrintServiceFactory

StreamReaderDelegate

StreamResult

StreamSource

StreamTokenizer

StrictMath

String

StringBuffer

StringBufferInputStream

StringBuilder

StringCharacterIterator

StringContent

StringHolder

StringIndexOutOfBoundsException

StringMonitor

StringMonitorMBean

StringNameHelper

StringReader

StringRefAddr

StringSelection

StringSeqHelper

StringSeqHolder

StringTokenizer

StringValueExp

Method Summary

Methods

Modifier and Type	Method and Description
char	<code>charAt(int index)</code> Returns the char value at the specified index.
int	<code>codePointAt(int index)</code> Returns the character (Unicode code point) at the specified index.
int	<code>codePointBefore(int index)</code> Returns the character (Unicode code point) before the specified index.
int	<code>codePointCount(int beginIndex, int endIndex)</code> Returns the number of Unicode code points in the specified text range of this String.
int	<code>compareTo(String anotherString)</code> Compares two strings lexicographically.
int	<code>compareToIgnoreCase(String str)</code> Compares two strings lexicographically, ignoring case differences.
String	<code>concat(String str)</code> Concatenates the specified string to the end of this string.
boolean	<code>contains(CharSequence s)</code> Returns true if and only if this string contains the specified sequence of char values.
boolean	<code>contentEquals(CharSequence cs)</code> Compares this string to the specified CharSequence.
boolean	<code>contentEquals(StringBuffer sb)</code> Compares this string to the specified StringBuffer.
static String	<code>copyValueOf(char[] data)</code> Returns a String that represents the character sequence in the array specified.
static String	<code>copyValueOf(char[] data, int offset, int count)</code> Returns a String that represents the character sequence in the array specified.
boolean	<code>endsWith(String suffix)</code> Tests if this string ends with the specified suffix.
boolean	<code>equals(Object anObject)</code> Compares this string to the specified object.
boolean	<code>equalsIgnoreCase(String anotherString)</code> Compares this String to another String, ignoring case considerations.
static String	<code>format(Locale l, String format, Object... args)</code> Returns a formatted string using the specified locale, format string, and arguments.
static String	<code>format(String format, Object... args)</code> Returns a formatted string using the specified format string and arguments.