

## NAME

SplitTextFiles.pl - Split CSV or TSV TextFile(s) into multiple text files

## SYNOPSIS

SplitTextFiles.pl TextFile(s)...

SplitTextFiles.pl [-f, --fast] [-h, --help] [--indelim comma | semicolon] [-l, --label yes | no] [-n, --numfiles number] [-o, --overwrite] [--outdelim comma | tab | semicolon] [-q, --quote yes | no] [-r, --root rootname] [-w, --workingdir dirname] TextFile(s)...

## DESCRIPTION

Split CSV or TSV *TextFile(s)* into multiple text files. Each new text file contains a subset of similar number of lines from the initial file. The file names are separated by space. The valid file extensions are *.csv* and *.tsv* for comma/semicolon and tab delimited text files respectively. All other file names are ignored. All the text files in a current directory can be specified by *\*.csv*, *\*.tsv*, or the current directory name. The --indelim option determines the format of *TextFile(s)*. Any file which doesn't correspond to the format indicated by --indelim option is ignored.

## OPTIONS

-f, --fast

In this mode, --indelim, --outdelim, and -q --quote options are ignored. The format of input and output file(s) are assumed to be similar. And the text lines from input *TextFile(s)* are just transferred to output file(s) without any processing.

-h, --help

Print this help message.

--indelim *comma | semicolon*

Input delimiter for CSV *TextFile(s)*. Possible values: *comma* or *semicolon*. Default value: *comma*. For TSV files, this option is ignored and *tab* is used as a delimiter.

-l, --label *yes | no*

First line contains column labels. Possible values: *yes* or *no*. Default value: *yes*.

-n, --numfiles *number*

Number of new files to generate for each TextFile(s). Default: 2.

-o, --overwrite

Overwrite existing files.

--outdelim *comma | tab | semicolon*

Output text file delimiter. Possible values: *comma*, *tab*, or *semicolon*. Default value: *comma*

-q, --quote *yes | no*

Put quotes around column values in output text file. Possible values: *yes* or *no*. Default value: *yes*.

-r, --root *rootname*

New text file names are generated using the root: <Root>Part<Count>.<Ext>. Default new file names: <InitialTextFileName>Part<Count>.<Ext>. The csv, and tsv <Ext> values are used for comma/semicolon, and tab delimited text files respectively. This option is ignored for multiple input files.

-w, --workingdir *dirname*

Location of working directory. Default: current directory.

## EXAMPLES

To split each CSV text files into 4 different text files type:

```
% SplitTextFiles.pl -n 5 -o Sample1.csv Sample2.csv
% SplitTextFiles.pl -n 5 -o *.csv
```

To split Sample1.tsv into 10 different CSV text files, type:

```
% SplitTextFiles.pl -n 10 --outdelim comma -o Sample1.csv
```

## AUTHOR

Manish Sud <msud@san.rr.com>

## SEE ALSO

JoinTextFiles.pl, MergeTextFiles.pl, ModifyTextFilesFormat.pl

## COPYRIGHT

Copyright (C) 2018 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

---

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.