NAME

RDKitUtil

SYNOPSIS

import RDKitUtil

DESCRIPTION

RDKitUtil module provides the following functions:

GetInlineSVGForMolecule, GetInlineSVGForMolecules, GetMolName, GetSVGForMolecule, GetSVGForMolecules, IsMolEmpty, MoleculesWriter, ReadAndValidateMolecules, ReadMolecules, ReadMoleculesFromMol2File, ReadMoleculesFromMolFile, ReadMoleculesFromPDBFile, ReadMoleculesFromSDFile, ReadMoleculesFromSMILESFile, WriteMolecules

FUNCTIONS

GetInlineSVGForMolecule

```
    GetInlineSVGForMolecule(Mol, Width, Height, Legend = None, AtomListToHighlight = None,
BondListToHighlight = None, BoldText = True)
```

Get SVG image text for a molecule suitable for inline embedding into a HTML page.

Arguments:

```
    Mol (object): RDKit molecule object.
    Width (int): Width of a molecule image in pixels.
    Height (int): Height of a molecule image in pixels.
    Legend (str): Text to display under the image.
    AtomListToHighlight (list): List of atoms to highlight.
    BondListToHighlight (list): List of bonds to highlight.
    BoldText (bool): Flag to make text bold in the image of molecule.
```

Returns:

```
    str : SVG image text for inline embedding into a HTML page using "img"
        tag: <img src="data:image/svg+xml;charset=UTF-8,SVGImageText>
```

GetInlineSVGForMolecules

```
    GetInlineSVGForMolecules(Mols, MolsPerRow, MolWidth, MolHeight, Legends = None,
AtomListsToHighlight = None, BondListsToHighLight = None, BoldText = True)
```

Get SVG image text for molecules suitable for inline embedding into a HTML page.

Arguments:

```
    Mols (list): List of RDKit molecule objects.
    MolsPerRow (int): Number of molecules per row.
    Width (int): Width of a molecule image in pixels.
    Height (int): Height of a molecule image in pixels.
    Legends (list): List containing strings to display under images.
    AtomListsToHighlight (list): List of lists containing atoms to highlight
        for molecules.
    BondListsToHighlight (list): List of lists containing bonds to highlight
        for molecules
    BoldText (bool): Flag to make text bold in the image of molecules.
```

Returns:

```
    str : SVG image text for inline embedding into a HTML page using "img"
        tag: <img src="data:image/svg+xml;charset=UTF-8,SVGImageText>
```

GetMolName

```
    GetMolName(Mol, MolNum = None)
```

Get molecule name.

Arguments:

```
    Mol (object): RDKit molecule object.
    MolNum (int or None): Molecule number in input file.
```

Returns:

```
    str : Molname corresponding to _Name property of a molecule, generated
        from specieid MolNum using the format "Mol%d" % MolNum, or an
        empty string.
```

GetSVGForMolecule

```
    GetSVGForMolecule(Mol, Width, Height, Legend = None, AtomListToHighlight = None,
BondListToHighlight = None, BoldText = True)
```

Get SVG image text for a molecule suitable for viewing in a browser.

Arguments:

```
Mol (object): RDKit molecule object.
Width (int): Width of a molecule image in pixels.
Height (int): Height of a molecule image in pixels.
Legend (str): Text to display under the image.
AtomListToHighlight (list): List of atoms to highlight.
BondListToHighlight (list): List of bonds to highlight.
BoldText (bool): Flag to make text bold in the image of molecule.
```

Returns:

```
str : SVG image text for writing to a SVG file for viewing in a browser.
```

GetSVGForMolecules

```
GetSVGForMolecules(Mols, MolsPerRow, MolWidth, MolHeight, Legends = None, AtomListsToHighlight =
None, BondListsToHighlight = None, BoldText = True)
```

Get SVG image text for molecules suitable for viewing in a browser.

Arguments:

```
Mols (list): List of RDKit molecule objects.
MolsPerRow (int): Number of molecules per row.
Width (int): Width of a molecule image in pixels.
Height (int): Height of a molecule image in pixels.
Legends (list): List containing strings to display under images.
AtomListsToHighlight (list): List of lists containing atoms to highlight
    for molecules.
BondListsToHighlight (list): List of lists containing bonds to highlight
    for molecules
BoldText (bool): Flag to make text bold in the image of molecules.
```

Returns:

```
str : SVG image text for writing to a SVG file for viewing in a browser.
```

IsMolEmpty

```
IsMolEmpty(Mol)
```

Check for the presence of atoms in a molecule.

Arguments:

```
Mol (object): RDKit molecule object.
```

Returns:

```
bool : True - No atoms in molecule; Otherwise, false.
```

MoleculesWriter

```
MoleculesWriter(FileName, **KeyWordArgs)
```

Set up a molecule writer.

Arguments:

```
FileName (str): Name of a file with complete path.
**KeyWordArgs (dictionary) : Parameter name and value pairs for writing and
    processing molecules.
```

Returns:

```
RDKit object : Molecule writer.
```

The file extension is used to determine type of the file and set up an appropriate file writer.

ReadAndValidateMolecules

```
ReadAndValidateMolecules(FileName, **KeyWordArgs)
```

Read molecules from an input file, validate all molecule objects, and return a list of valid and non-valid molecule objects along with their counts.

Arguments:

```
FileName (str): Name of a file with complete path.
**KeyWordArgs (dictionary) : Parameter name and value pairs for reading and
    processing molecules.
```

Returns:

```
list : List of valid RDKit molecule objects.
```

```
    int : Number of total molecules in input file.
    int : Number of valid molecules in input file.
```

The file extension is used to determine type of the file and set up an appropriate file reader.

ReadMolecules

```
    ReadMolecules(FileName, **KeyWordArgs)
```

Read molecules from an input file without performing any validation and creation of molecule objects.

Arguments:

```
    FileName (str): Name of a file with complete path.
    **KeyWordArgs (dictionary) : Parameter name and value pairs for reading and
        processing molecules.
```

Returns:

```
    list : List of RDKit molecule objects.
```

The file extension is used to determine type of the file and set up an appropriate file reader.

ReadMoleculesFromMol2File

```
    ReadMoleculesFromMol2File(FileName, Sanitize = True, RemoveHydrogens = True)
```

Read molecule from a Tripos Mol2 file.

Arguments:

```
    FileName (str): Name of a file with complete path.
    Sanitize (bool): Sanitize molecules.
    RemoveHydrogens (bool): Remove hydrogens from molecules.
```

Returns:

```
    list : List of RDKit molecule objects.
```

ReadMoleculesFromMolFile

```
    ReadMoleculesFromMolFile(FileName, Sanitize = True, RemoveHydrogens = True, StrictParsing = True)
```

Read molecule from a MDL Mol file.

Arguments:

```
    FileName (str): Name of a file with complete path.
    Sanitize (bool): Sanitize molecules.
    RemoveHydrogens (bool): Remove hydrogens from molecules.
    StrictParsing (bool): Perform strict parsing.
```

Returns:

```
    list : List of RDKit molecule objects.
```

ReadMoleculesFromPDBFile

```
    ReadMoleculesFromPDBFile(FileName, Sanitize = True, RemoveHydrogens = True)
```

Read molecule from a PDB file.

Arguments:

```
    FileName (str): Name of a file with complete path.
    Sanitize (bool): Sanitize molecules.
    RemoveHydrogens (bool): Remove hydrogens from molecules.
```

Returns:

```
    list : List of RDKit molecule objects.
```

ReadMoleculesFromSDFile

```
    ReadMoleculesFromSDFile(FileName, Sanitize = True, RemoveHydrogens = True, StrictParsing = True)
```

Read molecules from a SD file.

Arguments:

```
    FileName (str): Name of a file with complete path.
    Sanitize (bool): Sanitize molecules.
    RemoveHydrogens (bool): Remove hydrogens from molecules.
    StrictParsing (bool): Perform strict parsing.
```

Returns:

```
    list : List of RDKit molecule objects.
```

ReadMoleculesFromSMILESFile

```
    ReadMoleculesFromSMILESFile(FileName, SMILESDelimiter = ' ', SMILESColIndex = 0,
SMILESNameColIndex = 1, SMILESTitleLine = 1, Sanitize = 1)
```

Read molecules from a SMILES file.

Arguments:

```
    SMILESDelimiter (str): Delimiter for parsing SMILES line
    SMILESColIndex (int): Column index containing SMILES string.
    SMILESNameColIndex (int): Column index containing molecule name.
    SMILESTitleLine (int): Flag to indicate presence of title line.
    Sanitize (int): Sanitize molecules.
```

Returns:

```
    list : List of RDKit molecule objects.
```

WriteMolecules

```
    WriteMolecules(FileName, Mols, **KeyWordArgs)
```

Write molecules to an output file.

Arguments:

```
    FileName (str): Name of a file with complete path.
    Mols (list): List of RDKit molecule objects.
    **KeyWordArgs (dictionary) : Parameter name and value pairs for writing and
        processing molecules.
```

Returns:

```
    int : Number of total molecules.
    int : Number of processed molecules written to output file.
```

The file extension is used to determine type of the file and set up an appropriate file writer.

AUTHOR

Manish Sud <msud@san.rr.com>

COPYRIGHT

The functionality available in the script is implemented using RDKit, an open source toolkit for cheminformatics developed by Greg Landrum.