CISCO PACKET TRACER - PRINTABLE CHECKLIST

229 separate tasks | Check one at a time after verifying the actual activity requirements

Round/date: _____ Team: _____

Activity/file: _____ Initial: _____ Final: _____

Write N/A when task not assigned. Never modify the activity grader or overwrite working configs.

01. Read and preserve the Packet Tracer activity

- [ ] **C001** Read the entire Packet Tracer activity instruction pane N/A
- [ ] **C002** Identify required PKA/PKT file type and submission method N/A
- [ ] **C003** Record the exact device names mentioned in the task N/A
- [ ] **C004** Record all required configurations and changes N/A
- [ ] **C005** Record settings or services that must remain unchanged N/A
- [ ] **C006** Identify available Check Results or Activity Assessment controls N/A
- [ ] **C007** Use grading feedback only when the activity permits it N/A
- [ ] **C008** Save a working copy of the activity if permitted N/A
- [ ] **C009** Record initial completion result when shown N/A
- [ ] **C010** Identify all permitted source notes and external resources N/A
- [ ] **C011** Do not erase any device startup configuration N/A
- [ ] **C012** Do not reset or modify the activity assessment/grader N/A
- [ ] **C013** Keep a task list with each device and interface N/A

Notes / exceptions: _____

02. Inspect topology, IP plan and endpoints

- [ ] **C014** Identify all routers and their model/IOS capabilities N/A
- [ ] **C015** Identify all switches and model/port numbering N/A
- [ ] **C016** Identify every PC, server and wireless endpoint N/A
- [ ] **C017** Record each physical link between devices N/A
- [ ] **C018** Record router interface names and peer interfaces N/A
- [ ] **C019** Record client VLAN membership requirements N/A
- [ ] **C020** Record IPv4 addresses and masks for each LAN N/A

- [ ] **C021** Record client default gateways N/A
- [ ] **C022** Record DNS server addresses N/A
- [ ] **C023** Record any IPv6 prefixes and addresses N/A
- [ ] **C024** Record each server’s configured address and role N/A
- [ ] **C025** Record static and dynamic routing requirements N/A
- [ ] **C026** Check which topology devices are administratively shut down N/A
- [ ] **C027** Record each network service to test at the end N/A

Notes / exceptions: _____

03. Cisco IOS basics and safe baseline

- [ ] **C028** Open the CLI on each relevant router and switch N/A
- [ ] **C029** Identify user EXEC and privileged EXEC prompt N/A
- [ ] **C030** Enter enable mode only with authorized credentials N/A
- [ ] **C031** Check device model and IOS version N/A
- [ ] **C032** Inspect running configuration N/A
- [ ] **C033** Inspect saved startup configuration N/A
- [ ] **C034** Check interface IP addresses and status N/A
- [ ] **C035** Check relevant switch VLAN list N/A
- [ ] **C036** Check operational trunks if supported N/A
- [ ] **C037** Check router routing table N/A
- [ ] **C038** Check access lists if configured N/A
- [ ] **C039** Record original settings before any modification N/A
- [ ] **C040** Use question-mark help for an unsupported command N/A
- [ ] **C041** Do not run erase startup-config or reload as a shortcut N/A

Notes / exceptions: _____

04. Physical links and interface state

- [ ] **C042** Check every required cable connects correct ports N/A
- [ ] **C043** Check cable/media compatibility and interface modules N/A
- [ ] **C044** Check correct router/switch interface identity N/A
- [ ] **C045** Check both ends of an unexpectedly down link N/A

- [ ] **C046** Distinguish administratively down from down/down N/A
- [ ] **C047** Enable only a required disabled interface N/A
- [ ] **C048** Confirm link becomes operational after change N/A
- [ ] **C049** Check switch port speed and duplex if required N/A
- [ ] **C050** Check line protocol state where supported N/A
- [ ] **C051** Verify local gateway ping when IP is configured N/A
- [ ] **C052** Restore an intentionally disabled port if changed incorrectly N/A
- [ ] **C053** Record and resolve unexpected link failure before continuing N/A

Notes / exceptions: _____

05. PC, server and network addressing

- [ ] **C054** Open each PC Desktop IP Configuration N/A
- [ ] **C055** Check static versus DHCP choice N/A
- [ ] **C056** Check each client IPv4 address N/A
- [ ] **C057** Check each client subnet mask N/A
- [ ] **C058** Check each client default gateway N/A
- [ ] **C059** Check each client’s DNS server N/A
- [ ] **C060** Check server IP, subnet and gateway if present N/A
- [ ] **C061** Verify subnet network/broadcast logic for assigned prefix N/A
- [ ] **C062** Check no host uses a conventional broadcast/network address N/A
- [ ] **C063** Check duplicate addresses or incorrect host subnet N/A
- [ ] **C064** Run ipconfig on required PC when supported N/A
- [ ] **C065** Ping each client’s local gateway N/A
- [ ] **C066** Ping same-VLAN destination when required N/A
- [ ] **C067** Restore exact originally assigned IP data if needed N/A

Notes / exceptions: _____

06. VLANs, access ports and trunks

- [ ] **C068** Inspect existing VLAN IDs and names N/A
- [ ] **C069** Create only the missing task-required VLANs N/A
- [ ] **C070** Verify every required VLAN exists N/A

- [ ] **C071** Identify each access port for an endpoint N/A
- [ ] **C072** Configure correct access VLAN on each assigned port N/A
- [ ] **C073** Verify access port mode is appropriate N/A
- [ ] **C074** Confirm required access ports are enabled N/A
- [ ] **C075** Identify all inter-switch trunk links N/A
- [ ] **C076** Identify router-on-a-stick trunk links N/A
- [ ] **C077** Check trunking mode at both ends N/A
- [ ] **C078** Check 802.1Q tagging/encapsulation support N/A
- [ ] **C079** Check allowed VLAN list at both trunk ends N/A
- [ ] **C080** Check native VLAN setting and mismatch risks N/A
- [ ] **C081** Preserve existing required management and voice VLANs N/A
- [ ] **C082** Verify show interfaces trunk output N/A
- [ ] **C083** Verify required VLAN clients communicate N/A
- [ ] **C084** Restore accidentally pruned VLAN or wrong port mode N/A

Notes / exceptions: _____

07. VLAN gateways and inter-VLAN routing

- [ ] **C085** Identify router-on-a-stick versus Layer 3 switch design N/A
- [ ] **C086** Verify router physical interface for VLAN trunk is enabled N/A
- [ ] **C087** Check correct 802.1Q subinterface per VLAN N/A
- [ ] **C088** Check subinterface VLAN ID matches intended tagged VLAN N/A
- [ ] **C089** Check each subinterface IPv4 address and subnet N/A
- [ ] **C090** Check trunk carries every required routed VLAN N/A
- [ ] **C091** Check client gateways point at correct router/SVI N/A
- [ ] **C092** Check SVI exists on multilayer switch when used N/A
- [ ] **C093** Check operational Layer 2 member ports for each active SVI N/A
- [ ] **C094** Enable ip routing only on capable switch when required N/A
- [ ] **C095** Verify each client can reach its local gateway N/A
- [ ] **C096** Verify permitted communication between VLAN subnets N/A
- [ ] **C097** Restore previously correct subinterface/SVI settings if needed N/A

Notes / exceptions: _____

08. Static, default and dynamic routing

☐	**C098**	Inspect connected routes on each router	N/A
☐	**C099**	List all required remote destination networks	N/A
☐	**C100**	Check static route next hops for correct reachability	N/A
☐	**C101**	Check default route on the appropriate upstream router	N/A
☐	**C102**	Check return routes on remote networks	N/A
☐	**C103**	Check subnet mask/prefix for each installed route	N/A
☐	**C104**	Verify longest-prefix routing behavior if multiple routes match	N/A
☐	**C105**	Identify assigned dynamic routing protocol	N/A
☐	**C106**	Check OSPF process and area assignments if required	N/A
☐	**C107**	Check OSPF neighbor states	N/A
☐	**C108**	Check OSPF-learned routes	N/A
☐	**C109**	Check EIGRP AS/network selection if required	N/A
☐	**C110**	Check EIGRP neighbors and learned routes	N/A
☐	**C111**	Check RIPv2 version and network selection if required	N/A
☐	**C112**	Check routing protocol administrative distance when relevant	N/A
☐	**C113**	Ping an approved remote test host	N/A
☐	**C114**	Use traceroute to locate an unexpected routed failure	N/A
☐	**C115**	Undo only one incorrect route/protocol setting	N/A

Notes / exceptions: _____

09. DHCP pools, relay and DNS

☐	**C116**	Identify the actual DHCP server device	N/A
☐	**C117**	Inspect DHCP pool network and subnet mask	N/A
☐	**C118**	Inspect default-router option in DHCP pool	N/A
☐	**C119**	Inspect DNS server option in DHCP pool	N/A
☐	**C120**	Inspect reserved/excluded address ranges	N/A
☐	**C121**	Check pool has usable remaining leases	N/A
☐	**C122**	Check client-facing router helper address if DHCP is remote	N/A
☐	**C123**	Check DHCP snooping trust when configured	N/A

- [ ] **C124** Request/renew DHCP on one approved client N/A
- [ ] **C125** Verify assigned client IP and prefix N/A
- [ ] **C126** Verify assigned gateway and DNS data N/A
- [ ] **C127** Inspect DNS server service status N/A
- [ ] **C128** Inspect required DNS records and hostnames N/A
- [ ] **C129** Check client DNS server address matches service N/A
- [ ] **C130** Verify required hostname resolves or opens N/A
- [ ] **C131** Restore only an incorrect pool/helper/DNS record N/A

Notes / exceptions: _____

10. Application/server tasks

- [ ] **C132** Check required Packet Tracer server service list N/A
- [ ] **C133** Check HTTP or HTTPS enabled if required N/A
- [ ] **C134** Open required web page via IP N/A
- [ ] **C135** Open required web page via DNS hostname N/A
- [ ] **C136** Check FTP service state when required N/A
- [ ] **C137** Check FTP authorized user account N/A
- [ ] **C138** Test an authorized FTP file transfer N/A
- [ ] **C139** Check TFTP service/file when required N/A
- [ ] **C140** Check email domain and user accounts when required N/A
- [ ] **C141** Test mail send/receive if assigned N/A
- [ ] **C142** Check time/NTP if assigned N/A
- [ ] **C143** Check required application firewall/ACL path N/A
- [ ] **C144** Do not enable unrelated server services N/A
- [ ] **C145** Restore service/record data if a client test fails N/A

Notes / exceptions: _____

11. Cisco device login and SSH

- [ ] **C146** Check intended hostname and domain name N/A
- [ ] **C147** Check enable secret requirement N/A
- [ ] **C148** Check authorized local usernames and secrets N/A

- [ ] **C149** Check console line login and passwords if assigned N/A
- [ ] **C150** Check VTY lines and their transport settings N/A
- [ ] **C151** Check SSH keys/IOS support N/A
- [ ] **C152** Check SSH v2 setting where supported N/A
- [ ] **C153** Verify no unnecessary Telnet access if SSH-only required N/A
- [ ] **C154** Check management SVI/router interface IP reachability N/A
- [ ] **C155** Check VTY ACL or approved management hosts if assigned N/A
- [ ] **C156** Test a new authorized SSH login N/A
- [ ] **C157** Preserve console recovery if SSH fails N/A
- [ ] **C158** Check banner or password policy only if task requires it N/A
- [ ] **C159** Save device configuration after verified changes N/A

Notes / exceptions: _____

12. ACLs, port security and STP

- [ ] **C160** List traffic flows that must be allowed N/A
- [ ] **C161** List traffic flows that must be denied N/A
- [ ] **C162** Record source and destination networks for ACL N/A
- [ ] **C163** Record protocol and port for extended ACL N/A
- [ ] **C164** Check ACL wildcard mask against intended prefix N/A
- [ ] **C165** Inspect ACL rule order and implicit deny N/A
- [ ] **C166** Check ACL interface binding and direction N/A
- [ ] **C167** Apply only task-required ACL entries N/A
- [ ] **C168** Test one permitted flow across ACL N/A
- [ ] **C169** Test one intentionally blocked flow across ACL N/A
- [ ] **C170** Check access port maximum MAC address setting N/A
- [ ] **C171** Check port-security violation mode N/A
- [ ] **C172** Check learned/sticky MAC state when required N/A
- [ ] **C173** Confirm edge port security does not disable legitimate PC N/A
- [ ] **C174** Check STP topology and root bridge where required N/A
- [ ] **C175** Check PortFast only on genuine host-facing edge port N/A
- [ ] **C176** Check BPDU Guard does not disable switch uplink N/A
- [ ] **C177** Restore accidental ACL/port-security/STP disruption N/A

Notes / exceptions: _____

13. EtherChannel, NAT, wireless and IPv6

- ☐ **C178** Check whether EtherChannel is actually required N/A
- ☐ **C179** Check EtherChannel member ports and modes N/A
- ☐ **C180** Verify matching trunk/VLAN settings on bundle members N/A
- ☐ **C181** Check LACP negotiation compatibility N/A
- ☐ **C182** Verify show etherchannel summary where supported N/A
- ☐ **C183** Identify NAT inside and outside interfaces if required N/A
- ☐ **C184** Inspect NAT selection ACL N/A
- ☐ **C185** Check PAT overload mapping when required N/A
- ☐ **C186** Generate matching inside-to-outside traffic N/A
- ☐ **C187** Verify NAT translations appear N/A
- ☐ **C188** Record wireless SSID exactly as assigned N/A
- ☐ **C189** Check wireless security mode and passphrase N/A
- ☐ **C190** Verify client wireless adapter/association N/A
- ☐ **C191** Verify wireless client DHCP/address/gateway N/A
- ☐ **C192** Check IPv6 unicast-routing requirement N/A
- ☐ **C193** Check IPv6 addresses and prefix lengths N/A
- ☐ **C194** Check IPv6 neighbor and route information N/A
- ☐ **C195** Test authorized IPv6 reachability N/A
- ☐ **C196** Restore specific bad advanced configuration if needed N/A

Notes / exceptions: _____

14. Troubleshooting and simulation

- ☐ **C197** Test problem from lower layers upward N/A
- ☐ **C198** Check physical cable and interface first N/A
- ☐ **C199** Check client subnet and gateway next N/A
- ☐ **C200** Check access VLAN and trunk allowances N/A
- ☐ **C201** Check router subinterface or SVI N/A
- ☐ **C202** Check forward and return routes N/A

- ☐ **C203** Check ACL direction and actual permitted traffic N/A
- ☐ **C204** Check DHCP relay and server when lease fails N/A
- ☐ **C205** Check DNS when IP works but hostname fails N/A
- ☐ **C206** Check HTTP service when ping works but web fails N/A
- ☐ **C207** Check port security or BPDU shutdown when edge port fails N/A
- ☐ **C208** Check NAT only if translations are required N/A
- ☐ **C209** Use Packet Tracer Simulation Mode when helpful N/A
- ☐ **C210** Filter ARP/ICMP/DHCP/DNS protocol events where supported N/A
- ☐ **C211** Use Capture/Forward to see the first drop N/A
- ☐ **C212** Confirm intended blocked flows versus unintended drops N/A
- ☐ **C213** Verify a changed setting with actual client traffic N/A

Notes / exceptions: _____

15. Final review, saving and submission

- ☐ **C214** Recheck all task-required interface statuses N/A
- ☐ **C215** Recheck all PC/server IP and gateway settings N/A
- ☐ **C216** Recheck required VLANs and trunks N/A
- ☐ **C217** Recheck static or dynamic routes and return paths N/A
- ☐ **C218** Recheck DHCP leases and DNS functionality N/A
- ☐ **C219** Recheck web/FTP/email required services N/A
- ☐ **C220** Recheck SSH or management authentication N/A
- ☐ **C221** Recheck allowed and denied ACL flows N/A
- ☐ **C222** Recheck port security/STP and other advanced features N/A
- ☐ **C223** Inspect any permitted Check Results only as allowed N/A
- ☐ **C224** Confirm no unrelated working configuration was removed N/A
- ☐ **C225** Save running-config to startup-config when required N/A
- ☐ **C226** Save the correct PKA/PKT file under required name N/A
- ☐ **C227** Submit activity through the official method if required N/A
- ☐ **C228** Record completion/result and outstanding items N/A
- ☐ **C229** Confirm no invented credentials/IPs remain from examples N/A

Notes / exceptions: _____

FINAL REVIEW - required connectivity / saved file / reviewer:

_____