

# **Mastering ArduinoJson 6**

Efficient JSON serialization for embedded C++



Co	onten	ts	iv
1	Intro	oduction	1
	1.1	About this book	2
		1.1.1 Overview	2
		1.1.2 Code samples	2
		1.1.3 What's new in the third edition	3
	1.2	Introduction to JSON	4
		1.2.1 What is JSON?	4
		1.2.2 What is serialization?	5
		1.2.3 What can you do with JSON?	5
		1.2.4 History of JSON	7
		1.2.5 Why is JSON so popular?	8
		1.2.6 The JSON syntax	9
		1.2.7 Binary data in JSON	12
		1.2.8 Comments in JSON	13
	1.3	Introduction to ArduinoJson	14
		1.3.1 What ArduinoJson is	14
		1.3.2 What ArduinoJson is not	14
		1.3.3 What makes ArduinoJson different?	15
		1.3.4 Does size matter?	17
		1.3.5 What are the alternatives to ArduinoJson?	18
		1.3.6 How to install ArduinoJson	20
		1.3.7 The examples	25
	1.4	Summary	27
2	The	missing C++ course	28
	2.1	Why a C++ course?	29
	2.2	Harvard and von Neumann architectures	31
	2.3	Stack, heap, and globals	33
		2.3.1 Globals	34

		2.3.2	Heap
		2.3.3	Stack
	2.4	Pointer	rs
		2.4.1	What is a pointer?
		2.4.2	Dereferencing a pointer
		2.4.3	Pointers and arrays
		2.4.4	Taking the address of a variable
		2.4.5	Pointer to class and struct
		2.4.6	Pointer to constant
		2.4.7	The null pointer
		2.4.8	Why use pointers?
	2.5	Memor	y management
		2.5.1	malloc() and free()
		2.5.2	new and delete
		2.5.3	Smart pointers
		2.5.4	RAII
	2.6	Referer	nces
		2.6.1	What is a reference?
		2.6.2	Differences with pointers
		2.6.3	Reference to constant
		2.6.4	Rules of references
		2.6.5	Common problems
		2.6.6	Usage for references
	2.7	Strings	53
		2.7.1	How are the strings stored?
		2.7.2	String literals in RAM
		2.7.3	String literals in Flash
		2.7.4	Pointer to the "globals" section
		2.7.5	Mutable string in "globals"
		2.7.6	A copy in the stack
		2.7.7	A copy in the heap
		2.7.8	A word about the String class
		2.7.9	Pass strings to functions
	2.8	Summa	ary
3	Dese		with ArduinoJson 65
	3.1		ample of this chapter
	3.2	Deseria	alizing an object
		3.2.1	The JSON document 67
		3.2.2	Placing the JSON document in memory 67

	3.2.3	Introducing JsonDocument
	3.2.4	How to specify the capacity?
	3.2.5	How to determine the capacity? 69
	3.2.6	StaticJsonDocument or DynamicJsonDocument?
	3.2.7	Deserializing the JSON document
3.3	Extrac	ting values from an object
	3.3.1	Extracting values
	3.3.2	Explicit casts
	3.3.3	When values are missing
	3.3.4	Changing the default value
3.4	Inspect	ting an unknown object
	3.4.1	Getting a reference to the object
	3.4.2	Enumerating the keys
	3.4.3	Detecting the type of value
	3.4.4	Variant types and C++ types
	3.4.5	Testing if a key exists in an object
3.5	Deseria	alizing an array
	3.5.1	The JSON document
	3.5.2	Parsing the array
	3.5.3	The ArduinoJson Assistant
3.6	Extrac	ting values from an array
	3.6.1	Retrieving elements by index
	3.6.2	Alternative syntaxes
	3.6.3	When complex values are missing
3.7	Inspect	ting an unknown array
	3.7.1	Getting a reference to the array
	3.7.2	Capacity of JsonDocument for an unknown input 86
	3.7.3	Number of elements in an array
	3.7.4	Iteration
	3.7.5	Detecting the type of an element
3.8	The ze	ero-copy mode
	3.8.1	Definition
	3.8.2	An example
	3.8.3	Input buffer must stay in memory
3.9	Readin	g from read-only memory
	3.9.1	The example
	3.9.2	Duplication is required
	3.9.3	Practice
	3.9.4	Other types of read-only input

	3.10	Readin	g from a stream
		3.10.1	Reading from a file
		3.10.2	Reading from an HTTP response
	3.11	Summa	ary
4	Seria	alizing	with ArduinoJson 108
	4.1	_	cample of this chapter
	4.2		ng an object
		4.2.1	The example
		4.2.2	Allocating the JsonDocument
		4.2.3	Adding members
		4.2.4	Alternative syntax
		4.2.5	Creating an empty object
		4.2.6	Removing members
		4.2.7	Replacing members
	4.3	Creatir	ng an array
		4.3.1	The example
		4.3.2	Allocating the JsonDocument
		4.3.3	Adding elements
		4.3.4	Adding nested objects
		4.3.5	Creating an empty array
		4.3.6	Replacing elements
		4.3.7	Removing elements
	4.4	Writing	g to memory
		4.4.1	Minified JSON
		4.4.2	Specifying (or not) the buffer size
		4.4.3	Prettified JSON
		4.4.4	Measuring the length
		4.4.5	Writing to a String
		4.4.6	Casting a JsonVariant to a String
	4.5	Writing	g to a stream
		4.5.1	What's an output stream?
		4.5.2	Writing to the serial port
		4.5.3	Writing to a file
		4.5.4	Writing to a TCP connection
	4.6	Duplic	ation of strings
		4.6.1	An example
		4.6.2	Keys and values
		4.6.3	Copy only occurs when adding values
		4.6.4	ArduinoJson Assistant to the rescue

C 1 1 -	•••
Contents	VIII
	VIII

	4.7	Insertin	g special values	3
		4.7.1	Adding null	3
		4.7.2	Adding pre-formatted JSON	3
	4.8	Summa	ry	5
5	Adva	anced T	echniques 130	6
	5.1		ction	
	5.2		g the input	
	5.3		lizing in chunks	2
	5.4		treaming	7
	5.5		tic capacity	
	5.6		nemory leaks	
	5.7	_	xternal RAM	
	5.8	_	;	
	5.9		ng	
	5.10		readers and writers	
	5.11		converters	
			ePack	
			ry	
6	Insid	le Ardui		0
	6.1	Why Js	onDocument?	1
		6.1.1	Memory representation	1
		6.1.2	Dynamic memory	2
		6.1.3	Memory pool	3
		6.1.4	Strengths and weaknesses	4
	6.2	Inside J	sonDocument	ō
		6.2.1	Differences with JsonVariant	ō
		6.2.2	Fixed capacity	õ
		6.2.3	String deduplication	5
		6.2.4	Implementation of the allocator	5
		6.2.5	Implementation of JsonDocument	3
	6.3	Inside S	taticJsonDocument	9
		6.3.1	Capacity	9
		6.3.2	Stack memory	9
		6.3.3	Limitation	C
		6.3.4	Other usages	1
		6.3.5	Implementation	1
	6.4	Inside D	ynamicJsonDocument	2
		6.4.1	Capacity	2

	6.4.2	Shrinking a DynamicJsonDocument	2
	6.4.3	Automatic capacity	3
	6.4.4	Heap memory	4
	6.4.5	Allocator	4
	6.4.6	Implementation	5
	6.4.7	Comparison with StaticJsonDocument	5
	6.4.8	How to choose?	6
6.5	Inside	JsonVariant	7
	6.5.1	Supported types	7
	6.5.2	Reference semantics	7
	6.5.3	Creating a JsonVariant	8
	6.5.4	Implementation	9
	6.5.5	Two kinds of null	0
	6.5.6	Unsigned integers	1
	6.5.7	Integer overflows	1
	6.5.8	ArduinoJson's configuration	2
	6.5.9	Iterating through a JsonVariant	3
	6.5.10	The or operator	5
	6.5.11	The subscript operator	6
	6.5.12	Member functions	6
	6.5.13	Comparison operators	9
	6.5.14	Const reference	0
6.6	Inside	JsonObject	1
	6.6.1	Reference semantics	1
	6.6.2	Null object	1
	6.6.3	Create an object	2
	6.6.4	Implementation	2
	6.6.5	Subscript operator	3
	6.6.6	Member functions	4
	6.6.7	Const reference	7
6.7	Inside	JsonArray	8
	6.7.1	Member functions	8
	6.7.2	copyArray()	2
6.8	Inside	the parser	4
	6.8.1	Invoking the parser	4
	6.8.2	Two modes	5
	6.8.3	Pitfalls	5
	6.8.4	Nesting limit	6
	6.8.5	Quotes	7
	6.8.6	Escape sequences	8

		6.8.7	Comments	29
		6.8.8	NaN and Infinity	29
		6.8.9	Stream	29
		6.8.10	Filtering	30
	6.9	Inside	the serializer	31
		6.9.1	Invoking the serializer	31
		6.9.2	Measuring the length	32
		6.9.3	Escape sequences	33
		6.9.4	Float to string	33
		6.9.5	NaN and Infinity	34
	6.10	Miscell	aneous	35
		6.10.1	The version macro	35
		6.10.2	The private namespace	35
		6.10.3	The public namespace	36
		6.10.4	ArduinoJson.h and ArduinoJson.hpp	36
		6.10.5	The single header	37
		6.10.6	Code coverage	37
		6.10.7	Fuzzing	37
		6.10.8	Portability	38
		6.10.9	Online compiler	39
		6.10.10	) License	40
	6.11	Summa	ary	41
7	т		- A.S	40
7		ıblesho		42
	7.1			43
	7.2	_	m crashes	
		7.2.1 7.2.2	Undefined Behaviors	
			A bug in ArduinoJson?	
		7.2.3 7.2.4	9	45
		7.2.4	Use after free	
		7.2.5 7.2.6	Buffer overflow	
		7.2.7		
		7.2.7	Stack overflow	
			9	
	7 2	7.2.9	·	53
	7.3			55
		7.3.1		55
		7.3.2	·	56
		7.3.3	•	58
		7.3.4	NoMemory	62

		7.3.5	TooDeep
	7.4	Serializ	zation issues
		7.4.1	The JSON document is incomplete
		7.4.2	The JSON document contains garbage
		7.4.3	The serizalization is too slow
	7.5	Comm	on error messages
		7.5.1	no matching function for call to BasicJsonDocument() 267
		7.5.2	Invalid conversion from const char* to int
		7.5.3	No match for operator[]
		7.5.4	Ambiguous overload for operator=
		7.5.5	Call of overloaded function is ambiguous
		7.5.6	The value is not usable in a constant expression
	7.6	Asking	; for help
	7.7	Summ	ary
8	Case	e Studi	es 275
U	8.1		uration in SPIFFS
	0.1	8.1.1	Presentation
		8.1.2	The JSON document
		8.1.3	The configuration class
		8.1.4	Converters
		8.1.5	Saving the configuration to a file
		8.1.6	Reading the configuration from a file
		8.1.7	Sizing the JsonDocument
		8.1.8	Conclusion
	8.2		VeatherMap on MKR1000
	0.2	8.2.1	Presentation
		8.2.2	OpenWeatherMap's API
		8.2.3	The JSON response
		8.2.4	Reducing the size of the document
		8.2.5	The filter document
		8.2.6	The code
		8.2.7	Summary
	8.3	-	on ESP8266
		8.3.1	Presentation
		8.3.2	Reddit's API
		8.3.3	The response
		8.3.4	The main loop
		8.3.5	Sending the request
		8.3.6	Assembling the puzzle

C 1 1 -	••
Contents	XII

Index 31					
	Con	clusion		317	
		8.5.6	Summary	316	
		8.5.5	Printing values	314	
		8.5.4	Testing the type of a JsonVariant	313	
		8.5.3	Flushing after an error	312	
		8.5.2	Read from the serial port	311	
		8.5.1	Presentation	311	
	8.5		ive analyzer		
		8.4.10	Summary		
		8.4.9	Reading properties from Kodi		
		8.4.8	Sending notification to Kodi		
		8.4.7	JsonRpcClient		
		8.4.6	JsonRpcResponse	303	
		8.4.5	JsonRpcRequest	302	
		8.4.4	A JSON-RPC framework		
		8.4.3	JSON-RPC Response		
		8.4.2	JSON-RPC Request		
		8.4.1	Presentation		
	8.4	JSON-	RPC with Kodi		
		8.3.7	Summary	298	

## Chapter 4

## Serializing with ArduinoJson

Any fool can write code that a computer can understand.

Good programmers write code that humans can understand.

– Martin Fowler, Refactoring: Improving the Design of Existing Code

#### 4.1 The example of this chapter

Reading a JSON document is only half of the story; we'll now see how to write a JSON document with ArduinoJson.

In the previous chapter, we played with GitHub's API. We'll use a very different example for this chapter: pushing data to Adafruit IO.

Adafruit IO is a cloud storage service for IoT data. They have a free plan with the following restrictions:

- 30 data points per minute
- 30 days of data storage
- 5 feeds

If you need more, it's just \$10 a month. The service is very easy to use. All you need is an Adafruit account (yes, you can use the account from the Adafruit shop).

As we did in the previous chapter, we'll start with a simple JSON document and add complexity step by step.

Since Adafruit IO doesn't impose a secure connection, we can use a less powerful microcontroller than in the previous chapter; we'll use an Arduino UNO with an Ethernet Shield.





#### 4.2 Creating an object

#### 4.2.1 The example

Here is the JSON object we want to create:

```
{
  "value": 42,
  "lat": 48.748010,
  "lon": 2.293491
}
```

It's a flat object, meaning that it has no nested object or array, and it contains the following members:

- 1. "value" is an integer that we want to save in Adafruit IO.
- "lat" is the latitude coordinate.
- 3. "lon" is the longitude coordinate.

Adafruit IO supports other optional members (like the elevation coordinate and the time of measurement), but the three members above are sufficient for our example.

#### 4.2.2 Allocating the JsonDocument

As for the descrialization, we start by creating a JsonDocument to hold the memory representation of the object. The previous chapter introduced JsonDocument, so I'll assume that you're now familiar with it.

As you recall, a JsonDocument has a fixed capacity which we must set on creation. Here, we have one object with no nested values, so the size is JSON\_OBJECT\_SIZE(3). For a more complex document, you can use the <u>ArduinoJson Assistant</u> to compute the required capacity.

We saw that JsonDocument comes in two flavors: StaticJsonDocument, which lives in the stack, and DynamicJsonDocument, which resides in the heap. In this case, we can use a StaticJsonDocument because the document is small, and I never use the heap on AVR anyway. Indeed, the Arduino UNO has only 2KB of RAM, so we can't afford any heap

fragmentation. If you don't know which implementation of JsonDocument to choose for your project, consult the ArduinoJson Assistant.

Here is the code:

```
const int capacity = JSON_OBJECT_SIZE(3);
StaticJsonDocument<capacity> doc;
```

The JsonDocument is currently empty and JsonDocument::isNull() returns true. If we serialized it now, the output would be "null."

#### 4.2.3 Adding members

An empty JsonDocument automatically becomes an object when we add members to it. We do that with the subscript operator ([]), just like we did in the previous chapter:

```
doc["value"] = 42;
doc["lat"] = 48.748010;
doc["lon"] = 2.293491;
```

The memory usage is now JSON\_OBJECT\_SIZE(3), so the JsonDocument is full. When the JsonDocument is full, so it cannot accept any new member. If you try to add another value, the operation will fail and set the flag JsonDocument::overflowed() to true. To actually add more values, you must create a larger JsonDocument.

#### 4.2.4 Alternative syntax

Most of the time <code>JsonDocument::overflowed()</code> is enough, but ArduinoJson provides an alternative syntax that allows you to check whether the insertion succeed. Here is the equivalent of the previous snippet:

```
doc["value"].set(42);
doc["lat"].set(48.748010);
doc["lon"].set(2.293491);
```

The compiler generates the same executable as with the previous syntax, except that JsonVariant::set() returns true for success or false on failure.

To be honest, I never check if insertion succeeds in my programs. The reason is simple: the JSON document is roughly the same for each iteration; if it works once, it always works. There is no reason to bloat the code for a situation that cannot happen.

#### 4.2.5 Creating an empty object

We just saw that the JsonDocument becomes an object as soon as you insert a member, but what if you don't have any members to add? What if you want to create an empty object?

When you need an empty object, you cannot rely on the implicit conversion anymore. Instead, you must explicitly convert the JsonDocument to a JsonObject with JsonDocument::to<JsonObject>():

```
// Convert the document to an object
JsonObject obj = doc.to<JsonObject>();
```

This function clears the JsonDocument, so all existing references become invalid. Then, it creates an empty object at the root of the document and returns a reference to this object.

At this point, the JsonDocument is not empty anymore and JsonDocument::isNull() returns false. If we serialized this document, the output would be "{}".

#### 4.2.6 Removing members

It's possible to erase a member from an object by calling <code>JsonObject::remove(key)</code>. However, for reasons that will become clear in <a href="mailto:chapter-6">chapter 6</a>, this function doesn't release the memory in the <code>JsonDocument</code>.

The remove() function is a frequent cause of bugs because it creates a memory leak. Indeed, if you add and remove members in a loop, the JsonDocument grows, but memory is never released.

#### 4.2.7 Replacing members

It's possible to replace a member in the object, for example:

```
obj["value"] = 42;
obj["value"] = 43;
```

Most of the time, replacing a member doesn't require a new allocation in the JsonDocument. However, it can cause a memory leak if the old value has associated memory, for example, if the old value is a string, an array, or an object.



Replacing and removing values produce a memory leak inside the JsonDocument.

In practice, this problem only happens in programs that use a JsonDocument to store the application's state, which is not the purpose of ArduinoJson. Let's be clear; the sole purpose of ArduinoJson is to serialize and deserialize JSON documents.

Be careful not to fall into this common anti-pattern, and make sure you read the case studies to see how ArduinoJson should be used.

#### 4.3 Creating an array

#### 4.3.1 The example

Now that we can create objects, let's see how to create an array. Our new example will be an array that contains two objects.

The values 12 and 34 are just placeholder; in reality, we'll use the result from analogRead().

#### 4.3.2 Allocating the JsonDocument

As usual, we start by computing the capacity of the JsonDocument:

- There is one array with two elements: JSON\_ARRAY\_SIZE(2)
- There are two objects with two members: 2\*JSON\_OBJECT\_SIZE(2)

Here is the code:

```
const int capacity = JSON_ARRAY_SIZE(2) + 2*JSON_OBJECT_SIZE(2);
StaticJsonDocument<capacity> doc;
```

#### 4.3.3 Adding elements

In the previous section, we saw that an empty JsonDocument automatically becomes an object as soon as we insert the first member. This statement was only partially correct: it becomes an object as soon as we use it as an object.

Indeed, if we treat an empty JsonDocument as an array, it automatically becomes an array. For example, this happens if we call JsonDocument::add(), like so:

```
doc.add(1);
doc.add(2);
```

After these two lines, the JsonDocument contains [1,2].

Alternatively, we can create the same array with the [] operator, like so:

```
doc[0] = 1;
doc[1] = 2;
```

However, this second syntax is a little slower because it requires walking the list of members. Use this syntax to *replace* elements and use add() to add elements to the array.

Now that we can create an array, let's rewind a little because that's not the JSON array we want: instead of two integers, we need two nested objects.

#### 4.3.4 Adding nested objects

To add the nested objects to the array, we call JsonArray::createNestedObject(). This function creates a nested object, appends it to the array, and returns a reference.

Here is how to create our sample document:

```
JsonObject obj1 = doc.createNestedObject();
obj1["key"] = "a1";
obj1["value"] = analogRead(A1);

JsonObject obj2 = doc.createNestedObject();
obj2["key"] = "a2";
obj2["value"] = analogRead(A2);
```

Alternatively, we can create the same document like so:

```
doc[0]["key"] = "a1";
doc[0]["value"] = analogRead(A1);

doc[1]["key"] = "a2";
doc[1]["value"] = analogRead(A2);
```

Again, this syntax is slower because it needs to walk the list, so only use it for small documents.

#### 4.3.5 Creating an empty array

We saw that the JsonDocument becomes an array as soon as we add elements, but this doesn't allow creating an empty array. If we want to create an empty array, we need to convert the JsonDocument explicitly with JsonDocument::to<JsonArray>():

```
// Convert the JsonDocument to an array
JsonArray arr = doc.to<JsonArray>();
```

Now the JsonDocument contains [].

As we already saw, JsonDocument::to<T>() clears the JsonDocument, so it also invalidates all previously acquired references.

#### 4.3.6 Replacing elements

As for objects, it's possible to replace elements in arrays using JsonArray::operator[]:

```
arr[0] = 666;
arr[1] = 667;
```

Most of the time, replacing the value doesn't require a new allocation in the JsonDocument. However, if some memory was held by the previous value (a JsonObject, for example), this memory is not released. It's a limitation of ArduinoJson's memory allocator, as we'll see later in this book.

#### 4.3.7 Removing elements

As for objects, you can remove an element from the array, with JsonArray::remove():

```
arr.remove(0);
```

As I said, remove() doesn't release the memory from the JsonDocument, so you should never call this function in a loop.

### 4.4 Writing to memory

We saw how to construct an array. Now, it's time to serialize it into a JSON document. There are several ways to do that. We'll start with a JSON document in memory.

We could use a String, but as you know, I prefer avoiding dynamic memory allocation. Instead, we'd use a good old char[]:

```
// Declare a buffer to hold the result
char output[128];
```

#### 4.4.1 Minified JSON

To produce a JSON document from a JsonDocument, we simply need to call serializeJson():

```
// Produce a minified JSON document
serializeJson(doc, output);
```

After this call, the string output contains:

```
[{"key":"a1","value":12},{"key":"a2","value":34}]
```

As you see, there are neither space nor line breaks; it's a "minified" JSON document.

#### 4.4.2 Specifying (or not) the buffer size

If you're a C programmer, you may have been surprised that I didn't provide the buffer size to serializeJson(). Indeed, there is an overload of serializeJson() that takes a char\* and a size:

```
serializeJson(doc, output, sizeof(output));
```

However, that's not the overload we called in the previous snippet. Instead, we called a template method that infers the size of the buffer from its type (in this case, char[128]).

Of course, this shorter syntax only works because output is an array. If it were a char\* or a variable-length array, we would have had to specify the size.



#### Variable-length array

A variable-length array, or VLA, is an array whose size is unknown at compile time. Here is an example:

```
void f(int n) {
 char buf[n];
```

C99 and C11 allow VLAs, but not C++. However, some compilers support VLAs as an extension.

This feature is often criticized in C++ circles, but Arduino users seem to love it. That's why ArduinoJson supports VLAs in all functions that accept a string.

#### 4.4.3 Prettified JSON

The minified version is what you use to store or transmit a JSON document because the size is optimal. However, it's not very easy to read. Humans prefer "prettified" JSON documents with spaces and line breaks.

To produce a prettified document, you must use serializeJsonPretty() instead of serializeJson():

```
// Produce a prettified JSON document
serializeJsonPretty(doc, output);
```

Here is the content of output:

```
Γ
 {
   "key": "a1",
   "value": 12
  },
  {
```

```
"key": "a2",
    "value": 34
}
```

Of course, you need to make sure that the output buffer is big enough; otherwise, the JSON document will be incomplete.

#### 4.4.4 Measuring the length

ArduinoJson allows computing the length of the JSON document before producing it. This information is helpful for:

- 1. allocating an output buffer,
- 2. reserving the size on disk, or
- 3. setting the Content-Length header.

There are two methods, depending on the type of document you want to produce:

```
// Compute the length of the minified JSON document
int len1 = measureJson(doc);

// Compute the length of the prettified JSON document
int len2 = measureJsonPretty(doc);
```

In both cases, the result doesn't count the null-terminator.

By the way, serializeJson() and serializeJsonPretty() return the number of bytes they wrote. The results are the same as measureJson() and measureJsonPretty(), except if the output buffer is too small.



#### **Avoid prettified documents**

With the example above, the sizes are 73 and 110. In this case, the prettified version is only 50% bigger because the document is simple, but in most cases, the ratio is largely above 100%.

Remember, we're in an embedded environment: every byte counts, and so does every CPU cycle. Always prefer a minified version.

#### 4.4.5 Writing to a String

The functions serializeJson() and serializeJsonPretty() have overloads taking a String:

```
String output = "JSON = ";
serializeJson(doc, output);
```

The behavior is slightly different: the JSON document is appended to the String; it doesn't replace it. That means the above snippet sets the content of the output variable to:

```
JSON = [{"key":"a1","value":12},{"key":"a2","value":34}]
```

This behavior seems inconsistent? That's because ArduinoJson treats String like a stream: more on that later.

#### 4.4.6 Casting a JsonVariant to a String

You should remember from the chapter on deserialization that we must cast JsonVariant to the type we want to read.

It is also possible to cast a JsonVariant to a String. If the JsonVariant contains a string, the return value is a copy of the string. However, if the JsonVariant contains something else, the returned string is a serialization of the variant.

We could rewrite the previous example like this:

```
// Cast the JsonDocument to a string
String output = "JSON = " + doc.as<String>();
```

This trick works with JsonDocument and JsonVariant, but not with JsonArray and JsonObject because they don't have an as<T>() function.

### 4.5 Writing to a stream

#### 4.5.1 What's an output stream?

For now, every JSON document we produced remained in memory, but that's usually not what we want. In many situations, it's possible to send the JSON document directly to its destination (whether it's a file, a serial port, or a network connection) without any copy in RAM.

We saw in the previous chapter what an "input stream" is, and we saw that Arduino represents this concept with the Stream class. Similarly, there are "output streams," which are sinks of bytes. We can write to an output stream, but we cannot read. In the Arduino land, an output stream is materialized by the Print class.

Here are examples of classes derived from Print:

Library	Class	Well known instances
Core	HardwareSerial	Serial, Serial1
	BluetoothSerial	SerialBT
ESP	File	
LSI	WiFiClient	
	WiFiClientSecure	
Ethernet	EthernetClient	
Linemet	EthernetUDP	
GSM	GSMClient	
LiquidCrystal	LiquidCrystal	
SD	File	
SoftwareSerial	SoftwareSerial	
WiFi	WiFiClient	
Wire	TwoWire	Wire



#### std::ostream

In the C++ Standard Library, an output stream is represented by the std::ostream class.

ArduinoJson supports both Print and std::ostream.



#### Performance issues

serializeJson() writes bytes one by one to the output stream, which can result in bad performances with unbuffered streams like WiFiClient or File. We'll see a simple workaround in the next chapter.

#### 4.5.2 Writing to the serial port

The most famous implementation of Print is HardwareSerial, which is the class of Serial. To serialize a JsonDocument to the serial port of your Arduino, just pass Serial to serializeJson():

```
// Print a minified JSON document to the serial port
serializeJson(doc, Serial);

// Same with a prettified document
serializeJsonPretty(doc, Serial);
```

You can see the result in the Arduino Serial Monitor, which is very handy for debugging.

If you want to send JSON documents between two boards, I recommend using Serial1 for the communication link and keeping Serial for the debugging link. Of course, this

requires that your board has several UART, which is not the case of the UNO, so we would have to upgrade to a Leonardo (an excellent board, by the way).

Alternatively, you can use Wire for the communication link; but you must know that the Wire library limits the size of a message to 32 bytes (but there is a workaround for longer messages).

In theory, SoftwareSerial could also serve as the communication link, but I highly recommend against it because it's completely unreliable.

#### 4.5.3 Writing to a file

Similarly, we can use a File instance as the target of serializeJson() and serializeJsonPretty(). Here is an example with the SD library:

```
// Open file for writing
File file = SD.open("adafruit.txt", FILE_WRITE);

// Write a prettified JSON document to the file
serializeJsonPretty(doc, file);
```

You can find the complete source code for this example in the WriteSdCard folder of the zip file provided with the book.

You can apply the same technique to write a file on SPIFFS or LittleFS, as we'll see  $\underline{\text{in}}$  the case studies.

#### 4.5.4 Writing to a TCP connection

We're now reaching our goal of sending our measurements to Adafruit IO.

As I said in the introduction, we'll suppose that our program runs on an Arduino UNO with an Ethernet shield. Because the Arduino UNO has only 2KB of RAM, we'll not use the heap at all. As I said, I never use the heap on processors with so little RAM because I cannot afford any fragmentation.

#### Preparing the Adafruit IO account

If you want to run this program, you need an account on Adafruit IO (a free account is sufficient). Then, you need to copy your user name and your "AIO key" to the source code.

```
#define IO_USERNAME "bblanchon"
#define IO_KEY "aio_iCpP41N5k8yoZStMrh2US1AOhNAu"
```

We'll include the AIO key in an HTTP header, and it will authenticate our program on Adafruit's server:

```
X-AIO-Key: aio_iCpP41N5k8yoZStMrh2US1AOhNAu
```

Finally, you need to create a "group" named "arduinojson" in your Adafruit IO account. In this group, you need to create two feeds: "a1" and "a2."

#### The request

To send our measured samples to Adafruit IO, we have to send a POST request to http://io.adafruit.com/api/v2/bblanchon/groups/arduinojson/data, and include the following JSON document in the body:

```
"location": {
    "lat": 48.748010,
       "lon": 2.293491
},
    "feeds": [
        {
            "key": "a1",
            "value": 42
        },
        {
            "key": "a2",
            "value": 43
        }
        ]
```

```
}
```

As you see, it's a little more complex than our previous example because the array is not at the root of the document. Instead, the array is nested in an object under the key "feeds".

Let's review the HTTP request before jumping to the code:

```
POST /api/v2/bblanchon/groups/arduinojson/data HTTP/1.1
Host: io.adafruit.com
Connection: close
Content-Length: 103
Content-Type: application/json
X-AIO-Key: aio_iCpP41N5k8yoZStMrh2US1AOhNAu

{"location":{"lat":48.748010,"lon":2.293491},"feeds":[{"key":"a1",...
```

#### The code

OK, time for action! We'll open a TCP connection to io.adafruit.com using an EthernetClient, and we'll send the request. As far as ArduinoJson is concerned, there are very few changes compared to the previous examples because we can pass the EthernetClient as the target of serializeJson(). We'll call measureJson() to set the value of the Content-Length header.

Here is the code:

```
// Allocate JsonDocument
const int capacity = JSON_ARRAY_SIZE(2) + 4 * JSON_OBJECT_SIZE(2);
StaticJsonDocument<capacity> doc;

// Add the "location" object
JsonObject location = doc.createNestedObject("location");
location["lat"] = 48.748010;
location["lon"] = 2.293491;

// Add the "feeds" array
JsonArray feeds = doc.createNestedArray("feeds");
```

```
JsonObject feed1 = feeds.createNestedObject();
feed1["key"] = "a1";
feed1["value"] = analogRead(A1);
JsonObject feed2 = feeds.createNestedObject();
feed2["key"] = "a2";
feed2["value"] = analogRead(A2);
// Connect to the HTTP server
EthernetClient client;
client.connect("io.adafruit.com", 80);
// Send "POST /api/v2/bblanchon/groups/arduinojson/data HTTP/1.1"
client.println("POST /api/v2/" IO_USERNAME
               "/groups/arduinojson/data HTTP/1.1");
// Send the HTTP headers
client.println("Host: io.adafruit.com");
client.println("Connection: close");
client.print("Content-Length: ");
client.println(measureJson(doc));
client.println("Content-Type: application/json");
client.println("X-AIO-Key: " IO_KEY);
// Terminate headers with a blank line
client.println();
// Send JSON document in body
serializeJson(doc, client);
```

You can find the complete source code of this example in the AdafruitIo folder of the zip file. This code includes the necessary error checking that I removed from the manuscript for clarity.

Below is a picture showing the results on the Adafruit IO dashboard.



#### 4.6 Duplication of strings

Depending on the type, Arduino Json stores strings either by pointer or by copy. If the string is a const char\*, it stores a pointer; otherwise, it makes a copy. This feature reduces memory consumption when you use string literals.

String type	Storage
const char*	pointer
char*	сору
String	сору
constFlashStringHelper*	сору

As usual, the copy lives in the JsonDocument, so you may need to increase its capacity depending on the type of string you use.

ArduinoJson will store only one copy of each string, a feature called "string deduplication". For example, if you insert the string "hello" multiple times, the JsonDocument will only keep one copy.

#### 4.6.1 An example

Compare this program:

```
// Create the array ["value1", "value2"]
doc.add("value1");
doc.add("value2");

// Print the memory usage
Serial.println(doc.memoryUsage()); // 16
```

with the following:

```
// Create the array ["value1","value2"]
doc.add(String("value1"));
doc.add(String("value2"));
// Print the memory usage
```

```
Serial.println(doc.memoryUsage()); // 30
```

They both produce the same JSON document, but the second one requires much more memory because ArduinoJson copies the strings. If you run these programs on an ATmega328, you'll see 16 for the first and 30 for the second. On an ESP8266, it would be 32 and 46.

#### 4.6.2 Keys and values

The duplication rules apply equally to keys and values. In practice, we mostly use string literals for keys, so they are rarely duplicated. String values, however, often originate from variables and then entail string duplication.

Here is a typical example:

Again, the duplication occurs for any type of string except const char\*.

#### 4.6.3 Copy only occurs when adding values

In the example above, ArduinoJson copied the String because it needed to add it to the JsonDocument. On the other hand, if you use a String to extract a value from a JsonDocument, it doesn't make a copy.


Here is an example:

```
// The following line produces a copy of "key"
doc[String("key")] = "value";

// The following line produces no copy
const char* value = doc[String("key")];
```

#### 4.6.4 ArduinoJson Assistant to the rescue

As we saw in the previous chapter, the Assistant shows the number of bytes required to duplicate the strings of the document.



In practice, the actual size may differ from what the Assistant predicts because it doesn't know which strings need to be copied and which don't. By default, it assumes it must store keys by pointer and values by copy. Moreover, it doesn't deduplicate the values, in case you repeated the same placeholder several times in your sample input.

You can change the Assistant behavior by expanding the "Tweaks" section at the bottom of step 3, as shown in the picture above. You can choose the storage type (pointer or

copy) for keys and values. You can also enable or disable deduplication. The changes are instantly reflected into the "Strings" row of the table so that you can see the effect of each setting.

#### 4.7 Inserting special values

Before finishing this chapter, let's see how we can insert special values in the JSON document.

#### 4.7.1 Adding null

The first special value is null, which is a legal token in a JSON. There are several ways to add a null in a JsonDocument; here they are:

```
// Use a nullptr (requires C++11)
arr.add(nullptr);

// Use a null char-pointer
arr.add((char*)0);

// Use a null JsonArray, JsonObject, or JsonVariant
arr.add(JsonVariant());
```

#### 4.7.2 Adding pre-formatted JSON

The other special value is a JSON string that is already formatted and that ArduinoJson should not treat as a regular string.

You can do that by wrapping the string with a call to serialized():

```
// adds "[1,2]"
arr.add("[1,2]");

// adds [1,2]
arr.add(serialized("[1,2]"));
```

The program above produces the following JSON document:

```
[ "[1,2]", [1,2] ]
```

Use this feature when a part of the document cannot change; it will simplify your code and reduce the executable size. You can also use it to insert something that the library doesn't allow.

You can pass a Flash string or a String instance to serialized(), but its content will be copied into the JsonDocument. As usual, Flash strings must have the type const \_\_FlashStringHelper\* to be recognized as such.

### 4.8 Summary

In this chapter, we saw how to serialize a JSON document with ArduinoJson. Here are the key points to remember:

- Creating the document:
  - To add a member to an object, use the subscript operator ([])
  - To append an element to an array, call add()
  - The first time you add a member to a JsonDocument, it automatically becomes an object.
  - The first time you append an element to a JsonDocument, it automatically becomes an array.
  - You can explicitly convert a JsonDocument with JsonDocument::to<T>().
  - JsonDocument::to<T>() clears the JsonDocument, so it invalidates all previously acquired references.
  - JsonDocument::to<T>() return a reference to the root array or object.
  - To create a nested array or object, call createNestedArray() or createNestedObject().
  - When you insert a string in a JsonDocument, it makes a copy, except if it's a const char\*.
- Serializing the document:
  - To serialize a JsonDocument, call serializeJson() or serializeJsonPretty().
  - To compute the length of the JSON document, call measureJson() or measureJsonPretty().
  - serializeJson() appends to String, but it overrides the content of a char\*.
  - You can pass an instance of Print (like Serial, EthernetClient, WiFiClient, or File) to serializeJson() to avoid a copy in the RAM.

In the next chapter, we'll see advanced techniques like filtering and logging.

### Continue reading...

That was a free chapter from "Mastering ArduinoJson"; the book contains seven chapters like this one. Here is what readers say:

This book is 100% worth it. Between solving my immediate problem in minutes, Chapter 2, and the various other issues this book made solving easy, **it is totally worth it**. I build software but I work in managed languages and for someone just getting started in C++and embedded programming this book has been indispensable.

— Nathan Burnett

I think the missing C++course and the troubleshooting chapter **are worth the money by itself**. Very useful for C programming dinosaurs like myself.

— Doug Petican

The short C++section was a great refresher. The practical use of Arduino-Json in small embedded processors was just what I needed for my home automation work. **Certainly worth having!** Thank you for both the book and the library.

— Douglas S. Basberg

For a really reasonable price, not only you'll learn new skills, but you'll also be one of the few people that **contribute to sustainable open-source software**. Yes, giving money for free software is a political act!

The e-book comes in three formats: PDF, epub and mobi. If you purchase the e-book, you get access to newer versions for free. A carefully edited paperback edition is also available.

Ready to jump in?

Go to arduinojson.org/book and use the coupon code THIRTY to get a 30% discount.

Thank you for your support! Bount