```
<?xml version=“1.0”?>

<ancient_wonders>

</ancient_wonders>
```

```xml
<?xml version="1.0"?>
<ancient_wonders>
<wonder>
<name>Colosus of Rhodes</name>
</wonder>
</ancient_wonders>
```

.

```xml
<?xml version=“1.0”?>
<ancient_wonders>
<wonder>
<name language=“English”>Colosus of Rhodes</name>
<location> Rhodes, Greece</location>
<height units=“feet”> 107</height>
</wonder>
</ancient_wonders>
```

```xml
<?xml version=“1.0”?>
<ancient_wonders>
<wonder>
<name >Colosus of Rhodes</name>
<location> Rhodes, Greece</location>
<height units=“feet”>107</height>
<main_image file=“colossus.jpg” w=“528” h=“349”/>
</wonder>
</ancient_wonders>
```

```xml
<?xml version="1.0"?>
<ancient_wonders>
<wonder>
<name language="English">Colosus of Rhodes</name>
<location> Rhodes, Greece</location>
<height units="feet">107</height>
<main_image file="colossus.jpg" w="528" h="349"/>
<source sectionid="101" newspaperid="21"></source>
</wonder>
</ancient_wonders>
```

```xml
<?xml version="1.0"?>
<ancient_wonders>
<wonder>
<name language="English">Colosus of Rhodes</name>
<location> Rhodes, Greece</location>
<height units="feet">107</height>
<main_image file="colossus.jpg" w="528" h="349"/>
<!—this example comes from
Visual Quickstart Guide XML -->
<source sectionid="101" newspaperid="21"></source>
</wonder>
</ancient_wonders>
```

.

```xml
<?xml version="1.0"?>
<ancient_wonders>
<wonder>
<name language="English">Colosus of Rhodes</name>
<location> Rhodes, Greece</location>
<height units="feet">&lt; 107</height>
<main_image file="colossus.jpg" w="528" h="349"/>
<!—this example comes from
Visual Quickstart Guide XML -->
<source sectionid="101" newspaperid="21"></source>
</wonder>
</ancient_wonders>
```