



Front View

Rear View





Detail: Display : 7 Segment 2.3"

ACTUAL

DIFF.

D.T.L

Input : Counter Actual 1 Channel + Reset 1 Channel

: Contact Hour Counter 6 Channel

Communication: RS485 Modbus RTU

: Baud Rate 4800,9600,19200,38400,57600

: Parity None, Even, Odd

M/C : Setting with Remote & RS485

: Setting with Remote & RS485 SPM.OFC **ACTUAL** : Input per Minute real Time

: Setting with Remote & RS485 Target

Actual : Counter Input

: Different Target & Actual Diff.

D.T.L.

. n., . os:o i Machine 4_ 02:30 Die - ΠL - IØ + I Mafl Q Choek : 9[. 0327 Die Change: dE. 0058

D Change : dP. 0 (23)

D.T.L. : Timer Function

Technical Specification

Power Supply	100-240 VAC, 50-60Hz	
Display	7 Segment	
Input	Sensor NPN,PNP	
Output	-	
Memory	EEPROM with Battery	
Setting	Remote	
Communication	RS485 Modbus RTU	

REMARK			
Frame	Aluminum		
Color	Black		
Protact	IP30		
Model	TGM-62001		
APPEND			

APPEND				
Dimension	1.2"	-		
Dimension	2.3"	650W x 750H x 100D mm.		
Dimension	4"	-		
Character		Arial (Font), White PVC Sticker		

PRIMUS CO., LTD.			
Draft by	Suphot		
Date	15.01.2019		
Revision	1		
Customer			

Approve

ราคาตั้ง

7 Segment Display 2.3"

TGM-62001rev1 : 35,300 บาท