



- Detail :**
- แสดงผลด้วยตัวเลข 7 SEGMENT สีแดง
 - รับอินพุต 4 – 20 mA
 - สามารถตั้งค่า Scale High limit, Scale Low Limit ได้
 - สามารถตั้งค่า Alarm Output Relay ได้ 4 Function
 - High Low Alarm
 - High Alarm
 - Low Alarm
 - High Low Range Alarm
 - ตั้งค่าการทำงานด้วย Remote IF
 - สามารถตั้งค่าเพื่อเชื่อมต่อ RS485 ได้โดยเป็น Master ใช้ส่งข้อมูลเพื่อไปแสดงผลบนจอ TSM ได้
 - รองรับ Protocol Modbus RTU
 - รองรับการทำงานที่ความเร็ว 4800, 9600, 19200, 38400, 57600
 - รองรับการเข้ารหัส None, Even, Odd
 - รองรับการเชื่อมต่อแบบ 1 ต่อ 1 โดยกำหนด Address ให้ตรงกับ Slave ได้
 - สามารถตั้งค่าระยะเวลาการส่งได้
 - Output Supply 24V

Technical Specification

Power Supply	100-240 VAC, 50-60Hz
Display	7 Segment Display
Input	4- 20 mA 1 Channel
Output	Alarm Relay 1 Channel
Memory	EEPROM with Battery
Setting	Remote
Communication	RS485 Modbus RTU

REMARK		
Frame	Aluminum	
Color	Black	
Protection	IP30	
Model	TGM-62015	
APPEND		
Dimension	1.2"	<input type="checkbox"/>
	2.3"	400W x 150H x 100Dmm. <input type="checkbox"/>
	4"	700W x 200H x 100Dmm. <input type="checkbox"/>
Character	Arial (Font), White PVC Sticker	

PRIMUS CO., LTD.	
Draft by	Suphot
Date	01.02.2019
Revision	2, 3
Customer	
Approve	

ราคาตั้ง

Segment Big Display

- ☐ **TGM-62015rev2 [2.3"]:** **9,500** บาท
- ☐ **TGM-62015rev3 [4"]:** **12,000** บาท