

# RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-205-RWD-063

AGR No. : A204A-242

Applicant : SEONG JI INDUSTRIAL CO., LTD

Address : 54-33, Dongtanhana 1-gil, Gyeonggi-do, Hwaseong-si, South Korea

Manufacturer : SEONG JI INDUSTRIAL CO., LTD

Address : 54-33, Dongtanhana 1-gil, Gyeonggi-do, Hwaseong-si, South Korea

Type of Equipment : Asset Tracker

Model Name : IET10MO

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 32 pages (including this page)

Date of Incoming: May 20, 2020

Date of issue : May 29, 2020

# **SUMMARY**

The equipment complies with the standard; EN 300 328 V2.1.1.

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

Tae-Ho, Kim / Senior Manager

Tae-Ho, Kim / Senior Manag ONETECH Corp. Approved by:

Ki-Hong, Nam / Chief Engineer

Report No.: OT-205-RWD-063

ONETECH Corp.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-010(Rev.3)





# **CONTENTS**

	PAGE
1. APPLICANT AND MANUFACTURER INFORMATION	4
2. TEST SUMMARY	4
2.1 TEST STANDARDS AND RESULTS	4
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS	5
2.3 PURPOSE OF THE TEST	5
2.4 TEST FACILITY	5
3. EUT (EQUIPMENT UNDER TEST)	6
3.1 IDENTIFICATION OF EUT	6
3.2 ADDITIONAL INFORMATION ABOUT THE EUT	6
3.3 PERIPHERAL EQUIPMENT	7
3.4 MODE OF OPERATION DURING THE TEST	7
4. EUT MODIFICATIONS	7
5. TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN	8
5.1 OPERATING ENVIRONMENT	8
5.2 TEST SET-UP AND PROCEDURE	8
5.3 MEASUREMENT UNCERTAINTY	8
5.4 TEST EQUIPMENT USED	9
5.5 TEST DATA FOR RADIATED	10
5.5.1 Test data for 802.11b	10
5.5.2 Test data for 802.11g	13
5.5.3 Test data for 802.11n_HT20	16
5.6 LIMIT	19
6. RECEIVER SPURIOUS EMISSIONS	20
6.1 OPERATING ENVIRONMENT	20
6.2 TEST SET-UP AND PROCEDURE.	20
6.3 MEASUREMENT UNCERTAINTY	20
6.4 TEST EQUIPMENT USED	21
6.5 TEST DATA FOR RADIATED	22
6.5.1 Test data for 802.11b	22
6.5.2 Test data for 802.11g	25
6.5.3 Test data for 802.11n_HT20	28
6.6 LIMIT	31
APPENDIX I - TEST SET-UP PHOTO	32



Page 3 of 32 Report No.: OT-205-RWD-063

# **Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-205-RWD-063	May 29, 2020	Initial Release	All

<sup>\*</sup> Please contact us (e-mail:  $\underline{info@onetech.co.kr}$ ) for verification of this test report.





# 1. APPLICANT AND MANUFACTURER INFORMATION

-. Applicant : SEONG JI INDUSTRIAL CO., LTD

-. Address : 54-33, Dongtanhana 1-gil, Gyeonggi-do, Hwaseong-si, South Korea

-. Manufacturer : SEONG JI INDUSTRIAL CO., LTD

-. Address : 54-33, Dongtanhana 1-gil, Gyeonggi-do, Hwaseong-si, South Korea

#### 2. TEST SUMMARY

# 2.1 Test standards and results

CLAUSE	TEST ITEMS	RESULTS	REMARK
4.3.1.2 or 4.3.2.2	RF output power	-	Note1
4.3.2.3	Power Spectral Density	-	Note1
4.3.1.3 or 4.3.2.4	Duty Cycle, Tx-sequence, Tx-gap	-	Note1
4.3.1.4	Accumulated Transmit Time, Frequency Occupation & Hopping Sequence	-	Note1
4.3.1.5	Hopping Frequency Separation	-	Note1
4.3.1.6 or 4.3.2.5	Medium Utilisation (MU) factor	-	Note1
4.3.1.7 or 4.3.2.6	Adaptivity (Adaptive Frequency Hopping)	-	Note1
4.3.1.8 or 4.3.2.7	Occupied Channel Bandwidth	-	Note1
4.3.1.9 or 4.3.2.8	Transmitter Unwanted emissions in the out-of-band domain	-	Note1
4.3.1.10 or 4.3.2.9	Transmitter Unwanted emissions in the Spurious domain	PASS	-
4.3.1.11 or 4.3.2.10	Receiver spurious emissions	PASS	-
4.3.1.12 or 4.3.2.11	Receiver Blocking	-	Note1
4.3.1.13 or 4.3.2.12	Geo-location capability	-	Note1

Note1 - The EUT have a RF Test already approved. (Model: SRM200A / Report Number: HCT-RF-1911-CE017)

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-010(Rev.3)



Page 5 of 32 Report No.: OT-205-RWD-063

#### 2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

### 2.3 Purpose of the test

To determine whether the equipment under test fulfills the RF spectrum electro magnetic compatibility requirements of the standards stated in section 2.1.

# 2.4 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) - Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) - Designation No. KR0013





# 3. EUT (Equipment Under Test)

# 3.1 Identification of EUT

-. Equipment : Asset Tracker-. Model Name : IET10MO

-. Brand Name : -. Serial number : N/A

-. Manufacturer : SEONG JI INDUSTRIAL CO., LTD

## 3.2 Additional information about the EUT

The SEONG JI INDUSTRIAL CO., LTD, Model IET10MO (referred to as the EUT in this report) is a Asset Tracker. The product specification described herein was obtained from product data sheet or user's manual.

1	1	tained from product data sheet of user's mandar.
DEVICE TYPE	Asset Tracker	
Temperature Range	-30 °C ~ 60 °C	
	C'. E.	868.034 MHz ~ 868.226 MHz (Tx)
ODED ATTIVE	Sig Fox	869.429 MHz ~ 869.621 MHz (Rx)
OPERATING	GPS	1 559 MHz ~ 1 610 MHz
FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 472 MHz (802.11b/g/n(HT20))
	Sig Fox	DBPSK
MODULATION	Bluetooth LE	GFSK
TYPE	WILLIAM OF CALL	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)
	WLAN 2.4 GHz	802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
		Sig Fox : Metal Antenna
ANTENNA TYPE		Bluetooth LE / WLAN 2.4 GHz : Chip Antenna
		GPS : Ceramic Patch Antenna
		Sig Fox: 2.50 dBi
ANTENNA GAIN		Bluetooth LE: 2.50 dBi
		WLAN 2.4 GHz: 2.50 dBi
List of each Osc. or cry	ystal	22.769 LHz, 26 MHz, 22 MHz
Freq.(Freq. >= 1 MHz)	)	32.768 kHz, 26 MHz, 32 MHz



Page 7 of 32 Report No.: OT-205-RWD-063

# 3.3 Peripheral equipment

-. None

# 3.4 Mode of operation during the test

For WLAN the testing, software used to control the EUT for staying in continuous transmitting and receiving mode is programmed. For determining which data rate is the worst case, for following modes were investigated and then selected the worst test mode for all test items. To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XZ" axis, but the worst data was recorded in this test report.

# 3.5 Alternative type(s)/model(s); also covered by this test report.

-. None

#### 4. EUT MODIFICATIONS

-. None





# 5. Transmitter Unwanted emissions in the Spurious domain

# **5.1 Operating environment**

Temperature :  $24 \, ^{\circ}\text{C}$ 

Relative humidity : 49 % R.H.

# **5.2** Test set-up and procedure

EN 300 328 V2.1.1 clause 5.4.9

# **5.3** Measurement uncertainty

Radiated emission electric field intensity, 30 MHz  $\sim$  1 000 MHz  $\,$  : 3.7 dB

Radiated emission electric field intensity, 1 GHz ~ 12.75 GHz : 3.9 dI





# 5.4 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Feb. 21, 2020 (1Y)
■ - OSP120	Rohde & Schwarz	Open Switch and Control Unit	101364	N/A
■ - OSP150	Rohde & Schwarz	Open Switch and Control Unit	100871	N/A
■ - Controller CO 2000	Innco systems GmbH	Digital Controller	N/A	N/A
■ - VULB9163	Schwarzbeck	TRILOG Broadband Antenna	777	Apr. 08, 2020 (2Y)
□ - DT3000	Innco System	Turn Table	930611	N/A
■ - BBHA 9120D	Schwarzbeck	Horn Antenna	9120D-1366	Jul. 16, 2019 (1Y)
□ - BBHA 9170	Schwarzbeck	Horn Antenna	BBHA9170179	Jan. 07, 2020 (1Y)
□ - QMS-00208	Schwarzbeck	Horn Antenna	16111	Nov. 25, 2019 (1Y)
■ - MA 2000	Innco systems GmbH	Antenna master	N/A	N/A
■ - AS1700-EP	Innco systems GmbH	Antenna master	N/A	N/A
■ - DS 1200 S	Innco systems GmbH	Turn table	N/A	N/A
□ - FPA3-0.8-6.0R/1329	Innco systems GmbH	Communication antenna	411068-0003	N/A
□ - FPA3-0.8-6.0R/1329	Innco systems GmbH	Communication antenna	411068-0001	N/A
■ - DE3700-RH	Innco systems GmbH	Antenna master	N/A	N/A
■ - SFI101	Rohde & Schwarz	Wlan RSE Switchimg Aad Filter Unlt	N/A	N/A
■ - SCU03	Rohde & Schwarz	Signal Conditioning unit	100333	Feb. 19, 2020 (1Y)
■ - SCU18	Rohde & Schwarz	Signal Conditioning unit	102266	Jul. 24, 2019 (1Y)
□ - SCU40A	Rohde & Schwarz	Signal Conditioning unit	N/A	Feb. 20, 2020 (1Y)
□ - HPF 3GHz	Rohde & Schwarz	High Pass Filter	N/A	Feb. 19, 2020 (1Y)
□ - HPF 1.5GHz	Rohde & Schwarz	High Pass Filter	N/A	Feb. 19, 2020 (1Y)
□- HPF 3GHz	Rohde & Schwarz	High Pass Filter	N/A	Feb. 19, 2020 (1Y)
□ - F1 GSM 850	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F2 GSM 900	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F3 GSM 1800	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F4 GSM 1900	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F5 CDMA CELL	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F6 CDMA PCS	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)

All test equipment used is calibrated on a regular basis.



#### 5.5 Test data for Radiated

#### 5.5.1 Test data for 802.11b

#### 5.5.1.1 Test data (Below 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 100 kHz

-. Frequency range : 30 MHz ~ 1 GHz

-. Operating condition : Highest Output Power Transmitting Mode

-. Measurement distance : 3 m

Measurement distance	: 3 m				
Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
	Low Channel				
N	Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					

Remark: "H": Horizontal, "V": Vertical

#### 5.5.1.2 Test data (Above 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 1 MHz

-. Frequency range :  $1 \text{ GHz} \sim 12.75 \text{ GHz}$ 

-. Operating condition : Highest Output Power Transmitting Mode

-. Measurement distance : 3 m

	1				
Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
(1.2112)	(uBii)	l	(dDIII)	(41)	
	Low Channel				
N	Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					

Remark: "H": Horizontal, "V": Vertical


Tested by: Hyung-Kwon, Oh / Assistant Manager


It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-010(Rev.3)












# Low Channel - Transmitting Mode (Below 1 GHz)









**High Channel - Transmitting Mode (Above 1 GHz)** 



Page 13 of 32 Report No.: OT-205-RWD-063

## 5.5.2 Test data for 802.11g

## 5.5.2.1 Test data (Below 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 100 kHz

-. Frequency range : 30 MHz ~ 1 GHz

-. Operating condition : Highest Output Power Transmitting Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
Low Channel					
N	Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					

Remark: "H": Horizontal, "V": Vertical

#### 5.5.2.2 Test data (Above 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 1 MHz

-. Frequency range : 1 GHz ~ 12.75 GHz

-. Operating condition : Highest Output Power Transmitting Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
		Low Channel			
Measurements are 6 dB below these limits, the measurements are not reported.					
High Channel					
N	Measurements are 6 dB below these limits, the measurements are not reported.				


Remark: "H": Horizontal, "V": Vertical


Tested by: Hyung-Kwon, Oh / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-010(Rev.3)









# Low Channel - Transmitting Mode (Below 1 GHz)



**High Channel - Transmitting Mode (Below 1 GHz)** 







**High Channel - Transmitting Mode (Above 1 GHz)** 



Page 16 of 32 Report No.: OT-205-RWD-063

# 5.5.3 Test data for 802.11n\_HT20

#### 5.5.3.1 Test data (Below 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 100 kHz

-. Frequency range : 30 MHz ~ 1 GHz

-. Operating condition : Highest Output Power Transmitting Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
	Low Channel				
N	Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					

Remark: "H": Horizontal, "V": Vertical

#### 5.5.3.2 Test data (Above 1 GHz)

-. Test Date : August 08, 2019 ~ August 16, 2019

-. Resolution bandwidth : 1 MHz

-. Frequency range : 1 GHz ~ 12.75 GHz

-. Operating condition : Highest Output Power Transmitting Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
		Low Channel			
N	Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel					
M	Measurements are 6 dB below these limits, the measurements are not reported.				


Remark: "H": Horizontal, "V": Vertical


Tested by: Hyung-Kwon, Oh / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-010(Rev.3)









# Low Channel - Transmitting Mode (Below 1 GHz)



**High Channel - Transmitting Mode (Below 1 GHz)** 











# **5.6 Limit**

**Subclause: 4.3.2.9.3 Table 12** 

	Narrowband Spurious Emission			
Frequency Range	Maximum power, e.r.p. (≤ 1 GHz) e.i.r.p. (> 1 GHz)	Bandwidth		
30 MHz to 47 MHz	-36 dBm	100 kHz		
47 MHz to 74 MHz	-54 dBm	100 kHz		
74 MHz to 87.5 MHz	-36 dBm	100 kHz		
87,5 MHz to 118 MHz	-54 dBm	100 kHz		
118 MHz to 174 MHz	-36 dBm	100 kHz		
174 MHz to 230 MHz	-54 dBm	100 kHz		
230 MHz to 470 MHz	-36 dBm	100 kHz		
470 MHz to 862 MHz	-54 dBm	100 kHz		
862 MHz to 1 GHz	-36 dBm	100 kHz		
1 GHz to 12.75 GHz	-30 dBm	1 MHz		

Tested by: Hyung-Kwon, Oh / Assistant Manager





# 6. Receiver spurious emissions

# **6.1 Operating environment**

Temperature : 24.3 °C

Relative humidity : 43.9 % R.H.

# **6.2** Test set-up and procedure

EN 300 328 V2.1.1 clause 5.4.10

# **6.3 Measurement uncertainty**

Radiated emission electric field intensity,  $30 \text{ MHz} \sim 1000 \text{ MHz}$  : 3.7 dB Radiated emission electric field intensity,  $1 \text{ GHz} \sim 12.75 \text{ GHz}$  : 3.9 dB





# 6.4 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Feb. 21, 2020 (1Y)
■ - OSP120	Rohde & Schwarz	Open Switch and Control Unit	101364	N/A
■ - OSP150	Rohde & Schwarz	Open Switch and Control Unit	100871	N/A
■ - Controller CO 2000	Innco systems GmbH	Digital Controller	N/A	N/A
■ - VULB9163	Schwarzbeck	TRILOG Broadband Antenna	777	Apr. 08, 2020 (2Y)
□ - DT3000	Innco System	Turn Table	930611	N/A
■ - BBHA 9120D	Schwarzbeck	Horn Antenna	9120D-1366	Jul. 16, 2019 (1Y)
□ - BBHA 9170	Schwarzbeck	Horn Antenna	BBHA9170179	Jan. 07, 2020 (1Y)
□ - QMS-00208	Schwarzbeck	Horn Antenna	16111	Nov. 25, 2019 (1Y)
■ - MA 2000	Innco systems GmbH	Antenna master	N/A	N/A
■ - AS1700-EP	Innco systems GmbH	Antenna master	N/A	N/A
■ - DS 1200 S	Innco systems GmbH	Turn table	N/A	N/A
□ - FPA3-0.8-6.0R/1329	Innco systems GmbH	Communication antenna	411068-0003	N/A
□ - FPA3-0.8-6.0R/1329	Innco systems GmbH	Communication antenna	411068-0001	N/A
■ - DE3700-RH	Innco systems GmbH	Antenna master	N/A	N/A
■ - SFI101	Rohde & Schwarz	Wlan RSE Switchimg Aad Filter Unlt	N/A	N/A
■ - SCU03	Rohde & Schwarz	Signal Conditioning unit	100333	Feb. 19, 2020 (1Y)
■ - SCU18	Rohde & Schwarz	Signal Conditioning unit	102266	Jul. 24, 2019 (1Y)
□ - SCU40A	Rohde & Schwarz	Signal Conditioning unit	N/A	Feb. 20, 2020 (1Y)
□ - HPF 3GHz	Rohde & Schwarz	High Pass Filter	N/A	Feb. 19, 2020 (1Y)
□ - HPF 1.5GHz	Rohde & Schwarz	High Pass Filter	N/A	Feb. 19, 2020 (1Y)
□- HPF 3GHz	Rohde & Schwarz	High Pass Filter	N/A	Feb. 19, 2020 (1Y)
□ - F1 GSM 850	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F2 GSM 900	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F3 GSM 1800	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F4 GSM 1900	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F5 CDMA CELL	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)
□ - F6 CDMA PCS	Rohde & Schwarz	Filter	N/A	Feb. 19, 2020 (1Y)

All test equipment used is calibrated on a regular basis.





#### 6.5 Test data for Radiated

#### 6.5.1 Test data for 802.11b

#### 6.5.1.1 Test data (Below 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 100 kHz

-. Frequency range :  $30 \text{ MHz} \sim 1 \text{ GHz}$ -. Operating condition : Receiving Mode

-. Measurement distance : 3 m

Wicasurchicht distance	. 5 111			
Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)
Low Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				

Remark: "H": Horizontal, "V": Vertical

#### 6.5.1.2 Test data (Above 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 1 MHz

-. Frequency range  $: 1 \text{ GHz} \sim 12.75 \text{ GHz}$ -. Operating condition : Receiving Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)
Low Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				


Remark: "H": Horizontal, "V": Vertical


Tested by: Hyung-Kwon, Oh / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-010(Rev.3)









# Low Channel - Receiving Mode (Below 1 GHz)



High Channel - Receiving Mode (Below 1 GHz)







High Channel - Receiving Mode (Above 1 GHz)



Page 25 of 32 Report No.: OT-205-RWD-063

# 6.5.2 Test data for 802.11g

#### 6.5.2.1 Test data (Below 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 100 kHz

-. Frequency range : 30 MHz ~ 1 GHz-. Operating condition : Receiving Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
Low Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					
High Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					

Remark: "H": Horizontal, "V": Vertical

#### 6.5.2.2 Test data (Above 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 1 MHz

-. Frequency range : 1 GHz ~ 12.75 GHz-. Operating condition : Receiving Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)
Low Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				


Remark: "H": Horizontal, "V": Vertical


Tested by: Hyung-Kwon, Oh / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-010(Rev.3)









# Low Channel - Receiving Mode (Below 1 GHz)



High Channel - Receiving Mode (Below 1 GHz)







High Channel - Receiving Mode (Above 1 GHz)



Page 28 of 32 Report No.: OT-205-RWD-063

# 6.5.3 Test data for 802.11n\_HT20

#### 6.5.3.1 Test data (Below 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 100 kHz

-. Frequency range : 30 MHz ~ 1 GHz-. Operating condition : Receiving Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)	
Low Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					
High Channel					
Measurements are 6 dB below these limits, the measurements are not reported.					

Remark: "H": Horizontal, "V": Vertical

#### 10.5.3.2 Test data (Above 1 GHz)

-. Test Date : May 21, 2020 ~ May 25, 2020

-. Resolution bandwidth : 1 MHz

-. Frequency range  $: 1 \text{ GHz} \sim 12.75 \text{ GHz}$ -. Operating condition : Receiving Mode

-. Measurement distance : 3 m

Frequency (MHz)	Level (dBm)	Pol	Limit (dBm)	Margin (dB)
Low Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				
High Channel				
Measurements are 6 dB below these limits, the measurements are not reported.				


Remark: "H": Horizontal, "V": Vertical


Tested by: Hyung-Kwon, Oh / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.


EMC-010(Rev.3)









# Low Channel - Receiving Mode (Below 1 GHz)



High Channel - Receiving Mode (Below 1 GHz)







High Channel - Receiving Mode (Above 1 GHz)



# **6.6 Limit**

ONETECH

**Subclause: 4.3.2.10.3 Table 13** 

Frequency (MHz)	Maximum power, e.r.p.	Measurement bandwidth
30 MHz to 1 GHz	-57 dBm	100 kHz
1 GHz to 12.75 GHz	-47 dBm	1 MHz

Tested by: Hyung-Kwon, Oh / Assistant Manager





# APPENDIX I - TEST SET-UP PHOTO

