



# LSM1x0A

## F/W Download Guide

Rev 1.5

---

SJIT

January, 16, 2024

### Contents

---

<b>1. F/W DOWNLOAD - IAP.....</b>	<b>3</b>
3.1 F/W DOWNLOAD USING EXTRA PUTTY.....	3
3.2 F/W DOWNLOAD USING TERA TERM .....	7

## History

Date	Contents	Version	
2022-04-18	Create	V1.0	
2022-06-03	Add F/W merge (IAP + F/W)	V1.1	
2023-02-01	Delete unnecessary content	V1.2	
2023-02-02	Changed IAP speed(baud rate)	V1.3	
2023-07-03	Add factory reset process after firmware download	V1.4	


## 1. F/W Download - IAP

note: F/W downloader using IAP

Run as a Ymodem-enabled program (Extra putty, tera term, etc.)

Connect PC and module

- PC and module connection using micro 5pin cable




### 1.1 F/W download using Extra putty

Putty version: [Extra putty 0.30](#)


1)Putty standard setting

- Window -> Behaviour -> "Enable menu on Terminal" check




## 2) Serial connection

- Connection type: Serial
- Serial line: module port number Ex) COM24
- Speed(baud rate): 115200
- After setting as above, "Open" button click




## 3) Start download mode

- Press reset and enter '1' within 0.5 seconds




## 4) In download mode

- Files Transfer -> Ymodem -> Send click




5) Find and select the .bin file you want to install



※ Warning: In addition to binary (.bin) files created by building SDKs, you are responsible for any problems that occur when using other binary (.bin) files.

6) If you select a bin file and send it, the progress is displayed as shown in the figure below



7) After the download is complete, the size of the binary is printed and F/W is booted  
- User FW Speed(baud rate): 9600

Size: 152384 Bytes

-----  
SEONGJI INDUSTRIAL CO., LTD.  
-----

>> Device : LSM110A  
>> Mode : LoRa  
>> IAP\_VERSION : V1.0.0  
-----

>> APP\_VERSION: V1.0.0  
>> MH\_LORAWAN\_VERSION: V2.4.0  
>> MH\_RADIO\_VERSION: V1.2.0  
>> TXPOWER MODE : HIGH POWER  
>> L2\_SPEC\_VERSION: V1.0.4  
>> RP\_SPEC\_VERSION: V2-1.0.1  
-----

----- OTAA -----  
>> AppKey: 2B:7E:15:16:28:AE:D2:A6:AB:F7:15:88:09:CF:4F:3C  
>> NwkKey: 2B:7E:15:16:28:AE:D2:A6:AB:F7:15:88:09:CF:4F:3C  
----- ABP -----

>> AppSKey: 2B:7E:15:16:28:AE:D2:A6:AB:F7:15:88:09:CF:4F:3C  
>> NwkSKey: 2B:7E:15:16:28:AE:D2:A6:AB:F7:15:88:09:CF:4F:3C  
----- IDs -----


>> DevEui: 00:80:E1:15:00:09:0E:7A  
> AppEui: 01:01:01:01:01:01:01:01  
>> DevAddr: 00:09:0E:7A  
-----

## 1.2 F/W download using Tera term


Note: tera term does not work in the latest version(4.106), use version 4.72

### 1) Serial connection

- Setup -> "Serial port..." click



- Port: module port number Ex) COM24
- Baud rate: 115200
- After setting as above, "OK" button click




## 2) Start download mode


- Press reset and enter '1' within 0.5 seconds

```
IAP VERSION: 1.0.0
Waiting for the file to be sent ... (press 'a' to abort)
```

## 3) In download mode




## 4) Find and select the .bin file you want to install



※ Warning: In addition to binary (.bin) files created by building SDKs, you are responsible for any problems that occur when using other binary (.bin) files.




- 5) If you select a bin file and send it, the progress is displayed as shown in the figure below



- 6) After the download is complete, the size of the binary is printed and F/W is booted

- User FW Speed(baud rate): 9600



6) After setting Sigfox Mode & LoRa Mode, please set Initializing of restore flash factory settings by using ATCommand "AT\$RFS"



The screenshot shows a software interface for sending AT commands. At the top, there is a label "AT Command" above a text input field containing "AT\$RFS". To the right of the input field is a button labeled "AT SEND". Below the input field, the command "AT\$RFS" is displayed in blue. The output of the command is shown in orange text, consisting of a separator line, the text "SEONGJI INDUSTRIAL CO., LTD.", another separator line, and two lines of status information: ">> Device : LSM100A" and ">> Mode : Sigfox".

```
AT Command
AT$RFS
AT SEND

AT$RFS
-----
SEONGJI INDUSTRIAL CO., LTD.
-----
>> Device : LSM100A
>> Mode : Sigfox
```

( If you don't setting 'Initializing of restore flash factory settings', using updated RC lastly is not available )