

RAMP

The Research Assistant for Maniplexes and Polytopes

0.5

21 July 2021

Gabe Cunningham

Mark Mixer

Gordon Williams

Gabe Cunningham

Email: gabriel.cunningham@umb.edu

Homepage: <http://www.gabrielcunningham.com>

Address: Gabe Cunningham

Department of Mathematics

University of Massachusetts Boston

100 William T. Morrissey Blvd.

Boston MA 02125

Mark Mixer

Email: mixerm@wit.edu

Gordon Williams

Email: giwilliams@alaska.edu

Copyright

© 1997-2021 by Gabe Cunningham, Mark Mixer, and Gordon Williams

RAMP package is free software; you can redistribute it and/or modify it under the terms of the [GNU General Public License](#) as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

Acknowledgements

We appreciate very much all past and future comments, suggestions and contributions to this package and its documentation provided by **GAP** users and developers.

Contents

1	Graphs for Maniplexes	5
1.1	Graphs for maniplexes functions	5
2	Basics	13
2.1	Constructors	13
2.2	Sggis	15
3	Combinatorics and Structure	17
3.1	Faces	17
3.2	Flatness	19
3.3	Schlaflı symbol	19
3.4	Basics	20
3.5	Zigzags and holes	20
4	Actions	22
4.1	Automorphism group acting on faces and chains	22
4.2	Number of orbits and transitivity	23
4.3	Flag orbits	24
4.4	Faithfulness	25
5	Regular maps	27
5.1	Bicontactual regular maps	27
5.2	Operators on reflexible maps	28
5.3	Operations on Reflexible and Regular Maps	29
6	Constructions	30
6.1	Extensions, amalgamations, and quotients	30
6.2	Duality	31
6.3	Products	32
7	Databases	35
7.1	Regular polyhedra	35
8	Families of Polytopes	37
8.1	Classical Polytopes	37
8.2	Flat and tight polytopes	39
8.3	Toroids	40

8.4	Uniform Polyhedra	40
9	Groups	43
9.1	Groups	43
10	Mixing of Maniplexes	45
10.1	Mixing of Maniplexes functions	45
11	Properties	47
11.1	Orientability	47
12	Posets	49
12.1	Poset attributes	49
12.2	Poset constructors	53
12.3	Element Constructors	57
12.4	Element operations	59
12.5	Working with posets	60
13	Products of Posets and Digraphs	63
13.1	Construction methods	63
14	Comparing maniplexes	66
14.1	Quotients and covers	66
15	ramp automatic generated documentation	69
15.1	ramp automatic generated documentation of methods	69
16	Stratified Operations	71
16.1	Computational tools	71
17	Utility functions	72
17.1	Utility functions	72
	References	75
	Index	76

Chapter 1

Graphs for Maniplexes

1.1 Graphs for maniplexes functions

1.1.1 DirectedGraphFromListOfEdges (for IsList,IsList)

▷ DirectedGraphFromListOfEdges(*list*, *list*) (operation)

Returns: IsGraph. Note this returns a directed graph.

Given a list of vertices and a list of directed-edges (represented as ordered pairs), this outputs the directed graph with the appropriate vertex and directed-edge set.

Here we have a directed cycle on 3 vertices.

Example

```
gap> g:= DirectedGraphFromListOfEdges([1,2,3],[[1,2],[2,3],[3,1]]);
rec( adjacencies := [ [ 2 ], [ 3 ], [ 1 ] ], group := Group(),
    isGraph := true, names := [ 1, 2, 3 ], order := 3,
    representatives := [ 1, 2, 3 ], schreierVector := [ -1, -2, -3 ] )
```

1.1.2 GraphFromListOfEdges (for IsList,IsList)

▷ GraphFromListOfEdges(*list*, *list*) (operation)

Returns: IsGraph. Note this returns an undirected graph.

Given a list of vertices and a list of (directed) edges (represented as ordered pairs), this outputs the simple underlying graph with the appropriate vertex and directed-edge set.

Here we have a simple complete graph on 4 vertices.

Example

```
gap> g:= GraphFromListOfEdges([1,2,3,4],[[1,2],[2,3],[3,1], [1,4], [2,4], [3,4]]);
rec(
    adjacencies := [ [ 2, 3, 4 ], [ 1, 3, 4 ], [ 1, 2, 4 ], [ 1, 2, 3 ] ],
    group := Group(), isGraph := true, isSimple := true,
    names := [ 1, 2, 3, 4 ], order := 4, representatives := [ 1, 2, 3, 4 ]
    , schreierVector := [ -1, -2, -3, -4 ] )
```

1.1.3 UnlabeledFlagGraph (for IsGroup)

▷ UnlabeledFlagGraph(*group*) (operation)

Returns: IsGraph. Note this returns an undirected graph.

Given a group (assumed to be the connection group of a maniplex), this outputs the simple underlying flag graph.

Here we build the flag graph for the cube from its connection group.

Example

```
gap> g:= UnlabeledFlagGraph(ConnectionGroup(Cube(3)));
rec(
  adjacencies := [ [ 3, 11, 20 ], [ 7, 13, 18 ], [ 1, 4, 10 ],
    [ 3, 25, 34 ], [ 26, 28, 35 ], [ 7, 13, 41 ], [ 2, 6, 8 ],
    [ 7, 27, 32 ], [ 28, 33, 35 ], [ 3, 20, 45 ], [ 1, 14, 23 ],
    [ 15, 17, 24 ], [ 2, 6, 31 ], [ 11, 25, 44 ], [ 12, 45, 47 ],
    [ 18, 28, 40 ], [ 12, 19, 27 ], [ 2, 16, 21 ], [ 17, 22, 24 ],
    [ 1, 10, 38 ], [ 18, 32, 40 ], [ 19, 41, 48 ], [ 11, 35, 44 ],
    [ 12, 19, 34 ], [ 4, 14, 37 ], [ 5, 38, 42 ], [ 8, 17, 30 ],
    [ 5, 9, 16 ], [ 39, 41, 48 ], [ 27, 32, 47 ], [ 13, 33, 39 ],
    [ 8, 21, 30 ], [ 9, 31, 46 ], [ 4, 24, 37 ], [ 5, 9, 23 ],
    [ 43, 45, 47 ], [ 25, 34, 48 ], [ 20, 26, 43 ], [ 29, 31, 46 ],
    [ 16, 21, 42 ], [ 6, 22, 29 ], [ 26, 40, 43 ], [ 36, 38, 42 ],
    [ 14, 23, 46 ], [ 10, 15, 36 ], [ 33, 39, 44 ], [ 15, 30, 36 ],
    [ 22, 29, 37 ] ], group := Group(), isGraph := true,
  isSimple := true, names := [ 1 .. 48 ], order := 48,
  representatives := [ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14,
    15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30,
    31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46,
    47, 48 ],
  schreierVector := [ -1, -2, -3, -4, -5, -6, -7, -8, -9, -10, -11,
    -12, -13, -14, -15, -16, -17, -18, -19, -20, -21, -22, -23, -24,
    -25, -26, -27, -28, -29, -30, -31, -32, -33, -34, -35, -36, -37,
    -38, -39, -40, -41, -42, -43, -44, -45, -46, -47, -48 ] )
```

This also works with a maniplex input. Here we build the flag graph for the cube.

Example

```
gap> g:= UnlabeledFlagGraph(Cube(3));
```

1.1.4 FlagGraphWithLabels (for IsGroup)

▷ FlagGraphWithLabels(group)

(operation)

Returns: a triple [IsGraph, IsList, IsList].

Given a group (assumed to be the connection group of a maniplex), this outputs a triple [graph,list,list]. The graph is the unlabeled flag graph of the connection group. The first list gives the undirected edges in the flag graphs. The second list gives the labels for these edges.

Here we again build the flag graph for the cube from its connection group, but this time keep track of labels of the edges.

Example

```
gap> g:= FlagGraphWithLabels(ConnectionGroup(Cube(3)));
[ rec(
  adjacencies := [ [ 3, 11, 20 ], [ 7, 13, 18 ], [ 1, 4, 10 ],
    [ 3, 25, 34 ], [ 26, 28, 35 ], [ 7, 13, 41 ], [ 2, 6, 8 ],
    [ 7, 27, 32 ], [ 28, 33, 35 ], [ 3, 20, 45 ], [ 1, 14, 23 ],
    [ 15, 17, 24 ], [ 2, 6, 31 ], [ 11, 25, 44 ], [ 12, 45, 47 ],
    [ 18, 28, 40 ], [ 12, 19, 27 ], [ 2, 16, 21 ],
    [ 17, 22, 24 ], [ 1, 10, 38 ], [ 18, 32, 40 ],
```

```

[ 19, 41, 48 ], [ 11, 35, 44 ], [ 12, 19, 34 ],
[ 4, 14, 37 ], [ 5, 38, 42 ], [ 8, 17, 30 ], [ 5, 9, 16 ],
[ 39, 41, 48 ], [ 27, 32, 47 ], [ 13, 33, 39 ],
[ 8, 21, 30 ], [ 9, 31, 46 ], [ 4, 24, 37 ], [ 5, 9, 23 ],
[ 43, 45, 47 ], [ 25, 34, 48 ], [ 20, 26, 43 ],
[ 29, 31, 46 ], [ 16, 21, 42 ], [ 6, 22, 29 ],
[ 26, 40, 43 ], [ 36, 38, 42 ], [ 14, 23, 46 ],
[ 10, 15, 36 ], [ 33, 39, 44 ], [ 15, 30, 36 ],
[ 22, 29, 37 ] ], group := Group()), isGraph := true,
isSimple := true, names := [ 1 .. 48 ], order := 48,
representatives := [ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13,
14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28,
29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43,
44, 45, 46, 47, 48 ],
schreierVector := [ -1, -2, -3, -4, -5, -6, -7, -8, -9, -10, -11,
-12, -13, -14, -15, -16, -17, -18, -19, -20, -21, -22, -23,
-24, -25, -26, -27, -28, -29, -30, -31, -32, -33, -34, -35,
-36, -37, -38, -39, -40, -41, -42, -43, -44, -45, -46, -47,
-48 ] ),
[ [ 1, 3 ], [ 1, 11 ], [ 1, 20 ], [ 2, 7 ], [ 2, 13 ], [ 2, 18 ],
[ 3, 4 ], [ 3, 10 ], [ 4, 25 ], [ 4, 34 ], [ 5, 26 ], [ 5, 28 ],
[ 5, 35 ], [ 6, 7 ], [ 6, 13 ], [ 6, 41 ], [ 7, 8 ], [ 8, 27 ],
[ 8, 32 ], [ 9, 28 ], [ 9, 33 ], [ 9, 35 ], [ 10, 20 ],
[ 10, 45 ], [ 11, 14 ], [ 11, 23 ], [ 12, 15 ], [ 12, 17 ],
[ 12, 24 ], [ 13, 31 ], [ 14, 25 ], [ 14, 44 ], [ 15, 45 ],
[ 15, 47 ], [ 16, 18 ], [ 16, 28 ], [ 16, 40 ], [ 17, 19 ],
[ 17, 27 ], [ 18, 21 ], [ 19, 22 ], [ 19, 24 ], [ 20, 38 ],
[ 21, 32 ], [ 21, 40 ], [ 22, 41 ], [ 22, 48 ], [ 23, 35 ],
[ 23, 44 ], [ 24, 34 ], [ 25, 37 ], [ 26, 38 ], [ 26, 42 ],
[ 27, 30 ], [ 29, 39 ], [ 29, 41 ], [ 29, 48 ], [ 30, 32 ],
[ 30, 47 ], [ 31, 33 ], [ 31, 39 ], [ 33, 46 ], [ 34, 37 ],
[ 36, 43 ], [ 36, 45 ], [ 36, 47 ], [ 37, 48 ], [ 38, 43 ],
[ 39, 46 ], [ 40, 42 ], [ 42, 43 ], [ 44, 46 ] ],
[ 3, 2, 1, 3, 1, 2, 2, 1, 3, 1, 2, 3, 1, 1, 3, 2, 2, 1, 3, 1, 2, 3,
3, 2, 3, 1, 2, 3, 1, 2, 2, 1, 1, 3, 1, 2, 3, 1, 2, 3, 2, 3, 2, 2,
1, 1, 3, 2, 3, 2, 1, 1, 3, 3, 2, 3, 1, 1, 2, 1, 3, 3, 3, 2, 3, 1,
2, 3, 1, 2, 1, 2 ] ]

```

This also works with a maniplex input. Here we build the flag graph for the cube.

Example

```
gap> g:= FlagGraphWithLabels(Cube(3));
```

1.1.5 LayerGraph (for IsGroup, IsInt, IsInt)

▷ LayerGraph([group, int, int])

(operation)

Returns: IsGraph. Note this returns an undirected graph.

Given a group (assumed to be the connection group of a maniplex), and two integers, this outputs the simple underlying graph given by incidences of faces of those ranks. Note: There are no warnings yet to make sure that i, j are bounded by the rank.

Here we build the graph given by the 6 faces and 12 edges of a cube from its connection group.

Example

```
gap> g:= LayerGraph(ConnectionGroup(Cube(3)),2,1);
rec(
  adjacencies := [ [ 7, 10, 12, 17 ], [ 8, 10, 15, 18 ],
    [ 7, 9, 13, 14 ], [ 8, 11, 13, 16 ], [ 9, 12, 16, 18 ],
    [ 11, 14, 15, 17 ], [ 1, 3 ], [ 2, 4 ], [ 3, 5 ], [ 1, 2 ],
    [ 4, 6 ], [ 1, 5 ], [ 3, 4 ], [ 3, 6 ], [ 2, 6 ], [ 4, 5 ],
    [ 1, 6 ], [ 2, 5 ] ], group := Group(), isGraph := true,
  isSimple := true, names := [ 1 .. 18 ], order := 18,
  representatives := [ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14,
    15, 16, 17, 18 ],
  schreierVector := [ -1, -2, -3, -4, -5, -6, -7, -8, -9, -10, -11,
    -12, -13, -14, -15, -16, -17, -18 ] )
```

This also works with a maniplex input. Here we build the graph given by the 6 faces and 12 edges of a cube.

Example

```
gap> g:= LayerGraph(Cube(3),2,1);;
```

1.1.6 Skeleton (for IsManiplex)

▷ `Skeleton(maniplex)`

(operation)

Returns: `IsGraph`. Note this returns an undirected graph.

Given a maniplex, this outputs the 0-1 skeleton. The vertices are the 0-faces, and the edges are the 1-faces.

Here we build the skeleton of the dodecahedron.

Example

```
gap> g:= Skeleton(Dodecahedron());;
```

1.1.7 CoSkeleton (for IsManiplex)

▷ `CoSkeleton(maniplex)`

(operation)

Returns: `IsGraph`. Note this returns an undirected graph.

Given a maniplex, this outputs the $(n-1)$ -($n-2$) skeleton, i.e., the 0-1 skeleton of the dual. The vertices are the $(n-1)$ -faces, and the edges are the $(n-2)$ -faces.

Here we build the co-skeleton of the dodecahedron and verify that it is the skeleton of the icosahedron.

Example

```
gap> g:=CoSkeleton(Dodecahedron());;
gap> h:=Skeleton(Icosahedron());;
gap> g=h;
true
```

1.1.8 Hasse (for IsManiplex)

▷ `Hasse(group)`

(operation)

Returns: `IsGraph`. Note this returns a directed graph.

Given a group, assumed to be the connection group of a maniplex, this outputs the Hasse Diagram as a directed graph. Note: The unique minimal and maximal face are assumed.

Here we build the Hasse Diagram of a 3-simplex from its representation as a maniplex.

Example

```
gap> Hasse(Simplex(3));
rec(
  adjacencies := [ [ ], [ 1 ], [ 1 ], [ 1 ], [ 1 ], [ 2, 4 ],
    [ 2, 3 ], [ 3, 5 ], [ 2, 5 ], [ 4, 5 ], [ 3, 4 ], [ 6, 9, 10 ],
    [ 6, 7, 11 ], [ 8, 10, 11 ], [ 7, 8, 9 ], [ 12, 13, 14, 15 ] ],
  group := Group(), isGraph := true, names := [ 1 .. 16 ],
  order := 16,
  representatives := [ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14,
    15, 16 ],
  schreierVector := [ -1, -2, -3, -4, -5, -6, -7, -8, -9, -10, -11,
    -12, -13, -14, -15, -16 ] )
```

1.1.9 QuotientByLabel (for IsObject, IsList, IsList, IsList)

▷ QuotientByLabel(*object*, *list*, *list*, *list*) (operation)

Returns: IsGraph. Note this returns an undirected graph.

Given a graph, its edges, and its edge labels, and a sublist of labels, this creates the underlying simple graph of the quotient identifying vertices connected by labels not in the sublist.

Here we start with the flag graph of the 3-cube (with edge labels 1,2,3), and identify any vertices not connected by edge by edges of label 1. We can then check that this new graph is bipartite.

Example

```
gap> P:=Cube(3);;
gap> f:=FlagGraphWithLabels(P);;
gap> g:=f[1];;
gap> ed:=f[2];;
gap> lab:=f[3]; #Note This triple is to be replace by a single object.
[ 3, 2, 1, 3, 1, 2, 1, 2, 3, 2, 1, 3, 2, 1, 1, 3, 2, 2, 3, 1, 3, 1, 2, 3, 2, 1, 1, 2, 2, 3, 1, 3,
  3, 1, 2, 1, 3, 2, 2, 1, 2, 2, 3, 1, 1, 3, 1, 3, 3, 2, 1, 2, 1, 3, 3, 1, 3, 2, 2, 2, 2, 3, 3, 1,
gap> Q:=QuotientByLabel(g,ed,lab,[1]);
rec( adjacencies := [ [ 5, 6, 8 ], [ 3, 4, 7 ], [ 2, 6, 8 ], [ 2, 5, 8 ], [ 1, 4, 7 ], [ 1, 3, 7 ],
  isSimple := true, names := [ 1 .. 8 ], order := 8, representatives := [ 1, 2, 3, 4, 5, 6, 7, 8 ]
gap> IsBipartite(Q);
true
```

1.1.10 EdgeLabeledGraphFromEdges (for IsList, IsList, IsList)

▷ EdgeLabeledGraphFromEdges(*list*, *list*, *list*) (operation)

Returns: IsEdgeLabeledGraph.

Given a list of vertices, a list of edges, and a list of edge labels, this represents the edge labeled (multi)-graph with those parameters. Semi-edges are represented by a singleton in the edge list. Loops are represented by edges [i,i]

Here we have an edge labeled cycle graph with 6 vertices and edges alternating in labels 0,1.

Example

```
V:=[1..6];;
Edges:=[[1,2],[2,3],[3,4],[4,5],[5,6],[6,1]];;
L:=[0,1,0,1,0,1];;
gamma:=EdgeLabeledGraphFromEdges(V,Edges,L);
```

1.1.11 FlagGraph (for IsGroup)

▷ `FlagGraph(group)` (operation)

Returns: `IsEdgeLabeledGraph`.

Given *group*, assumed to be a connection group, output the labeled flag graph. The input could also be a maniplex, then the connection group is calculated.

Here we have the flag graph of the 3-simplex from its connection group.

Example

```
C:=ConnectionGroup(Simplex(3));
gamma:=FlagGraph(C);
```

1.1.12 UnlabeledSimpleGraph (for IsEdgeLabeledGraph)

▷ `UnlabeledSimpleGraph(edge-labeled-graph)` (operation)

Returns: `IsGraph`.

Given an edge labeled (multi) graph, it returns the underlying simple graph, with semi-edges, loops, and multiple-edges removed.

Here we have underlying simple graph for the flag graph of the cube.

Example

```
gamma:=UnlabeledSimpleGraph(FlagGraph(Cube(3)));
```

1.1.13 EdgeLabelPreservingAutomorphismGroup (for IsEdgeLabeledGraph)

▷ `EdgeLabelPreservingAutomorphismGroup(edge-labeled-graph)` (operation)

Returns: `IsGroup`.

Given an edge labeled (multi) graph, it returns automorphism group (preserving the labels). Note, for now the labels are assumed to be [1..n]. Note This tends to be very slow. I would like to look for a way to go back and forth between flag automorphisms and poset automorphisms, as the latter are much faster to compute.

Here we have the automorphism group of the flag graph of the cube.

Example

```
g:=EdgeLabelPreservingAutomorphismGroup(FlagGraph(Cube(3)));
Size(g);
```

1.1.14 Simple (for IsEdgeLabeledGraph)

▷ `Simple(edge-labeled-graph)` (operation)

Returns: `IsEdgeLabeledGraph`.

Given an edge labeled (multi) graph, it returns another edge labeled graph where semi-edges, loops, and multiple edges are removed. Note only the "first" edge label is retained if there are multiple edges.

1.1.15 ConnectedComponents (for IsEdgeLabeledGraph, IsList)

▷ `ConnectedComponents(edge-labeled-graph)` (operation)

Returns: `IsGraph`.

Given an edge labeled (multi) graph and a list of labels, it returns connected components of the graph not using edges in the list of labels. Note if the second argument is not used, it is assumed to be an empty list, and the connected components of the original graph are returned.

Here we see that each connected component of the flag graph of the cube (which has labels 1,2,3) where edges of label 2 are removed, is a 4 cycle.

Example

```
gamma:=ConnectedComponents(FlagGraph(Cube(3)), [2]);
```

1.1.16 PRGraph (for IsGroup)

▷ PRGraph(*group*) (operation)

Returns: IsEdgeLabeledGraph .

Given a group, it returns the permutation representation graph for that group. When the group is a string C-group this is also called a CPR graph. The labels of the edges are [1...r] where r is the number of generators of the group.

Here we see the CPR graph of the automorphism group of a cube (acting on its 8 vertices).

Example

```
G:=AutomorphismGroup(Cube(3));
H:=Group(G.2,G.3);
phi:=FactorCosetAction(G,H);
G2:=Range(phi);
gamma:=PRGraph(G2);
```

1.1.17 CPRGraphFromGroups (for IsGroup, IsGroup)

▷ CPRGraphFromGroups(*group*, *subgroup*) (operation)

Returns: IsEdgeLabeledGraph.

Given a group and a subgroup. Returns the graph of the action of the first group on cosets of the subgroup.

1.1.18 AdjacentVertices (for IsEdgeLabeledGraph, IsObject)

▷ AdjacentVertices(*EdgeLabeledGraph*, *vertex*) (operation)

Returns: IsList.

Takes in an edge labeled graph and a vertex, and outputs a list of the adjacent vertices.

1.1.19 LabeledAdjacentVertices (for IsEdgeLabeledGraph, IsObject)

▷ LabeledAdjacentVertices(*EdgeLabeledGraph*, *vertex*) (operation)

Returns: IsList, IsList.

Takes in an edge labeled graph and a vertex, and outputs two lists: the list of adjacent vertices, and the labels of the corresponding edges.

1.1.20 SemiEdges (for IsEdgeLabeledGraph)

▷ SemiEdges(*EdgeLabeledGraph*) (operation)

Returns: IsList.

Takes in an edge labeled graph and a vertex, and outputs a list of semiedges

1.1.21 LabeledSemiEdges (for IsEdgeLabeledGraph)

▷ `LabeledSemiEdges(EdgeLabeledGraph)` (operation)

Returns: `IsList`, `IsList`.

Takes in an edge labeled graph and a vertex, and outputs two lists: `SemiEdges` and their labels

1.1.22 ViewGraph (for IsEdgeLabeledGraph, IsString)

▷ `ViewGraph(EdgeLabeledGraph, String)` (operation)

Returns: `IsString`.

This takes an edge labeled graph and outputs code to view the graph in other software. Currently `mathematica` and `sage` are supported.

1.1.23 ViewGraph (for IsObject, IsString)

▷ `ViewGraph(Graph, String)` (operation)

Returns: `IsString`.

This takes a graph and outputs code to view the graph in other software. Currently `mathematica` and `sage` are supported.

Chapter 2

Basics

2.1 Constructors

2.1.1 ReflexibleManiplex

- ▷ `ReflexibleManiplex(g)` (operation)
- ▷ `ReflexibleManiplex(sym[, relations])` (operation)

Returns: `IsReflexibleManiplex`

In the first form, we are given an Sggi g and we return the reflexible maniplex with that automorphism group, where the privileged generators are those returned by `GeneratorsOfGroup(g)`.

Example

```
gap> g := Group([(1,2), (2,3), (3,4)]);
gap> M := ReflexibleManiplex(g);
gap> M = Simplex(3);
true
```

This function first checks whether g is an Sggi. Use `ReflexibleManiplexNC` to bypass that check. The second form returns the universal reflexible maniplex with Schläfli symbol sym . If the optional argument $relations$ is given, then we return the reflexible maniplex with the given defining relations. The relations can be given by a list of Tietze words or as a string of relators or relations that involve r_0 etc.

Example

```
gap> q := ReflexibleManiplex([4,3,4], "(r0 r1 r2)^3, (r1 r2 r3)^3");;
gap> q = ReflexibleManiplex([4,3,4], "(r0 r1 r2)^3 = (r1 r2 r3)^3 = 1");;
true
gap> p := ReflexibleManiplex([infinity], "r0 r1 r0 = r1 r0 r1");;
```

If the option `set_schlafl` is set, then we set the Schläfli symbol to the one given. This may not be the correct Schläfli symbol, since the relations may cause a collapse, so this should only be used if you know that the Schläfli symbol is correct.

2.1.2 Maniplex (for IsPermGroup)

- ▷ `Maniplex(G)` (operation)
- Returns:** `IsManiplex`

Given a permutation group G on the set $[1..N]$, returns a maniplex with N flags with connection group G . The output may not make sense if G is not an sggi.

Example

```
gap> G := Group([(1,2)(3,4)(5,6), (2,3)(4,5)(1,6)]);;
gap> M := Maniplex(G);
Pgon(3)
gap> c := ConnectionGroup(Cube(3));
<permutation group with 3 generators>
gap> Maniplex(c) = Cube(3);
true
```

2.1.3 Maniplex (for IsReflexibleManiplex, IsGroup)

▷ `Maniplex(M , H)` (operation)

Returns: `IsManiplex`

Let M be a reflexible maniplex and let H be a subgroup of `AutomorphismGroup(M)`. This returns the maniplex M/H . This will be reflexible if and only if H is normal. For most purposes, it is probably easier to use `QuotientManiplex`, which takes a string of relations as input instead of a subgroup. The example below builds the map $\{4, 4\}_{(1,0),(0,2)}$.

Example

```
gap> M := ReflexibleManiplex([4,4]);
CubicTiling(2)
gap> G := AutomorphismGroup(M);
<fp group of size infinity on the generators [ r0, r1, r2 ]>
gap> H := Subgroup(G, [G.1*G.2*G.3*G.2, (G.2*G.1*G.2*G.3)^2]);
Group([ r0*r1*r2*r1, (r1*r0*r1*r2)^2 ])
gap> M2 := Maniplex(M, H);
3-maniplex
gap> Size(M2);
16
```

2.1.4 Maniplex (for IsFunction, IsList)

▷ `Maniplex(F , $inputs$)` (operation)

Returns: `IsManiplex`

Constructs a formal maniplex, represented by an operation F and a list of arguments $inputs$. By itself, this does not really `_do_` anything – it creates a maniplex object that only knows the operation F and the $inputs$. However, many polytope operations (such as `Pyramid(M)`, `Medial(M)`, etc) use this construction as a base, and then add "attribute computers" that tell the formal maniplex how to compute certain things in terms of properties of the base. See `AddAttrComputer` for more information.

2.1.5 Maniplex (for IsPoset)

▷ `Maniplex(P)` (operation)

Returns: `IsManiplex`

Constructs the maniplex from the given poset P . This assumes that P actually defines a maniplex.

2.1.6 IsPolytopal (for IsManiplex)

▷ `IsPolytopal(M)` (property)

Returns: `true` or `false`

Returns whether the maniplex M is polytopal; i.e., the flag graph of a polytope.

2.2 Sggis

2.2.1 UniversalSggi

▷ `UniversalSggi(n)` (operation)

▷ `UniversalSggi(sym)` (operation)

Returns: `IsFpGroup`

In the first form, returns the universal Coxeter Group of rank n . In the second form, returns the Coxeter Group with Schläfli symbol sym .

2.2.2 Sggi (for IsList, IsList)

▷ `Sggi($symbol[, relations]$)` (operation)

Returns: `IsFpGroup`

Returns the `sggi` defined by the given Schläfli symbol and with the given relations. The relations can be given by a list of Tietze words or as a string of relators or relations that involve r_0 etc. If no relations are given, then returns the universal `sggi` with the given Schläfli symbol.

Example

```
gap> g := Sggi([4,3,4], "(r0 r1 r2)^3, (r1 r2 r3)^3");;
gap> h := Sggi([4,4], "r0 = r2");;
gap> k := Sggi([infinity, infinity], [[1,2,1,2,1,2], [2,3,2,3,2,3]]);;
gap> k = Sggi([3,3]);
true
```

2.2.3 IsGgi (for IsGroup)

▷ `IsGgi(g)` (property)

Returns: whether g is generated by involutions. Or more specifically, whether `GeneratorsOfGroup(g)` all have order 2 or less.

2.2.4 IsStringy (for IsGroup)

▷ `IsStringy(g)` (property)

Returns: whether every pair of non-adjacent generators of g commute.

2.2.5 IsSggi (for IsGroup)

▷ `IsSggi(g)` (property)

Returns: whether g is a string group generated by involutions. Equivalent to `IsGgi(g)` and `IsStringy(g)`.

2.2.6 IsStringC (for IsGroup)

▷ `IsStringC(G)` (operation)

For an `sggi` G , returns whether the group is a string C group.

2.2.7 IsStringCPlus (for IsGroup)

▷ `IsStringCPlus(G)` (operation)

For a "string rotation group" G , returns whether the group is a string C+ group. It does not check whether G is a string rotation group.

2.2.8 SggiElement (for IsGroup, IsString)

▷ `SggiElement(g, str)` (operation)

Returns: the element of g with underlying word str .

Example

```
gap> g := Group((1,2),(2,3),(3,4));;
gap> SggiElement(g, "r0 r1");
(1,3,2)
```

For convenience, you can also use a reflexible maniplex M in place of g , in which case `AutomorphismGroup(M)` is used for g .

2.2.9 SggiFamily (for IsGroup, IsList)

▷ `SggiFamily(parent, words)` (operation)

Given a *parent* group and a list of strings that represent words in r_0, r_1 , etc, returns a function. That function accepts a list of positive integers L , and returns the quotient of *parent* by the relations that set the order of each $words[i]$ to $L[i]$.

Example

```
gap> f := SggiFamily(Sggi([4,4]), ["r0 r1 r2 r1"]);
function( orders ) ... end
gap> g := f([3]);
<fp group on the generators [ r0, r1, r2 ]>
gap> Size(g);
72
gap> h := f([6]);
<fp group on the generators [ r0, r1, r2 ]>
gap> IsQuotient(h,g);
true
```

One of the advantages of building an `SggiFamily` is that testing whether one member of the family is a quotient of another member can be done quite quickly.

Chapter 3

Combinatorics and Structure

3.1 Faces

3.1.1 NumberOfFaces (for IsManiplex, IsInt)

▷ `NumberOfFaces(M , i)` (operation)

Returns The number of i -faces of M .

3.1.2 NumberOfVertices (for IsManiplex)

▷ `NumberOfVertices(M)` (attribute)

Returns the number of vertices of M .

3.1.3 NumberOfEdges (for IsManiplex)

▷ `NumberOfEdges(M)` (attribute)

Returns the number of edges of M .

3.1.4 NumberOfFacets (for IsManiplex)

▷ `NumberOfFacets(M)` (attribute)

Returns the number of facets of M .

3.1.5 NumberOfRidges (for IsManiplex)

▷ `NumberOfRidges(M)` (attribute)

Returns the number of ridges (($n-2$)-faces) of M .

3.1.6 Fvector (for IsManiplex)

▷ `Fvector(M)` (attribute)

Returns the f-vector of M .

3.1.7 Section (for IsManiplex, IsInt, IsInt)

▷ `Section(M, j, i)` (operation)

Returns the section F_j / F_i , where F_j is the j -face of the base flag of M and F_i is the i -face of the base flag.

3.1.8 Section (for IsManiplex, IsInt, IsInt, IsInt)

▷ `Section(M, j, i, k)` (operation)

Returns the section F_j / F_i , where F_j is the j -face of flag number k of M and F_i is the i -face of the same flag.

3.1.9 Sections (for IsManiplex, IsInt, IsInt)

▷ `Sections(M, j, i)` (operation)

Returns all sections of type F_j / F_i , where F_j is a j -face and F_i is an incident i -face.

3.1.10 Facets (for IsManiplex)

▷ `Facets(M)` (attribute)

Returns the facet-types of M (i.e. the maniplexes corresponding to the facets).

3.1.11 Facet (for IsManiplex, IsInt)

▷ `Facet(M, k)` (operation)

Returns the facet of M that contains the flag number k (that is, the maniplex corresponding to the facet).

3.1.12 Facet (for IsManiplex)

▷ `Facet(M)` (attribute)

Returns the facet of M that contains flag number 1 (that is, the maniplex corresponding to the facet).

3.1.13 VertexFigures (for IsManiplex)

▷ `VertexFigures(M)` (attribute)

Returns the types of vertex-figures of M (i.e. the maniplexes corresponding to the vertex-figures).

3.1.14 VertexFigure (for IsManiplex, IsInt)

▷ `VertexFigure(M, k)` (operation)

Returns the vertex-figures of M that contains flag number k .

3.1.15 VertexFigure (for IsManiplex)

▷ `VertexFigure(M)` (attribute)

Returns the vertex-figures of M that contains the base flag.

3.2 Flatness

3.2.1 IsFlat

▷ `IsFlat(M)` (property)

▷ `IsFlat(M, i, j)` (operation)

Returns: true or false

In the first form, returns true if every vertex of the maniplex M is incident to every facet. In the second form, returns true if every i -face of the maniplex M is incident to every j -face.

3.3 Schläfli symbol

3.3.1 SchläfliSymbol (for IsManiplex)

▷ `SchläfliSymbol(M)` (attribute)

Returns the Schläfli symbol of the maniplex M . Each entry is either an integer or a set of integers, where entry number i shows the polygons that we obtain as sections of $(i+1)$ -faces over $(i-2)$ -faces.

3.3.2 PseudoSchläfliSymbol (for IsManiplex)

▷ `PseudoSchläfliSymbol(M)` (attribute)

Sometimes when we make a maniplex, we know that the Schläfli symbol must be a quotient of some symbol. This most frequently happens because we start with a maniplex with a given Schläfli symbol and then take a quotient of it. In this case, we store the given Schläfli symbol and call it a *pseudo-Schläfli symbol* of M . Note that whenever we compute the actual Schläfli symbol of M , we update the pseudo-Schläfli symbol to match.

3.3.3 IsEquivelar (for IsManiplex)

▷ `IsEquivelar(M)` (property)

Returns: the the maniplex M is equivelar; i.e., whether its Schläfli Symbol consists of integers at each position (no lists).

3.3.4 IsDegenerate (for IsManiplex)

▷ `IsDegenerate(M)` (property)

Returns: true or false

Returns whether the maniplex M has any sections that are digons. We may eventually want to include maniplexes with even smaller sections.

3.3.5 IsTight (for IsManiplex)

▷ `IsTight(P)` (property)

Returns: true or false

Returns whether the polytope P is tight, meaning that it has a Schläfli symbol $\{k_1, \dots, k_{n-1}\}$ and has $2 k_1 \dots k_{n-1}$ flags, which is the minimum possible. This property doesn't make any sense for non-polytopal maniplexes, which aren't constrained by this lower bound.

3.4 Basics

3.4.1 Size (for IsManiplex)

▷ `Size(M)` (attribute)

Returns: The number of flags of the maniplex M .

Synonym: `NumberOfFlags`.

3.4.2 RankManiplex (for IsManiplex)

▷ `RankManiplex(M)` (attribute)

Returns: The rank of the maniplex M .

3.5 Zigzags and holes

3.5.1 ZigzagLength (for IsManiplex, IsInt)

▷ `ZigzagLength(M, j)` (operation)

Returns: The lengths of j -zigzags of the 3-maniplex M . This corresponds to the lengths of orbits under $r_0(r_1 r_2)^j$.

3.5.2 ZigzagVector (for IsManiplex)

▷ `ZigzagVector(M)` (attribute)

Returns: The lengths of all zigzags of the 3-maniplex M . A rank 3 maniplex of type $\{p, q\}$ has $\text{Floor}(q/2)$ distinct zigzag lengths because the j -zigzags are the same as the $(q-j)$ -zigzags.

3.5.3 PetrieLength (for IsManifold)

- ▷ `PetrieLength(M)` (attribute)
Returns: The length of the petrie polygons of the manifold M .

3.5.4 HoleLength (for IsManifold, IsInt)

- ▷ `HoleLength(M , j)` (operation)
Returns: The lengths of j -holes of the 3-manifold M . This corresponds to the lengths of orbits under $r_0 (r_1 r_2)^{j-1} r_2$.

3.5.5 HoleVector (for IsManifold)

- ▷ `HoleVector(M)` (attribute)
Returns: The lengths of all zigzags of the 3-manifold M . A rank 3 manifold of type $\{p, q\}$ has $\text{Floor}(q/2)$ distinct zigzag lengths because the j -zigzags are the same as the $(q-j)$ -zigzags.

Chapter 4

Actions

4.1 Automorphism group acting on faces and chains

4.1.1 AutomorphismGroupOnChains (for IsManiplex, IsCollection)

▷ AutomorphismGroupOnChains(M , I) (operation)

Returns a permutation group, representing the action of AutomorphismGroup(M) on the chains of M of type I .

4.1.2 AutomorphismGroupOnIFaces (for IsManiplex, IsInt)

▷ AutomorphismGroupOnIFaces(M , i) (operation)

Returns a permutation group, representing the action of AutomorphismGroup(M) on the i -faces of M .

4.1.3 AutomorphismGroupOnVertices (for IsManiplex)

▷ AutomorphismGroupOnVertices(M) (attribute)

Returns a permutation group, representing the action of AutomorphismGroup(M) on the vertices of M .

4.1.4 AutomorphismGroupOnEdges (for IsManiplex)

▷ AutomorphismGroupOnEdges(M) (attribute)

Returns a permutation group, representing the action of AutomorphismGroup(M) on the edges of M .

4.1.5 AutomorphismGroupOnFacets (for IsManiplex)

▷ AutomorphismGroupOnFacets(M) (attribute)

Returns a permutation group, representing the action of `AutomorphismGroup(M)` on the facets of M .

4.2 Number of orbits and transitivity

4.2.1 NumberOfChainOrbits (for IsManifold, IsCollection)

▷ `NumberOfChainOrbits(M , I)` (operation)

Returns the number of orbits of chains of type I under the action of `AutomorphismGroup(M)`.

4.2.2 NumberOfIFaceOrbits (for IsManifold, IsInt)

▷ `NumberOfIFaceOrbits(M , i)` (operation)

Returns the number of orbits of i -faces under the action of `AutomorphismGroup(M)`.

4.2.3 NumberOfVertexOrbits (for IsManifold)

▷ `NumberOfVertexOrbits(M)` (attribute)

Returns the number of orbits of vertices under the action of `AutomorphismGroup(M)`.

4.2.4 NumberOfEdgeOrbits (for IsManifold)

▷ `NumberOfEdgeOrbits(M)` (attribute)

Returns the number of orbits of edges under the action of `AutomorphismGroup(M)`.

4.2.5 NumberOfFacetOrbits (for IsManifold)

▷ `NumberOfFacetOrbits(M)` (attribute)

Returns the number of orbits of facets under the action of `AutomorphismGroup(M)`.

4.2.6 IsChainTransitive (for IsManifold, IsCollection)

▷ `IsChainTransitive(M , I)` (operation)

Returns whether the action of `AutomorphismGroup(M)` on chains of type I is transitive.

4.2.7 IsIFaceTransitive (for IsManifold, IsInt)

▷ `IsIFaceTransitive(M , i)` (operation)

Returns whether the action of `AutomorphismGroup(M)` on i -faces is transitive.

4.2.8 IsVertexTransitive (for IsManiplex)

- ▷ `IsVertexTransitive(M)` (property)
Returns: true or false
 Returns whether the action of `AutomorphismGroup(M)` on vertices is transitive.

4.2.9 IsEdgeTransitive (for IsManiplex)

- ▷ `IsEdgeTransitive(M)` (property)
Returns: true or false
 Returns whether the action of `AutomorphismGroup(M)` on edges is transitive.

4.2.10 IsFacetTransitive (for IsManiplex)

- ▷ `IsFacetTransitive(M)` (property)
Returns: true or false
 Returns whether the action of `AutomorphismGroup(M)` on facets is transitive.

4.2.11 IsFullyTransitive (for IsManiplex)

- ▷ `IsFullyTransitive(M)` (property)
Returns: true or false
 Returns whether the action of `AutomorphismGroup(M)` on i -faces is transitive for every i .

4.3 Flag orbits

4.3.1 SymmetryTypeGraph (for IsManiplex)

- ▷ `SymmetryTypeGraph(M)` (attribute)
 Returns the Symmetry Type Graph of the maniplex M , encoded as a permutation group on `Rank(M)` generators.

4.3.2 NumberOfFlagOrbits (for IsManiplex)

- ▷ `NumberOfFlagOrbits(M)` (attribute)
 Returns the number of orbits of the automorphism group of M on its flags.

4.3.3 FlagOrbitRepresentatives (for IsManiplex)

- ▷ `FlagOrbitRepresentatives(M)` (attribute)
 Returns one flag from each orbit under the action of `AutomorphismGroup(M)`.

4.3.4 FlagOrbitsStabilizer (for IsManifold)

▷ `FlagOrbitsStabilizer(M)` (attribute)

Returns: g

Returns the subgroup of the connection group that preserves the flag orbits under the action of the automorphism group.

Example

```
gap> m:=Prism(Dodecahedron());
Prism(Dodecahedron())
gap> s:=FlagOrbitsStabilizer(m);
<permutation group of size 207360000 with 12 generators>
gap> IsSubgroup(ConnectionGroup(m),s);
true
gap> AsSet(Orbit(AutomorphismGroupOnFlags(m),1))=AsSet(Orbit(s,1));
true
```

4.3.5 IsReflexible (for IsManifold)

▷ `IsReflexible(M)` (property)

Returns: Whether the manifold M is reflexible (has one flag orbit).

4.3.6 IsChiral (for IsManifold)

▷ `IsChiral(M)` (property)

Returns: Whether the manifold M is chiral.

4.3.7 IsRotary (for IsManifold)

▷ `IsRotary(M)` (property)

Returns: Whether the manifold M is rotary; i.e., whether it is either reflexible or chiral.

4.3.8 FlagOrbits (for IsManifold)

▷ `FlagOrbits(M)` (attribute)

Returns a list of lists of flags, representing the orbits of flags under the action of `AutomorphismGroup(M)`.

4.4 Faithfulness

4.4.1 IsVertexFaithful (for IsReflexibleManifold)

▷ `IsVertexFaithful(M)` (property)

Returns: true or false

Returns whether the reflexible manifold M is vertex-faithful; i.e., whether the action of the automorphism group on the vertices is faithful.

4.4.2 IsFacetFaithful (for IsReflexibleManiplex)

▷ `IsFacetFaithful(M)` (property)

Returns: true or false

Returns whether the reflexible maniplex M is facet-faithful; i.e., whether the action of the automorphism group on the facets is faithful.

4.4.3 MaxVertexFaithfulQuotient (for IsReflexibleManiplex)

▷ `MaxVertexFaithfulQuotient(M)` (operation)

Returns the maximal vertex-faithful reflexible maniplex covered by M .

Chapter 5

Regular maps

5.1 Bicontactual regular maps

The names for the maps in this section are from S.E. Wilson's paper of the same title.

5.1.1 Epsilon ϵ_k (for IsInt)

▷ Epsilon $\epsilon(k)$ (operation)

Returns: maniplex

Given an integer k , gives the map ϵ_k , which is $\{k, 2\}_k$ when k is even, and $\{k, 2\}_{2k}$ when k is odd.

Example

```
gap> Epsilonk(5);
AbstractRegularPolytope([ 5, 2 ])
gap> Epsilonk(6);
AbstractRegularPolytope([ 6, 2 ])
```

5.1.2 Deltak δ_k (for IsInt)

▷ Deltak $\delta(k)$ (operation)

Returns: maniplex

Given an integer k , gives the map δ_k , which is $\{2k, 2\}/2$ when k is even, and $\{2k, 2\}_k$ when k is odd.

Example

```
gap> Deltak(5);
AbstractRegularPolytope([ 10, 2 ], "(r0 r1)^5 r2")
gap> Deltak(6);
AbstractRegularPolytope([ 12, 2 ], "(r0 r1)^6 r2")
```

5.1.3 Mk M_k (for IsInt)

▷ Mk $M(k)$ (operation)

Returns: maniplex

Given an integer k , gives the map M_k , which is $\{2k, 2k\}_{1,0}$ when k is even, and $\{2k, k\}_2$ when k is odd.

Example

```
gap> Mk(5);Mk(6);
AbstractRegularPolytope([ 10, 5 ], "(r0 r1)^5 r0 = r2")
AbstractRegularPolytope([ 12, 12 ], "(r0 r1)^6 r0 = r2")
```

5.1.4 MkPrime (for IsInt)

▷ `MkPrime(k)` (operation)

Returns: maniplex

Given an integer k , gives the map M'_k , which is $\{k, k\}_2$ when k is even, and $\{k, 2k\}_2$ when k is odd. `MkPrime(k, i)` gives the map $M'_{k,i}$.

Example

```
gap> MkPrime(5);MkPrime(6);
ReflexibleManiplex([ 5, 10 ], "(r2*r1*(r0 r2))^5,z1^2")
ReflexibleManiplex([ 6, 6 ], "(r2*r1*(r0 r2))^6,z1^2")
```

5.1.5 Bk2l (for IsInt,IsInt)

▷ `Bk2l(k, l)` (operation)

Returns: maniplex

Given integers k, l , gives the map $B(k, 2l)$.

Example

```
gap> Bk2l(4,5);
3-maniplex with 80 flags
```

5.1.6 Bk2lStar (for IsInt,IsInt)

▷ `Bk2lStar(k, l)` (operation)

Returns: maniplex

Given integers k, l , gives the map $B^*(k, 2l)$.

Example

```
gap> Bk2lStar(5,7);
3-maniplex with 140 flags
```

5.2 Operators on reflexible maps

5.2.1 Opp (for IsManiplex)

▷ `Opp(map)` (operation)

Returns: oppositeMap

Forms the opposite map of the maniplex map .

Example

```
gap> Opp(Bk2lStar(5,7));
Petrial(Dual(Petrial(3-maniplex with 140 flags)))
```

5.2.2 Hole (for IsManiplex, IsInt)

▷ `Hole(map, j)` (operation)

Returns: `newMap`

Given *map* and integer *j*, will form the map $H_j(\text{map})$. Note that if the action of $[r_0, (r_1 r_2)^{j-1} r_1, r_2]$ on the flags forms multiple orbits, then the resulting map will be on just one of those orbits.

Example

```
gap> Hole(Bk2lStar(5,7),2);
3-maniplex with 140 flags
```

5.3 Operations on Reflexible and Regular Maps

The goal would be to implement the operations in BerPisWil17, as well as those suggested in the conclusion.

Chapter 6

Constructions

6.1 Extensions, amalgamations, and quotients

6.1.1 UniversalPolytope (for IsInt)

- ▷ `UniversalPolytope(n)` (operation)
Returns: the universal polytope of rank n .

6.1.2 UniversalExtension (for IsManiplex)

- ▷ `UniversalExtension(M)` (operation)
Returns: the universal extension of M , i.e. the maniplex with facets isomorphic to M that covers all other maniplexes with facets isomorphic to M .
Currently only defined for reflexible maniplexes.

6.1.3 UniversalExtension (for IsManiplex, IsInt)

- ▷ `UniversalExtension(M , k)` (operation)
Returns: the universal extension of M with last entry of Schlafli symbol k . Currently only defined for reflexible maniplexes.

6.1.4 TrivialExtension (for IsManiplex)

- ▷ `TrivialExtension(M)` (operation)
Returns: the trivial extension of M , also known as $\{M, 2\}$.

6.1.5 FlatExtension (for IsManiplex, IsInt)

- ▷ `FlatExtension(M , k)` (operation)
Returns: the flat extension of M with last entry of Schlafli symbol k . (As defined in "Flat Extensions of Abstract Polytopes".)
Currently only defined for reflexible maniplexes.

6.1.6 Amalgamate (for IsManiplex, IsManiplex)

▷ `Amalgamate($M1$, $M2$)` (operation)

Returns: the amalgamation of $M1$ and $M2$. Implicitly assumes that $M1$ and $M2$ are compatible. Currently only defined for reflexible maniplexes.

6.1.7 Medial (for IsManiplex)

▷ `Medial(M)` (operation)

Returns: Given a 3-maniplex M , returns its medial.

6.2 Duality

6.2.1 Dual (for IsManiplex)

▷ `Dual(M)` (operation)

Returns: The maniplex that is dual to M .

6.2.2 IsSelfDual (for IsManiplex)

▷ `IsSelfDual(M)` (property)

Returns: Whether this maniplex is isomorphic to its dual. Also works for IsPoset objects.

6.2.3 IsInternallySelfDual (for IsReflexibleManiplex)

▷ `IsInternallySelfDual(M [, x])` (property)

Returns: true or false

Returns whether this maniplex is "internally self-dual", as defined by Cunningham and Mixer in [CM17] (<https://doi.org/10.11575/cdm.v12i2.62785>). That is, if M is self-dual, and the automorphism of `AutomorphismGroup(M)` that induces the isomorphism between M and its dual is an inner automorphism. If the optional group element x is given, then we first check whether x is a dualizing automorphism of M , and if not, then we search the whole automorphism group of M .

Example

```
gap> IsInternallySelfDual(Simplex(4));
true
gap> IsInternallySelfDual(ARP([4,4], "h2^6"));
false
gap> IsInternallySelfDual(ARP([4,4], "h2^5"));
true
gap> IsInternallySelfDual(Cube(3));
false
gap> M := InternallySelfDualPolyhedron2(10,1);;
gap> g := AutomorphismGroup(M);;
gap> IsInternallySelfDual(M, (g.1*g.3*g.2)^6);
true
```

6.2.4 IsExternallySelfDual (for IsReflexibleManiplex)

▷ `IsExternallySelfDual(M)` (property)

Returns: true or false

Returns whether this maniplex is "externally self-dual", as defined by Cunningham and Mixer in [CM17] (<https://doi.org/10.11575/cdm.v12i2.62785>). That is, if M is self-dual, and the automorphism of `AutomorphismGroup(M)` that induces the isomorphism between M and its dual is an outer automorphism.

Example

```
gap> IsExternallySelfDual(Simplex(4));
false
gap> IsExternallySelfDual(ARP([4,4], "h2^6"));
true
gap> IsExternallySelfDual(ARP([4,4], "h2^5"));
false
gap> IsExternallySelfDual(Cube(3));
false
```

6.2.5 Petrial (for IsManiplex)

▷ `Petrial(M)` (attribute)

Returns: The Petrial (Petrie dual) of M . Note that this is not necessarily a polytope, even if M is. When $\text{Rank}(M) > 3$, this is the "generalized Petrial" which essentially replaces r_{n-3} with $r_{n-3}r_{n-1}$ in the set of generators.

6.2.6 IsSelfPetrial (for IsManiplex)

▷ `IsSelfPetrial(M)` (property)

Returns: Whether this maniplex is isomorphic to its Petrial.

6.2.7 DirectDerivates (for IsManiplex)

▷ `DirectDerivates(M)` (operation)

Returns a list of the *direct derivates* of M , which are the images of M under duality and Petriality. A 3-maniplex has up to 6 direct derivates, and an n -maniplex with $n \geq 4$ has up to 8. If the option 'polytopal' is set, then only returns those direct derivates that are polytopal.

6.3 Products

6.3.1 Pyramid (for IsManiplex)

▷ `Pyramid(M)` (operation)

Returns the pyramid over M .

6.3.2 Pyramid (for IsInt)

▷ `Pyramid(k)` (operation)

Returns the pyramid over a k -gon.

6.3.3 Prism (for IsManiplex)

▷ `Prism(M)` (operation)

Returns the prism over M .

6.3.4 Prism (for IsInt)

▷ `Prism(k)` (operation)

Returns the prism over a k -gon.

6.3.5 Antiprism (for IsManiplex)

▷ `Antiprism(M)` (operation)

Returns the antiprism over M .

6.3.6 Antiprism (for IsInt)

▷ `Antiprism(k)` (operation)

Returns the antiprism over a k -gon.

6.3.7 JoinProduct (for IsManiplex, IsManiplex)

▷ `JoinProduct($M1$, $M2$)` (operation)

Returns: Maniplex

Given two maniplexes, this forms the join product. May give weird results if the maniplexes aren't faithfully represented by their posets.

6.3.8 CartesianProduct (for IsManiplex, IsManiplex)

▷ `CartesianProduct($M1$, $M2$)` (operation)

Returns: Maniplex

Given two maniplexes, this forms the cartesian product. May give weird results if the maniplexes aren't faithfully represented by their posets.

6.3.9 DirectSumOfManiplexes (for IsManiplex, IsManiplex)

▷ `DirectSumOfManiplexes($M1$, $M2$)` (operation)

Returns: Maniplex

Given two maniplexes, this forms the direct sum. May give weird results if the maniplexes aren't faithfully represented by their posets.

6.3.10 TopologicalProduct (for IsManiplex, IsManiplex)

▷ `TopologicalProduct($M1$, $M2$)` (operation)

Returns: Maniplex

Given two maniplexes, this forms the direct sum. May give weird results if the maniplexes aren't faithfully represented by their posets.

Chapter 7

Databases

7.1 Regular polyhedra

7.1.1 DegeneratePolyhedra

▷ `DegeneratePolyhedra(sizerange)` (function)

Returns all degenerate polyhedra (of type $\{2, q\}$ and $\{p, 2\}$) with sizes in *sizerange*. Also accepts a single integer *maxsize* as input to indicate a sizerange of $[1..maxsize]$.

7.1.2 FlatRegularPolyhedra

▷ `FlatRegularPolyhedra(sizerange)` (function)

Returns all nondegenerate flat regular polyhedra with sizes in *sizerange*. Also accepts a single integer *maxsize* as input to indicate a sizerange of $[1..maxsize]$. Currently supports a maxsize of 4000 or less.

7.1.3 RegularToroidalPolyhedra44

▷ `RegularToroidalPolyhedra44(sizerange)` (function)

Returns all regular toroidal polyhedra of type $\{4,4\}$ with sizes in *sizerange*. Also accepts a single integer *maxsize* as input to indicate a sizerange of $[1..maxsize]$.

7.1.4 RegularToroidalPolyhedra36

▷ `RegularToroidalPolyhedra36(sizerange)` (function)

Returns all regular toroidal polyhedra of type $\{3,6\}$ with sizes in *sizerange*. Also accepts a single integer *maxsize* as input to indicate a sizerange of $[1..maxsize]$.

7.1.5 SmallRegularPolyhedraFromFile

▷ `SmallRegularPolyhedraFromFile(sizerange)` (function)

Returns all regular polyhedra with sizes in *sizerange* flags that are stored separately in a file. These are polyhedra that are not part of one of several infinite families that are covered by the other generators. The return value of this function is unstable and may change as more infinite families of polyhedra are identified and written as separate generators.

7.1.6 SmallRegularPolyhedra

▷ SmallRegularPolyhedra(*sizerange*) (function)

Returns all regular polyhedra with sizes in *sizerange* flags. Currently supports a maxsize of 4000 or less. You can also set options "nondegenerate", "nonflat", and "nontoroidal".

Example

```
L1 := SmallRegularPolyhedra(500);;
L2 := SmallRegularPolyhedra(1000 : nondegenerate);;
L3 := SmallRegularPolyhedra(2000 : nondegenerate, nonflat);;
```

7.1.7 SmallDegenerateRegular4Polytopes

▷ SmallDegenerateRegular4Polytopes(*sizerange*) (function)

Returns all degenerate regular 4-polytopes with sizes in *sizerange* flags. Currently supports a maxsize of 8000 or less.

7.1.8 SmallRegular4Polytopes

▷ SmallRegular4Polytopes(*sizerange*) (function)

Returns all regular 4-polytopes with sizes in *sizerange* flags. Currently supports a maxsize of 4000 or less.

7.1.9 SmallChiralPolyhedra

▷ SmallChiralPolyhedra(*sizerange*) (function)

Returns all chiral polyhedra with sizes in *sizerange* flags. Currently supports a maxsize of 4000 or less.

7.1.10 SmallChiral4Polytopes

▷ SmallChiral4Polytopes(*sizerange*) (function)

Returns all chiral 4-polytopes with sizes in *sizerange* flags. Currently supports a maxsize of 4000 or less.

Chapter 8

Families of Polytopes

8.1 Classical Polytopes

8.1.1 Vertex

- ▷ `Vertex()` (operation)
Returns: the universal 0-polytope.

8.1.2 Edge

- ▷ `Edge()` (operation)
Returns: the universal 1-polytope.

8.1.3 Pgon (for IsInt)

- ▷ `Pgon(p)` (operation)
Returns: the p-gon.

8.1.4 Cube (for IsInt)

- ▷ `Cube(n)` (operation)
Returns: the n-cube.

8.1.5 HemiCube (for IsInt)

- ▷ `HemiCube(n)` (operation)
Returns: the n-hemi-cube.

8.1.6 CrossPolytope (for IsInt)

- ▷ `CrossPolytope(n)` (operation)
Returns: the n-cross-polytope.

8.1.7 HemiCrossPolytope (for IsInt)

- ▷ `HemiCrossPolytope(n)` (operation)
Returns: the *n*-hemi-cross-polytope.

8.1.8 Simplex (for IsInt)

- ▷ `Simplex(n)` (operation)
Returns: the *n*-simplex.

8.1.9 CubicTiling (for IsInt)

- ▷ `CubicTiling(n)` (operation)
Returns: the rank *n*+1 polytope; the tiling of E^n by *n*-cubes.

8.1.10 Dodecahedron

- ▷ `Dodecahedron()` (operation)
Returns: the dodecahedron, {5, 3}.

8.1.11 HemiDodecahedron

- ▷ `HemiDodecahedron()` (operation)
Returns: the hemi-dodecahedron, {5, 3}_5.

8.1.12 Icosahedron

- ▷ `Icosahedron()` (operation)
Returns: the icosahedron, {3, 5}.

8.1.13 HemiIcosahedron

- ▷ `HemiIcosahedron()` (operation)
Returns: the hemi-icosahedron, {3, 5}_5.

8.1.14 24Cell

- ▷ `24Cell()` (operation)
Returns: the 24-cell, {3, 4, 3}.

8.1.15 Hemi24Cell

- ▷ `Hemi24Cell()` (operation)
Returns: the hemi-24-cell, {3, 4, 3}_6.

8.1.16 120Cell

- ▷ `120Cell()` (operation)
Returns: the 120-cell, {5, 3, 3}.

8.1.17 Hemi120Cell

▷ `Hemi120Cell()` (operation)
Returns: the hemi-120-cell, {5, 3, 3}_15.

8.1.18 600Cell

▷ `600Cell()` (operation)
Returns: the 600-cell, {3, 3, 5}.

8.1.19 Hemi600Cell

▷ `Hemi600Cell()` (operation)
Returns: the hemi-600-cell, {3, 3, 5}_15.

8.1.20 BrucknerSphere

▷ `BrucknerSphere()` (operation)
Returns: Bruckner's sphere.

8.1.21 InternallySelfDualPolyhedron1 (for IsInt)

▷ `InternallySelfDualPolyhedron1(p)` (operation)
Returns: the internally self-dual polyhedron of type {p, p} described in Theorem 5.3 of [CM17] (<https://doi.org/10.11575/cdm.v12i2.62785>). p must be at least 7.

8.1.22 InternallySelfDualPolyhedron2 (for IsInt, IsInt)

▷ `InternallySelfDualPolyhedron2(p, k)` (operation)
Returns: the internally self-dual polyhedron of type {p, p} described in Theorem 5.8 of [CM17] (<https://doi.org/10.11575/cdm.v12i2.62785>). p must be even and at least 6, and k must be odd.

8.2 Flat and tight polytopes

8.2.1 FlatOrientablyRegularPolyhedron (for IsInt, IsInt, IsInt, IsInt)

▷ `FlatOrientablyRegularPolyhedron(p, q, i, j)` (operation)
Returns: the flat orientably regular polyhedron with automorphism group $[p, q] / (r_2 r_1 r_0 r_1 = (r_0 r_1)^i (r_1 r_2)^j)$.

This function validates the inputs to make sure that the polyhedron is well-defined. Use `FlatOrientablyRegularPolyhedronNC` if you do not want this validation.

8.2.2 FlatOrientablyRegularPolyhedraOfType (for IsList)

▷ `FlatOrientablyRegularPolyhedraOfType(sym)` (operation)
Returns: a list of all flat, orientably regular polyhedra with Schlafli symbol *sym*.

8.2.3 TightOrientablyRegularPolytopesOfType (for IsList)

▷ TightOrientablyRegularPolytopesOfType(*sym*) (operation)

Returns: a list of all tight, orientably regular polytopes with Schläfli symbol *sym*.

When *sym* has length 2, this just calls FlatOrientablyRegularPolyhedraOfType(*sym*).

8.3 Toroids

8.3.1 CubicalToroid (for IsInt,IsInt,IsInt)

▷ CubicalToroid(*s*, *k*, *n*) (operation)

Returns: IsManifold

Given IsInt triple *s*, *k*, *n*, will return the regular toroid $\{4, 3^{n-2}, 4\}_{\vec{s}}$ where $\vec{s} = (s^k, 0^{n-k})$.

Example

```
gap> m44:=CubicalToroid(3,2,2);;
gap> m44=ToroidalMap44([3,3]);
true
```

8.3.2 3343Toroid (for IsInt,IsInt)

▷ 3343Toroid(*s*, *k*) (operation)

Returns: IsManifold

Given IsInt pair *s*, *k*, will return the regular toroid $\{3, 3, 4, 3\}_{\vec{s}}$ where $\vec{s} = (s^k, 0^{n-k})$. Note that *k* must be 0 or 1.

8.3.3 24CellToroid (for IsInt,IsInt)

▷ 24CellToroid(*s*, *k*) (operation)

Returns: IsManifold

Given IsInt pair *s*, *k*, will return the regular toroid $\{3, 4, 3, 3\}_{\vec{s}}$ where $\vec{s} = (s^k, 0^{n-k})$. Note that *k* must be 0 or 1.

8.4 Uniform Polyhedra

8.4.1 Cuboctahedron

▷ Cuboctahedron() (operation)

Returns: manifold

Constructs the cuboctahedron.

8.4.2 TruncatedTetrahedron

▷ TruncatedTetrahedron() (operation)

Returns: manifold

Constructs the truncated tetrahedron.

8.4.3 TruncatedOctahedron

- ▷ `TruncatedOctahedron()` (operation)
Returns: maniplex
Constructs the truncated octahedron.

8.4.4 TruncatedCube

- ▷ `TruncatedCube()` (operation)
Returns: maniplex
Constructs the truncated octahedron.

8.4.5 Icosadodecahedron

- ▷ `Icosadodecahedron()` (operation)
Returns: maniplex
Constructs the icosadodecahedron.

8.4.6 TruncatedIcosahedron

- ▷ `TruncatedIcosahedron()` (operation)
Returns: maniplex
Constructs the truncated icosahedron.

8.4.7 SmallRhombicuboctahedron

- ▷ `SmallRhombicuboctahedron()` (operation)
Returns: maniplex
Constructs the small rhombicuboctahedron.

8.4.8 Pseudorhombicuboctahedron

- ▷ `Pseudorhombicuboctahedron()` (operation)
Returns: maniplex
Constructs the pseudorhombicuboctahedron.

8.4.9 SnubCube

- ▷ `SnubCube()` (operation)
Returns: maniplex
Constructs the snub cube.

8.4.10 SmallRhombicosidodecahedron

- ▷ `SmallRhombicosidodecahedron()` (operation)
Returns: maniplex
Constructs the small rhombicosidodecahedron.

8.4.11 GreatRhombicosidodecahedron

- ▷ GreatRhombicosidodecahedron() (operation)
 Returns: maniplex
 Constructs the great rhombicosidodecahedron.

8.4.12 SnubDodecahedron

- ▷ SnubDodecahedron() (operation)
 Returns: maniplex
 Constructs the small snub dodecahedron.

8.4.13 TruncatedDodecahedron

- ▷ TruncatedDodecahedron() (operation)
 Returns: maniplex
 Constructs the truncated dodecahedron.

8.4.14 GreatRhombicuboctahedron

- ▷ GreatRhombicuboctahedron() (operation)
 Returns: maniplex
 Constructs the great rhombicuboctahedron.

Chapter 9

Groups

9.1 Groups

9.1.1 AutomorphismGroup (for IsManiplex)

▷ `AutomorphismGroup(M)` (attribute)

Returns the automorphism group of M . This group is not guaranteed to be in any particular form.

9.1.2 AutomorphismGroupFpGroup (for IsManiplex)

▷ `AutomorphismGroupFpGroup(M)` (attribute)

Returns the automorphism group of M as a finitely presented group.

9.1.3 AutomorphismGroupPermGroup (for IsManiplex)

▷ `AutomorphismGroupPermGroup(M)` (attribute)

Returns the automorphism group of M as a permutation group.

9.1.4 AutomorphismGroupOnFlags (for IsManiplex)

▷ `AutomorphismGroupOnFlags(M)` (attribute)

Returns the automorphism group of M as a permutation group action on the flags of M .

9.1.5 ConnectionGroup (for IsManiplex)

▷ `ConnectionGroup(M)` (attribute)

Returns the connection group of M as a permutation group. We may eventually allow other types of connection groups. Synonym: `MonodromyGroup`

9.1.6 EvenConnectionGroup (for IsManiplex)

▷ `EvenConnectionGroup(M)` (attribute)

Returns the even-word subgroup of the connection group of M as a permutation group.

9.1.7 RotationGroup (for IsManiplex)

▷ `RotationGroup(M)` (attribute)

Returns the rotation group of M . This group is not guaranteed to be in any particular form.

9.1.8 ChiralityGroup (for IsRotaryManiplex)

▷ `ChiralityGroup(M)` (attribute)

Returns the chirality group of the rotary maniplex M . This is the kernel of the group epimorphism from the rotation group of M to the rotation group of its maximal reflexible quotient. In particular, the chirality group is trivial if and only if M is reflexible.

9.1.9 ExtraRelators (for IsReflexibleManiplex)

▷ `ExtraRelators(M)` (attribute)

For a reflexible maniplex M , returns the relators needed to define its automorphism group as a quotient of the string Coxeter group given by its Schläfli symbol. Not particularly robust at the moment.

9.1.10 ExtraRotRelators (for IsRotaryManiplex)

▷ `ExtraRotRelators(M)` (attribute)

For a reflexible maniplex M , returns the relators needed to define its rotation group as a quotient of the rotation group of a string Coxeter group given by its Schläfli symbol. Not particularly robust at the moment.

Chapter 10

Mixing of Maniplexes

10.1 Mixing of Maniplexes functions

10.1.1 Mix (for IsPermGroup, IsPermGroup)

▷ `Mix(permgroupe, permgroupe)` (operation)

Returns: `IsGroup` .

Given two (permutation) groups returns the mix of those groups. Note, also works with `FPgroups`.

Here we build the mix of the connection groups of a 3-cube and an edge.

Example

```
gap> g1:=ConnectionGroup(Cube(3));
<permutation group with 3 generators>
gap> g2:=ConnectionGroup(Edge());
Group([ (1,2) ])
gap> Mix(g1,g2);
<permutation group with 3 generators>
```

10.1.2 Mix (for IsFpGroup, IsFpGroup)

▷ `Mix(fpgroup, fpgroup)` (operation)

Returns the Mix of two Finitely Presented groups `gp` and `gq`.

10.1.3 Mix (for IsReflexibleManiplex, IsReflexibleManiplex)

▷ `Mix(maniplex, maniplex)` (operation)

Returns: `IsReflexibleManiplex` .

Given maniplexes returns the `IsReflexibleManiplex` from the mix of their connection groups

10.1.4 Mix (for IsManiplex, IsManiplex)

▷ `Mix(arg1, arg2)` (operation)

10.1.5 Comix (for IsFpGroup, IsFpGroup)

▷ `Comix(fpgroup, fpgroup)` (operation)

Returns the comix of two Finitely Presented groups *gp* and *gq*.

10.1.6 Comix (for IsReflexibleManiplex, IsReflexibleManiplex)

▷ `Comix(maniplex, maniplex)` (operation)

Returns: `IsReflexibleManiplex` .

Given maniplexes returns the `IsReflexibleManiplex` from the comix of their connection groups

10.1.7 CtoL (for IsInt,IsInt,IsInt,IsInt)

▷ `CtoL(int, int, int, int)` (operation)

Returns: `IsInteger` .

`CtoL` Returns an integer between 1 and $N*M$ associated with the pair $[a,b]$. `LtoC` Returns an ordered pair $[a,b]$ associated with the integer between 1 and $N*M$. a should range between 1 and N , and b should range between 1 and M . N is how many columns (x coordinates), M is how many rows (y coordinates) in a matrix. Functions are inverses.

10.1.8 FlagMix (for IsManiplex, IsManiplex)

▷ `FlagMix(permgrou, permgrou)` (operation)

Returns: `IsManiplex` .

Given two (permutation) groups *gp*, *gg* this returns the maniplex of the "flag" mix of two maniplexes with connection groups *gp* and *gq*.

Chapter 11

Properties

11.1 Orientability

11.1.1 IsOrientable (for IsManiplex)

- ▷ `IsOrientable(M)` (property)
Returns: true or false
A maniplex is orientable if its flag graph is bipartite.

11.1.2 IsIOrientable (for IsManiplex, IsList)

- ▷ `IsIOrientable(M, I)` (operation)

For a subset I of $\{0, \dots, n-1\}$, a maniplex is I -orientable if every closed path in its flag graph contains an even number of edges with colors in I .

11.1.3 IsVertexBipartite (for IsManiplex)

- ▷ `IsVertexBipartite(M)` (property)
Returns: true or false
A maniplex is vertex-bipartite if its 1-skeleton is bipartite. This is equivalent to being I -orientable for $I = \{0\}$.

11.1.4 IsFacetBipartite (for IsManiplex)

- ▷ `IsFacetBipartite(M)` (property)
Returns: true or false
A maniplex is facet-bipartite if the 1-skeleton of its dual is bipartite. This is equivalent to being I -orientable for $I = \{n-1\}$.

11.1.5 OrientableCover (for IsManiplex)

- ▷ `OrientableCover(M)` (attribute)
Returns the minimal *orientable cover* of the maniplex M .

11.1.6 IOrientableCover (for IsManiplex, IsList)

▷ IOrientableCover(M)

(operation)

Returns the minimal *I-orientable cover* of the maniplex M .

Chapter 12

Posets

12.1 Poset attributes

Posets have many properties we might be interested in. Here's a few.

12.1.1 MaximalChains (for IsPoset)

▷ `MaximalChains(poset)` (attribute)

Gives the list of maximal chains in a poset in terms of the elements of the poset. Synonyms are `FlagsList` and `Flags`. Tends to work faster (sometimes significantly) if the poset `HasPartialOrder`.

Synonym is `FlagsList`.

Example

```
gap> poset:=PosetFromManiplex(HemiCube(3));
A poset using the IsPosetOfFlags representation.
gap> MaximalChains(poset)[1];
[ An element of a poset made of flags, An element of a poset made of flags,
  An element of a poset made of flags, An element of a poset made of flags,
  An element of a poset made of flags ]
gap> List(last,x->RankInPoset(x,poset));
[ -1, 0, 1, 2, 3 ]
```

12.1.2 RankPoset (for IsPoset)

▷ `RankPoset(poset)` (attribute)

If the poset `IsP1`, ranks are assumed to run from -1 to n , and function will return n . If `IsP1(poset)=false`, ranks are assumed to run from 1 to n . In RAMP, at least currently, we are assuming that graded/ranked posets are bounded. Note that in general what you *actually* want to do is call `Rank(poset)`. The reason is that `Rank` will calculate the `RankPoset` if it isn't set, and then set and store the value in the poset.

12.1.3 ElementsList (for IsPoset)

▷ `ElementsList(poset)` (attribute)

Will recover the list of faces of the poset, format may depend on *type* of representation of poset.

- We also have `FacesList` and `Faces` as synonyms for this command.

12.1.4 OrderingFunction (for IsPoset)

▷ `OrderingFunction(poset)` (attribute)

`OrderingFunction` is an attribute of a poset which stores a function for ordering elements.

Example

```
gap> p:=PosetFromManiplex(Cube(2));;
gap> p3:=PosetFromElements(RankedFaceListOfPoset(p),PairCompareFlagsList);;
gap> f3:=FacesList(p3);;
gap> OrderingFunction(p3)(ElementObject(f3[2]),ElementObject(f3[1]));
true
gap> OrderingFunction(p3)(ElementObject(f3[1]),ElementObject(f3[2]));
false
```

12.1.5 IsFlaggable (for IsPoset)

▷ `IsFlaggable(poset)` (property)

Returns: true or false

Checks or creates the value of the attribute `IsFlaggable` for an `IsPoset`. Point here is to see if the structure of the poset is sufficient to determine the flag graph. For `IsPosetOfFlags` this is another way of saying that the intersection of the faces (thought of as collections of flags) containing a flag is that selfsame flag. (Might be equivalent to prepolytopal... but Gabe was tired and Gordon hasn't bothered to think about it yet.) Now also works with generic poset element types (not just `IsPosetOfFlags`).

12.1.6 IsAtomic (for IsPoset)

▷ `IsAtomic(poset)` (property)

Returns: true or false

This checks whether or not the faces of an `IsP1` poset may be described uniquely in terms of the posets atoms.

The terminology as used here is approximately that of Ziegler's *Lectures on Polytopes* where a lattice is atomic if every element is the join of atoms.

Example

```
gap> po:=BinaryRelationOnPoints([[2,3],[4,5],[4,5],[6],[6],[ ]]);;
gap> po:=ReflexiveClosureBinaryRelation(TransitiveClosureBinaryRelation(po));;
gap> p:=PosetFromPartialOrder(po);; IsAtomic(p);
false
gap> p2:=PosetFromManiplex(Cube(3));; IsAtomic(p2);
true
```

12.1.7 PartialOrder (for IsPoset)

▷ `PartialOrder(poset)` (attribute)

Returns: partial order

`HasPartialOrder` Checks if `poset` has a declared partial order (binary relation). `SetPartialOrder` assigns a partial order to the `poset`. In many cases, `PartialOrder` is able to compute one from structural information.

12.1.8 Lattices

▷ `IsLattice(poset)` (property)

▷ `IsAllMeets(arg)` (property)

▷ `IsAllJoins(arg)` (property)

Returns: IsBool

`IsLattice` determines whether a poset is a lattice or not. `IsAllMeets` determines whether all meets in a poset are unique. `IsAllJoins` determines whether all joins in a poset are unique.

Example

```
gap> poset:=PosetFromManiplex(Cube(3));;
gap> IsLattice(poset);
true
gap> bad:=PosetFromManiplex(HemiCube(3));;
gap> IsLattice(bad);
fail
```

Here's a simple example of when a lattice isn't atomic.

Example

```
gap> l:=[[2,3,4],[5,7],[5,6],[6,7],[8],[8],[8,9],[10],[10],[]];;
gap> b:=BinaryRelationOnPoints(l);;
po:=ReflexiveClosureBinaryRelation(TransitiveClosureBinaryRelation(b));;
gap> poset:=PosetFromPartialOrder(po);;
gap> IsLattice(poset);
true
gap> IsAtomic(poset);
false
```

12.1.9 ListIsP1Poset (for IsList)

▷ `ListIsP1Poset(list)` (operation)

Returns: true or false

Given `list`, comprised of sublists of faces ordered by rank, each face listing the flags on the face, this function will tell you if the list corresponds to a P1 poset or not.

12.1.10 IsP1 (for IsPoset)

▷ `IsP1(poset)` (property)

Returns: true or false

Determines whether a poset has property P1 from ARP.

Example

```
gap> p:=PosetFromElements(AllSubgroups(AlternatingGroup(4)),IsSubgroup);
A poset using the IsPosetOfIndices representation
gap> IsP1(p);
true
gap> p2:=PosetFromFaceListOfFlags([[1],[2]],[[1,2]]]);
A poset using the IsPosetOfFlags representation with 3 faces.
gap> IsP1(p2);
false
```

12.1.11 IsP2 (for IsPoset)▷ IsP2(*poset*)

(property)

Returns: true or false

Determines whether a poset has property P2 from ARP.

Example

```
gap> poset:=PosetFromManiplex(HemiCube(3));
gap> IsP2(poset);
true
```

Another nice example

Example

```
gap> g:=AlternatingGroup(4);; a:=AllSubgroups(g);; poset:=PosetFromElements(a,IsSubgroup);
A poset using the IsPosetOfIndices representation
gap> IsP2(poset);
false
```

12.1.12 IsP3 (for IsPoset)▷ IsP3(*poset*)

(property)

Returns: true or false

Determines whether a poset is strongly flag connected (property P3' from ARP). May also be called with command IsStronglyFlagConnected. If you are not working with a pre-polytope, expect this to take a LONG time.

Helper for IsP3

12.1.13 IsFlagConnected (for IsPoset)▷ IsFlagConnected(*poset*)

(property)

Returns: true or false

Determines whether a poset is flag connected.

12.1.14 IsP4 (for IsPoset)▷ IsP4(*poset*)

(property)

Returns: true or false

Determines whether a poset satisfies the diamond condition. May also be invoked using IsDiamondCondition.

12.1.15 IsPolytope (for IsPoset)

▷ `IsPolytope(poset)` (property)

Returns: true or false

Determines whether a poset is an abstract polytope.

Example

```
gap> poset:=PosetFromManiplex(Cube(3));
A poset using the IsPosetOfFlags representation with 28 faces.
gap> IsPolytope(poset);
true
gap> KnownPropertiesOfObject(poset);
[ "IsP1", "IsP2", "IsP3", "IsP4", "IsPolytope" ]
gap> poset2:=PosetFromElements(AllSubgroups(AlternatingGroup(4)),IsSubgroup);
A poset using the IsPosetOfIndices representation
gap> IsPolytope(poset2);
false
gap> KnownPropertiesOfObject(poset2);
[ "IsP1", "IsP2", "IsPolytope" ]
```

12.1.16 IsPrePolytope (for IsPoset)

▷ `IsPrePolytope(poset)` (property)

Returns: true or false

Determines whether a poset is an abstract pre-polytope.

12.1.17 IsSelfDual (for IsPoset)

▷ `IsSelfDual(poset)` (property)

Returns: IsBool

Determines whether a poset is self dual.

Example

```
gap> poset:=PosetFromManiplex(Simplex(5));
A poset using the IsPosetOfFlags representation.
gap> IsSelfDual(poset);
true
gap> poset2:=PosetFromManiplex(PyramidOver(Cube(3)));
gap> IsSelfDual(poset2);
false
```

12.2 Poset constructors

I'm in the process of reconciling all of this, but there are going to be a number of ways to define a poset:

- As an `IsPosetOfFlags`, where the underlying description is an ordered list of length $n + 2$. Each of the $n + 2$ list elements is a list of faces, and the assumption is that these are the faces of rank $i - 2$, where i is the index in the master list (e.g., `1 [1] [1]` would usually correspond to the unique -1 face of a polytope – and there won't be an `1 [1] [2]`). Each face is then a list of the flags incident with that face.

- As an `IsPosetOfIndices`, where the underlying description is a binary relation on a set of indices, which correspond to labels for the elements of the poset.
- If the poset is known to be atomic, then by a description of the faces in terms of the atoms... usually we'll just need the list of the elements of maximal rank, from which all other elements may be obtained.
- As an `IsPosetOfElements`, where the elements could be anything, and we have a known function determining the partial order on the elements.

Usually, we assume that the poset will have a natural rank function on it. More information on the poset attributes that are important in the study of abstract polytopes and maniplexes is available in [MS02], [MPW14], and [Wil12].

12.2.1 PosetFromFaceListOfFlags (for IsList)

▷ `PosetFromFaceListOfFlags(list)` (operation)

Returns: `IsPosetOfFlags`.

Given a *list* of lists of faces in increasing rank, where each face is described by the incident flags, gives you a `IsPosetOfFlags` object back. Posets constructed this way are assumed to be `IsP1` and `IsP2`.

Here we have a poset using the `IsPosetOfFlags` description for the triangle.

Example

```
gap> poset:=PosetFromFaceListOfFlags([[1,2,3,4,5,6]], [[1,2],[3,6],[4,5]], [[1,4],[2,3],[5,6]], [[1,2,3,4,5,6]]);
A poset using the IsPosetOfFlags representation with 8 faces.
gap> FaceListOfPoset(poset);
[[ [ 1, 2, 3, 4, 5, 6 ] ], [ [ 1, 2 ], [ 3, 6 ], [ 4, 5 ] ], [ [ 1, 4 ], [ 2, 3 ] ], [ [ 5, 6 ] ], [ [ 1, 2, 3, 4, 5, 6 ] ]]
```

12.2.2 PosetFromConnectionGroup (for IsPermGroup)

▷ `PosetFromConnectionGroup(g)` (operation)

Returns: `IsPosetOfFlags` with `IsP1=true`.

Given a group, returns a poset with an internal representation as a list of faces ordered by rank, where each face is represented as a list of the flags it contains. Note that this function includes the minimal (empty) face and the maximal face of the maniplex. Note that the *i*-faces correspond to the *i* + 1 item in the list because of how GAP indexes lists.

Example

```
gap> g:=Group([(1,4)(2,3)(5,6),(1,2)(3,6)(4,5)]);
Group([ (1,4)(2,3)(5,6), (1,2)(3,6)(4,5) ])
gap> PosetFromConnectionGroup(g);
A poset using the IsPosetOfFlags representation with 8 faces.
```

12.2.3 PosetFromManiplex (for IsManiplex)

▷ `PosetFromManiplex(mani)` (operation)

Returns: `IsPosetOfFlags`

Given a maniplex, returns a poset of the maniplex with an internal representation as a list of faces ordered by rank, where each face is represented as a list of the flags it contains. Note that this function does include the minimal (empty) face and the maximal face of the maniplex. Note that the *i*-faces correspond to the *i* + 1 item in the list because of how GAP indexes lists.

Example

```
gap> p:=HemiCube(3);
Regular 3-polytope of type [ 4, 3 ] with 24 flags
gap> PosetFromManiplex(p);
A poset using the IsPosetOfFlags representation with 15 faces.
```

12.2.4 PosetFromPartialOrder (for IsBinaryRelation)

▷ PosetFromPartialOrder(*partialOrder*) (operation)

Returns: IsPosetOfIndices

Given a partial order on a finite set of size n , this function will create a partial order on $[1..n]$.

Example

```
gap> l:=List([[1,1],[1,2],[1,3],[1,4],[2,4],[2,2],[3,3],[4,4]],x->Tuple(x));
gap> r:=BinaryRelationByElements(Domain([1..4]), l);
<general mapping: Domain([ 1 .. 4 ]) -> Domain([ 1 .. 4 ]) >
gap> poset:=PosetFromPartialOrder(r);
A poset using the IsPosetOfIndices representation
gap> h:=HasseDiagramBinaryRelation(PartialOrder(poset));
<general mapping: Domain([ 1 .. 4 ]) -> Domain([ 1 .. 4 ]) >
gap> Successors(h);
[ [ 2, 3 ], [ 4 ], [ ], [ ] ]
```

Note that what we've accomplished here is the poset containing the elements 1, 2, 3, 4 with partial order determined by whether the first element divides the second. The essential information about the poset can be obtained from the Hasse diagram.

12.2.5 PosetFromAtomicList (for IsList)

▷ PosetFromAtomicList(*list*) (operation)

Returns: IsPosetOfAtoms

Given a list of elements, where each element is given as a list of atoms, this function will construct the corresponding poset. Note that this will construct any implied faces as well (i.e., all possible intersections of the listed faces).

Example

```
gap> list:=[[1,2,3],[1,2,4],[1,3,4],[2,3,4]];
[ [ 1, 2, 3 ], [ 1, 2, 4 ], [ 1, 3, 4 ], [ 2, 3, 4 ] ]
gap> poset:=PosetFromAtomicList(list);
gap> List(Faces(poset), AtomList);
[ [ ], [ 1 ], [ 1, 2 ], [ 1, 2, 3 ], [ 1, 2, 4 ], [ 1, 3 ], [ 1, 3, 4 ], [ 1, 4 ], [ 2 ], [ 2, 3 ], [ 2, 3, 4 ], [ 2, 4 ], [ 3 ], [ 3, 4 ], [ 4 ], [ 1..4 ] ]
```

12.2.6 PosetFromElements (for IsList, IsFunction)

▷ PosetFromElements(*list_of_faces*, *func*) (operation)

Returns: IsPosetOfElements

This is for gathering elements with a known ordering *func* on two variables into a poset. Also note, the expectation is that *func* behaves similarly to IsSubset, i.e., *func* (x,y)=true means y is less than x in the order.

Example

```

gap> g:=SymmetricGroup(3);
Sym( [ 1 .. 3 ] )
gap> asg:=AllSubgroups(g);
[ Group(()), Group([ (2,3) ]), Group([ (1,2) ]), Group([ (1,3) ]), Group([ (1,2,3) ]), Group([ (1,3,2) ])]
gap> poset:=PosetFromElements(asg,IsSubgroup);
A poset on 6 elements using the IsPosetOfIndices representation.
gap> HasseDiagramBinaryRelation(PartialOrder(poset));
<general mapping: Domain([ 1 .. 6 ]) -> Domain([ 1 .. 6 ]) >
gap> Successors(last);
[ [ 2, 3, 4, 5 ], [ 6 ], [ 6 ], [ 6 ], [ 6 ], [ ] ]
gap> List( ElementsList(poset){[2,6]}, ElementObject);
[ Group([ (2,3) ]), Group([ (1,2,3), (2,3) ]) ]

```

12.2.7 PosetFromSuccessorList (for IsList)

▷ PosetFromSuccessorList(successorsList) (operation)

Returns: poset

Given a list of immediate successors, will construct the poset. A valid list of successors is of the form $[[2,3], [3], []]$ where the i -th entry is a list of elements that are greater than the i -th element in the partial order that determines the poset. If the given list isn't reflexive and transitive, this function will induce those properties from the given list of successors.

Example

```

gap> p:=PosetFromManiplex(HemiCube(3));;
gap> Print(p);
PosetFromSuccessorList([ [ 2, 3, 4, 5 ], [ 6, 7, 9 ], [ 6, 8, 11 ], [ 7, 10, 11 ],
[ 8, 9, 10 ], [ 1, 2, 13 ], [ 12, 14 ], [ 12, 14 ], [ 13, 14 ], [ 12, 13 ], [ 13, 14 ],
[ 15 ], [ 15 ], [ 15 ], [ ] ]);

```

12.2.8 Helper functions for special partial orders

▷ PairCompareFlagsList(list1, list2) (operation)

▷ PairCompareAtomsList(list1, list2) (operation)

Returns: true or false

The functions PairCompareFlagsList and PairCompareAtomsList are used in poset construction. Function assumes $list1$ and $list2$ are of the form $[listOfFlags, i]$ where $listOfFlags$ is a list of flags in the face and i is the rank of the face. Allows comparison of HasFlagList elements. Function assumes $list1$ and $list2$ are of the form $[listOfAtoms, int]$ where $listOfAtoms$ is a list of flags in the face and int is the rank of the face. Allows comparison of HasAtomList elements.

12.2.9 DualPoset (for IsPoset)

▷ DualPoset(poset) (operation)

Returns: dual

Given a $poset$, will construct a poset isomorphic to the dual of $poset$.

Example

```

gap> p:=PosetFromManiplex(Cube(3));; c:=PosetFromManiplex(CrossPolytope(3));;
gap> IsIsomorphicPoset(DualPoset(DualPoset(p)),p);
true

```



```
gap> IsIsomorphicPoset(DualPoset(p),c);
true
gap> IsIsomorphicPoset(DualPoset(p),p);
false
```

12.2.10 Section (for IsFace, IsFace, IsPoset)

▷ `Section(face1, face2, poset)`

(operation)

Returns: section

Constructs the section of the *poset* *face1/face2*.

Example

```
gap> poset:=PosetFromManiplex(PyramidOver(Cube(2))));
gap> faces:=Faces(poset);;List(faces,x->RankInPoset(x,poset));
[ -1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 3 ]
gap> IsIsomorphicPoset(Section(faces[15],faces[1],poset),PosetFromManiplex(Simplex(2)));
true
gap> IsIsomorphicPoset(Section(faces[16],faces[1],poset),PosetFromManiplex(Cube(2)));
true
gap> IsIsomorphicPoset(Section(faces[20],faces[2],poset),PosetFromManiplex(Cube(2)));
true
```

12.2.11 Cleaving polytopes

▷ `Cleave(polytope, k)`

(operation)

▷ `PartiallyCleave(arg1, arg2)`

(operation)

Returns: cleavedPolytope

Given a *polytope* \mathcal{P} , and an integer k , `Cleave(polytope,k)` will construct the k^{th} -cleaved polytope of \mathcal{P} . Cleaved polytopes were introduced by Daniel Pellicer [Pel18] (<https://doi.org/10.1007/s00493-016-3518-3>). Given a *polytope* \mathcal{P} , and an integer k , `PartiallyCleave(polytope,k)` will construct the k^{th} -partially cleaved polytope of \mathcal{P} .

12.3 Element Constructors

12.3.1 PosetElementWithOrder (for IsObject,IsFunction)

▷ `PosetElementWithOrder(obj, func)`

(operation)

Returns: IsFace

Creates a face with *obj* and ordering function *func*. Note that by convention *func(a,b)* should return true when $b \leq a$.

12.3.2 PosetElementFromListOfFlags (for IsList,IsPoset,IsInt)

▷ `PosetElementFromListOfFlags(list, poset, n)`

(operation)

Returns: IsPosetElement

This is used to create a face of rank *n* from a *list* of flags of *poset*.

12.3.3 PosetElementFromAtomList (for IsList)

▷ PosetElementFromAtomList(*list*) (operation)

Returns: IsFace

Creates a face with *list* of atoms. If you wish to assign ranks or membership in a poset, you must do this separately.

12.3.4 PosetElementFromIndex (for IsObject)

▷ PosetElementFromIndex(*obj*) (operation)

Returns: IsFace

Creates a face with index *obj* at rank *n*.

12.3.5 PosetElementWithPartialOrder (for IsObject, IsBinaryRelation)

▷ PosetElementWithPartialOrder(*obj*, *order*) (operation)

Returns: IsFace

Creates a face with index *obj* and BinaryRelation *order* on *obj*. Function does not check to make sure *order* has *obj* in its domain.

12.3.6 RanksInPosets (for IsPosetElement)

▷ RanksInPosets(*posetelement*) (attribute)

Returns: list

Gives the list of posets *posetelement* is in, and the corresponding rank (if available) as a list of ordered pairs of the form [poset,rank]. #! Note that this attribute is mutable, so if you modify it you may break things.

12.3.7 AddRanksInPosets (for IsPosetElement,IsPoset,IsInt)

▷ AddRanksInPosets(*posetelement*, *poset*, *int*) (operation)

Returns: null

Adds an entry in the list of RanksInPosets for *posetelement* corresponding to *poset* with assigned rank *int*.

12.3.8 FlagList (for IsPosetElement)

▷ FlagList(*posetelement*, {*face*}) (attribute)

Returns: list

Description of *posetelement* n as a list of incident flags (when present).

12.3.9 AtomList (for IsPosetElement)

▷ AtomList(*posetelement*, {*face*}) (attribute)

Returns: list

Description of *posetelement* n as a list of atoms (when present).

12.4 Element operations

12.4.1 RankInPoset (for IsPosetElement, IsPoset)

▷ RankInPoset([*face*, *poset*]) (operation)

Returns: IsInt

Given an element *face* and a poset *poset* to which it belongs, will give you the rank of *face* in *poset*.

12.4.2 IsSubface (for IsFace, IsFace, IsPoset)

▷ IsSubface([*face1*, *face2*, *poset*]) (operation)

Returns: true or false

face1 and *face2* are IsFace or IsPosetElement. IsSubface will check to see if *face2* is a subface of *face1* in *poset*. You may drop the argument *poset* if the faces only belong to one poset in common. Warning: if the elements are made up of atoms, then IsSubface doesn't need to know what poset you are working with.

12.4.3 IsEqualFaces (for IsFace, IsFace, IsPoset)

▷ IsEqualFaces(*arg1*, *arg2*, *arg3*) (operation)

Determines whether two faces are equal in a poset. Note that $\backslash =$ tests whether they are the identical object or not.

12.4.4 AreIncidentElements (for IsObject, IsObject)

▷ AreIncidentElements(*object1*, *object2*) (operation)

Returns: true or false

Given two poset elements, will tell you if they are incident.

- Synonym function: AreIncidentFaces.

12.4.5 Meet (for IsFace, IsFace, IsPoset)

▷ Meet(*face1*, *face2*, *poset*) (operation)

Returns: meet

Finds (when possible) the meet of two elements in a poset.

12.4.6 Join (for IsFace, IsFace, IsPoset)

▷ Join(*face1*, *face2*, *poset*) (operation)

Returns: meet

Finds (when possible) the join of two elements in a poset.

12.5 Working with posets

12.5.1 IsIsomorphicPoset (for IsPoset,IsPoset)

▷ IsIsomorphicPoset(*poset1*, *poset2*) (operation)

Returns: true or false

Determines whether *poset1* and *poset2* are isomorphic by checking to see if their Hasse diagrams are isomorphic.

Example

```
gap> IsIsomorphicPoset( PosetFromManiplex( PyramidOver( Cube(3) ) ), PosetFromManiplex( PrismOver( Cube(3) ) ) )
false
gap> IsIsomorphicPoset( PosetFromManiplex( PyramidOver( Cube(3) ) ), PosetFromManiplex( PyramidOver( Cube(3) ) ) )
true
```

12.5.2 PosetIsomorphism (for IsPoset,IsPoset)

▷ PosetIsomorphism(*poset1*, *poset2*) (operation)

Returns: map on face indices

When *poset1* and *poset2* are isomorphic, will give you a map from the faces of *poset1* to the faces of *poset2*.

12.5.3 FlagsAsFlagListFaces (for IsPoset)

▷ FlagsAsFlagListFaces(*poset*) (operation)

Returns: IsList

Given a *poset*, this will give you a version of the list of flags in terms of the proper faces described in the *poset*; i.e., this gives a list of flags where each face is described in terms of its (enumerated) list of incident flags. Note that the flag list does not include the minimal face or the maximal face if the *poset* is P2.

12.5.4 RankedFaceListOfPoset (for IsPoset)

▷ RankedFaceListOfPoset(*IsPosetOfFlags*) (operation)

Returns: list

Gives a list of [*face*,*rank*] pairs for all the faces of *poset*. Assumptions here are that faces are lists of incident flags.

12.5.5 AdjacentFlag (for IsPosetOfFlags,IsList,IsInt)

▷ AdjacentFlag(*poset*, *flag*, *i*) (operation)

Returns: flag(s)

Given a *poset*, a *flag*, and a *rank*, this function will give you the *i*-adjacent flag. Note that adjacencies are listed from ranks 0 to one less than the dimension. You can replace *flag* with the integer corresponding to that flag. Appending true to the arguments will give the position of the flag instead of its description from FlagsAsFlagListFaces.

12.5.6 AdjacentFlags (for IsPoset,IsList,IsInt)

▷ AdjacentFlags(*poset*, *flagaslistoffaces*, *adjacencyrank*) (operation)

If your poset isn't P4, there may be multiple adjacent maximal chains at a given rank. This function handles that case. May substitute IsInt for *flagaslistoffaces* corresponding to position of flag in list of maximal chains.

12.5.7 EqualChains (for IsList,IsList)

▷ EqualChains(*flag1*, *flag2*) (operation)

Determines whether two chains are equal.

12.5.8 ConnectionGeneratorOfPoset (for IsPoset,IsInt)

▷ ConnectionGeneratorOfPoset(*poset*, *i*) (operation)

Returns: A permutation on the flags.

Given a *poset* and an integer *i*, this function will give you the associated permutation for the rank *i*-connection.

12.5.9 ConnectionGroup (for IsPoset)

▷ ConnectionGroup(*poset*) (attribute)

Returns: IsPermGroup

Given a *poset* that is IsPrePolytope, this function will give you the connection group.

12.5.10 AutomorphismGroup (for IsPoset)

▷ AutomorphismGroup(*poset*) (attribute)

Given a *poset*, gives the automorphism group of the poset as an action on the maximal chains.

12.5.11 AutomorphismGroupOnElements (for IsPoset)

▷ AutomorphismGroupOnElements(*poset*) (attribute)

Given a *poset*, gives the automorphism group of the poset as an action on the elements.

12.5.12 FaceListOfPoset (for IsPoset)

▷ FaceListOfPoset(*poset*) (operation)

Returns: list

Gives a list of faces collected into lists ordered by increasing rank. Suitable as input for PosetFromFaceListOfFlags. Argument must be IsPosetOfFlags.

12.5.13 RankPosetElements (for IsPoset)

▷ RankPosetElements(*poset*) (operation)

Assigns to each face of a poset (when possible) the rank of the element in the poset.

12.5.14 FacesByRankOfPoset (for IsPoset)

▷ FacesByRankOfPoset(*poset*) (operation)

Returns: list

Gives lists of faces ordered by rank. Also sets the rank for each of the faces.

12.5.15 HasseDiagramOfPoset (for IsPoset)

▷ HasseDiagramOfPoset(*poset*) (operation)

Returns: directed graph

12.5.16 AsPosetOfAtoms (for IsPoset)

▷ AsPosetOfAtoms(*poset*) (operation)

Returns: posetFromAtoms

If *poset* is an IsP1 poset admits a description of its elements in terms of its atoms, this function will construct an isomorphic poset whose faces are described using PosetFromAtomList.

Example

```
gap> poset:=PosetFromManiplex(Cube(2));;
gap> p2:=AsPosetOfAtoms(poset);
A poset on 10 elements using the IsPosetOfIndices representation.
gap> IsIsomorphicPoset(poset,p2);
true
```

12.5.17 Max/min faces

▷ MinFace(*poset*) (operation)

▷ MaxFace(*arg*) (operation)

Returns: face

Gives the minimal/maximal face of a *poset* when it IsP1 and IsP2.

Chapter 13

Products of Posets and Digraphs

This uses the work of Gleason and Hubard.

13.1 Construction methods

The products documented in this section were defined by Gleason and Hubard in [GH18] (<https://doi.org/10.1016/j.jcta.2018.02.002>).

13.1.1 JoinProduct (for IsPoset,IsPoset)

▷ JoinProduct(*poset1*, *poset2*) (operation)

Returns: poset

Given two posets, this forms the join product. If given two partial orders, returns the join product of the partial orders. If given two maniplexes, returns the join product of the maniplexes.

Example

```
gap> p:=PosetFromManiplex(Cube(2));
A poset
gap> rel:=BinaryRelationOnPoints([[1,2],[2]]);
Binary Relation on 2 points
gap> p1:=PosetFromPartialOrder(rel);
A poset using the IsPosetOfIndices representation
gap> j:=JoinProduct(p,p1);
A poset using the IsPosetOfIndices representation
gap> IsIsomorphicPoset(j,PosetFromManiplex(PyramidOver(Cube(2))));
true
```

13.1.2 CartesianProduct (for IsPoset,IsPoset)

▷ CartesianProduct(*polytope1*, *polytope2*) (operation)

Returns: polytope

Given two polytopes, forms the cartesian product of the polytopes. Should also work if you give it any two posets. If given two maniplexes, returns the join product of the maniplexes.

Example

```
gap> p1:=PosetFromManiplex(Edge());
A poset
```

```
gap> p2:=PosetFromManiplex(Simplex(2));
A poset
gap> c:=CartesianProduct(p1,p2);
A poset using the IsPosetOfIndices representation
gap> IsIsomorphicPoset(c,PosetFromManiplex(PrismOver(Simplex(2))));
true
```

13.1.3 DirectSumOfPosets (for IsPoset,IsPoset)

▷ `DirectSumOfPosets(polytope1, polytope2)` (operation)

Returns: polytope

Given two polytopes, forms the direct sum of the polytopes.

Example

```
gap> p1:=PosetFromManiplex(Cube(2));;p2:=PosetFromManiplex(Edge());;
gap> ds:=DirectSumOfPosets(p1,p2);
A poset using the IsPosetOfIndices representation.
gap> IsIsomorphicPoset(ds,PosetFromManiplex(CrossPolytope(3)));
true
```

13.1.4 TopologicalProduct (for IsPoset,IsPoset)

▷ `TopologicalProduct(polytope1, polytope2)` (operation)

Returns: polytope

Given two polytopes, forms the topological product of the polytopes. If given two maniplexes, returns the join product of the maniplexes.

Here we demonstrate that the topological product (as expected) when taking the product of a triangle with itself gives us the torus $\{4,4\}_{(3,0)}$ with 72 flags.

Example

```
gap> p:=PosetFromManiplex(Pgon(3));
A poset using the IsPosetOfFlags representation.
gap> tp:=TopologicalProduct(p,p);
A poset using the IsPosetOfIndices representation.
gap> s0 := (5,6);;
gap> s1 := (1,2)(3,5)(4,6);;
gap> s2 := (2,3);;
gap> poly := Group([s0,s1,s2]);;
gap> torus:=PosetFromManiplex(ReflexibleManiplex(poly));
A poset using the IsPosetOfFlags representation.
gap> IsIsomorphicPoset(p,tp);
false
gap> IsIsomorphicPoset(torus,tp);
true
```

13.1.5 Antiprism (for IsPoset)

▷ `Antiprism(polytope)` (operation)

Returns: poset

Given a `polytope` (actually, should work for any poset), will return the antiprism of the `polytope` (poset). If given two maniplexes, returns the join product of the maniplexes.

Example

```
gap> p:=PosetFromManiplex(Pgon(3));;  
gap> a:=Antiprism(p);;  
gap> IsIsomorphicPoset(a,PosetFromManiplex(CrossPolytope(3)));  
true  
gap> p:=PosetFromManiplex(Pgon(4));;a:=Antiprism(p);;  
gap> d:=DualPoset(p);;ad:=Antiprism(d);;  
gap> IsIsomorphicPoset(a,ad);  
true
```

Chapter 14

Comparing maniplexes

14.1 Quotients and covers

14.1.1 IsQuotient (for IsManiplex, IsManiplex)

▷ `IsQuotient($M1$, $M2$)` (operation)

Returns whether $M2$ is a quotient of $M1$.

14.1.2 IsQuotient (for IsSggi, IsSggi)

▷ `IsQuotient(g , h)` (operation)

Returns whether h is a quotient of g . That is, whether there is a homomorphism sending each generator of g to the corresponding generator of h .

14.1.3 IsCover (for IsManiplex, IsManiplex)

▷ `IsCover($M1$, $M2$)` (operation)

Returns whether $M2$ is a cover of $M1$.

14.1.4 IsIsomorphicManiplex (for IsManiplex, IsManiplex)

▷ `IsIsomorphicManiplex($M1$, $M2$)` (operation)

Returns whether $M1$ is isomorphic to $M2$.

14.1.5 SmallestRegularCover (for IsManiplex)

▷ `SmallestRegularCover(M)` (attribute)

Returns the smallest regular cover of M , which is the maniplex whose automorphism group is the connection group of M .

14.1.6 QuotientManiplex (for IsReflexibleManiplex, IsString)

▷ `QuotientManiplex(M, relStr)` (operation)

Given a reflexible maniplex M , generates the subgroup S of `AutomorphismGroup(M)` given by `relStr`, and returns the quotient maniplex M / S . For example, `QuotientManiplex(CubicTiling(2), "(r0 r1 r2 r1)^5, (r1 r0 r1 r2)^2")` returns the toroidal map $\{4,4\}_{\{(5,0),(0,2)\}}$. You can also input this as `CubicTiling(2) / "(r0 r1 r2 r1)^5, (r1 r0 r1 r2)^2"`.

14.1.7 ReflexibleQuotientManiplex (for IsManiplex, IsList)

▷ `ReflexibleQuotientManiplex(M, rels)` (operation)

Given a reflexible maniplex M , generates the normal closure N of the subgroup S of `AutomorphismGroup(M)` given by `relStr`, and returns the quotient maniplex M / N , which will be reflexible. For example, `QuotientManiplex(CubicTiling(2), "(r0 r1 r2 r1)^5, (r1 r0 r1 r2)^2")` returns the toroidal map $\{4,4\}_{\{(1,0)\}}$, because the normal closure of the group generated by $(r0 r1 r2 r1)^5$ and $(r1 r0 r1 r2)^2$ is the group generated by $r0 r1 r2 r1$ and $r1 r0 r1 r2$.

14.1.8 QuotientSggi (for IsGroup, IsList)

▷ `QuotientSggi(g, rels)` (operation)

Returns: the quotient of g by `rels`, which is either a list of Tietze words or a string of relations that is parsed by `ParseStringCRel`s.

Example

```
gap> g := UniversalSggi(3);
<fp group of size infinity on the generators [ r0, r1, r2 ]>
gap> h := QuotientSggi(g, "(r0 r1)^5, (r1 r2)^3, (r0 r1 r2)^5");
<fp group on the generators [ r0, r1, r2 ]>
gap> Size(h);
60
```

14.1.9 QuotientSggiByNormalSubgroup (for IsGroup, IsGroup)

▷ `QuotientSggiByNormalSubgroup(g, n)` (operation)

Returns: g/n

Given an `sggi` g and a normal subgroup n in g , this function will give you the quotient in a way that respects the generators (i.e., the generators of the quotient will be the images of the generators of the original group).

Example

```
gap> g:=AutomorphismGroup(Cube(3));
<fp group of size 48 on the generators [ r0, r1, r2 ]>
gap> q:=QuotientSggiByNormalSubgroup(g,Group([(g.1*g.2*g.3)^3]));
Group([ (1,2)(3,7)(4,6)(5,10)(8,14)(9,16)(11,18)(12,20)(13,17)(15,23)(19,22)(21,24), (1,3)(2,5)(4,6), (1,4)(2,6)(3,5), (1,5)(2,4)(3,6), (1,6)(2,3)(4,5), (1,7)(2,8)(3,9), (1,8)(2,9)(3,7), (1,10)(2,11)(3,12), (1,11)(2,12)(3,10), (1,13)(2,14)(3,15), (1,14)(2,15)(3,13), (1,16)(2,17)(3,18), (1,17)(2,18)(3,16), (1,19)(2,19)(3,21), (1,20)(2,20)(3,22), (1,21)(2,21)(3,23), (1,22)(2,22)(3,24), (1,23)(2,23)(3,25), (1,24)(2,24)(3,26), (1,25)(2,25)(3,27), (1,26)(2,26)(3,28), (1,27)(2,27)(3,29), (1,28)(2,28)(3,30), (1,29)(2,29)(3,31), (1,30)(2,30)(3,32), (1,31)(2,31)(3,33), (1,32)(2,32)(3,34), (1,33)(2,33)(3,35), (1,34)(2,34)(3,36), (1,35)(2,35)(3,37), (1,36)(2,36)(3,38), (1,37)(2,37)(3,39), (1,38)(2,38)(3,40), (1,39)(2,39)(3,41), (1,40)(2,40)(3,42), (1,41)(2,41)(3,43), (1,42)(2,42)(3,44), (1,43)(2,43)(3,45), (1,44)(2,44)(3,46), (1,45)(2,45)(3,47), (1,46)(2,46)(3,48), (1,47)(2,47)(3,49), (1,48)(2,48)(3,50), (1,49)(2,49)(3,51), (1,50)(2,50)(3,52), (1,51)(2,51)(3,53), (1,52)(2,52)(3,54), (1,53)(2,53)(3,55), (1,54)(2,54)(3,56), (1,55)(2,55)(3,57), (1,56)(2,56)(3,58), (1,57)(2,57)(3,59), (1,58)(2,58)(3,60), (1,59)(2,59)(3,61), (1,60)(2,60)(3,62), (1,61)(2,61)(3,63), (1,62)(2,62)(3,64), (1,63)(2,63)(3,65), (1,64)(2,64)(3,66), (1,65)(2,65)(3,67), (1,66)(2,66)(3,68), (1,67)(2,67)(3,69), (1,68)(2,68)(3,70), (1,69)(2,69)(3,71), (1,70)(2,70)(3,72), (1,71)(2,71)(3,73), (1,72)(2,72)(3,74), (1,73)(2,73)(3,75), (1,74)(2,74)(3,76), (1,75)(2,75)(3,77), (1,76)(2,76)(3,78), (1,77)(2,77)(3,79), (1,78)(2,78)(3,80), (1,79)(2,79)(3,81), (1,80)(2,80)(3,82), (1,81)(2,81)(3,83), (1,82)(2,82)(3,84), (1,83)(2,83)(3,85), (1,84)(2,84)(3,86), (1,85)(2,85)(3,87), (1,86)(2,86)(3,88), (1,87)(2,87)(3,89), (1,88)(2,88)(3,90), (1,89)(2,89)(3,91), (1,90)(2,90)(3,92), (1,91)(2,91)(3,93), (1,92)(2,92)(3,94), (1,93)(2,93)(3,95), (1,94)(2,94)(3,96), (1,95)(2,95)(3,97), (1,96)(2,96)(3,98), (1,97)(2,97)(3,99), (1,98)(2,98)(3,100), (1,99)(2,99)(3,101), (1,100)(2,100)(3,102), (1,101)(2,101)(3,103), (1,102)(2,102)(3,104), (1,103)(2,103)(3,105), (1,104)(2,104)(3,106), (1,105)(2,105)(3,107), (1,106)(2,106)(3,108), (1,107)(2,107)(3,109), (1,108)(2,108)(3,110), (1,109)(2,109)(3,111), (1,110)(2,110)(3,112), (1,111)(2,111)(3,113), (1,112)(2,112)(3,114), (1,113)(2,113)(3,115), (1,114)(2,114)(3,116), (1,115)(2,115)(3,117), (1,116)(2,116)(3,118), (1,117)(2,117)(3,119), (1,118)(2,118)(3,120), (1,119)(2,119)(3,121), (1,120)(2,120)(3,122), (1,121)(2,121)(3,123), (1,122)(2,122)(3,124), (1,123)(2,123)(3,125), (1,124)(2,124)(3,126), (1,125)(2,125)(3,127), (1,126)(2,126)(3,128), (1,127)(2,127)(3,129), (1,128)(2,128)(3,130), (1,129)(2,129)(3,131), (1,130)(2,130)(3,132), (1,131)(2,131)(3,133), (1,132)(2,132)(3,134), (1,133)(2,133)(3,135), (1,134)(2,134)(3,136), (1,135)(2,135)(3,137), (1,136)(2,136)(3,138), (1,137)(2,137)(3,139), (1,138)(2,138)(3,140), (1,139)(2,139)(3,141), (1,140)(2,140)(3,142), (1,141)(2,141)(3,143), (1,142)(2,142)(3,144), (1,143)(2,143)(3,145), (1,144)(2,144)(3,146), (1,145)(2,145)(3,147), (1,146)(2,146)(3,148), (1,147)(2,147)(3,149), (1,148)(2,148)(3,150), (1,149)(2,149)(3,151), (1,150)(2,150)(3,152), (1,151)(2,151)(3,153), (1,152)(2,152)(3,154), (1,153)(2,153)(3,155), (1,154)(2,154)(3,156), (1,155)(2,155)(3,157), (1,156)(2,156)(3,158), (1,157)(2,157)(3,159), (1,158)(2,158)(3,160), (1,159)(2,159)(3,161), (1,160)(2,160)(3,162), (1,161)(2,161)(3,163), (1,162)(2,162)(3,164), (1,163)(2,163)(3,165), (1,164)(2,164)(3,166), (1,165)(2,165)(3,167), (1,166)(2,166)(3,168), (1,167)(2,167)(3,169), (1,168)(2,168)(3,170), (1,169)(2,169)(3,171), (1,170)(2,170)(3,172), (1,171)(2,171)(3,173), (1,172)(2,172)(3,174), (1,173)(2,173)(3,175), (1,174)(2,174)(3,176), (1,175)(2,175)(3,177), (1,176)(2,176)(3,178), (1,177)(2,177)(3,179), (1,178)(2,178)(3,180), (1,179)(2,179)(3,181), (1,180)(2,180)(3,182), (1,181)(2,181)(3,183), (1,182)(2,182)(3,184), (1,183)(2,183)(3,185), (1,184)(2,184)(3,186), (1,185)(2,185)(3,187), (1,186)(2,186)(3,188), (1,187)(2,187)(3,189), (1,188)(2,188)(3,190), (1,189)(2,189)(3,191), (1,190)(2,190)(3,192), (1,191)(2,191)(3,193), (1,192)(2,192)(3,194), (1,193)(2,193)(3,195), (1,194)(2,194)(3,196), (1,195)(2,195)(3,197), (1,196)(2,196)(3,198), (1,197)(2,197)(3,199), (1,198)(2,198)(3,200), (1,199)(2,199)(3,201), (1,200)(2,200)(3,202), (1,201)(2,201)(3,203), (1,202)(2,202)(3,204), (1,203)(2,203)(3,205), (1,204)(2,204)(3,206), (1,205)(2,205)(3,207), (1,206)(2,206)(3,208), (1,207)(2,207)(3,209), (1,208)(2,208)(3,210), (1,209)(2,209)(3,211), (1,210)(2,210)(3,212), (1,211)(2,211)(3,213), (1,212)(2,212)(3,214), (1,213)(2,213)(3,215), (1,214)(2,214)(3,216), (1,215)(2,215)(3,217), (1,216)(2,216)(3,218), (1,217)(2,217)(3,219), (1,218)(2,218)(3,220), (1,219)(2,219)(3,221), (1,220)(2,220)(3,222), (1,221)(2,221)(3,223), (1,222)(2,222)(3,224), (1,223)(2,223)(3,225), (1,224)(2,224)(3,226), (1,225)(2,225)(3,227), (1,226)(2,226)(3,228), (1,227)(2,227)(3,229), (1,228)(2,228)(3,230), (1,229)(2,229)(3,231), (1,230)(2,230)(3,232), (1,231)(2,231)(3,233), (1,232)(2,232)(3,234), (1,233)(2,233)(3,235), (1,234)(2,234)(3,236), (1,235)(2,235)(3,237), (1,236)(2,236)(3,238), (1,237)(2,237)(3,239), (1,238)(2,238)(3,240), (1,239)(2,239)(3,241), (1,240)(2,240)(3,242), (1,241)(2,241)(3,243), (1,242)(2,242)(3,244), (1,243)(2,243)(3,245), (1,244)(2,244)(3,246), (1,245)(2,245)(3,247), (1,246)(2,246)(3,248), (1,247)(2,247)(3,249), (1,248)(2,248)(3,250), (1,249)(2,249)(3,251), (1,250)(2,250)(3,252), (1,251)(2,251)(3,253), (1,252)(2,252)(3,254), (1,253)(2,253)(3,255), (1,254)(2,254)(3,256), (1,255)(2,255)(3,257), (1,256)(2,256)(3,258), (1,257)(2,257)(3,259), (1,258)(2,258)(3,260), (1,259)(2,259)(3,261), (1,260)(2,260)(3,262), (1,261)(2,261)(3,263), (1,262)(2,262)(3,264), (1,263)(2,263)(3,265), (1,264)(2,264)(3,266), (1,265)(2,265)(3,267), (1,266)(2,266)(3,268), (1,267)(2,267)(3,269), (1,268)(2,268)(3,270), (1,269)(2,269)(3,271), (1,270)(2,270)(3,272), (1,271)(2,271)(3,273), (1,272)(2,272)(3,274), (1,273)(2,273)(3,275), (1,274)(2,274)(3,276), (1,275)(2,275)(3,277), (1,276)(2,276)(3,278), (1,277)(2,277)(3,279), (1,278)(2,278)(3,280), (1,279)(2,279)(3,281), (1,280)(2,280)(3,282), (1,281)(2,281)(3,283), (1,282)(2,282)(3,284), (1,283)(2,283)(3,285), (1,284)(2,284)(3,286), (1,285)(2,285)(3,287), (1,286)(2,286)(3,288), (1,287)(2,287)(3,289), (1,288)(2,288)(3,290), (1,289)(2,289)(3,291), (1,290)(2,290)(3,292), (1,291)(2,291)(3,293), (1,292)(2,292)(3,294), (1,293)(2,293)(3,295), (1,294)(2,294)(3,296), (1,295)(2,295)(3,297), (1,296)(2,296)(3,298), (1,297)(2,297)(3,299), (1,298)(2,298)(3,300), (1,299)(2,299)(3,301), (1,300)(2,300)(3,302), (1,301)(2,301)(3,303), (1,302)(2,302)(3,304), (1,303)(2,303)(3,305), (1,304)(2,304)(3,306), (1,305)(2,305)(3,307), (1,306)(2,306)(3,308), (1,307)(2,307)(3,309), (1,308)(2,308)(3,310), (1,309)(2,309)(3,311), (1,310)(2,310)(3,312), (1,311)(2,311)(3,313), (1,312)(2,312)(3,314), (1,313)(2,313)(3,315), (1,314)(2,314)(3,316), (1,315)(2,315)(3,317), (1,316)(2,316)(3,318), (1,317)(2,317)(3,319), (1,318)(2,318)(3,320), (1,319)(2,319)(3,321), (1,320)(2,320)(3,322), (1,321)(2,321)(3,323), (1,322)(2,322)(3,324), (1,323)(2,323)(3,325), (1,324)(2,324)(3,326), (1,325)(2,325)(3,327), (1,326)(2,326)(3,328), (1,327)(2,327)(3,329), (1,328)(2,328)(3,330), (1,329)(2,329)(3,331), (1,330)(2,330)(3,332), (1,331)(2,331)(3,333), (1,332)(2,332)(3,334), (1,333)(2,333)(3,335), (1,334)(2,334)(3,336), (1,335)(2,335)(3,337), (1,336)(2,336)(3,338), (1,337)(2,337)(3,339), (1,338)(2,338)(3,340), (1,339)(2,339)(3,341), (1,340)(2,340)(3,342), (1,341)(2,341)(3,343), (1,342)(2,342)(3,344), (1,343)(2,343)(3,345), (1,344)(2,344)(3,346), (1,345)(2,345)(3,347), (1,346)(2,346)(3,348), (1,347)(2,347)(3,349), (1,348)(2,348)(3,350), (1,349)(2,349)(3,351), (1,350)(2,350)(3,352), (1,351)(2,351)(3,353), (1,352)(2,352)(3,354), (1,353)(2,353)(3,355), (1,354)(2,354)(3,356), (1,355)(2,355)(3,357), (1,356)(2,356)(3,358), (1,357)(2,357)(3,359), (1,358)(2,358)(3,360), (1,359)(2,359)(3,361), (1,360)(2,360)(3,362), (1,361)(2,361)(3,363), (1,362)(2,362)(3,364), (1,363)(2,363)(3,365), (1,364)(2,364)(3,366), (1,365)(2,365)(3,367), (1,366)(2,366)(3,368), (1,367)(2,367)(3,369), (1,368)(2,368)(3,370), (1,369)(2,369)(3,371), (1,370)(2,370)(3,372), (1,371)(2,371)(3,373), (1,372)(2,372)(3,374), (1,373)(2,373)(3,375), (1,374)(2,374)(3,376), (1,375)(2,375)(3,377), (1,376)(2,376)(3,378), (1,377)(2,377)(3,379), (1,378)(2,378)(3,380), (1,379)(2,379)(3,381), (1,380)(2,380)(3,382), (1,381)(2,381)(3,383), (1,382)(2,382)(3,384), (1,383)(2,383)(3,385), (1,384)(2,384)(3,386), (1,385)(2,385)(3,387), (1,386)(2,386)(3,388), (1,387)(2,387)(3,389), (1,388)(2,388)(3,390), (1,389)(2,389)(3,391), (1,390)(2,390)(3,392), (1,391)(2,391)(3,393), (1,392)(2,392)(3,394), (1,393)(2,393)(3,395), (1,394)(2,394)(3,396), (1,395)(2,395)(3,397), (1,396)(2,396)(3,398), (1,397)(2,397)(3,399), (1,398)(2,398)(3,400), (1,399)(2,399)(3,401), (1,400)(2,400)(3,402), (1,401)(2,401)(3,403), (1,402)(2,402)(3,404), (1,403)(2,403)(3,405), (1,404)(2,404)(3,406), (1,405)(2,405)(3,407), (1,406)(2,406)(3,408), (1,407)(2,407)(3,409), (1,408)(2,408)(3,410), (1,409)(2,409)(3,411), (1,410)(2,410)(3,412), (1,411)(2,411)(3,413), (1,412)(2,412)(3,414), (1,413)(2,413)(3,415), (1,414)(2,414)(3,416), (1,415)(2,415)(3,417), (1,416)(2,416)(3,418), (1,417)(2,417)(3,419), (1,418)(2,418)(3,420), (1,419)(2,419)(3,421), (1,420)(2,420)(3,422), (1,421)(2,421)(3,423), (1,422)(2,422)(3,424), (1,423)(2,423)(3,425), (1,424)(2,424)(3,426), (1,425)(2,425)(3,427), (1,426)(2,426)(3,428), (1,427)(2,427)(3,429), (1,428)(2,428)(3,430), (1,429)(2,429)(3,431), (1,430)(2,430)(3,432), (1,431)(2,431)(3,433), (1,432)(2,432)(3,434), (1,433)(2,433)(3,435), (1,434)(2,434)(3,436), (1,435)(2,435)(3,437), (1,436)(2,436)(3,438), (1,437)(2,437)(3,439), (1,438)(2,438)(3,440), (1,439)(2,439)(3,441), (1,440)(2,440)(3,442), (1,441)(2,441)(3,443), (1,442)(2,442)(3,444), (1,443)(2,443)(3,445), (1,444)(2,444)(3,446), (1,445)(2,445)(3,447), (1,446)(2,446)(3,448), (1,447)(2,447)(3,449), (1,448)(2,448)(3,450), (1,449)(2,449)(3,451), (1,450)(2,450)(3,452), (1,451)(2,451)(3,453), (1,452)(2,452)(3,454), (1,453)(2,453)(3,455), (1,454)(2,454)(3,456), (1,455)(2,455)(3,457), (1,456)(2,456)(3,458), (1,457)(2,457)(3,459), (1,458)(2,458)(3,460), (1,459)(2,459)(3,461), (1,460)(2,460)(3,462), (1,461)(2,461)(3,463), (1,462)(2,462)(3,464), (1,463)(2,463)(3,465), (1,464)(2,464)(3,466), (1,465)(2,465)(3,467), (1,466)(2,466)(3,468), (1,467)(2,467)(3,469), (1,468)(2,468)(3,470), (1,469)(2,469)(3,471), (1,470)(2,470)(3,472), (1,471)(2,471)(3,473), (1,472)(2,472)(3,474), (1,473)(2,473)(3,475), (1,474)(2,474)(3,476), (1,475)(2,475)(3,477), (1,476)(2,476)(3,478), (1,477)(2,477)(3,479), (1,478)(2,478)(3,480), (1,479)(2,479)(3,481), (1,480)(2,480)(3,482), (1,481)(2,481)(3,483), (1,482)(2,482)(3,484), (1,483)(2,483)(3,485), (1,484)(2,484)(3,486), (1,485)(2,485)(3,487), (1,486)(2,486)(3,488), (1,487)(2,487)(3,489), (1,488)(2,488)(3,490), (1,489)(2,489)(3,491), (1,490)(2,490)(3,492), (1,491)(2,491)(3,493), (1,492)(2,492)(3,494), (1,493)(2,493)(3,495), (1,494)(2,494)(3,496), (1,495)(2,495)(3,497), (1,496)(2,496)(3,498), (1,497)(2,497)(3,499), (1,498)(2,498)(3,500), (1,499)(2,499)(3,501), (1,500)(2,500)(3,502), (1,501)(2,501)(3,503), (1,502)(2,502)(3,504), (1,503)(2,503)(3,505), (1,504)(2,504)(3,506), (1,505)(2,505)(3,507), (1,506)(2,506)(3,508), (1,507)(2,507)(3,509), (1,508)(2,508)(3,510), (1,509)(2,509)(3,511), (1,510)(2,510)(3,512), (1,511)(2,511)(3,513), (1,512)(2,512)(3,514), (1,513)(2,513)(3,515), (1,514)(2,514)(3,516), (1,515)(2,515)(3,517), (1,516)(2,516)(3,518), (1,517)(2,517)(3,519), (1,518)(2,518)(3,520), (1,519)(2,519)(3,521), (1,520)(2,520)(3,522), (1,521)(2,521)(3,523), (1,522)(2,522)(3,524), (1,523)(2,523)(3,525), (1,524)(2,524)(3,526), (1,525)(2,525)(3,527), (1,526)(2,526)(3,528), (1,527)(2,527)(3,529), (1,528)(2,528)(3,530), (1,529)(2,529)(3,531), (1,530)(2,530)(3,532), (1,531)(2,531)(3,533), (1,532)(2,532)(3,534), (1,533)(2,533)(3,535), (1,534)(2,534)(3,536), (1,535)(2,535)(3,537), (1,536)(2,536)(3,538), (1,537)(2,537)(3,539), (1,538)(2,538)(3,540), (1,539)(2,539)(3,541), (1,540)(2,540)(3,542), (1,541)(2,541)(3,543), (1,542)(2,542)(3,544), (1,543)(2,543)(3,545), (1,544)(2,544)(3,546), (1,545)(2,545)(3,547), (1,546)(2,546)(3,548), (1,547)(2,547)(3,549), (1,548)(2,548)(3,550), (1,549)(2,549)(3,551), (1,550)(2,550)(3,552), (1,551)(2,551)(3,553), (1,552)(2,552)(3,554), (1,553)(2,553)(3,555), (1,554)(2,554)(3,556), (1,555)(2,555)(3,557), (1,556)(2,556)(3,558), (1,557)(2,557)(3,559), (1,558)(2,558)(3,560), (1,559)(2,559)(3,561), (1,560)(2,560)(3,562), (1,561)(2,561)(3,563), (1,562)(2,562)(3,564), (1,563)(2,563)(3,565), (1,564)(2,564)(3,566), (1,565)(2,565)(3,567), (1,566)(2,566)(3,568), (1,567)(2,567)(3,569), (1,568)(2,568)(3,570), (1,569)(2,569)(3,571), (1,570)(2,570)(3,572), (1,571)(2,571)(3,573), (1,572)(2,572)(3,574), (1,573)(2,573)(3,575), (1,574)(2,574)(3,576), (1,575)(2,575)(3,577), (1,576)(2,576)(3,578), (1,577)(2,577)(3,579), (1,578)(2,578)(3,580), (1,579)(2,579)(3,581), (1,580)(2,580)(3,582), (1,581)(2,581)(3,583), (1,582)(2,582)(3,584), (1,583)(2,583)(3,585), (1,584)(2,584)(3,586), (1,585)(2,585)(3,587), (1
```

14.1.10 QuotientManifoldByAutomorphismSubgroup (for IsManifold, IsPermGroup)

▷ `QuotientManifoldByAutomorphismSubgroup(m, h)` (operation)

Returns: m/h

Given a manifold m , and a subgroup h of the automorphism group on the flags, this function will give you the manifold in which the orbits of flags under the action of h are identified. Note that this function doesn't do any prechecks, and may break easily when m/h isn't a manifold or when m/h is of lower rank (sorry!).

Example

```
gap> m:=Cube(3);
Cube(3)
gap> a:=AutomorphismGroupOnFlags(m);
<permutation group with 3 generators>
gap> h:=Group((a.3*a.1*a.2)^3);
Group([ (1,7)(2,3)(4,18)(5,19)(6,20)(8,11)(9,12)(10,13)(14,32)(15,33)(16,34)(17,35)(21,25)(22,26)
gap> q:=QuotientManifoldByAutomorphismSubgroup(m,h);
3-manifold with 24 flags
gap> last=HemiCube(3);
true
```

Chapter 15

ramp automatic generated documentation

15.1 ramp automatic generated documentation of methods

15.1.1 UniversalRotationGroup (for IsInt)

▷ `UniversalRotationGroup(n)` (operation)

Returns the rotation subgroup of the universal Coxeter Group of rank *n*.

15.1.2 UniversalRotationGroup (for IsList)

▷ `UniversalRotationGroup(sym)` (operation)

Returns the rotation subgroup of the Coxeter Group with Schläfli symbol *sym*.

15.1.3 RotaryManiplex (for IsGroup)

▷ `RotaryManiplex(g)` (operation)

Given a group *g* (which should be a string rotation group), returns the rotary maniplex with that rotation group, where the privileged generators are those returned by `GeneratorsOfGroup(g)`.

15.1.4 RotaryManiplex (for IsList)

▷ `RotaryManiplex(sym)` (operation)

Returns the universal rotary maniplex (in fact, regular polytope) with Schläfli symbol *sym*.

15.1.5 RotaryManiplex (for IsList, IsList)

▷ `RotaryManiplex(symbol, relations)` (operation)

Returns the rotary maniplex with the given Schläfli symbol and with the given relations. The relations are given by a string that refers to the generators *s*₁, *s*₂, etc. For example:

Example

```
gap> M := RotaryManiplex([4,4], "(s2^-1 s1)^6");;
```

If the option `set_schlafl` is set, then we set the Schläfli symbol to the one given. This may not be the correct Schläfli symbol, since the relations may cause a collapse, so this should only be used if you know that the Schläfli symbol is correct.

15.1.6 EnantiomorphicForm (for IsRotaryManiplex)

▷ `EnantiomorphicForm(M)` (operation)

The *enantiomorphic form* of a rotary maniplex is the same maniplex, but where we choose the new base flag to be one of the flags that is adjacent to the original base flag. If M is reflexible, then this choice has no effect. Otherwise, if M is chiral, then the enantiomorphic form gives us a different presentation for the rotation group.

15.1.7 DatabaseString (for IsManiplex)

▷ `DatabaseString(M)` (operation)

Returns: String

Given a maniplex M , returns a string representation of M suitable for saving in a database for later retrieval.

15.1.8 ManiplexFromDatabaseString (for IsString)

▷ `ManiplexFromDatabaseString(maniplexString)` (operation)

Returns: IsManiplex

Given a string *maniplexString*, representing a maniplex stored in a database, returns the maniplex that is represented.

Chapter 16

Stratified Operations

16.1 Computational tools

Some description.

Chapter 17

Utility functions

17.1 Utility functions

17.1.1 InfoRamp

▷ InfoRamp (info class)

The InfoClass for the Ramp package.

17.1.2 AbstractPolytope

▷ AbstractPolytope(*args*) (function)

Calls Maniplex(*args*) and marks the output as polytopal.

17.1.3 AbstractRegularPolytope

▷ AbstractRegularPolytope(*args*) (function)

Calls ReflexibleManiplex(*args*) and marks the output as polytopal. Also available as ARP(*args*).

17.1.4 AbstractRotaryPolytope

▷ AbstractRotaryPolytope(*args*) (function)

Calls RotaryManiplex(*args*) and marks the output as polytopal.

17.1.5 TranslatePerm

▷ TranslatePerm(*perm*, *k*) (function)

Returns a new permutation obtained from *perm* by adding *k* to each moved point.

17.1.6 MultPerm

▷ `MultPerm(perm, multiplier, offset)` (function)

Multiplies together *perm*, `TranslatePerm(perm, offset)`, `TranslatePerm(perm, offset*2)`, ..., with *multiplier* terms, and returns the result.

17.1.7 PermFromRange

▷ `PermFromRange(perm1, perm2)` (function)

Returns: Permutation

This attempts to construct a permutation that we would write as *perm1* ... *perm2*. Probably it is clearest to look at some examples:

Example

```
gap> PermFromRange((1,2), (9,10));
(1,2)(3,4)(5,6)(7,8)(9,10)
gap> PermFromRange((1,3), (13,15));
(1,3)(4,6)(7,9)(10,12)(13,15)
gap> PermFromRange((2,3,4), (8,9,10));
(2,3,4)(5,6,7)(8,9,10)
```

17.1.8 ParseStringCRels

▷ `ParseStringCRels(rels, g)` (function)

Returns: a list of relators

This helper function is used in several maniplex constructors. Given a string *rels* that represents relations in an sggi, and an sggi *g*, returns a list of elements in the free group of *g* represented by *rels*. These can then be used to form a quotient of *g*.

Example

```
gap> g := AutomorphismGroup(CubicTiling(2));
gap> rels := "(r0 r1 r2 r1)^6";
gap> newrels := ParseStringCRels(rels, g);
[ (r0*r1*r2*r1)^6 ]
gap> newrels[1] in FreeGroupOfFpGroup(g);
true
gap> g2 := FactorGroupFpGroupByRels(g, newrels);
<fp group on the generators [ r0, r1, r2 ]>
```

For convenience, you may use *z1*, *z2*, etc and *h1*, *h2*, etc in relations, where *zj* means *r0* (*r1* *r2*)^{*j*} (the "j-zigzag" word) and *hj* means *r0* (*r1* *r2*)^{*j-1*} *r1* (the "j-hole" word).

17.1.9 ParseRotGpRels

▷ `ParseRotGpRels(rels, g)` (function)

This helper function is used in several maniplex constructors. It is analogous to `ParseStringCRels`, but for rotation groups instead.

17.1.10 AddOrAppend

▷ `AddOrAppend(L, x)` (function)

Given a list L and an object x , this calls `Append(L, x)` if x is a list; otherwise it calls `Add(L, x)`. Note that since strings are internally represented as lists, `AddOrAppend(L, "foo")` will append the characters 'f', 'o', 'o'.

Example

```
gap> L := [1, 2, 3];;
gap> AddOrAppend(L, 4);
gap> L;
[1, 2, 3, 4]
gap> AddOrAppend(L, [5, 6]);
gap> L;
[1, 2, 3, 4, 5, 6];
```

17.1.11 WrappedPosetOperation

▷ `WrappedPosetOperation(posetOp)` (function)

Given a poset operation, creates a bare-bones maniplex operation that delegates to the poset operation.

Example

```
gap> myjoin := WrappedPosetOperation(JoinProduct);
function( arg... ) ... end
gap> M := myjoin(Pgon(4), Vertex());
3-maniplex
gap> M = Pyramid(4);
true
```

Usually, you will want to eventually create a fuller-featured wrapper of the poset operation – one that can infer more information from its arguments. But this method is a good way to quickly test whether a poset operation works on maniplexes the way one expects.

References

- [CM17] Gabe Cunningham and Mark Mixer. Internal and external duality in abstract polytopes. *Contrib. Discrete Math.*, 12(2):187–214, 2017. [31](#), [32](#), [39](#)
- [GH18] Ian Gleason and Isabel Hubbard. Products of abstract polytopes. *J. Combin. Theory Ser. A*, 157:287–320, 2018. [63](#)
- [MPW14] Barry Monson, Daniel Pellicer, and Gordon I. Williams. Mixing and monodromy of abstract polytopes. *Trans. of the AMS*, 366:2651–2681, 2014. [54](#)
- [MS02] Peter McMullen and Egon Schulte. *Abstract Regular Polytopes*. Cambridge University Press, 2002. [54](#)
- [Pel18] Daniel Pellicer. Cleaved abstract polytopes. *Combinatorica*, 38(3):709–737, 2018. [57](#)
- [Wil12] Steve Wilson. Maniplexes: Part 1: maps, polytopes, symmetry and operators. *Symmetry*, 4(2):265–275, 2012. [54](#)

Index

- 120Cell, [38](#)
- 24Cell, [38](#)
- 24CellToroid
 - for IsInt,IsInt, [40](#)
- 3343Toroid
 - for IsInt,IsInt, [40](#)
- 600Cell, [39](#)

- AbstractPolytope, [72](#)
- AbstractRegularPolytope, [72](#)
- AbstractRotaryPolytope, [72](#)
- AddOrAppend, [74](#)
- AddRanksInPosets
 - for IsPosetElement,IsPoset,IsInt, [58](#)
- AdjacentFlag
 - for IsPosetOfFlags,IsList,IsInt, [60](#)
- AdjacentFlags
 - for IsPoset,IsList,IsInt, [61](#)
- AdjacentVertices
 - for IsEdgeLabeledGraph, IsObject, [11](#)
- Amalgamate
 - for IsManiplex, IsManiplex, [31](#)
- Antiprism
 - for IsInt, [33](#)
 - for IsManiplex, [33](#)
 - for IsPoset, [64](#)
- AreIncidentElements
 - for IsObject,IsObject, [59](#)
- AsPosetOfAtoms
 - for IsPoset, [62](#)
- AtomList
 - for IsPosetElement, [58](#)
- AutomorphismGroup
 - for IsManiplex, [43](#)
 - for IsPoset, [61](#)
- AutomorphismGroupFpGroup
 - for IsManiplex, [43](#)
- AutomorphismGroupOnChains
 - for IsManiplex, IsCollection, [22](#)
- AutomorphismGroupOnEdges
 - for IsManiplex, [22](#)
- AutomorphismGroupOnElements
 - for IsPoset, [61](#)
- AutomorphismGroupOnFacets
 - for IsManiplex, [22](#)
- AutomorphismGroupOnFlags
 - for IsManiplex, [43](#)
- AutomorphismGroupOnIFaces
 - for IsManiplex, IsInt, [22](#)
- AutomorphismGroupOnVertices
 - for IsManiplex, [22](#)
- AutomorphismGroupPermGroup
 - for IsManiplex, [43](#)

- Bk21
 - for IsInt,IsInt, [28](#)
- Bk21Star
 - for IsInt,IsInt, [28](#)
- BrucknerSphere, [39](#)

- CartesianProduct
 - for IsManiplex, IsManiplex, [33](#)
 - for IsPoset,IsPoset, [63](#)
- ChiralityGroup
 - for IsRotaryManiplex, [44](#)
- Cleave
 - for IsPoset,IsInt, [57](#)
- Comix
 - for IsFpGroup, IsFpGroup, [46](#)
 - for IsReflexibleManiplex, IsReflexibleManiplex, [46](#)
- ConnectedComponents
 - for IsEdgeLabeledGraph, IsList, [10](#)
- ConnectionGeneratorOfPoset
 - for IsPoset,IsInt, [61](#)
- ConnectionGroup
 - for IsManiplex, [43](#)
 - for IsPoset, [61](#)

- CoSkeleton
 - for IsManiplex, 8
- CPRGraphFromGroups
 - for IsGroup, IsGroup, 11
- CrossPolytope
 - for IsInt, 37
- CtoL
 - for IsInt, IsInt, IsInt, IsInt, 46
- Cube
 - for IsInt, 37
- CubicalToroid
 - for IsInt, IsInt, IsInt, 40
- CubicTiling
 - for IsInt, 38
- Cuboctahedron, 40
- DatabaseString
 - for IsManiplex, 70
- DegeneratePolyhedra, 35
- Deltak
 - for IsInt, 27
- DirectDerivates
 - for IsManiplex, 32
- DirectedGraphFromListOfEdges
 - for IsList, IsList, 5
- DirectSumOfManiplexes
 - for IsManiplex, IsManiplex, 34
- DirectSumOfPosets
 - for IsPoset, IsPoset, 64
- Dodecahedron, 38
- Dual
 - for IsManiplex, 31
- DualPoset
 - for IsPoset, 56
- Edge, 37
- EdgeLabeledGraphFromEdges
 - for IsList, IsList, IsList, 9
- EdgeLabelPreservingAutomorphismGroup
 - for IsEdgeLabeledGraph, 10
- ElementsList
 - for IsPoset, 50
- EnantiomorphicForm
 - for IsRotaryManiplex, 70
- EpsilonK
 - for IsInt, 27
- EqualChains
 - for IsList, IsList, 61
- EvenConnectionGroup
 - for IsManiplex, 44
- ExtraRelators
 - for IsReflexibleManiplex, 44
- ExtraRotRelators
 - for IsRotaryManiplex, 44
- FaceListOfPoset
 - for IsPoset, 61
- FacesByRankOfPoset
 - for IsPoset, 62
- Facet
 - for IsManiplex, 18
 - for IsManiplex, IsInt, 18
- Facets
 - for IsManiplex, 18
- FlagGraph
 - for IsGroup, 10
- FlagGraphWithLabels
 - for IsGroup, 6
- FlagList
 - for IsPosetElement, 58
- FlagMix
 - for IsManiplex, IsManiplex, 46
- FlagOrbitRepresentatives
 - for IsManiplex, 24
- FlagOrbits
 - for IsManiplex, 25
- FlagOrbitsStabilizer
 - for IsManiplex, 25
- FlagsAsFlagListFaces
 - for IsPoset, 60
- FlatExtension
 - for IsManiplex, IsInt, 30
- FlatOrientablyRegularPolyhedraOfType
 - for IsList, 39
- FlatOrientablyRegularPolyhedron
 - for IsInt, IsInt, IsInt, IsInt, 39
- FlatRegularPolyhedra, 35
- Fvector
 - for IsManiplex, 18
- GraphFromListOfEdges
 - for IsList, IsList, 5
- GreatRhombicosidodecahedron, 42
- GreatRhombicuboctahedron, 42

Hasse
 for IsManiplex, 8
 HasseDiagramOfPoset
 for IsPoset, 62
 Hemi120Cell, 39
 Hemi24Cell, 38
 Hemi600Cell, 39
 HemiCrossPolytope
 for IsInt, 38
 HemiCube
 for IsInt, 37
 HemiDodecahedron, 38
 HemiIcosahedron, 38
 Hole
 for IsManiplex, IsInt, 29
 HoleLength
 for IsManiplex, IsInt, 21
 HoleVector
 for IsManiplex, 21

 Icosadodecahedron, 41
 Icosahedron, 38
 InfoRamp, 72
 InternallySelfDualPolyhedron1
 for IsInt, 39
 InternallySelfDualPolyhedron2
 for IsInt, IsInt, 39
 IOrientableCover
 for IsManiplex, IsList, 48
 IsAllJoins
 for IsPoset, 51
 IsAllMeets
 for IsPoset, 51
 IsAtomic
 for IsPoset, 50
 IsChainTransitive
 for IsManiplex, IsCollection, 23
 IsChiral
 for IsManiplex, 25
 IsCover
 for IsManiplex, IsManiplex, 66
 IsDegenerate
 for IsManiplex, 20
 IsEdgeTransitive
 for IsManiplex, 24
 IsEqualFaces
 for IsFace, IsFace, IsPoset, 59

 IsEquivelar
 for IsManiplex, 20
 IsExternallySelfDual
 for IsReflexibleManiplex, 32
 IsFacetBipartite
 for IsManiplex, 47
 IsFacetFaithful
 for IsReflexibleManiplex, 26
 IsFacetTransitive
 for IsManiplex, 24
 IsFlagConnected
 for IsPoset, 52
 IsFlaggable
 for IsPoset, 50
 IsFlat
 for IsManiplex, 19
 for IsManiplex, IsInt, IsInt, 19
 IsFullyTransitive
 for IsManiplex, 24
 IsGgi
 for IsGroup, 15
 IsIFaceTransitive
 for IsManiplex, IsInt, 23
 IsInternallySelfDual
 for IsReflexibleManiplex, 31
 IsIOrientable
 for IsManiplex, IsList, 47
 IsIsomorphicManiplex
 for IsManiplex, IsManiplex, 66
 IsIsomorphicPoset
 for IsPoset, IsPoset, 60
 IsLattice
 for IsPoset, 51
 IsOrientable
 for IsManiplex, 47
 IsP1
 for IsPoset, 51
 IsP2
 for IsPoset, 52
 IsP3
 for IsPoset, 52
 IsP4
 for IsPoset, 52
 IsPolytopal
 for IsManiplex, 14
 IsPolytope

- for IsPoset, 53
- IsPrePolytope
 - for IsPoset, 53
- IsQuotient
 - for IsManiplex, IsManiplex, 66
 - for IsSggi, IsSggi, 66
- IsReflexible
 - for IsManiplex, 25
- IsRotary
 - for IsManiplex, 25
- IsSelfDual
 - for IsManiplex, 31
 - for IsPoset, 53
- IsSelfPetrial
 - for IsManiplex, 32
- IsSggi
 - for IsGroup, 15
- IsStringC
 - for IsGroup, 15
- IsStringCPlus
 - for IsGroup, 16
- IsStringy
 - for IsGroup, 15
- IsSubface
 - for IsFace, IsFace, IsPoset, 59
- IsTight
 - for IsManiplex, 20
- IsVertexBipartite
 - for IsManiplex, 47
- IsVertexFaithful
 - for IsReflexibleManiplex, 25
- IsVertexTransitive
 - for IsManiplex, 24
- Join
 - for IsFace, IsFace, IsPoset, 59
- JoinProduct
 - for IsManiplex, IsManiplex, 33
 - for IsPoset, IsPoset, 63
- LabeledAdjacentVertices
 - for IsEdgeLabeledGraph, IsObject, 11
- LabeledSemiEdges
 - for IsEdgeLabeledGraph, 12
- LayerGraph
 - for IsGroup, IsInt, IsInt, 7
- License, 2
- ListIsP1Poset
 - for IsList, 51
- Maniplex
 - for IsFunction, IsList, 14
 - for IsPermGroup, 13
 - for IsPoset, 14
 - for IsReflexibleManiplex, IsGroup, 14
- ManiplexFromDatabaseString
 - for IsString, 70
- MaxFace
 - for IsPoset, 62
- MaximalChains
 - for IsPoset, 49
- MaxVertexFaithfulQuotient
 - for IsReflexibleManiplex, 26
- Medial
 - for IsManiplex, 31
- Meet
 - for IsFace, IsFace, IsPoset, 59
- MinFace
 - for IsPoset, 62
- Mix
 - for IsFpGroup, IsFpGroup, 45
 - for IsManiplex, IsManiplex, 45
 - for IsPermGroup, IsPermGroup, 45
 - for IsReflexibleManiplex, IsReflexibleManiplex, 45
- Mk
 - for IsInt, 27
- MkPrime
 - for IsInt, 28
- MultPerm, 73
- NumberOfChainOrbits
 - for IsManiplex, IsCollection, 23
- NumberOfEdgeOrbits
 - for IsManiplex, 23
- NumberOfEdges
 - for IsManiplex, 17
- NumberOfFacetOrbits
 - for IsManiplex, 23
- NumberOfFacets
 - for IsManiplex, 17
- NumberOfFlagOrbits
 - for IsManiplex, 24
- NumberOfIFaceOrbits

- for IsManiplex, IsInt, [23](#)
- NumberOfIFaces
 - for IsManiplex, IsInt, [17](#)
- NumberOfRidges
 - for IsManiplex, [17](#)
- NumberOfVertexOrbits
 - for IsManiplex, [23](#)
- NumberOfVertices
 - for IsManiplex, [17](#)
- Opp
 - for IsManiplex, [28](#)
- OrderingFunction
 - for IsPoset, [50](#)
- OrientableCover
 - for IsManiplex, [47](#)
- PairCompareAtomsList
 - for IsList, IsList, [56](#)
- PairCompareFlagsList
 - for IsList, IsList, [56](#)
- ParseRotGpRels, [73](#)
- ParseStringCRels, [73](#)
- PartiallyCleave
 - for IsPoset, IsInt, [57](#)
- PartialOrder
 - for IsPoset, [51](#)
- PermFromRange, [73](#)
- Petrial
 - for IsManiplex, [32](#)
- PetrieLength
 - for IsManiplex, [21](#)
- Pgon
 - for IsInt, [37](#)
- PosetElementFromAtomList
 - for IsList, [58](#)
- PosetElementFromIndex
 - for IsObject, [58](#)
- PosetElementFromListOfFlags
 - for IsList, IsPoset, IsInt, [57](#)
- PosetElementWithOrder
 - for IsObject, IsFunction, [57](#)
- PosetElementWithPartialOrder
 - for IsObject, IsBinaryRelation, [58](#)
- PosetFromAtomicList
 - for IsList, [55](#)
- PosetFromConnectionGroup
 - for IsPermGroup, [54](#)
- PosetFromElements
 - for IsList, IsFunction, [55](#)
- PosetFromFaceListOfFlags
 - for IsList, [54](#)
- PosetFromManiplex
 - for IsManiplex, [54](#)
- PosetFromPartialOrder
 - for IsBinaryRelation, [55](#)
- PosetFromSuccessorList
 - for IsList, [56](#)
- PosetIsomorphism
 - for IsPoset, IsPoset, [60](#)
- PRGraph
 - for IsGroup, [11](#)
- Prism
 - for IsInt, [33](#)
 - for IsManiplex, [33](#)
- Pseudorhombicuboctahedron, [41](#)
- PseudoSchlaflSymbol
 - for IsManiplex, [19](#)
- Pyramid
 - for IsInt, [33](#)
 - for IsManiplex, [32](#)
- QuotientByLabel
 - for IsObject, IsList, IsList, IsList, [9](#)
- QuotientManiplex
 - for IsReflexibleManiplex, IsString, [67](#)
- QuotientManiplexByAutomorphismSubgroup
 - for IsManiplex, IsPermGroup, [68](#)
- QuotientSggi
 - for IsGroup, IsList, [67](#)
- QuotientSggiByNormalSubgroup
 - for IsGroup, IsGroup, [67](#)
- RankedFaceListOfPoset
 - for IsPoset, [60](#)
- RankInPoset
 - for IsPosetElement, IsPoset, [59](#)
- RankManiplex
 - for IsManiplex, [20](#)
- RankPoset
 - for IsPoset, [49](#)
- RankPosetElements
 - for IsPoset, [62](#)
- RanksInPosets

- for IsPosetElement, 58
- ReflexibleManiplex
 - for IsGroup, 13
 - for IsList, 13
- ReflexibleQuotientManiplex
 - for IsManiplex, IsList, 67
- RegularToroidalPolyhedra36, 35
- RegularToroidalPolyhedra44, 35
- RotaryManiplex
 - for IsGroup, 69
 - for IsList, 69
 - for IsList, IsList, 69
- RotationGroup
 - for IsManiplex, 44
- SchlaflSymbol
 - for IsManiplex, 19
- Section
 - for IsFace, IsFace, IsPoset, 57
 - for IsManiplex, IsInt, IsInt, 18
 - for IsManiplex, IsInt, IsInt, IsInt, 18
- Sections
 - for IsManiplex, IsInt, IsInt, 18
- SemiEdges
 - for IsEdgeLabeledGraph, 11
- Sggi
 - for IsList, IsList, 15
- SggiElement
 - for IsGroup, IsString, 16
- SggiFamily
 - for IsGroup, IsList, 16
- Simple
 - for IsEdgeLabeledGraph, 10
- Simplex
 - for IsInt, 38
- Size
 - for IsManiplex, 20
- Skeleton
 - for IsManiplex, 8
- SmallChiral4Polytopes, 36
- SmallChiralPolyhedra, 36
- SmallDegenerateRegular4Polytopes, 36
- SmallestRegularCover
 - for IsManiplex, 66
- SmallRegular4Polytopes, 36
- SmallRegularPolyhedra, 36
- SmallRegularPolyhedraFromFile, 35
- SmallRhombicosidodecahedron, 41
- SmallRhombicuboctahedron, 41
- SnubCube, 41
- SnubDodecahedron, 42
- SymmetryTypeGraph
 - for IsManiplex, 24
- TightOrientablyRegularPolytopesOfType
 - for IsList, 40
- TopologicalProduct
 - for IsManiplex, IsManiplex, 34
 - for IsPoset, IsPoset, 64
- TranslatePerm, 72
- TrivialExtension
 - for IsManiplex, 30
- TruncatedCube, 41
- TruncatedDodecahedron, 42
- TruncatedIcosahedron, 41
- TruncatedOctahedron, 41
- TruncatedTetrahedron, 40
- UniversalExtension
 - for IsManiplex, 30
 - for IsManiplex, IsInt, 30
- UniversalPolytope
 - for IsInt, 30
- UniversalRotationGroup
 - for IsInt, 69
 - for IsList, 69
- UniversalSggi
 - for IsInt, 15
 - for IsList, 15
- UnlabeledFlagGraph
 - for IsGroup, 5
- UnlabeledSimpleGraph
 - for IsEdgeLabeledGraph, 10
- Vertex, 37
- VertexFigure
 - for IsManiplex, 19
 - for IsManiplex, IsInt, 19
- VertexFigures
 - for IsManiplex, 19
- ViewGraph
 - for IsEdgeLabeledGraph, IsString, 12
 - for IsObject, IsString, 12
- WrappedPosetOperation, 74

ZigzagLength
for IsManiplex, IsInt, [20](#)
ZigzagVector
for IsManiplex, [20](#)