

REACT PROJECT

24pw35

```
1. import { useState } from "react";  
import { QRCodeCanvas } from "qrcode.react"  
import  
"bootstrap/dist/css/bootstrap.min.css";
```

```
function App(){  
  
  const [inputText,setInputText] =  
  useState("") const [qrText,setQRText] =  
  useState("")  
  
  const handleChange = (e) => {  
    const value = e.target.value  
    setInputText(value)  
    if(value.trim()==="){  
      setQRText("")  
    }  
    else{  
      setQRText(value)
```

```
}  
}
```

```
console.log(inputText)  
return(  

```

```
  <div className="container d-flex justify-content-center align  
items-center bg-black min-vh-100 min-vw-100">
```

```
    <div className="card shadow bg-light w-50 h-50">
```

```
      <h3 className="text-center mb-4">QR CODE
```

```
      GENERATOR</h3> <input
```

```
        type="text"
```

```
        value={inputText}
```

```
        onChange={handleChange}
```

```
        className="form-control mb-4 w-50 ms-5"
```

```
        placeholder="Enter text..."
```

```
      />
```

```
    {qrText && (  

```

```
      <div className="d-flex justify-content-center">
```

```
        <QRCodeCanvas value={qrText}
```

```
        size={200}></QRCodeCanvas> </div>
```

```
    )}
```

```
  </div>
```

```
    </div>  
  )  
}
```

```
export default App;
```

OUTPUT:

2.

APP.JSX:

```
import Card from "./Card.jsx"
```

```
import pr1 from "./assets/pr1.jpg"
```

```
import pr2 from "./assets/pr2.jpg"
```

```
import pr3 from "./assets/pr3.jpg"
import pr4 from "./assets/pr4.jpg"
import pr5 from "./assets/pr5.jpg"
import { useState } from "react"
import "bootstrap/dist/css/bootstrap.min.css"
function App(){
```

```
  const [products] = useState(
    [{name: "Product 1",price: 200,id: 1,img_link: pr1},
     {name: "Product 2",price: 300,id: 2,img_link: pr2},
     {name: "Product 3",price: 100,id: 3,img_link: pr3},
     {name: "Product 4",price: 150,id: 4,img_link: pr4},
     {name: "Product 5",price: 50,id: 5,img_link: pr5}
  ]
)
```

```
  const [cart,updateCart] = useState([])
  const total = cart.reduce((sum, item) => sum + item.price, 0);

  const handleProductAdd = (product) => {
    const alreadyExist = cart.some((item)=>item.id ===
    product.id) if(alreadyExist){
      alert(`${product.name} already in cart`)
    }
  }
}
```

```
}  
else{  
    updateCart([...cart,product])  
}  
}  
return(
```

```

<div className="container min-vh-100 min-vw-100">
  <nav className="navbar navbar-dark bg-dark rounded mb-4 px
3">
MyShop</span>
    <span className="text-white fw-semibold">
      Cart: {cart.length} items | Total: Rs.{total}
    </span>
  </nav>

  <div className="row">
    {products.map((product)=>(
      <div className="col-12 col-md-4 col-sm-6 mb-4">
        <Card key={product.id} name={product.name}
price={product.price} id={product.id}
img_link={product.img_link} addToCart={() =>
handleProductAdd(product)}
isInCart={cart.some((item)=>item.id===product.id)}/
        > </div>
      ))}
    </div>
  </div>
)
}

```

```
export default App
```

CARD.JSX:

```
import "bootstrap/dist/css/bootstrap.min.css"
function
  Card({name,price,id,img_link,addToCart,isInCart}){
  return(
    <div className="card shadow d-flex flex-column justify-content
left align-items-center" style={{borderRadius: "10px", border:
isInCart?"2px solid green" : "1px solid red"}}>
      <div className="card-header w-100">
        <h1>{name}</h1>
        <h5>Price: {price}</h5>
      </div>
      <div className="card-body">
        <img src={img_link} className="card-img-top"
alt="product" style={{ height: "150px", objectFit: "cover"
}}/> </div>
      <div className="card-footer w-100 d-flex flex-
column"> <p className="fs-3">This is Product {id}
      </p>
      <button className="btn btn-danger ms-auto"
onClick={addToCart} disabled={isInCart}>Add to
      Cart</button> </div>
    </div>
  )
}
```

```
}
```

```
export default Card
```

OUTPUT:

3.

APP.JSX

```
//import { useState } from "react"
```

```
import "bootstrap/dist/css/bootstrap.min.css"
```

```
import Question from "./Question"
```

```
function App(){
```

```
  const questions = [
```

```
    {key: 1, ques: "What is the capital of France?", opt1: "Germany", opt2: "Paris", opt3: "Chennai", opt4: "Virudhunagar", ans: "Paris"},
```

```
    {key: 2, ques: "Which animal gives milk?", opt1: "Cow", opt2: "Lizard", opt3: "Honey Bee", opt4: "Dog", ans: "Cow"},
```

```
    {key: 3, ques: "Which transport goes in water?", opt1: "Truck", opt2: "Lorry", opt3: "Boat", opt4: "Bike", ans: "Boat"},
```

```
    {key: 4, ques: "What do you listen to?", opt1: "Ads", opt2: "Serials", opt3: "Songs", opt4: "Movies", ans: "Songs"},
```

```
    {key: 5, ques: "What is the essential things in life?", opt1:
"Water", opt2: "Air", opt3: "Road", opt4: "Money", ans: "Water"},
  ]
```

```
    return(
      <div className="container d-flex flex-column justify-content
center align-items-center gap-3 min-vh-100 min-vw-100"
style={{background: "#d1a7a9"}}>
        {questions.map((question) => (
          <Question key={question.key} question={question.ques}
opt1={question.opt1} opt2={question.opt2}
opt3={question.opt3} opt4={question.opt4} ans={question.ans}
/>
        )))
      </div>
    )
  }
}
```

```
export default App
```

QUESTION.JSX

```
import
```

```
"bootstrap/dist/css/bootstrap.min.css"
```

```
import { useState } from "react"
```

```
let score = 0
```

```
function Question({question,opt1,opt2,opt3,opt4,ans}){
```

```
  const [submitted,setSubmitted] = useState("")
```

```
  const [answered,setAnswered] =
```

```
  useState(false) const handleSubmit = () =>{
```

```
    if(submitted==="){
```

```
      alert("Please answer the question");
```

```
      return;
```

```
    }
```

```
    setAnswered(true)
```

```
    if(submitted===ans){
```

```
      score++
```

```
      console.log(score)
```

```
    }
```

```
  }
```

```
  return(
```

```
    <div className="container w-100 bg-white mt-2 mb-2" style={{border: "2px solid black"}}>
```

```

<h1>{question}</h1>

<form action="" className="d-flex flex-column mb-2">

    <label htmlFor="opt1"><input type="radio"
name={question} value={opt1} checked={submitted===opt1}
onChange={(e)=>{setSubmitted(e.target.value)}}/>{opt1}</label
>

    <label htmlFor="opt2"><input type="radio"
name={question} value={opt2} checked={submitted===opt2}
onChange={(e)=>{setSubmitted(e.target.value)}}/>{opt2}</label
>

    <label htmlFor="opt3"><input type="radio"
name={question} value={opt3} checked={submitted===opt3}
onChange={(e)=>{setSubmitted(e.target.value)}}/>{opt3}</label
>

    <label htmlFor="opt4"><input type="radio"
name={question} value={opt4} checked={submitted===opt4}
onChange={(e)=>{setSubmitted(e.target.value)}}/>{opt4}</label
>

</form>

{!answered

    ? <button className="btn btn-primary mb-2"
onClick={handleSubmit}>Submit</button>

    : <p className={submitted===ans ? "text-success fw-bold"
: "text-danger fw-bold"}>

        {submitted===ans ? "Correct!" : `Wrong! Answer is
${ans}`}

    </p>

```

```
    }  
  </div>  
)  
}  
export default
```

Question **OUTPUT:**