

CORE JAVA MCQs

1. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "30");  
    }  
}
```

- A) 102030
- B) 3030
- C) 303
- D) 1020

Answer: B

2. Which statement about JVM is correct?

- A) It compiles Java source code into bytecode
- B) It executes bytecode into machine code
- C) It writes Java programs
- D) It manages only memory allocation

Answer: B

3. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int x = 5;  
        System.out.println(x++ + ++x);  
    }  
}
```

- A) 10
- B) 11
- C) 12
- D) 13

Answer: B

4. Which of the following is NOT a primitive type in Java?

- A) int
- B) boolean
- C) String
- D) char

CORE JAVA MCQs

Answer: C

5. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int[] arr = new int[3];  
        System.out.println(arr[0]);  
    }  
}
```

- A) Garbage value
- B) null
- C) 0
- D) Error

Answer: C

6. Which keyword is used for inheritance in Java?

- A) implements
- B) extends
- C) inherit
- D) this

Answer: B

7. What will be the output?

```
public class Test {  
    static int x;  
    public static void main(String[] args) {  
        System.out.println(x);  
    }  
}
```

- A) Garbage value
- B) null
- C) 0
- D) Error

Answer: C

8. Which concept allows same method name with different parameters?

CORE JAVA MCQs

- A) Encapsulation
- B) Polymorphism (Overloading)
- C) Abstraction
- D) Inheritance

Answer: B

9. What will be the output?

```
class A {  
    void show() {  
        System.out.println("A");  
    }  
}  
class B extends A {  
    void show() {  
        System.out.println("B");  
    }  
}  
public class Test {  
    public static void main(String[] args) {  
        A obj = new B();  
        obj.show();  
    }  
}
```

- A) A
- B) B
- C) Error
- D) Null

Answer: B

10. Which memory area stores objects in Java?

- A) Stack
- B) Heap
- C) Method Area
- D) Register

Answer: B

11. What will be the output?

```
System.out.println(5 + 2 * 3);
```

- A) 21

CORE JAVA MCQs

- B) 11
- C) 16
- D) 15

Answer: B

12. Which access modifier is most restrictive?

- A) public
- B) protected
- C) default
- D) private

Answer: D

13. What will be the output?

```
String s = "Java";  
s.concat("8");  
System.out.println(s);
```

- A) Java8
- B) Java
- C) 8Java
- D) Error

Answer: B

14. Which keyword prevents method overriding?

- A) static
- B) final
- C) abstract
- D) this

Answer: B

15. What will be the output?

```
System.out.println(10 == 10.0);
```

- A) true
- B) false

CORE JAVA MCQs

- C) Error
- D) undefined

Answer: A

16. Which keyword refers to parent class constructor?

- A) this
- B) super
- C) parent
- D) base

Answer: B

17. What will be the output?

```
int x = 5;  
System.out.println(x++ + x++);
```

- A) 9
- B) 10
- C) 11
- D) 12

Answer: C

18. Which interface is used for functional programming?

- A) Runnable
- B) Serializable
- C) FunctionalInterface
- D) Comparator

Answer: C

19. What will be the output?

```
System.out.println("A" + "B" + 3 + 4);
```

- A) AB34
- B) AB7
- C) 34AB

CORE JAVA MCQs

- D) Error

Answer: A

20. Which keyword is used to define interface?

- A) class
- B) interface
- C) implements
- D) abstract

Answer: B

21. What will be the output?

```
System.out.println(0.1 + 0.2 == 0.3);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

22. Which collection allows duplicates?

- A) Set
- B) Map
- C) List
- D) None

Answer: C

23. What will be the output?

```
int a = 10, b = a;  
b = 20;  
System.out.println(a);
```

- A) 10
- B) 20
- C) Error
- D) null

CORE JAVA MCQs

Answer: A

24. Which method starts a thread?

- A) run()
- B) start()
- C) execute()
- D) init()

Answer: B

25. What will be the output?

```
System.out.println("Java".charAt(2));
```

- A) J
- B) a
- C) v
- D) Error

Answer: C

26. Which keyword handles exceptions?

- A) try
- B) catch
- C) throw
- D) all of the above

Answer: D

27. What will be the output?

```
String s = null;  
System.out.println(s + "Java");
```

- A) nullJava
- B) Java
- C) Error
- D) null

Answer: A

CORE JAVA MCQs

28. Which interface is used for sorting objects?

- A) Runnable
- B) Comparable
- C) Serializable
- D) Cloneable

Answer: B

29. What will be the result?

```
System.out.println(10 / 0);
```

- A) 0
- B) Infinity
- C) ArithmeticException
- D) NaN

Answer: C

30. Which keyword is used for abstraction?

- A) abstract
- B) final
- C) static
- D) this

Answer: A

31. What will be the output?

```
System.out.println("10" + 10 - 10);
```

- A) 100
- B) 1010
- C) 10
- D) Error

Answer: D

CORE JAVA MCQs

32. Which method is used to compare objects in Set uniqueness?

- A) equals()
- B) hashCode()
- C) both
- D) compareTo()

Answer: C

33. What will be the output?

```
int x = 0;  
System.out.println(x++);
```

- A) 0
- B) 1
- C) Error
- D) undefined

Answer: A

34. Which Java memory area stores method calls?

- A) Heap
- B) Stack
- C) Cache
- D) Register

Answer: B

35. What will be the output?

```
System.out.println(true + true);
```

- A) true
- B) 2
- C) Error
- D) false

Answer: C

36. Which keyword creates an object?

CORE JAVA MCQs

- A) create
- B) new
- C) object
- D) init

Answer: B

37. What will be the output?

```
System.out.println("5" + 2 * 3);
```

- A) 11
- B) 56
- C) 10
- D) Error

Answer: B

38. Which method removes last element from ArrayList?

- A) remove()
- B) pop()
- C) delete()
- D) cut()

Answer: A

39. What will be the output?

```
System.out.println(null == undefined);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: C

40. Which keyword prevents inheritance?

- A) static
- B) final

CORE JAVA MCQs

- C) private
- D) abstract

Answer: B

41. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + 20 + 30);  
    }  
}
```

- A) 60
- B) 102030
- C) 1030
- D) 2030

Answer: B

42. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(20 + 30 + "10");  
    }  
}
```

- A) 5010
- B) 203010
- C) 201030
- D) 3010

Answer: A

43. Which of the following is true about Java?

- A) Java is platform dependent
- B) Java is platform independent
- C) Java is machine dependent
- D) Java runs only on Windows

Answer: B

CORE JAVA MCQs

44. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int x = 10;  
        System.out.println(x-- - --x);  
    }  
}
```

- A) 2
- B) 1
- C) 0
- D) -1

Answer: A

45. Which keyword is used to inherit a class?

- A) implements
- B) extends
- C) inherit
- D) this

Answer: B

46. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 + 5 + "5" + 5 + 5);  
    }  
}
```

- A) 10555
- B) 101010
- C) 10510
- D) 55555

Answer: A

47. Which concept allows multiple methods with same name but different parameters?

- A) Overriding
- B) Overloading
- C) Encapsulation
- D) Abstraction

CORE JAVA MCQs

Answer: B

48. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 < 2 < 3);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

49. Which memory area stores objects in Java?

- A) Stack
- B) Heap
- C) Register
- D) Cache

Answer: B

50. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s1 = "Java";  
        String s2 = "Java";  
        System.out.println(s1 == s2);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

51. Which keyword is used for abstraction?

CORE JAVA MCQs

- A) final
- B) abstract
- C) static
- D) this

Answer: B

52. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 / 3);  
    }  
}
```

- A) 3.33
- B) 3
- C) 4
- D) Error

Answer: B

53. Which of the following is NOT a feature of Java?

- A) Platform independent
- B) Object-oriented
- C) Pointer support
- D) Secure

Answer: C

54. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int a = 5;  
        System.out.println(a++ + ++a + a++);  
    }  
}
```

- A) 16
- B) 17
- C) 18
- D) 19

Answer: B

CORE JAVA MCQs

55. Which keyword is used to prevent method overriding?

- A) static
- B) final
- C) abstract
- D) this

Answer: B

56. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true && false || true);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

57. Which interface is used for sorting in collections?

- A) Comparable
- B) Runnable
- C) Cloneable
- D) Serializable

Answer: A

58. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("A" + 1 + 2);  
    }  
}
```

- A) A12
- B) A3
- C) 3A

CORE JAVA MCQs

- D) Error

Answer: A

59. Which keyword is used to call parent class constructor?

- A) this
- B) super
- C) parent
- D) base

Answer: B

60. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(0.1 + 0.2);  
    }  
}
```

- A) 0.3
- B) 0.30000000000000004
- C) 0.2
- D) Error

Answer: B

61. Which collection allows duplicate elements?

- A) Set
- B) Map
- C) List
- D) None

Answer: C

62. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".length());  
    }  
}
```

CORE JAVA MCQs

- A) 3
- B) 4
- C) 5
- D) Error

Answer: B

63. Which method is used to start a thread?

- A) run()
- B) start()
- C) execute()
- D) init()

Answer: B

64. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Hello".charAt(1));  
    }  
}
```

- A) H
- B) e
- C) l
- D) o

Answer: B

65. Which keyword is used to handle exceptions?

- A) try
- B) catch
- C) finally
- D) all of the above

Answer: D

66. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        String s = null;  
        System.out.println(s);  
    }  
}
```

- A) null
- B) error
- C) undefined
- D) empty

Answer: A

67. Which interface is used for lambda expressions?

- A) Serializable
- B) FunctionalInterface
- C) Cloneable
- D) Comparable

Answer: B

68. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 + "5" + 5);  
    }  
}
```

- A) 105
- B) 555
- C) 10
- D) Error

Answer: B

69. Which keyword prevents inheritance?

- A) static
- B) final
- C) abstract
- D) this

Answer: B

CORE JAVA MCQs

70. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 == 10.0);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

71. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int a = 10;  
        int b = a++ + ++a;  
        System.out.println(b);  
    }  
}
```

- A) 21
- B) 22
- C) 23
- D) 20

Answer: B

72. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + 2 * 3);  
    }  
}
```

- A) 16
- B) 106
- C) 1023
- D) Error

Answer: B

CORE JAVA MCQs

73. Which statement about constructor is correct?

- A) Constructor has return type
- B) Constructor name is same as class name
- C) Constructor can be static
- D) Constructor cannot be overloaded

Answer: B

74. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(3 + 4 + "5" + 6);  
    }  
}
```

- A) 75
- B) 3456
- C) 75
- D) Error

Answer: A

75. Which of the following is true about interface?

- A) Can have constructors
- B) Supports multiple inheritance
- C) Cannot have methods
- D) Can be instantiated

Answer: B

76. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + 3 + "Java");  
    }  
}
```

- A) 6Java
- B) 123Java
- C) Java6

CORE JAVA MCQs

- D) Error

Answer: A

77. Which keyword is used for memory cleanup?

- A) finalize
- B) delete
- C) free
- D) destroy

Answer: A

78. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java" == new String("Java"));  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

79. Which method is used to compare content of strings?

- A) ==
- B) equals()
- C) compare()
- D) match()

Answer: B

80. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 / 3.0);  
    }  
}
```

CORE JAVA MCQs

- A) 3
- B) 3.0
- C) 3.3333
- D) Error

Answer: C

81. Which Java feature supports multiple inheritance?

- A) Class
- B) Interface
- C) Object
- D) Package

Answer: B

82. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(0 == 0.0);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

83. Which keyword is used to create thread?

- A) thread
- B) new
- C) start
- D) run

Answer: B

84. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("A" + "B" + 1 + 2 + 3);  
    }  
}
```

- A) AB6
- B) AB123
- C) 6AB
- D) Error

Answer: A

85. Which collection maintains insertion order?

- A) HashSet
- B) TreeSet
- C) LinkedHashSet
- D) HashMap

Answer: C

86. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 + 5 + "Java" + 5 * 2);  
    }  
}
```

- A) 10Java10
- B) 55Java10
- C) Java10
- D) Error

Answer: A

87. Which keyword is used for exception throwing?

- A) try
- B) catch
- C) throw
- D) finally

Answer: C

CORE JAVA MCQs

88. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int x = 5;  
        System.out.println(++x + x++);  
    }  
}
```

- A) 11
- B) 12
- C) 13
- D) 10

Answer: B

89. Which Java keyword defines constant?

- A) static
- B) final
- C) const
- D) immutable

Answer: B

90. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".substring(1,3));  
    }  
}
```

- A) Ja
- B) av
- C) va
- D) Jav

Answer: B

91. Which class is root of all Java classes?

- A) Main
- B) Object

CORE JAVA MCQs

- C) Base
- D) Root

Answer: B

92. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "30" + 40);  
    }  
}
```

- A) 303040
- B) 3030
- C) 30340
- D) Error

Answer: A

93. Which keyword is used for abstraction class?

- A) interface
- B) abstract
- C) final
- D) static

Answer: B

94. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" - 2);  
    }  
}
```

- A) 8
- B) 102
- C) NaN
- D) Error

Answer: A

CORE JAVA MCQs

95. Which method is used to get string length?

- A) size()
- B) length()
- C) count()
- D) getLength()

Answer: B

96. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true ? 1 : 2);  
    }  
}
```

- A) 1
- B) 2
- C) true
- D) Error

Answer: A

97. Which concept allows runtime method selection?

- A) Overloading
- B) Overriding
- C) Encapsulation
- D) Abstraction

Answer: B

98. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java" + 1 + 2 + 3);  
    }  
}
```

- A) Java6
- B) Java123
- C) 6Java
- D) Error

CORE JAVA MCQs

Answer: B

99. Which package contains Scanner class?

- A) java.util
- B) java.io
- C) java.lang
- D) java.net

Answer: A

100. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 < 2 < 3 < 4);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

101. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        Integer a = 127;  
        Integer b = 127;  
        System.out.println(a == b);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

102. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        Integer a = 128;  
        Integer b = 128;  
        System.out.println(a == b);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

103. Which Java concept is demonstrated by method overloading?

- A) Runtime polymorphism
- B) Compile-time polymorphism
- C) Encapsulation
- D) Abstraction

Answer: B

104. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s = "hello";  
        s.toUpperCase();  
        System.out.println(s);  
    }  
}
```

- A) HELLO
- B) hello
- C) Error
- D) null

Answer: B

105. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "Java" + 10 + 20);  
    }  
}
```

CORE JAVA MCQs

```
}  
}
```

- A) 30Java1020
- B) Java301020
- C) 30Java30
- D) Error

Answer: A

106. Which statement about constructors is correct?

- A) They can be inherited
- B) They can be overloaded
- C) They have return type
- D) They are abstract

Answer: B

107. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(0.0 == -0.0);  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

108. Which collection does NOT allow duplicates?

- A) ArrayList
- B) LinkedList
- C) HashSet
- D) Vector

Answer: C

CORE JAVA MCQs

109. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".compareTo("abd"));  
    }  
}
```

- A) positive
- B) negative
- C) 0
- D) error

Answer: B

110. Which keyword is used to prevent inheritance?

- A) static
- B) final
- C) abstract
- D) private

Answer: B

111. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 / 2);  
    }  
}
```

- A) 2.5
- B) 2
- C) 3
- D) error

Answer: B

112. Which method is used to convert string to integer?

- A) parseInt()
- B) valueOf()
- C) toInt()
- D) convert()

CORE JAVA MCQs

Answer: A

113. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java" + null);  
    }  
}
```

- A) Javanull
- B) nullJava
- C) Java
- D) Error

Answer: A

114. Which interface allows sorting using custom logic?

- A) Comparable
- B) Comparator
- C) Runnable
- D) Serializable

Answer: B

115. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + 3 + 4 + "5");  
    }  
}
```

- A) 10
- B) 105
- C) 12345
- D) Error

Answer: B

116. Which keyword is used for exception handling block cleanup?

- A) catch

CORE JAVA MCQs

- B) finally
- C) throw
- D) try

Answer: B

117. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + (2 + 3));  
    }  
}
```

- A) 105
- B) 103
- C) 53
- D) Error

Answer: A

118. Which Java memory stores local variables?

- A) Heap
- B) Stack
- C) Method Area
- D) Code Cache

Answer: B

119. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".equals("java"));  
    }  
}
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

CORE JAVA MCQs

120. Which keyword is used for interface implementation?

- A) extends
- B) implements
- C) inherit
- D) this

Answer: B

121. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int x = 10;  
        System.out.println(x > 5 ? x < 15 ? "A" : "B" : "C");  
    }  
}
```

- A) A
- B) B
- C) C
- D) Error

Answer: A

122. Which method removes duplicates in Stream API?

- A) distinct()
- B) filter()
- C) map()
- D) reduce()

Answer: A

123. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(2 + 3 * 4 - 5);  
    }  
}
```

- A) 9
- B) 10
- C) 11
- D) 7

CORE JAVA MCQs

Answer: A

124. Which keyword is used for object creation?

- A) create
- B) new
- C) alloc
- D) init

Answer: B

125. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s = "Java";  
        System.out.println(s.substring(1));  
    }  
}
```

- A) J
- B) ava
- C) Java
- D) error

Answer: B

126. Which collection maintains sorted order?

- A) HashSet
- B) TreeSet
- C) LinkedList
- D) ArrayList

Answer: B

127. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("a".hashCode() == "a".hashCode());  
    }  
}
```

CORE JAVA MCQs

- A) true
- B) false
- C) error
- D) undefined

Answer: A

128. Which keyword is used to refer current class object?

- A) this
- B) super
- C) self
- D) base

Answer: A

129. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + "3" + 4 + 5);  
    }  
}
```

- A) 3345
- B) 334
- C) 12345
- D) Error

Answer: A

130. Which Java feature supports dynamic method dispatch?

- A) Overloading
- B) Overriding
- C) Encapsulation
- D) Abstraction

Answer: B

131. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + "3" + 4 + 5);  
    }  
}
```

- A) 3345
- B) 12345
- C) 334
- D) 15

Answer: A

132. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s1 = "Java";  
        String s2 = new String("Java");  
        System.out.println(s1 == s2);  
    }  
}
```

- A) true
- B) false
- C) error
- D) undefined

Answer: B

133. Which concept is used in method overloading resolution?

- A) Runtime binding
- B) Compile-time binding
- C) Dynamic binding only
- D) Late binding

Answer: B

134. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + 2 + 3);  
    }  
}
```

CORE JAVA MCQs

- A) 15
- B) 1023
- C) 123
- D) Error

Answer: B

135. Which of the following is a marker interface?

- A) Runnable
- B) Serializable
- C) Comparator
- D) Iterable

Answer: B

136. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int a = 5;  
        System.out.println(a++ + ++a + a++);  
    }  
}
```

- A) 18
- B) 19
- C) 20
- D) 21

Answer: B

137. Which method is used to convert string to uppercase?

- A) upper()
- B) toUpperCase()
- C) uppercase()
- D) convertUpper()

Answer: B

138. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + 30 + "Java");  
    }  
}
```

- A) 60Java
- B) Java60
- C) 102030Java
- D) Error

Answer: A

139. Which keyword is used to handle multiple exceptions in one block?

- A) multi
- B) catch-multi
- C) multicatch
- D) union

Answer: C

140. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".indexOf("a"));  
    }  
}
```

- A) 0
- B) 1
- C) 2
- D) 3

Answer: B

141. Which collection allows key-value pairs?

- A) List
- B) Set
- C) Map
- D) Queue

Answer: C

CORE JAVA MCQs

142. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 / 2 * 2);  
    }  
}
```

- A) 5
- B) 4
- C) 2
- D) 6

Answer: B

143. Which keyword prevents method overriding?

- A) static
- B) final
- C) abstract
- D) this

Answer: B

144. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".replace('a', 'A'));  
    }  
}
```

- A) JAvA
- B) JAVA
- C) Java
- D) JaaA

Answer: A

145. Which method is used to compare two objects logically?

- A) ==
- B) equals()
- C) compare()

CORE JAVA MCQs

- D) match()

Answer: B

146. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(0.1 + 0.2 == 0.3);  
    }  
}
```

- A) true
- B) false
- C) error
- D) undefined

Answer: B

147. Which keyword is used for inheritance?

- A) inherit
- B) extends
- C) implements
- D) this

Answer: B

148. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".toUpperCase().charAt(1));  
    }  
}
```

- A) A
- B) B
- C) C
- D) b

Answer: B

149. Which Java feature allows runtime polymorphism?

CORE JAVA MCQs

- A) Overloading
- B) Overriding
- C) Encapsulation
- D) Abstraction

Answer: B

150. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 > 5 ? 10 < 20 ? 1 : 2 : 3);  
    }  
}
```

- A) 1
- B) 2
- C) 3
- D) error

Answer: A

151. Which method removes duplicates in Stream API?

- A) filter()
- B) distinct()
- C) map()
- D) collect()

Answer: B

152. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".substring(1,4));  
    }  
}
```

- A) Jav
- B) ava
- C) av
- D) va

Answer: B

CORE JAVA MCQs

153. Which keyword is used to refer parent class?

- A) this
- B) super
- C) base
- D) parent

Answer: B

154. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + (2 + 3) + 5);  
    }  
}
```

- A) 1055
- B) 105
- C) 10
- D) error

Answer: A

155. Which collection does NOT allow duplicates?

- A) ArrayList
- B) HashSet
- C) LinkedList
- D) Vector

Answer: B

156. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".equalsIgnoreCase("JAVA"));  
    }  
}
```

- A) true
- B) false
- C) error

CORE JAVA MCQs

- D) undefined

Answer: A

157. Which keyword is used for exception throwing?

- A) throw
- B) throws
- C) try
- D) catch

Answer: A

158. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + "3" + 4 + 5);  
    }  
}
```

- A) 3345
- B) 12345
- C) 15
- D) error

Answer: A

159. Which method is used to start a thread?

- A) run()
- B) start()
- C) execute()
- D) init()

Answer: B

160. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Hello".charAt(0) + "World".charAt(0));  
    }  
}
```

CORE JAVA MCQs

- A) HW
- B) 142
- C) 136
- D) error

Answer: B

161. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 + 2 + "3" + 4 + 5);  
    }  
}
```

- A) 7345
- B) 5345
- C) 734
- D) 52345

Answer: A

162. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s = "Java";  
        System.out.println(s.substring(0, 2) + s.charAt(2));  
    }  
}
```

- A) Jav
- B) Ja
- C) Java
- D) Jaa

Answer: A

163. Which concept allows same method name in parent and child class?

- A) Overloading
- B) Overriding
- C) Encapsulation
- D) Abstraction

Answer: B

CORE JAVA MCQs

164. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + 2 + 3 + 4);  
    }  
}
```

- A) 19
- B) 10234
- C) 23410
- D) error

Answer: B

165. Which collection maintains insertion order?

- A) HashSet
- B) TreeSet
- C) LinkedHashSet
- D) HashMap

Answer: C

166. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "30" + 40 + 50);  
    }  
}
```

- A) 30304050
- B) 30Java4050
- C) 303050
- D) error

Answer: A

167. Which keyword is used to prevent inheritance?

- A) static
- B) final
- C) abstract

CORE JAVA MCQs

- D) this

Answer: B

168. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".replace("a", "A"));  
    }  
}
```

- A) JAvA
- B) JAVA
- C) Java
- D) jAvA

Answer: A

169. Which method is used to compare string values?

- A) ==
- B) equals()
- C) compare()
- D) match()

Answer: B

170. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(2 * 3 + 4 / 2);  
    }  
}
```

- A) 8
- B) 10
- C) 7
- D) 6

Answer: A

171. Which interface is used for sorting objects?

CORE JAVA MCQs

- A) Comparator
- B) Runnable
- C) Serializable
- D) Iterable

Answer: A

172. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".compareTo("abc"));  
    }  
}
```

- A) 0
- B) 1
- C) -1
- D) error

Answer: A

173. Which keyword is used for abstraction?

- A) abstract
- B) final
- C) static
- D) this

Answer: A

174. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".charAt(1) + "Java".charAt(2));  
    }  
}
```

- A) 213
- B) 215
- C) 214
- D) 210

Answer: C

CORE JAVA MCQs

175. Which Java memory stores method calls?

- A) Heap
- B) Stack
- C) Method area
- D) Cache

Answer: B

176. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true && true || false);  
    }  
}
```

- A) true
- B) false
- C) error
- D) undefined

Answer: A

177. Which keyword is used to create object?

- A) create
- B) new
- C) alloc
- D) init

Answer: B

178. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" - 1);  
    }  
}
```

- A) 9
- B) 101
- C) error

CORE JAVA MCQs

- D) NaN

Answer: A

179. Which collection allows key-value pairs?

- A) List
- B) Set
- C) Map
- D) Queue

Answer: C

180. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".toUpperCase().length());  
    }  
}
```

- A) 3
- B) 2
- C) 4
- D) error

Answer: A

181. Which keyword is used for exception handling?

- A) try
- B) catch
- C) finally
- D) all of the above

Answer: D

182. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + 3 + "4" + 5);  
    }  
}
```

CORE JAVA MCQs

- A) 64
- B) 12345
- C) 64
- D) 345

Answer: A

183. Which method is used to remove duplicates in Set?

- A) equals()
- B) hashCode()
- C) both
- D) compare()

Answer: C

184. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 / 3 * 3);  
    }  
}
```

- A) 9
- B) 10
- C) 12
- D) 6

Answer: A

185. Which keyword is used for inheritance?

- A) inherit
- B) extends
- C) implements
- D) this

Answer: B

186. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".indexOf('a', 2));  
    }  
}
```

- A) 0
- B) 1
- C) 2
- D) 3

Answer: C

187. Which interface is used in lambda expressions?

- A) Serializable
- B) FunctionalInterface
- C) Cloneable
- D) Comparator

Answer: B

188. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 + "5" + 5 + 5);  
    }  
}
```

- A) 5555
- B) 1055
- C) 555
- D) error

Answer: A

189. Which method starts thread execution?

- A) run()
- B) start()
- C) execute()
- D) init()

Answer: B

CORE JAVA MCQs

190. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Hello".substring(1, 4));  
    }  
}
```

- A) Hel
- B) ell
- C) ello
- D) lo

Answer: B

191. Which Java feature supports runtime polymorphism?

- A) Overloading
- B) Overriding
- C) Encapsulation
- D) Abstraction

Answer: B

192. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + 30 + "Java" + 10);  
    }  
}
```

- A) 60Java10
- B) Java6010
- C) 60Java
- D) error

Answer: A

193. Which keyword is used to refer current object?

- A) this
- B) super
- C) self

CORE JAVA MCQs

- D) base

Answer: A

194. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".concat("SE").length());  
    }  
}
```

- A) 4
- B) 5
- C) 6
- D) 7

Answer: C

195. Which collection does NOT allow duplicates?

- A) ArrayList
- B) HashSet
- C) LinkedList
- D) Vector

Answer: B

196. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".compareTo("abd"));  
    }  
}
```

- A) 1
- B) 0
- C) negative
- D) error

Answer: C

197. Which keyword is used for abstraction?

CORE JAVA MCQs

- A) abstract
- B) final
- C) static
- D) this

Answer: A

198. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(2 + 3 * 4 + "Java");  
    }  
}
```

- A) 14Java
- B) 20Java
- C) 14
- D) Java14

Answer: A

199. Which method is used to get string length?

- A) size()
- B) length()
- C) count()
- D) getSize()

Answer: B

200. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true ? false ? 1 : 2 : 3);  
    }  
}
```

- A) 1
- B) 2
- C) 3
- D) error

Answer: B

CORE JAVA MCQs

201. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "Java" + 10 * 2);  
    }  
}
```

- A) 30Java20
- B) 30Java102
- C) 1020Java
- D) Java3020

Answer: A

202. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s = "Java";  
        System.out.println(s + 1 + 2 + 3);  
    }  
}
```

- A) Java123
- B) Java6
- C) 6Java
- D) Error

Answer: A

203. Which statement about Java arrays is correct?

- A) Arrays are dynamic in size
- B) Arrays store only objects
- C) Arrays are fixed in size
- D) Arrays cannot store primitives

Answer: C

204. What will be the output?

```
public class Test {  
    public static void main(String[] args) {
```

CORE JAVA MCQs

```
        int[] arr = {1, 2, 3};  
        System.out.println(arr[1] + arr[2]);  
    }  
}
```

- A) 5
- B) 6
- C) 4
- D) Error

Answer: A

205. Which concept is demonstrated by method overloading?

- A) Runtime polymorphism
- B) Compile-time polymorphism
- C) Encapsulation
- D) Abstraction

Answer: B

206. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" - 2 + 3);  
    }  
}
```

- A) 11
- B) 103
- C) 8
- D) Error

Answer: A

207. Which keyword is used to inherit a class in Java?

- A) implements
- B) extends
- C) inherit
- D) this

Answer: B

CORE JAVA MCQs

208. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 > 3 ? 10 : 20);  
    }  
}
```

- A) 10
- B) 20
- C) true
- D) false

Answer: A

209. Which of the following is NOT a feature of OOP?

- A) Encapsulation
- B) Abstraction
- C) Compilation
- D) Polymorphism

Answer: C

210. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".charAt(3));  
    }  
}
```

- A) J
- B) v
- C) a
- D) Error

Answer: C

211. Which memory area stores objects in Java?

- A) Stack
- B) Heap
- C) Register

CORE JAVA MCQs

- D) Method area

Answer: B

212. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 / 4);  
    }  
}
```

- A) 2.5
- B) 2
- C) 3
- D) Error

Answer: B

213. Which keyword is used to prevent inheritance?

- A) static
- B) final
- C) abstract
- D) this

Answer: B

214. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".equals("ABC"));  
    }  
}
```

- A) true
- B) false
- C) Error
- D) null

Answer: B

215. Which interface is used for sorting custom objects?

CORE JAVA MCQs

- A) Runnable
- B) Comparable
- C) Serializable
- D) Cloneable

Answer: B

216. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + "3" + 4 + 5);  
    }  
}
```

- A) 3345
- B) 12345
- C) 15
- D) Error

Answer: A

217. Which method starts execution of a thread?

- A) run()
- B) start()
- C) execute()
- D) init()

Answer: B

218. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s = null;  
        System.out.println(s + "Java");  
    }  
}
```

- A) Java
- B) nullJava
- C) Error
- D) Null

Answer: B

CORE JAVA MCQs

219. Which collection allows duplicate elements?

- A) Set
- B) Map
- C) List
- D) TreeSet

Answer: C

220. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".indexOf('a'));  
    }  
}
```

- A) 0
- B) 1
- C) 2
- D) 3

Answer: B

221. Which keyword is used for exception handling?

- A) try
- B) catch
- C) finally
- D) all of the above

Answer: D

222. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + (2 + 3));  
    }  
}
```

- A) 105
- B) 103
- C) 53

CORE JAVA MCQs

- D) Error

Answer: A

223. Which method is used to remove duplicates in a Set?

- A) equals()
- B) hashCode()
- C) both equals and hashCode
- D) compare()

Answer: C

224. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 + 2 * 3);  
    }  
}
```

- A) 21
- B) 11
- C) 16
- D) 15

Answer: B

225. Which keyword is used for interface implementation?

- A) extends
- B) implements
- C) inherit
- D) this

Answer: B

226. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".substring(1, 3));  
    }  
}
```

CORE JAVA MCQs

- A) Ja
- B) av
- C) va
- D) Jav

Answer: B

227. Which collection maintains sorted order?

- A) HashSet
- B) TreeSet
- C) ArrayList
- D) LinkedList

Answer: B

228. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".compareTo("abd"));  
    }  
}
```

- A) positive
- B) 0
- C) negative
- D) error

Answer: C

229. Which keyword is used to refer parent class?

- A) this
- B) super
- C) base
- D) parent

Answer: B

230. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java" + null);  
    }  
}
```

- A) Java
- B) nullJava
- C) Javanull
- D) Error

Answer: C

231. Which Java feature supports runtime polymorphism?

- A) Overloading
- B) Overriding
- C) Encapsulation
- D) Abstraction

Answer: B

232. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(0.1 + 0.2);  
    }  
}
```

- A) 0.3
- B) 0.30000000000000004
- C) 0.2
- D) Error

Answer: B

233. Which keyword is used to create object?

- A) create
- B) new
- C) object
- D) init

Answer: B

CORE JAVA MCQs

234. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true ? false : true);  
    }  
}
```

- A) true
- B) false
- C) error
- D) null

Answer: B

235. Which method is used to convert string to integer?

- A) toInt()
- B) parseInt()
- C) valueOfInt()
- D) convert()

Answer: B

236. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".toUpperCase());  
    }  
}
```

- A) java
- B) JAVA
- C) Java
- D) error

Answer: B

237. Which collection allows key-value pairs?

- A) List
- B) Set
- C) Map

CORE JAVA MCQs

- D) Queue

Answer: C

238. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "30" + 40);  
    }  
}
```

- A) 303040
- B) 3030
- C) 10203040
- D) error

Answer: A

239. Which keyword is used for abstraction?

- A) final
- B) abstract
- C) static
- D) this

Answer: B

240. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".length());  
    }  
}
```

- A) 2
- B) 3
- C) 4
- D) error

Answer: B

241. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        int a = 5;  
        System.out.println(a++ + ++a);  
    }  
}
```

- A) 10
- B) 11
- C) 12
- D) 13

Answer: C

242. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".replace('a', 'A').charAt(1));  
    }  
}
```

- A) J
- B) A
- C) v
- D) a

Answer: B

243. Which statement about == and equals() is correct?

- A) Both compare content
- B) Both compare references
- C) == compares reference, equals() compares content
- D) Both work same for strings

Answer: C

244. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("10" + 2 * 3);  
    }  
}
```

- A) 36

CORE JAVA MCQs

- B) 106
- C) 1023
- D) 610

Answer: B

245. Which collection does NOT allow duplicates and maintains sorted order?

- A) HashSet
- B) LinkedHashSet
- C) TreeSet
- D) ArrayList

Answer: C

246. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(3 + 4 + "Java" + 5 + 6);  
    }  
}
```

- A) 7Java56
- B) Java75
- C) 34Java56
- D) error

Answer: A

247. Which keyword is used to prevent method overriding?

- A) static
- B) final
- C) abstract
- D) this

Answer: B

248. What will be the output?

```
public class Test {  
    public static void main(String[] args) {
```

CORE JAVA MCQs

```
        System.out.println("abc".compareTo("ab"));  
    }  
}
```

- A) positive
- B) negative
- C) 0
- D) error

Answer: A

249. Which Java memory stores objects?

- A) Stack
- B) Heap
- C) Registers
- D) Cache

Answer: B

250. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 / 3 + 3 * 2);  
    }  
}
```

- A) 9
- B) 8
- C) 7
- D) 10

Answer: A

251. Which keyword is used for interface implementation?

- A) extends
- B) implements
- C) inherit
- D) this

Answer: B

CORE JAVA MCQs

252. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".charAt(0) + "Java".charAt(1));  
    }  
}
```

- A) 193
- B) 194
- C) 195
- D) 196

Answer: B

253. Which interface is required for lambda expressions?

- A) Serializable
- B) FunctionalInterface
- C) Cloneable
- D) Comparable

Answer: B

254. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".substring(2));  
    }  
}
```

- A) Ja
- B) va
- C) ava
- D) Jav

Answer: B

255. Which collection allows duplicate elements?

- A) Set
- B) Map
- C) List
- D) TreeSet

CORE JAVA MCQs

Answer: C

256. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + 3 + "4" + 5 + 6);  
    }  
}
```

- A) 64456
- B) 64
- C) 123456
- D) error

Answer: A

257. Which keyword is used for exception handling?

- A) try
- B) catch
- C) finally
- D) all of the above

Answer: D

258. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".indexOf('v'));  
    }  
}
```

- A) 2
- B) 3
- C) 4
- D) -1

Answer: B

259. Which method starts a thread execution?

- A) run()

CORE JAVA MCQs

- B) start()
- C) execute()
- D) init()

Answer: B

260. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true && false || true);  
    }  
}
```

- A) true
- B) false
- C) error
- D) undefined

Answer: A

261. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int x = 10;  
        x += x++ + ++x;  
        System.out.println(x);  
    }  
}
```

- A) 31
- B) 32
- C) 33
- D) 34

Answer: B

262. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s = "Java";  
        s.concat("SE");  
        System.out.println(s);  
    }  
}
```

CORE JAVA MCQs

- A) JavaSE
- B) SEJava
- C) Java
- D) error

Answer: C

263. Which concept is used when method name is same but parameters differ?

- A) Overriding
- B) Overloading
- C) Encapsulation
- D) Abstraction

Answer: B

264. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc" + 1 + 2 + 3);  
    }  
}
```

- A) abc123
- B) abc6
- C) 6abc
- D) error

Answer: A

265. Which collection does NOT allow null values in TreeSet?

- A) HashSet
- B) TreeSet
- C) ArrayList
- D) LinkedList

Answer: B

266. What will be the output?

CORE JAVA MCQs

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "Java" + 30 - 10);  
    }  
}
```

- A) 30Java20
- B) Error
- C) 30Java3010
- D) Java20

Answer: B

267. Which keyword is used to call parent class constructor?

- A) this
- B) super
- C) base
- D) parent

Answer: B

268. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".charAt(1) + "Java".charAt(3));  
    }  
}
```

- A) 211
- B) 212
- C) 213
- D) 214

Answer: B

269. Which Java feature supports data hiding?

- A) Abstraction
- B) Encapsulation
- C) Polymorphism
- D) Inheritance

Answer: B

CORE JAVA MCQs

270. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(5 > 3 ? 2 > 1 ? "A" : "B" : "C");  
    }  
}
```

- A) A
- B) B
- C) C
- D) error

Answer: A

271. Which method is used to convert string to integer?

- A) Integer.valueOf()
- B) Integer.parseInt()
- C) parse()
- D) convert()

Answer: B

272. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".substring(1, 3) + "Java".charAt(3));  
    }  
}
```

- A) ava
- B) av a
- C) av a (space)
- D) error

Answer: A

273. Which keyword is used to prevent inheritance?

- A) static
- B) final
- C) abstract

CORE JAVA MCQs

- D) private

Answer: B

274. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int[] arr = {1, 2, 3, 4};  
        System.out.println(arr[arr[2]]);  
    }  
}
```

- A) 3
- B) 4
- C) 2
- D) 1

Answer: B

275. Which collection maintains insertion order?

- A) HashSet
- B) TreeSet
- C) LinkedHashSet
- D) HashMap

Answer: C

276. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".compareTo("abc"));  
    }  
}
```

- A) 1
- B) 0
- C) -1
- D) error

Answer: B

CORE JAVA MCQs

277. Which keyword is used for abstraction?

- A) final
- B) abstract
- C) static
- D) this

Answer: B

278. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(2 + 3 + 4 + "Java" + 5 + 6);  
    }  
}
```

- A) 9Java56
- B) Java956
- C) 234Java56
- D) error

Answer: A

279. Which method returns length of array?

- A) length()
- B) size()
- C) length (property)
- D) getLength()

Answer: C

280. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true || false && false);  
    }  
}
```

- A) true
- B) false
- C) error
- D) undefined

CORE JAVA MCQs

Answer: A

281. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        int a = 5;  
        System.out.println(a++ * ++a);  
    }  
}
```

- A) 30
- B) 35
- C) 36
- D) 42

Answer: C

282. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        String s1 = "Hello";  
        String s2 = new String("Hello");  
        System.out.println(s1.equals(s2) && s1 == s2);  
    }  
}
```

- A) true
- B) false
- C) error
- D) true false

Answer: B

283. Which statement is correct about `final` keyword?

- A) final variable can be reassigned
- B) final method can be overridden
- C) final class cannot be inherited
- D) final constructor is allowed

Answer: C

CORE JAVA MCQs

284. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".compareToIgnoreCase("java"));  
    }  
}
```

- A) 0
- B) 1
- C) -1
- D) error

Answer: A

285. Which collection does NOT allow duplicates and maintains insertion order?

- A) HashSet
- B) TreeSet
- C) LinkedHashSet
- D) ArrayList

Answer: C

286. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(10 + 20 + "30" + 40 + 50);  
    }  
}
```

- A) 30304050
- B) 30Java4050
- C) 1020304050
- D) error

Answer: A

287. Which keyword is used to call parent class method?

- A) this
- B) super
- C) base
- D) parent

CORE JAVA MCQs

Answer: B

288. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".substring(2, 4));  
    }  
}
```

- A) Ja
- B) av
- C) va
- D) Jav

Answer: B

289. Which principle ensures data hiding?

- A) Inheritance
- B) Polymorphism
- C) Encapsulation
- D) Abstraction

Answer: C

290. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(3 + 4 * 2 + 6 / 3);  
    }  
}
```

- A) 11
- B) 14
- C) 13
- D) 12

Answer: B

291. Which method is used to convert integer to string?

- A) String.parse()

CORE JAVA MCQs

- B) String.valueOf()
- C) Integer.toString()
- D) both B and C

Answer: D

292. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("abc".charAt(0) + "abc".charAt(1));  
    }  
}
```

- A) 195
- B) 196
- C) 197
- D) 198

Answer: B

293. Which interface is used in collections framework for sorting?

- A) Runnable
- B) Comparator
- C) Serializable
- D) Cloneable

Answer: B

294. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".replace("J", "j").length());  
    }  
}
```

- A) 3
- B) 4
- C) 5
- D) error

Answer: B

CORE JAVA MCQs

295. Which collection allows key-value pairs?

- A) List
- B) Set
- C) Map
- D) Queue

Answer: C

296. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println("Java".indexOf("a", 2));  
    }  
}
```

- A) 1
- B) 2
- C) 3
- D) -1

Answer: C

297. Which keyword is used for abstraction in Java?

- A) final
- B) abstract
- C) static
- D) this

Answer: B

298. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(1 + 2 + "3" + 4 + 5 + 6);  
    }  
}
```

- A) 33456
- B) 334
- C) 123456
- D) error

CORE JAVA MCQs

Answer: A

299. Which method is used to check string equality ignoring case?

- A) equals()
- B) compare()
- C) equalsIgnoreCase()
- D) match()

Answer: C

300. What will be the output?

```
public class Test {  
    public static void main(String[] args) {  
        System.out.println(true && false || true && false);  
    }  
}
```

- A) true
- B) false
- C) error
- D) undefined

Answer: B
