

WPT MCQs

1. What will be the output status code if a requested webpage is not found on the server?

- A) 200
- B) 301
- C) 404
- D) 500

Answer: C

2. Which HTTP method is idempotent?

- A) POST
- B) PUT
- C) CONNECT
- D) PATCH

Answer: B

3. Which protocol provides secure communication over the web?

- A) FTP
- B) HTTP
- C) HTTPS
- D) SMTP

Answer: C

4. What will be the output?

```
<p id="demo">Hello</p>
```

```
<script>  
document.getElementById("demo").innerHTML = "World";  
</script>
```

- A) Hello
- B) World
- C) Error
- D) Blank Page

Answer: B

5. Which HTML tag is used to create a hyperlink?

WPT MCQs

- A) <link>
- B) <a>
- C) <href>
- D) <hyper>

Answer: B

6. Which CSS property changes text color?

- A) font-color
- B) text-color
- C) color
- D) background-color

Answer: C

7. What will be the output?

```
<script>
let x = 5;
let y = "5";

console.log(x == y);
</script>
```

- A) false
- B) true
- C) undefined
- D) Error

Answer: B

8. Which selector selects all paragraph elements in jQuery?

- A) \$("p")
- B) \$("#p")
- C) \$(".p")
- D) \$("paragraph")

Answer: A

9. Which HTML5 tag is used for playing videos?

WPT MCQs

- A) <media>
- B) <movie>
- C) <video>
- D) <play>

Answer: C

10. What will be the output?

```
console.log(typeof null);
```

- A) null
- B) object
- C) undefined
- D) string

Answer: B

11. Which CSS property is used for responsive layouts in Bootstrap?

- A) float
- B) flex
- C) grid system
- D) align

Answer: C

12. What does DOM stand for?

- A) Document Object Model
- B) Data Object Management
- C) Digital Ordinance Model
- D) Desktop Object Method

Answer: A

13. What will be the output?

```
let a = [1,2,3];  
console.log(a.length);
```

- A) 2

WPT MCQs

- B) 3
- C) 4
- D) Undefined

Answer: B

14. Which Bootstrap class creates a responsive container?

- A) .box
- B) .container
- C) .grid
- D) .wrapper

Answer: B

15. Which JavaScript keyword declares a block-scoped variable?

- A) var
- B) int
- C) let
- D) define

Answer: C

16. What will be the output?

```
console.log(2 + "2");
```

- A) 4
- B) 22
- C) Error
- D) undefined

Answer: B

17. Which HTTP status code indicates successful request?

- A) 404
- B) 500
- C) 302
- D) 200

WPT MCQs

Answer: D

18. Which HTML attribute specifies unique element identification?

- A) class
- B) id
- C) style
- D) name

Answer: B

19. What will be the output?

```
let x = 10;  
  
if(x > 5)  
    console.log("A");  
else  
    console.log("B");
```

- A) A
- B) B
- C) Error
- D) No Output

Answer: A

20. Which CSS property controls text size?

- A) text-style
- B) font-size
- C) text-size
- D) font-style

Answer: B

21. Which JavaScript method converts JSON string into object?

- A) JSON.stringify()
- B) JSON.object()
- C) JSON.parse()
- D) JSON.convert()

WPT MCQs

Answer: C

22. What will be the output?

```
console.log(Boolean(0));
```

- A) true
- B) false
- C) undefined
- D) Error

Answer: B

23. Which HTML tag is used for unordered lists?

- A)
- B)
- C)
- D) <list>

Answer: B

24. Which JavaScript method adds element at array end?

- A) shift()
- B) unshift()
- C) push()
- D) pop()

Answer: C

25. What will be the output?

```
let x = "10";  
let y = 2;
```

```
console.log(x - y);
```

- A) 8
- B) 102
- C) Error
- D) NaN

WPT MCQs

Answer: A

26. Which Bootstrap class is used for buttons?

- A) .button
- B) .btn
- C) .click-btn
- D) .bootstrap-btn

Answer: B

27. Which JavaScript operator checks both value and datatype?

- A) ==
- B) =
- C) ===
- D) !=

Answer: C

28. What will be the output?

```
for(let i=1;i<=3;i++){  
    console.log(i);  
}
```

- A) 123
- B) 1 2 3
- C) Infinite Loop
- D) Error

Answer: B

29. Which event occurs when user clicks HTML element?

- A) onchange
- B) onmouseover
- C) onclick
- D) onsubmit

Answer: C

WPT MCQs

30. Which jQuery symbol is used to access jQuery?

- A) #
- B) \$
- C) &
- D) @

Answer: B

31. What will be the output?

```
let arr = [10,20,30];  
console.log(arr[1]);
```

- A) 10
- B) 20
- C) 30
- D) undefined

Answer: B

32. Which CSS property adds space inside border?

- A) margin
- B) spacing
- C) padding
- D) border-spacing

Answer: C

33. Which HTML tag is used to insert image?

- A) <image>
- B) <pic>
- C)
- D) <src>

Answer: C

34. What will be the output?

WPT MCQs

```
console.log(typeof []);
```

- A) array
- B) object
- C) list
- D) undefined

Answer: B

35. Which JavaScript function delays execution?

- A) delay()
- B) timeout()
- C) setTimeout()
- D) setDelay()

Answer: C

36. Which HTTP method is mainly used to retrieve data?

- A) POST
- B) GET
- C) DELETE
- D) PUT

Answer: B

37. What will be the output?

```
let x = 5;  
console.log(++x);
```

- A) 5
- B) 6
- C) 7
- D) Error

Answer: B

38. Which CSS property changes background color?

- A) color

WPT MCQs

- B) bg-color
- C) background-color
- D) bgcolor

Answer: C

39. Which React component type uses hooks?

- A) Class Component
- B) Functional Component
- C) Pure Component
- D) Parent Component

Answer: B

40. What will be the output?

```
console.log("5" + 1);
```

- A) 6
- B) 51
- C) Error
- D) undefined

Answer: B

41. Which method removes last array element?

- A) shift()
- B) push()
- C) pop()
- D) splice()

Answer: C

42. Which HTML tag creates table row?

- A) <td>
- B) <th>
- C) <tr>
- D) <table-row>

WPT MCQs

Answer: C

43. What will be the output?

```
console.log(10 == "10");
```

- A) false
- B) true
- C) Error
- D) undefined

Answer: B

44. Which Bootstrap class creates danger button?

- A) .btn-alert
- B) .btn-red
- C) .btn-danger
- D) .danger-btn

Answer: C

45. Which JavaScript method converts object into JSON string?

- A) JSON.parse()
- B) JSON.stringify()
- C) JSON.convert()
- D) JSON.object()

Answer: B

46. What will be the output?

```
let x = [1,2];  
x.push(3);
```

```
console.log(x.length);
```

- A) 2
- B) 3
- C) 4
- D) undefined

WPT MCQs

Answer: B

47. Which keyword is used to define class in JavaScript?

- A) function
- B) object
- C) class
- D) define

Answer: C

48. Which HTML tag defines form?

- A) <input>
- B) <form>
- C) <fieldset>
- D) <label>

Answer: B

49. What will be the output?

```
console.log(typeof "Hello");
```

- A) object
- B) string
- C) text
- D) undefined

Answer: B

50. Which Node.js module handles file operations?

- A) os
- B) path
- C) fs
- D) http

Answer: C

WPT MCQs

51. What will be the output?

```
console.log(0 == false);
```

- A) false
- B) true
- C) Error
- D) undefined

Answer: B

52. Which HTML attribute is used to specify input placeholder text?

- A) value
- B) text
- C) placeholder
- D) hint

Answer: C

53. What will be the output?

```
let arr = [1,2,3];  
console.log(arr.pop());
```

- A) 1
- B) 2
- C) 3
- D) undefined

Answer: C

54. Which HTTP status code represents "Unauthorized"?

- A) 200
- B) 301
- C) 401
- D) 500

Answer: C

55. What will be the output?

WPT MCQs

```
console.log(typeof NaN);
```

- A) number
- B) NaN
- C) undefined
- D) object

Answer: A

56. Which CSS property makes text bold?

- A) font-weight
- B) text-style
- C) font-style
- D) bold

Answer: A

57. What will be the output?

```
let x = 10;

function test() {
  let x = 20;
  console.log(x);
}

test();
```

- A) 10
- B) 20
- C) undefined
- D) Error

Answer: B

58. Which method adds element at beginning of array?

- A) push()
- B) pop()
- C) unshift()
- D) shift()

Answer: C

WPT MCQs

59. What will be the output?

```
console.log("5" - "2");
```

- A) 52
- B) 3
- C) Error
- D) NaN

Answer: B

60. Which HTML tag is used for dropdown?

- A) <select>
- B) <dropdown>
- C) <list>
- D) <option>

Answer: A

61. What will be the output?

```
console.log(1 + true);
```

- A) 1
- B) 2
- C) true1
- D) Error

Answer: B

62. Which jQuery method hides an element?

- A) hide()
- B) remove()
- C) delete()
- D) none()

Answer: A

WPT MCQs

63. What will be the output?

```
let x = [10,20,30];  
console.log(x.includes(20));
```

- A) false
- B) true
- C) undefined
- D) Error

Answer: B

64. Which tag is used to define a table header cell?

- A) <td>
- B) <tr>
- C) <th>
- D) <thead>

Answer: C

65. What will be the output?

```
console.log("Hello".length);
```

- A) 4
- B) 5
- C) 6
- D) undefined

Answer: B

66. Which HTTP method is used to update data partially?

- A) GET
- B) POST
- C) PUT
- D) PATCH

Answer: D

67. What will be the output?

WPT MCQs

```
console.log([] == false);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

68. Which JavaScript method converts string to integer?

- A) parseInt()
- B) toNumber()
- C) Number.parse()
- D) int()

Answer: A

69. What will be the output?

```
let x = 3;  
console.log(x ** 2);
```

- A) 6
- B) 9
- C) 3
- D) Error

Answer: B

70. Which React feature manages component state?

- A) Props
- B) Hooks
- C) DOM
- D) Routes

Answer: B

71. What will be the output?

```
console.log(typeof function() {});
```

WPT MCQs

- A) function
- B) object
- C) undefined
- D) null

Answer: A

72. Which HTML tag is used for line break?

- A)

- B) <lb>
- C) <break>
- D) <hr>

Answer: A

73. What will be the output?

```
console.log(10 > 5 > 1);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

74. Which method is used to parse JSON in JavaScript?

- A) JSON.parse()
- B) JSON.stringify()
- C) JSON.convert()
- D) JSON.read()

Answer: A

75. What will be the output?

```
let a = [1,2,3];  
delete a[1];  
console.log(a.length);
```

- A) 2

WPT MCQs

- B) 3
- C) 1
- D) Error

Answer: B

76. Which Bootstrap class is used for alerts?

- A) .warning
- B) .alert
- C) .message
- D) .notice

Answer: B

77. What will be the output?

```
console.log(null == undefined);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

78. Which HTML tag is used for navigation links?

- A) <nav>
- B) <menu>
- C) <links>
- D) <navigate>

Answer: A

79. What will be the output?

```
console.log(2 + 2 + "2");
```

- A) 222
- B) 42
- C) 4

WPT MCQs

- D) Error

Answer: B

80. Which method removes first element of array?

- A) pop()
- B) shift()
- C) unshift()
- D) slice()

Answer: B

81. What will be the output?

```
console.log(typeof undefined);
```

- A) null
- B) undefined
- C) object
- D) string

Answer: B

82. Which HTTP method is safe and idempotent?

- A) POST
- B) DELETE
- C) GET
- D) PATCH

Answer: C

83. What will be the output?

```
console.log([1,2] + [3,4]);
```

- A) 1,2,3,4
- B) 1,23,4
- C) 1,23,4 (string)
- D) Error

WPT MCQs

Answer: C

84. Which JavaScript object is used for timing events?

- A) Time
- B) Window
- C) Date
- D) Timer

Answer: B

85. What will be the output?

```
console.log(!"false");
```

- A) false
- B) true
- C) undefined
- D) Error

Answer: B

86. Which HTML tag is used for embedding audio?

- A) <sound>
- B) <audio>
- C) <music>
- D) <media>

Answer: B

87. What will be the output?

```
console.log(5 + null);
```

- A) 5
- B) 0
- C) 5
- D) 6

Answer: A

WPT MCQs

88. Which jQuery method is used for animation?

- A) animate()
- B) move()
- C) motion()
- D) effect()

Answer: A

89. What will be the output?

```
console.log(3 == "3" && 3 === "3");
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

90. Which Node.js module is used for creating server?

- A) fs
- B) http
- C) url
- D) path

Answer: B

91. What will be the output?

```
console.log(10 / 0);
```

- A) 0
- B) Infinity
- C) Error
- D) undefined

Answer: B

WPT MCQs

92. Which HTML tag defines section in document?

- A) <section>
- B) <div>
- C) <part>
- D) <block>

Answer: A

93. What will be the output?

```
console.log("5" * "2");
```

- A) 52
- B) 10
- C) Error
- D) NaN

Answer: B

94. Which method is used to convert string to uppercase?

- A) upperCase()
- B) toUpperCase()
- C) uppercase()
- D) convertUpper()

Answer: B

95. What will be the output?

```
console.log([1,2,3].indexOf(2));
```

- A) 0
- B) 1
- C) 2
- D) -1

Answer: B

96. Which HTML attribute makes input required?

WPT MCQs

- A) mandatory
- B) required
- C) validate
- D) important

Answer: B

97. What will be the output?

```
console.log(typeof (typeof 10));
```

- A) number
- B) string
- C) undefined
- D) object

Answer: B

98. Which React concept passes data to components?

- A) State
- B) Props
- C) Hooks
- D) Lifecycle

Answer: B

99. What will be the output?

```
console.log(0.1 + 0.2 === 0.3);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

100. Which JavaScript feature handles asynchronous operations cleanly?

- A) callbacks
- B) loops

WPT MCQs

- C) promises
- D) variables

Answer: C

101. What will be the output?

```
console.log([] + []);
```

- A) []
- B) ""
- C) undefined
- D) Error

Answer: B

102. What will be the output?

```
console.log([] == ![]);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

103. Which HTTP status code indicates "Resource created successfully"?

- A) 200
- B) 201
- C) 204
- D) 301

Answer: B

104. What will be the output?

```
console.log(typeof NaN === typeof Number("abc"));
```

- A) true
- B) false

WPT MCQs

- C) Error
- D) undefined

Answer: A

105. Which HTML tag is used to group form elements?

- A) <fieldset>
- B) <group>
- C) <formset>
- D) <section>

Answer: A

106. What will be the output?

```
let x = [1,2,3];  
x[10] = 5;  
console.log(x.length);
```

- A) 3
- B) 4
- C) 10
- D) 11

Answer: D

107. Which CSS property is used for stacking elements?

- A) z-index
- B) stack-order
- C) layer
- D) position-index

Answer: A

108. What will be the output?

```
console.log("2" - 1 + 1);
```

- A) 2
- B) 11
- C) 21

WPT MCQs

- D) Error

Answer: A

109. Which JavaScript keyword creates a constant reference?

- A) let
- B) var
- C) const
- D) fixed

Answer: C

110. What will be the output?

```
console.log(true + true + true);
```

- A) 1
- B) 2
- C) 3
- D) true

Answer: C

111. Which method is used to stop event bubbling?

- A) stopPropagation()
- B) preventDefault()
- C) stopEvent()
- D) cancelBubble()

Answer: A

112. What will be the output?

```
console.log(10 > 5 > 2);
```

- A) true
- B) false
- C) Error
- D) undefined

WPT MCQs

Answer: B

113. Which Node.js function reads file asynchronously?

- A) fs.readFile()
- B) fs.open()
- C) fs.load()
- D) fs.get()

Answer: A

114. What will be the output?

```
console.log("hello".charAt(1));
```

- A) h
- B) e
- C) l
- D) o

Answer: B

115. Which HTML tag is used for metadata?

- A) <meta>
- B) <data>
- C) <head>
- D) <info>

Answer: A

116. What will be the output?

```
console.log(3 + 4 + "5");
```

- A) 12
- B) 75
- C) 345
- D) Error

Answer: B

WPT MCQs

117. Which jQuery method changes HTML content?

- A) text()
- B) html()
- C) val()
- D) change()

Answer: B

118. What will be the output?

```
console.log("10" > "2");
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

119. Which JavaScript method removes whitespace from both ends?

- A) trim()
- B) strip()
- C) clean()
- D) cut()

Answer: A

120. What will be the output?

```
console.log(typeof (null + 1));
```

- A) number
- B) object
- C) undefined
- D) NaN

Answer: A

WPT MCQs

121. Which Bootstrap component creates navigation bar?

- A) navbar
- B) navbox
- C) navigation
- D) header-bar

Answer: A

122. What will be the output?

```
let a = 5;  
let b = a++;  
console.log(b);
```

- A) 5
- B) 6
- C) 4
- D) undefined

Answer: A

123. Which HTTP method is used for deleting data?

- A) GET
- B) POST
- C) DELETE
- D) REMOVE

Answer: C

124. What will be the output?

```
console.log([] + 1 + 2);
```

- A) 12
- B) 3
- C) "12"
- D) Error

Answer: C

125. Which JavaScript method checks condition for all array elements?

WPT MCQs

- A) some()
- B) every()
- C) filter()
- D) map()

Answer: B

126. What will be the output?

```
console.log(2 ** 3 ** 2);
```

- A) 64
- B) 512
- C) 256
- D) Error

Answer: B

127. Which HTML attribute specifies alternative text for image?

- A) title
- B) alt
- C) src
- D) desc

Answer: B

128. What will be the output?

```
console.log(1 < 2 < 3);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

129. Which JavaScript structure handles asynchronous flow better than callbacks?

- A) loops
- B) promises

WPT MCQs

- C) arrays
- D) objects

Answer: B

130. What will be the output?

```
console.log("5" + 3 - 1);
```

- A) 52
- B) 532
- C) 53
- D) Error

Answer: A

131. Which DOM method selects element by class?

- A) getElementById
- B) querySelector
- C) getElementsByClassName
- D) Both B and C

Answer: D

132. What will be the output?

```
console.log(!!0);
```

- A) true
- B) false
- C) undefined
- D) Error

Answer: B

133. Which HTML tag is used for embedding external page?

- A) <embed>
- B) <iframe>
- C) <frame>
- D) <external>

WPT MCQs

Answer: B

134. What will be the output?

```
console.log(typeof ({} + []));
```

- A) string
- B) object
- C) undefined
- D) Error

Answer: A

135. Which JavaScript feature is used in React for passing data?

- A) State
- B) Props
- C) Hooks
- D) Events

Answer: B

136. What will be the output?

```
console.log(5 == "5" == true);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

137. Which method is used to send HTTP request in Axios?

- A) axios.send()
- B) axios.request()
- C) axios.get()
- D) Both B and C

Answer: D

WPT MCQs

138. What will be the output?

```
console.log([] == 0);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

139. Which JavaScript method executes after delay repeatedly?

- A) setTimeout
- B) setInterval
- C) delayLoop
- D) repeat

Answer: B

140. What will be the output?

```
console.log("0" == false);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

141. Which Node.js module provides event-driven architecture?

- A) events
- B) fs
- C) http
- D) url

Answer: A

WPT MCQs

142. What will be the output?

```
console.log(3 + 2 + "1");
```

- A) 321
- B) 51
- C) 6
- D) Error

Answer: B

143. Which CSS unit is relative to viewport width?

- A) px
- B) em
- C) vw
- D) rem

Answer: C

144. What will be the output?

```
console.log("abc" > "abd");
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

145. Which method converts string to lowercase?

- A) lower()
- B) toLowerCase()
- C) lowercase()
- D) changeCase()

Answer: B

146. What will be the output?

WPT MCQs

```
console.log(null == 0);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

147. Which HTML tag is used for scalable graphics?

- A) <canvas>
- B) <svg>
- C) <graphic>
- D) <vector>

Answer: B

148. What will be the output?

```
console.log(1 + "1" - 1);
```

- A) 10
- B) 11
- C) 1
- D) Error

Answer: A

149. Which JavaScript function converts callback-based function into promise?

- A) promisify
- B) asyncify
- C) convertPromise
- D) wrap

Answer: A

150. What will be the output?

```
console.log(typeof (function() {} ()))
```

WPT MCQs

- A) function
- B) object
- C) undefined
- D) string

Answer: C

151. What will be the output?

```
console.log([] + {});
```

- A) "[object Object]"
- B) "{}"
- C) "undefined"
- D) Error

Answer: A

152. What will be the output?

```
console.log({} + []);
```

- A) "[object Object]"
- B) 0
- C) "[object Object]" (string)
- D) Error

Answer: D

153. Which HTTP status code is used for "Forbidden"?

- A) 401
- B) 403
- C) 404
- D) 405

Answer: B

154. What will be the output?

```
console.log("10" - - "5");
```

WPT MCQs

- A) 5
- B) 15
- C) 105
- D) Error

Answer: B

155. Which HTML attribute is required for form submission URL?

- A) method
- B) action
- C) target
- D) href

Answer: B

156. What will be the output?

```
console.log(1 < 2 < 1);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

157. Which JavaScript method removes elements from array?

- A) splice()
- B) slice()
- C) remove()
- D) cut()

Answer: A

158. What will be the output?

```
console.log(typeof (function(){}));
```

- A) function
- B) object

WPT MCQs

- C) undefined
- D) string

Answer: A

159. Which CSS property controls element visibility without removing layout space?

- A) display
- B) visibility
- C) opacity
- D) hidden

Answer: B

160. What will be the output?

```
console.log(+ "10" + 10);
```

- A) 1010
- B) 20
- C) 10
- D) Error

Answer: B

161. Which HTML tag is used for semantic navigation?

- A) <div>
- B) <nav>
- C) <menu>
- D) <section>

Answer: B

162. What will be the output?

```
console.log([] == ![] == []);
```

- A) true
- B) false
- C) Error

WPT MCQs

- D) undefined

Answer: B

163. Which JavaScript feature helps avoid callback hell?

- A) loops
- B) promises
- C) variables
- D) arrays

Answer: B

164. What will be the output?

```
console.log(3 > 2 > 1);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

165. Which method converts JSON to string?

- A) JSON.parse()
- B) JSON.stringify()
- C) JSON.convert()
- D) JSON.encode()

Answer: B

166. What will be the output?

```
console.log(typeof (Infinity));
```

- A) number
- B) infinity
- C) undefined
- D) object

WPT MCQs

Answer: A

167. Which DOM event triggers when input value changes?

- A) onclick
- B) onchange
- C) oninput
- D) onsubmit

Answer: C

168. What will be the output?

```
console.log(0.1 + 0.2);
```

- A) 0.3
- B) 0.30000000000000004
- C) 0.2
- D) Error

Answer: B

169. Which Node.js method writes file asynchronously?

- A) fs.writeFileSync
- B) fs.writeFile
- C) fs.saveFile
- D) fs.createFile

Answer: B

170. What will be the output?

```
console.log("5" + -"2");
```

- A) 52
- B) 3
- C) 53
- D) Error

Answer: B

WPT MCQs

171. Which JavaScript keyword is hoisted but undefined initially?

- A) let
- B) const
- C) var
- D) class

Answer: C

172. What will be the output?

```
console.log(!![]);
```

- A) false
- B) true
- C) undefined
- D) Error

Answer: B

173. Which HTTP method is safe but not idempotent?

- A) GET
- B) DELETE
- C) POST
- D) PUT

Answer: C

174. What will be the output?

```
console.log("true" == true);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

WPT MCQs

175. Which HTML attribute prevents form submission?

- A) disabled
- B) readonly
- C) novalidate
- D) hidden

Answer: C

176. What will be the output?

```
console.log([10] + [10]);
```

- A) 20
- B) 1010
- C) 10,10
- D) Error

Answer: B

177. Which React feature manages side effects?

- A) useState
- B) useEffect
- C) useRef
- D) useMemo

Answer: B

178. What will be the output?

```
console.log("10" > 2 > 1);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

179. Which method is used to traverse DOM in jQuery?

WPT MCQs

- A) find()
- B) search()
- C) locate()
- D) traverse()

Answer: A

180. What will be the output?

```
console.log(2 + 3 + "4" + 5);
```

- A) 54
- B) 2345
- C) 54
- D) Error

Answer: A

181. Which JavaScript function runs after Promise resolves?

- A) then()
- B) catch()
- C) resolve()
- D) finallyOnly()

Answer: A

182. What will be the output?

```
console.log(typeof null === typeof {});
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

183. Which Bootstrap class makes image responsive?

- A) .img-fluid
- B) .img-responsive

WPT MCQs

- C) .responsive-img
- D) .fluid-img

Answer: A

184. What will be the output?

```
console.log("5" * null);
```

- A) 0
- B) 5
- C) NaN
- D) Error

Answer: A

185. Which method is used to stop interval execution?

- A) stopInterval()
- B) clearInterval()
- C) cancelInterval()
- D) endInterval()

Answer: B

186. What will be the output?

```
console.log([1,2,3].map(x => x * 2));
```

- A) [2,4,6]
- B) [1,2,3]
- C) 6
- D) Error

Answer: A

187. Which Node.js module handles URLs?

- A) fs
- B) http
- C) url
- D) path

WPT MCQs

Answer: C

188. What will be the output?

```
console.log(3 + 2 + 1 == "6");
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

189. Which JavaScript feature is used for destructuring?

- A) arrays
- B) objects
- C) both arrays and objects
- D) loops

Answer: C

190. What will be the output?

```
console.log([] + 0);
```

- A) 0
- B) "0"
- C) ""
- D) Error

Answer: B

191. Which HTML tag is used for drawing graphics dynamically?

- A) <svg>
- B) <canvas>
- C) <draw>
- D) <graphic>

Answer: B

WPT MCQs

192. What will be the output?

```
console.log(5 + "5" - 5);
```

- A) 50
- B) 50
- C) 0
- D) Error

Answer: A

193. Which JavaScript method checks condition in array?

- A) filter()
- B) map()
- C) reduce()
- D) forEach()

Answer: A

194. What will be the output?

```
console.log("abc" + + "def");
```

- A) abcNaN
- B) abcdef
- C) Error
- D) undefined

Answer: A

195. Which HTTP status code indicates server error?

- A) 200
- B) 300
- C) 400
- D) 500

Answer: D

WPT MCQs

196. What will be the output?

```
console.log(!!" ");
```

- A) false
- B) true
- C) undefined
- D) Error

Answer: B

197. Which React concept improves performance by memoization?

- A) useState
- B) useEffect
- C) useMemo
- D) useRef

Answer: C

198. What will be the output?

```
console.log([] == 0 == false);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

199. Which JavaScript operator spreads elements?

- A) ...
- B) ##
- C) @@
- D) &&&

Answer: A

200. What will be the output?

WPT MCQs

```
console.log("10" - "5" + "2");
```

- A) 7
- B) 52
- C) 5
- D) Error

Answer: B

201. What will be the output?

```
console.log(1 + "2" + 3 - 4);
```

- A) 123-4
- B) 121
- C) 119
- D) NaN

Answer: C

202. What will be the output?

```
console.log([] == ![]);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

203. Which statement about HTTP is correct?

- A) It is stateful
- B) It is stateless
- C) It uses persistent memory
- D) It requires cookies always

Answer: B

204. What will be the output?

```
console.log(typeof typeof 10);
```

WPT MCQs

- A) number
- B) string
- C) undefined
- D) object

Answer: B

205. Which method is used to send data securely in HTTP?

- A) GET
- B) POST
- C) PUT
- D) HTTPS

Answer: B

206. What will be the output?

```
console.log(3 < 2 < 1);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

207. Which DOM method returns NodeList?

- A) getElementById
- B) querySelector
- C) getElementsByClassName
- D) Both B and C

Answer: D

208. What will be the output?

```
console.log("5" + + "5");
```

- A) 55
- B) 10

WPT MCQs

- C) 5NaN
- D) Error

Answer: B

209. Which HTTP status code means "Redirect"?

- A) 200
- B) 201
- C) 301
- D) 500

Answer: C

210. What will be the output?

```
console.log([] + [] + 1);
```

- A) 1
- B) "1"
- C) 0
- D) Error

Answer: B

211. Which JavaScript concept allows function inside function?

- A) Encapsulation
- B) Closure
- C) Inheritance
- D) Overloading

Answer: B

212. What will be the output?

```
console.log(1 == "1" == "1");
```

- A) true
- B) false
- C) Error
- D) undefined

WPT MCQs

Answer: B

213. Which HTML tag is used for embedding JavaScript?

- A) <script>
- B) <js>
- C) <code>
- D) <javascript>

Answer: A

214. What will be the output?

```
console.log("2" * "3" + "4");
```

- A) 6
- B) 64
- C) 10
- D) Error

Answer: B

215. Which Node.js module is used for HTTP server?

- A) fs
- B) http
- C) url
- D) events

Answer: B

216. What will be the output?

```
console.log(null + 1);
```

- A) null
- B) 1
- C) 0
- D) NaN

Answer: B

WPT MCQs

217. Which JavaScript function handles asynchronous code better?

- A) callback
- B) promise
- C) async/await
- D) all of the above

Answer: D

218. What will be the output?

```
console.log("10" - 5 - "2");
```

- A) 3
- B) 5
- C) 2
- D) Error

Answer: A

219. Which Bootstrap class hides element?

- A) .hidden
- B) .d-none
- C) .hide
- D) .remove

Answer: B

220. What will be the output?

```
console.log([] == 0);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

WPT MCQs

221. Which JavaScript operator is right-associative?

- A) +
- B) -
- C) =
- D) *

Answer: C

222. What will be the output?

```
console.log("5" - - 1);
```

- A) 4
- B) 6
- C) 51
- D) Error

Answer: B

223. Which HTML tag is used for grouping inline elements?

- A) <div>
- B)
- C) <section>
- D) <block>

Answer: B

224. What will be the output?

```
console.log(0.1 + 0.2 == 0.3);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

225. Which method is used to stop event default behavior?

WPT MCQs

- A) stopPropagation()
- B) preventDefault()
- C) stopEvent()
- D) cancel()

Answer: B

226. What will be the output?

```
console.log(" " == false);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

227. Which JavaScript method converts string to number?

- A) Number()
- B) parseInt()
- C) parseFloat()
- D) All of the above

Answer: D

228. What will be the output?

```
console.log([] + 1 + []);
```

- A) 1
- B) "1"
- C) "1"
- D) Error

Answer: B

229. Which React concept allows component reuse?

- A) Props
- B) Hooks

WPT MCQs

- C) State
- D) Lifecycle

Answer: A

230. What will be the output?

```
console.log(2 + 3 + "4" + 5 + 6);
```

- A) 5546
- B) 546
- C) 23456
- D) Error

Answer: A

231. Which HTTP method is idempotent but not safe?

- A) GET
- B) POST
- C) PUT
- D) DELETE

Answer: C

232. What will be the output?

```
console.log(typeof (undefined + 1));
```

- A) number
- B) undefined
- C) NaN
- D) object

Answer: A

233. Which JavaScript structure is used for key-value pairs?

- A) array
- B) object
- C) list
- D) set

WPT MCQs

Answer: B

234. What will be the output?

```
console.log("5" > 2 > 1);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

235. Which DOM property changes HTML content?

- A) innerText
- B) innerHTML
- C) textContent
- D) all of the above

Answer: D

236. What will be the output?

```
console.log(3 + 4 + 5 == "12");
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

237. Which JavaScript method is used for scheduling execution once?

- A) setInterval
- B) setTimeout
- C) delay
- D) wait

Answer: B

WPT MCQs

238. What will be the output?

```
console.log([] == [] );
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

239. Which HTTP header carries JSON data type?

- A) Content-Type
- B) Data-Type
- C) Accept-JSON
- D) Type

Answer: A

240. What will be the output?

```
console.log(+ "100" + + "20");
```

- A) 120
- B) 10020
- C) 80
- D) Error

Answer: A

241. What will be the output?

```
console.log([] + {} + []);
```

- A) "[object Object]"
- B) "[object Object]undefined"
- C) "undefined"
- D) Error

Answer: A

WPT MCQs

242. What will be the output?

```
console.log({} + [] + {});
```

- A) "[object Object][object Object]"
- B) "[object Object]"
- C) Error
- D) NaN

Answer: C

243. Which statement is true about JavaScript event loop?

- A) Executes synchronous code first
- B) Executes callbacks before main thread
- C) Runs only promises
- D) Blocks execution until completion

Answer: A

244. What will be the output?

```
console.log(typeof (function() {}));
```

- A) function
- B) object
- C) undefined
- D) string

Answer: A

245. Which HTTP method is used for partial updates?

- A) PUT
- B) PATCH
- C) POST
- D) UPDATE

Answer: B

WPT MCQs

246. What will be the output?

```
console.log("10" + -"10");
```

- A) 0
- B) 1010
- C) "10-10"
- D) NaN

Answer: D

247. Which JavaScript feature allows default parameter values?

- A) ES5
- B) ES6
- C) ES3
- D) ES1

Answer: B

248. What will be the output?

```
console.log(1 + 2 + "3" + 4 + 5);
```

- A) 3345
- B) 3345
- C) 12345
- D) Error

Answer: A

249. Which DOM method removes element?

- A) deleteElement
- B) removeChild
- C) erase
- D) destroy

Answer: B

250. What will be the output?

WPT MCQs

```
console.log([] == false == ![]);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

251. Which React concept improves performance by avoiding unnecessary re-renders?

- A) useState
- B) React.memo
- C) useEffect
- D) props drilling

Answer: B

252. What will be the output?

```
console.log("5" * null + 1);
```

- A) 1
- B) 0
- C) NaN
- D) 5

Answer: A

253. Which HTTP status code indicates "Bad Request"?

- A) 400
- B) 401
- C) 403
- D) 404

Answer: A

254. What will be the output?

```
console.log(typeof (null + null));
```

WPT MCQs

- A) number
- B) object
- C) undefined
- D) NaN

Answer: A

255. Which JavaScript method flattens array?

- A) flatten()
- B) flat()
- C) merge()
- D) reduce()

Answer: B

256. What will be the output?

```
console.log("2" * "3" + "4" - 1);
```

- A) 5
- B) 64
- C) 6
- D) Error

Answer: A

257. Which Node.js feature handles asynchronous operations?

- A) blocking I/O
- B) event loop
- C) threads only
- D) compiler

Answer: B

258. What will be the output?

```
console.log([] + [] == 0);
```

- A) true
- B) false

WPT MCQs

- C) Error
- D) undefined

Answer: A

259. Which JavaScript keyword defines asynchronous function?

- A) async
- B) await
- C) promise
- D) defer

Answer: A

260. What will be the output?

```
console.log(1 < 2 < 3 < 4);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

261. What will be the output?

```
console.log([] + 1);
```

- A) 1
- B) "1"
- C) 0
- D) Error

Answer: B

262. What will be the output?

```
console.log(1 + true + false);
```

- A) 1
- B) 2

WPT MCQs

- C) 3
- D) Error

Answer: B

263. Which HTTP status code means "Not Modified"?

- A) 200
- B) 301
- C) 304
- D) 404

Answer: C

264. What will be the output?

```
console.log("5" - true);
```

- A) 4
- B) 5
- C) 6
- D) NaN

Answer: A

265. Which method is used in React to update state?

- A) setState
- B) updateState
- C) changeState
- D) modifyState

Answer: A

266. What will be the output?

```
console.log(typeof (NaN == NaN));
```

- A) boolean
- B) number
- C) undefined
- D) object

WPT MCQs

Answer: A

267. Which HTML tag is used for inline styling?

- A) <css>
- B) <style>
- C) style attribute
- D) <script>

Answer: C

268. What will be the output?

```
console.log([] == ![]);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

269. Which JavaScript method is used for scheduling repeated execution?

- A) setTimeout
- B) setInterval
- C) repeat
- D) loopTimer

Answer: B

270. What will be the output?

```
console.log("10" * null);
```

- A) 0
- B) 10
- C) NaN
- D) Error

Answer: A

WPT MCQs

271. Which React feature allows sharing state globally?

- A) Props
- B) Context API
- C) Hooks only
- D) DOM

Answer: B

272. What will be the output?

```
console.log(3 + 2 + "1" - 1);
```

- A) 321
- B) 51
- C) 30
- D) Error

Answer: B

273. Which HTTP method is used to create a new resource?

- A) GET
- B) POST
- C) DELETE
- D) PATCH

Answer: B

274. What will be the output?

```
console.log([] + {} == {} + []);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

WPT MCQs

275. Which JavaScript concept prevents direct access to variables?

- A) Inheritance
- B) Encapsulation
- C) Polymorphism
- D) Abstraction only

Answer: B

276. What will be the output?

```
console.log("5" + 2 * 3);
```

- A) 11
- B) 56
- C) 10
- D) Error

Answer: B

277. Which Node.js module is used for file paths?

- A) fs
- B) path
- C) url
- D) http

Answer: B

278. What will be the output?

```
console.log(!!"0");
```

- A) false
- B) true
- C) undefined
- D) Error

Answer: B

279. Which JavaScript method removes last element?

WPT MCQs

- A) shift()
- B) pop()
- C) slice()
- D) remove()

Answer: B

280. What will be the output?

```
console.log("2" + 2 - 2);
```

- A) 20
- B) 22
- C) 2
- D) NaN

Answer: C

281. Which HTML tag defines form input field?

- A) <input>
- B) <field>
- C) <textbox>
- D) <data>

Answer: A

282. What will be the output?

```
console.log(typeof ({} + []));
```

- A) object
- B) string
- C) undefined
- D) Error

Answer: B

283. Which JavaScript method filters array elements?

- A) map()
- B) filter()

WPT MCQs

- C) reduce()
- D) find()

Answer: B

284. What will be the output?

```
console.log("10" > "2");
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: B

285. Which CSS property controls spacing outside element?

- A) padding
- B) margin
- C) border
- D) spacing

Answer: B

286. What will be the output?

```
console.log(null == undefined);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

287. Which React hook is used for referencing DOM elements?

- A) useState
- B) useEffect
- C) useRef
- D) useMemo

WPT MCQs

Answer: C

288. What will be the output?

```
console.log("5" - "2" + "1");
```

- A) 31
- B) 3
- C) 21
- D) Error

Answer: A

289. Which JavaScript feature allows waiting for async operations?

- A) callbacks
- B) promises
- C) async/await
- D) all of the above

Answer: D

290. What will be the output?

```
console.log([] + 0 + []);
```

- A) 0
- B) "0"
- C) ""
- D) Error

Answer: B

291. Which HTTP status code means "Internal Server Error"?

- A) 400
- B) 401
- C) 500
- D) 503

Answer: C

WPT MCQs

292. What will be the output?

```
console.log(typeof (function* () {}));
```

- A) function
- B) object
- C) generator
- D) undefined

Answer: A

293. Which JavaScript method joins array elements into string?

- A) concat()
- B) join()
- C) merge()
- D) toString()

Answer: B

294. What will be the output?

```
console.log("5" - -"5");
```

- A) 10
- B) 55
- C) 0
- D) Error

Answer: A

295. Which DOM method selects element by ID?

- A) getElementByClass
- B) getElementById
- C) querySelectorAll
- D) getNodes

Answer: B

WPT MCQs

296. What will be the output?

```
console.log([] == false);
```

- A) true
- B) false
- C) Error
- D) undefined

Answer: A

297. Which JavaScript operator has highest precedence?

- A) +
- B) =
- C) ()
- D) ==

Answer: C

298. What will be the output?

```
console.log("10" / "2" + "1");
```

- A) 51
- B) 6
- C) 61
- D) Error

Answer: A

299. Which React feature optimizes rendering lists?

- A) keys
- B) props
- C) state
- D) refs

Answer: A

300. What will be the output?

WPT MCQs

```
console.log(1 + "2" + "3" - 3);
```

- A) 120
- B) 123
- C) 21
- D) NaN

Answer: A
