

CSC 212: Data Structures and Abstractions

12: Linked Lists (part 2)

Prof. Marco Alvarez

Department of Computer Science and Statistics
University of Rhode Island

Fall 2025



Recursion

• Definition

- ✓ method of solving problems that involves breaking a problem into smaller and smaller subproblems (of the same structure) until reaching a small enough problem that can be solved trivially

• Recursive functions

- ✓ technically, a recursive function is one that invokes itself
- ✓ must contain at least one base case and one recursive call
- ✓ **base case**: a terminating condition that halts the recursion
- ✓ **recursive case**: a condition that perpetuates the recursion by calling the function again

2


Why recursion?

• Can we live without it?

- ✓ yes, every recursive function has an equivalent iterative solution

• However ...

- ✓ some formulas are inherently recursive in nature
- ✓ some problems naturally lend themselves to recursive solutions



<https://courses.cs.washington.edu/courses/cse120/17sp/labs/11/tree.html>

3

Practice

• Write a recursive function to add all elements in a vector

- ✓ trace the call sequence, including the parameters passed at each step

```
int sum_array(std::vector<int>& A, int n) {  
    // base case  
    if (n == 1) {  
        return A[0];  
    }  
  
    // recursive call  
    int partial_sum = sum_array(A, n-1);  
  
    // return sum  
    return A[n-1] + partial_sum;  
}
```

4

SLL Methods (recursive implementation)

- `clear()`
 - ✓ traverse the list and deletes each node
 - ✓ resets head and tail to nullptr and size to zero
- `print()`
 - ✓ uses a temporary pointer to traverse the list starting from the head
 - ✓ prints the value stored in each node during traversal
- `search(value)`
 - ✓ uses a temporary pointer to traverse the list starting from the head
 - ✓ compares each node's value with the target value
 - ✓ returns true if the value is found; otherwise, returns false

5

Methods (recursive implementation)

- `at(index)`
 - ✓ returns the element at the specified index (starting from 0)
- `reverse()`
 - ✓ traverses the list and reverses the direction of all node pointers
 - ✓ swaps the head and tail pointers

6