WEEK 11

To construct a WLAN and make the nodes communicate wirelessly

OBSERVATION:



Ping output

Packet Tracer PC Command Line

PC> Ping 10.0.0.3

Pinging 10.0.0.3 with 32 bytes of data:

Request timed out.

Reply from 10.0.0.3: bytes=32 time=0ms TTL=127

Ping stats

Packets: Sent = 4, Received = 3, Lost = 1 (25% loss)

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 1ms, Average = 0ms

Observation :-

-> A WLAN is a group of colocated devices that form a network based on radio transmission

-> Data is sent in packets, each device layer with table & protocols MAC address to end points for security.

-> The access point is the base station that acts as hub to which other stations connect

-> With access point we can connect multiple networks wirelessly.

NLP
01/09/2023

TOPOLOGY:


Cisco Packet Tracer Student
Logical
10.0.0.1
Router-PT
Router0
Fa1/1
Fa2/1
Switch-PT
Switch0
Access Point-PT
Access Point0
Fa0
PC-PT
PC0
10.0.0.2
PC-PT
PC2
10.0.0.3
Laptop-PT
10.0.0.4
Realtime


PC1
Physical
Config
Desktop
Custom Interface
MODULES
WMP300N
PT-HOST-NM-1AM
PT-HOST-NM-1CE
PT-HOST-NM-1CFE
PT-HOST-NM-1CGE
PT-HOST-NM-1FFE
PT-HOST-NM-1FGE
PT-HOST-NM-1W
PT-HOST-NM-1W-A
PT-HOST-NM-3G/4G
PT-HEADPHONE
PT-MICROPHONE
PT-CAMERA
PT-USB-HARD-DRIVE
Physical Device View
Zoom In
Original Size
Zoom Out
Customize Icon in Physical View
Customize Icon in Logical View
The Linksys-WMP300N module provides one 2.4GHz wireless interface suitable for connection to wireless networks. The module supports protocols that use Ethernet for LAN access.


Laptop0
Physical
Config
Desktop
Custom Interface
MODULES
WPC300N
PT-LAPTOP-NM-1AM
PT-LAPTOP-NM-1CE
PT-LAPTOP-NM-1CFE
PT-LAPTOP-NM-1CGE
PT-LAPTOP-NM-1FFE
PT-LAPTOP-NM-1FGE
PT-LAPTOP-NM-1W
PT-LAPTOP-NM-1W-A
PT-LAPTOP-NM-3G/4G
PT-HEADPHONE
PT-MICROPHONE
PT-CAMERA
PT-USB-HARD-DRIVE
Physical Device View
Zoom In
Original Size
Zoom Out
Customize Icon in Physical View
Customize Icon in Logical View
The Linksys-WPC300N module provides one 2.4GHz wireless interface suitable for connection to wireless networks. The module supports protocols that use Ethernet for LAN access.

OUTPUT:


PC0
Physical
Config
Desktop
Custom Interface
Command Prompt
X
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
PC>ping 10.0.0.3
Pinging 10.0.0.3 with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.
Ping statistics for 10.0.0.3:
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
PC>ping 10.0.0.3
Pinging 10.0.0.3 with 32 bytes of data:
Reply from 10.0.0.3: bytes=32 time=21ms TTL=128
Reply from 10.0.0.3: bytes=32 time=7ms TTL=128
Reply from 10.0.0.3: bytes=32 time=9ms TTL=128
Reply from 10.0.0.3: bytes=32 time=10ms TTL=128
Ping statistics for 10.0.0.3:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 7ms, Maximum = 21ms, Average = 11ms
PC>