BIO INSPIRED ALGORITHMS · 23DS7BSBIO

Cover Slide/Main Slide

Plant Disease Detection using Transfer-Learning CNN Optimized with Differential Evolution

INTELLIGENCE, NATURALLY.

Under the guidance of

Manoj Kumar S, Assistant Professor

Academic Year 2026–2027

TEAM 10

Aryanraj S Singh
1BM23CD008

Richik Chaudhuri
1BM23CD050

Suraj B
1BM23CD061

Sushant Deo
1BM23CD062

FIND THE BEST RECIPE

Introduction to Optimization Problems

01

Choose

Seven decisions define a training recipe: learning, regularization, architecture and augmentation.

02

Measure

Train on the training split. Measure macro-F1 on validation images only.

03

Improve

Search for a better recipe under a fixed evaluation budget.

VARIATION · EXPLORATION · SELECTION

What are Nature-Inspired Algorithms?

01

A population

Maintain several possible solutions instead of one guess.

02

Useful variation

Create trials by mutation and recombination.

03

Evidence-led selection

Keep a candidate when its measured fitness is no worse.

A MAP OF THE FIELD

Classification of Nature-Inspired Algorithms

01

Evolutionary

Genetic Algorithm

Differential Evolution

Evolution Strategies

02

Swarm

Particle Swarm

Ant Colony

Artificial Bee Colony

03

Other families

Simulated Annealing

Biogeography


Teaching–Learning

TOMATO LEAF HEALTH

Problem Statement


Evolve seven training decisions. Maximize validation macro-F1.

18,146 images · 10 classes · group-aware 70 / 15 / 15 split · 14 exact duplicates removed




THE FULL SYSTEM

Implementation and Results (1/10)



A PRE-REGISTERED BASELINE


Implementation and Results (2/10)



The head and the number of unfrozen feature blocks are architecture genes.

DIFFERENTIAL EVOLUTION, FROM SCRATCH

Implementation and Results (3/10)



THE CHROMOSOME AND ITS SEARCH BUDGET


Implementation and Results (4/10)

GENE	DECODED CHOICE	SCALE
Learning rate	$10^{-4.5}$ to 10^{-2}	Logarithmic
Weight decay	10^{-6} to 10^{-2}	Logarithmic
Dropout	0.0 to 0.6	Linear
Head width	0, 128, 256, 512	Categorical
Unfrozen blocks	0 to 9	Integer
Label smoothing	0.0 to 0.2	Linear
Augmentation magnitude	0 to 15; 0 = no extra RandAugment	Integer

NP 8 · F 0.6 · CR 0.9 · 8 generations · 72 evaluations per method

SEARCH UNDER AN EQUAL BUDGET

Implementation and Results (5/10)



Proxy validation fitness; final test performance is evaluated separately.

BEFORE AND AFTER: MEASURED PERFORMANCE

Implementation and Results (6/10)

Figure becomes available after its experiment completes.

DRAFT DESIGN PREVIEW — final evaluation has not completed.

WHERE DO THE MODELS DISAGREE?

Implementation and Results (7/10)

Figure becomes available after its experiment completes.

EVERY CLASS COUNTS

Implementation and Results (8/10)

Figure becomes available after its experiment completes.

Per-class F1 across all three seeds; classes ordered by measured gain.

WHERE THE MODELS LOOK

Implementation and Results (9/10)

Figure becomes available after its experiment completes.

Within-image normalized activation; attention is not a lesion mask or causal proof.

BEYOND THE IDEAL IMAGE

Implementation and Results (10/10)

Figure becomes available after its experiment completes.

Seed-zero models · identical held-out images and deterministic corruption settings.

PLANTWISE · INTELLIGENCE, NATURALLY

Live Demo

01

Diagnose

Compare exact baseline and DE seed-zero checkpoints on a sample leaf.

02

Explain

Inspect top-three probabilities and genuine Grad-CAM attention.

03

Evolve

Change the landscape and watch the population converge.

ACCURACY IS ONLY THE BEGINNING

Performance Metrics and Benchmarking (1/5)

01

Classification

Accuracy = correct / total

Precision = TP / (TP + FP)

Recall = TP / (TP + FN)

02

Macro-F1

F1 = 2PR / (P + R)

Macro-F1 = mean class F1

Every class counts equally.

03

Beyond accuracy

ROC-AUC: ranking quality

ECE: calibration gap


Latency: time per forward pass

Performance Metrics and Benchmarking (2/5)

Confidence intervals and paired statistics appear after the locked evaluation.

FIVE ALGORITHMS. EQUAL EVALUATIONS.

Performance Metrics and Benchmarking (3/5)



30 runs per algorithm/function · 20,000 evaluations per run · 10 dimensions

NO UNIVERSAL WINNER

Performance Metrics and Benchmarking (4/5)

FUNCTION	DE	jDE	GA	PSO	Random Search
Sphere	2.59e-15	1.27e-23	1.06e-03	2.59e-26	1.17e+01
Rosenbrock	4.72e-01	3.33e+00	7.66e+00	2.66e+00	8.99e+03
Rastrigin	3.00e+01	2.05e-12	3.30e+00	6.47e+00	6.44e+01
Ackley	5.46e-07	2.02e-11	4.47e-01	2.33e-12	1.66e+01
Griewank	4.57e-01	1.29e-05	6.22e-01	8.24e-02	4.10e+01

Median final objective · lower is better · 30 seeds per method and function

THE COST OF A BETTER RECIPE

Performance Metrics and Benchmarking (5/5)

Measured training and inference costs appear after all runs complete.

WHAT THE EVIDENCE SUPPORTS

Advantages and Limitations

01

Advantages

Auditable operators

Reproducible data splits

Equal-budget control

Offline inference

02

Limitations

Controlled-condition images

One crop/split; one search per method

Proxy-fidelity noise

Training cost

FROM THE LAB TOWARD THE FIELD

Future Scope

01

Field evidence

Validate on real field images with an explicit class mapping.

02

Efficient intelligence

Optimize quality alongside latency and model size.

03

Adaptive learning

Explore SHADE, multi-fidelity search and expert feedback.

VERIFIED DOI SOURCES

References (1/2)

01 Storn, Rainer et al. (1997). Differential Evolution -- A Simple and Efficient Heuristic for global Optimization over Continuous Spaces

DOI: 10.1023/a:1008202821328

02 Mohanty, Sharada P. et al. (2016). Using Deep Learning for Image-Based Plant Disease Detection

DOI: 10.3389/fpls.2016.01419

03 Tan, Mingxing et al. (2019). EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks

DOI: 10.48550/arxiv.1905.11946

04 Das, Swagatam et al. (2011). Differential Evolution: A Survey of the State-of-the-Art

DOI: 10.1109/tevc.2010.2059031

05 Brest, Janez et al. (2006). Self-Adapting Control Parameters in Differential Evolution: A Comparative Study on Numerical Benchmark Problems

DOI: 10.1109/tevc.2006.872133

VERIFIED DOI SOURCES

References (2/2)

06 Selvaraju, Ramprasaath R. et al. (2017). Grad-CAM: Visual Explanations from Deep Networks via Gradient-Based Localization

DOI: 10.1109/iccv.2017.74

07 Dietterich, Thomas G. et al. (1998). Approximate Statistical Tests for Comparing Supervised Classification Learning Algorithms

DOI: 10.1162/089976698300017197

08 Guo, Chuan et al. (2017). On Calibration of Modern Neural Networks

DOI: 10.48550/arxiv.1706.04599

09 Hendrycks, Dan et al. (2019). Benchmarking Neural Network Robustness to Common Corruptions and Perturbations

DOI: 10.48550/arxiv.1903.12261

10 Singh, Davinder et al. (2020). PlantDoc: A Dataset for Visual Plant Disease Detection

DOI: 10.1145/3371158.3371196

TEAM 10 · 23DS7BSBIO

Thank You / Questions

A healthier future.

One leaf at a time.

Plantwise · Intelligence, naturally.

github.com/Suraj-B12/
BIO-INSPIRED-ALGO---AAT