



Digital Image Processing

Lecture #9

Ming-Sui (Amy) Lee

[Course Information]

■ Following Schedule

| | | | |
|-------|-----------|-------|-------------------|
| 03/28 | Lecture 4 | 05/16 | Proposal |
| 04/04 | 溫書假 | 05/23 | Lecture 9 |
| 04/11 | Lecture 5 | 05/30 | Lecture 10 |
| 04/18 | Lecture 6 | 06/06 | Lecture 11 |
| 04/25 | Midterm | 06/13 | Demo |
| 05/02 | Lecture 7 | 06/20 | Demo |
| 05/09 | Lecture 8 | 06/27 | Final Package Due |

Announcement

- **Proposal - Due: 11:59pm on May 15, 2018**
 - 1) Demo video
 - 6-minute video in mpg, avi, mp4 or wmv
 - Provide a valid link on CEIBA for us to download
 - [Teamxx_ProposalDemo.mpg/avi/mp4/wmv](#)
 - 2) Written report
 - [Teamxx_ProposalReport.PDF](#)
 - Upload to CEIBA
 - Remember to include
 - Paper title / Motivation / Problem definition /
 - Algorithm / Expected results
 - Reference



Image Enhancement in Frequency Domain


[Background]




- **Jean Baptiste Joseph Fourier (1807)**
 - Any periodic function
 - Can be expressed as the sum of sines and/or cosines of different frequencies, each multiplied by a different coefficient → **Fourier series**
 - Functions that are not periodic
 - Can be expressed as the integral of sines and/or cosines multiplied by a weighting function → **Fourier transform**
 - Important characteristic
 - A function can be reconstructed completely without losing any information
 - Fourier/frequency domain processing

[Fourier Transform]

■ Example



Basis Functions



combination

Fourier Transform

■ Continuous cases

○ (Continuous) Fourier Transform (CFT)

■ One-dimensional

$$F(u) = \int_{-\infty}^{\infty} f(x) e^{-j2\pi ux} dx$$

$$f(x) = \int_{-\infty}^{\infty} F(u) e^{j2\pi ux} du$$

Euler's formula:

$$e^{j\theta} = \cos \theta + j \sin \theta$$

■ Two-dimensional

$$F(u, v) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} f(x, y) e^{-j2\pi(ux+vy)} dx dy$$


$$f(x, y) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} F(u, v) e^{j2\pi(ux+vy)} du dv$$

Fourier Transform

Continuous Cases

- CFT of a square wave between $[-\frac{W}{2}, \frac{W}{2}]$ with amplitude A :

$$\begin{aligned} F(u) &= \int_{-\infty}^{\infty} f(x) e^{-j2\pi ux} dx = \int_{-W/2}^{W/2} A e^{-j2\pi ux} dx = \frac{-A}{j2\pi u} [e^{-j2\pi ux}]_{-W/2}^{W/2} \\ &= \frac{-A}{j2\pi u} [e^{-j\pi uW} - e^{j\pi uW}] = \frac{A}{j2\pi u} [e^{j\pi uW} - e^{-j\pi uW}] = AW \frac{\sin(\pi uW)}{\pi uW} \end{aligned}$$



Fourier Transform

■ Discrete cases

○ Discrete Fourier Transform (DFT)

■ One-dimensional





$$\text{Let } F(u) \stackrel{\Delta}{=} F(u\Delta u) \quad \Delta u = \frac{1}{M\Delta j}$$
$$f(k) \stackrel{\Delta}{=} f(j_0 + k\Delta j)$$

$$\Rightarrow \begin{cases} F(u) = \frac{1}{M} \sum_{k=0}^{M-1} f(k) e^{-j2\pi uk/M}, & u = 0, 1, \dots, M-1 \\ f(k) = \sum_{u=0}^{M-1} F(u) e^{j2\pi uk/M}, & k = 0, 1, \dots, M-1 \end{cases}$$

//Note// DFT and its inverse always exist

Fourier Transform

■ Example



Fourier Transform

- Discrete cases

- One-dimensional

- Mathematical prism

- Separate a function into various components

frequency

$$F(u) = \frac{1}{M} \sum_{k=0}^{M-1} f(k) e^{-j2\pi uk / M}, \quad u = 0, 1, \dots, M-1$$

frequency component

$$= \frac{1}{M} \sum_{k=0}^{M-1} f(k) [\cos(2\pi uk / M) - j \sin(2\pi uk / M)]$$

Fourier Transform

■ Discrete cases

○ Two-dimensional

$$F(u, v) = \frac{1}{MN} \sum_{j=0}^{M-1} \sum_{k=0}^{N-1} f(j, k) e^{-j2\pi\left(\frac{uj}{M} + \frac{vk}{N}\right)} \rightarrow \text{Complex}$$

$$f(j, k) = \sum_{u=0}^{M-1} \sum_{v=0}^{N-1} F(u, v) e^{j2\pi\left(\frac{uj}{M} + \frac{vk}{N}\right)}$$


Fourier Spectrum: $|F(u, v)| = \left[R^2(u, v) + I^2(u, v) \right]^{1/2}$

Phase Angle: $\phi(u, v) = \tan^{-1} \left[\frac{I(u, v)}{R(u, v)} \right]$

Power Spectrum: $P(u, v) = |F(u, v)|^2 = R^2(u, v) + I^2(u, v)$ 12


Fourier Transform

Example




$$\mathcal{F}[f(j, k)(-1)^{j+k}] = F(u - M/2, v - N/2)$$

Centering & log transformation



$$F(0, 0) = \frac{1}{MN} \sum_{x=0}^{M-1} \sum_{y=0}^{N-1} f(x, y)$$

Average/dc component (zero frequency)





Fourier Transform

■ Log Transformation

$$s = c \log(1 + r), \quad r \geq 0$$


- Expand the dynamic range of low gray-level values
- Compress the dynamic range of images with large variations in pixel values



Map a narrow range of low-gray-level values in the input image into a wide range of output levels

Fourier Transform

■ Example



- Strong edges $\rightarrow \pm 45^\circ$ directions
- Oxide protrusions \rightarrow vertical component slightly slant to the left
- Zeros in the vertical frequency component \rightarrow narrow vertical span of the oxide protrusions

[Fourier Transform]

■ Properties

○ Centering

$$\mathcal{F}[f(j,k)(-1)^{j+k}] = F(u - M/2, v - N/2)$$

○ Conjugate symmetry


If $f(j,k)$ is real,

$$F(u, v) = F^*(-u, -v)$$

$$|F(u, v)| = |F(-u, -v)|$$

Frequency-Domain Filtering

■ Filtering in the frequency domain



(a) Multiply the input image by $(-1)^{j+k}$ to center the transform

(b) Compute $F(u, v)$

(c) Multiply $F(u, v)$ by a filter function $H(u, v)$


(d) Compute the inverse DFT of the result in (c)

(e) Obtain the real part of (d)

(f) Multiply the result in (e) by $(-1)^{j+k}$

Frequency-Domain Filtering


■ Filtering in the frequency domain





Frequency-Domain Filtering

■ Basic filters and their properties

- Low-pass filter
- High-pass filter
- Notch filter




- Attenuates high frequencies
- Passes low frequencies





Frequency-Domain Filtering

■ Basic filters and their properties

- Low-pass filter
- **High-pass filter**
- Notch filter



- Attenuates low frequencies
- Passes high frequencies



[Frequency-Domain Filtering]


- Basic filters and their properties

- Low-pass filter


- **Modified high-pass filter**

- Adding a constant of one-half the filter height to the filter function to avoid complete elimination

- Notch filter



Modified high-pass filter




Frequency-Domain Filtering

■ Basic filters and their properties



○ Notch filter

$$H(u, v) = \begin{cases} 0 & \text{if } (u, v) = (\alpha, \beta) \\ 1 & \text{otherwise} \end{cases}$$

→ A constant function with a hole at the origin



http://www.soontai.com/da_filterprofile.html



Frequency-Domain Filtering

■ Convolution Theorem

○ Discrete convolution

$$f(j, k) * h(j, k) = \frac{1}{MN} \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} f(m, n) h(j - m, k - n)$$

■ Flip → shift → sum of products

○ Fourier transform pairs

$$f(j, k) * h(j, k) \Leftrightarrow F(u, v) H(u, v)$$

$$f(j, k) \underline{h(j, k)} \Leftrightarrow F(u, v) * \underline{H(u, v)}$$

Impulse
function

Impulse
response

Convolution
Theorem


[Frequency-Domain Filtering]

■ Gaussian filter

○ One-dimensional

$$H(u) = Ae^{-u^2/2\sigma^2}$$

$$h(k) = \sqrt{2\pi}\sigma Ae^{-2\pi^2\sigma^2k^2}$$



○ Important characteristics

- Easy to specify and manipulate
- Fourier transform of a Gaussian function is a 'real' Gaussian function
- Two functions behave reciprocally w.r.t one another





[Frequency-Domain Filtering]

- Gaussian filter
 - Low-pass filter

$$H(u) = Ae^{-u^2/2\sigma^2}$$

$$h(k) = \sqrt{2\pi}\sigma Ae^{-2\pi^2\sigma^2k^2}$$



- All the values are positive in both domains
- The narrower the frequency domain filter, the wider the spatial domain filter, i.e. more severe blurring effect

[Frequency-Domain Filtering]


■ Gaussian filter

○ High-pass filter

- Construct a high-pass filter as a difference of Gaussians

$$H(u) = Ae^{-u^2/2\sigma_1^2} - Be^{-u^2/2\sigma_2^2}$$

$$h(k) = \sqrt{2\pi} \left(\sigma_1 Ae^{-2\pi^2\sigma_1^2 k^2} - \sigma_2 Be^{-2\pi^2\sigma_2^2 k^2} \right)$$



Comparison

- **Comparison of spatial-domain and frequency-domain filtering**
 - **Filtering in spatial domain**
 - Specific masks are needed
 - **Filtering in frequency domain**
 - $f(j,k) * h(j,k) \Leftrightarrow F(u,v)H(u,v)$
 $f(j,k)h(j,k) \Leftrightarrow F(u,v) * H(u,v)$
 - **Easy to implement**
 - Fast Fourier Transform (FFT)
 - **Save computation complexity for larger signal size**

[Frequency-Domain Filtering]

- Smoothing frequency-domain filters

$$G(u, v) = H(u, v)F(u, v)$$

- Ideal low-pass filters (ILPF)
- Butterworth low-pass filters (BLPF)
- Gaussian low-pass filters (GLPF)

Frequency-Domain Filtering


■ Ideal low-pass filters

$$H(u, v) = \begin{cases} 1 & \text{if } D(u, v) \leq D_0 \\ 0 & \text{if } D(u, v) > D_0 \end{cases}$$

Radius:
Non-negative

$$D(u, v) = [(u - M/2)^2 + (v - N/2)^2]^{1/2}$$

< Distance from point (u,v) to the center of the frequency rectangle >



Perspective plot





Image display




Radial cross section


[Frequency-Domain Filtering]

- Ideal low-pass filters

- Example



Original image
(in spatial domain)




Radius = 5, 15, 30, 80 & 230
(in frequency domain)

[Frequency-Domain Filtering]

- Ideal low-pass filters



- Example (with radius = 5, 15, 30, 80 & 230)





Frequency-Domain Filtering

■ Ideal low-pass filters


○ Example



Frequency domain



spatial domain





→ Blurred with "ringing artifacts"

Frequency-Domain Filtering

■ Ideal low-pass filters

- Ideal LPF presents a Sinc function in the spatial domain
- Radius of the main lobe is inversely proportional to the cutoff frequency



Frequency-Domain Filtering


■ Butterworth low-pass filters

$$H(u, v) = \frac{1}{1 + [D(u, v) / D_0]^{2n}}$$

n : order (must be an integer)

$$D(u, v) = [(u - M/2)^2 + (v - N/2)^2]^{1/2}$$

< Distance from point (u,v) to the center of the frequency rectangle >



Perspective plot






Image display



Radial cross section

[Frequency-Domain Filtering]

- Butterworth low-pass filters ($n=2$)
 - Example (with radius = 5, 15, 30, 80 & 230)




[Frequency-Domain Filtering]

■ Butterworth low-pass filters

- Order $n = 1, 2, 5,$ and 20 with cutoff=5 pixels

$$H(u, v) = \frac{1}{1 + [D(u, v) / D_0]^{2n}}$$

Spatial representation of BLPF




Frequency-Domain Filtering

■ Gaussian low-pass filters

$$H(u, v) = e^{-D^2(u, v)/2\sigma^2} \text{ or } e^{-D^2(u, v)/2D_0^2}$$

D_0 is the cutoff frequency



Perspective plot





Image display









Radial cross section

→ Gaussian in frequency domain → Gaussian in spatial domain

→ No ringing artifacts

[Frequency-Domain Filtering]

- Gaussian low-pass filters



“ No ringing artifacts “

“ achieve less smoothing than BLPF “


Frequency-Domain Filtering

■ Examples

○ Gaussian low-pass filters

■ Connect broken characters

Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.



Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.



[Frequency-Domain Filtering]

■ Examples

○ Gaussian low-pass filters


■ Reduction in skin fine lines



Original



Cutoff=100



Cutoff=80

[Frequency-Domain Filtering]

- Sharpening frequency-domain filters

$$H_{hp}(u, v) = 1 - H_{lp}(u, v)$$


- Ideal high-pass filters
- Butterworth high-pass filters
- Gaussian high-pass filters
- The Laplacian in the frequency domain

[Frequency-Domain Filtering]



■ Ideal high-pass filters

$$H(u, v) = \begin{cases} 0 & \text{if } D(u, v) \leq D_0 \\ 1 & \text{if } D(u, v) > D_0 \end{cases}$$

$$D(u, v) = [(u - M/2)^2 + (v - N/2)^2]^{1/2}$$




Spatial domain




[Frequency-Domain Filtering]


- Ideal high-pass filters
 - Example (with radius = 15, 30 & 80)



Original



Cutoff=15



Cutoff=30



Cutoff=80


[Frequency-Domain Filtering]

■ Butterworth high-pass filters

$$H(u, v) = \frac{1}{1 + [D_0 / D(u, v)]^{2n}}$$

n: order (must be an integer)

$$D(u, v) = [(u - M/2)^2 + (v - N/2)^2]^{1/2}$$



Perspective plot







Image display




Radial cross section

Spatial domain




[Frequency-Domain Filtering]


- Butterworth high-pass filters ($n=2$)
 - Example (with radius = 15, 30 & 80)



Original



Cutoff=15



Cutoff=30




Cutoff=80

[Frequency-Domain Filtering]

■ Gaussian high-pass filters


$$H(u, v) = 1 - e^{-D^2(u, v) / 2D_0^2}$$

D_0 is the cutoff frequency



Frequency-Domain Filtering

- Gaussian high-pass filters
 - Example (with radius = 15, 30 & 80)



//Note// High-pass filters can be constructed by the difference of Gaussian low-pass filters
→ more parameters → more control over the filter shape

[Frequency-Domain Filtering]

■ The Laplacian in the Frequency domain

$$\mathfrak{F}\left[\frac{d^n f(x)}{dx^n}\right] = (ju)^n F(u)$$

$$\begin{aligned}\mathfrak{F}\left[\frac{\partial^2 f(x, y)}{\partial x^2} + \frac{\partial^2 f(x, y)}{\partial y^2}\right] &= (ju)^2 F(u, v) + (jv)^2 F(u, v) \\ &= -(u^2 + v^2)F(u, v)\end{aligned}$$

$$\mathfrak{F}[\nabla^2 f(x, y)] = -(u^2 + v^2)F(u, v)$$

$$G(u, v) = H(u, v)F(u, v)$$


$$\Rightarrow H(u, v) = -(u^2 + v^2) \Rightarrow H(u, v) = -\left[\left(u - \frac{M}{2}\right)^2 + \left(v - \frac{N}{2}\right)^2\right]$$

Center of the filter needs to be shifted

[Frequency-Domain Filtering]

■ The Laplacian in the Frequency domain


$$\mathfrak{I}[\nabla^2 f(x, y)] = -((u - M/2)^2 + (v - N/2)^2)F(u, v)$$




Frequency-Domain Filtering

Comparison


Ideal



Butterworth




Gaussian



[Frequency-Domain Filtering]


- Comparison – spatial representation



[Frequency-Domain Filtering]

■ Homomorphic filtering

○ Recall: (Lecture #2)



$$f(x, y) = i(x, y)r(x, y)$$

- **Illumination**

$$0 < i(x, y) < \infty$$

- **Reflectance**

$$0 < r(x, y) < 1$$

Frequency-Domain Filtering

■ Homomorphic filtering

$$f(x, y) = i(x, y)r(x, y)$$

- The Fourier transform of the product of two functions is NOT separable

$$\mathfrak{F}\{f(x, y)\} \neq \mathfrak{F}\{i(x, y)\} \mathfrak{F}\{r(x, y)\}$$

- Define

$$z(x, y) = \ln f(x, y) = \ln i(x, y) + \ln r(x, y)$$

$$\begin{aligned} \Rightarrow \mathfrak{F}\{z(x, y)\} &= \mathfrak{F}\{\ln f(x, y)\} \\ &= \mathfrak{F}\{\ln i(x, y)\} + \mathfrak{F}\{\ln r(x, y)\} \end{aligned}$$

$$\text{or } Z(u, v) = F_i(u, v) + F_r(u, v)$$

[Frequency-Domain Filtering]

■ Homomorphic filtering

$$\begin{aligned} S(u, v) &= H(u, v)Z(u, v) \\ &= H(u, v)F_i(u, v) + H(u, v)F_r(u, v) \end{aligned}$$

$$\begin{aligned} \Rightarrow s(x, y) &= \mathfrak{S}^{-1}\{S(u, v)\} \\ &= \mathfrak{S}^{-1}\{H(u, v)F_i(u, v)\} + \mathfrak{S}^{-1}\{H(u, v)F_r(u, v)\} \end{aligned}$$

○ let

$$i'(x, y) = \mathfrak{S}^{-1}\{H(u, v)F_i(u, v)\}$$

$$r'(x, y) = \mathfrak{S}^{-1}\{H(u, v)F_r(u, v)\}$$

$$\Rightarrow s(x, y) = i'(x, y) + r'(x, y)$$

[Frequency-Domain Filtering]

- **Homomorphic filtering**

$$s(x, y) = i'(x, y) + r'(x, y)$$

$$\begin{aligned} g(x, y) &= e^{s(x, y)} \\ &= e^{i'(x, y)} \cdot e^{r'(x, y)} = i_0(x, y) r_0(x, y) \end{aligned}$$


where

$$i_0(x, y) = e^{i'(x, y)} \quad \text{and} \quad r_0(x, y) = e^{r'(x, y)}$$

are the illumination and reflectance components of the output image

Frequency-Domain Filtering

Homomorphic filtering



[Frequency-Domain Filtering]

■ Two components

- Illumination component
 - Vary slowly (slow spatial variations)
 - Associate low frequencies
- Reflectance component
 - Vary abruptly
 - Associate high frequencies

■ Homomorphic filter

- Separation of illumination & reflectance components
- Affect the low- and high-frequency components of the Fourier transform in different ways


Frequency-Domain Filtering

■ Example

“circularly”
symmetric


$H(u, v)$

Dynamic range compression
& Contrast enhancement



$$D(u, v) = [(u - M/2)^2 + (v - N/2)^2]^{1/2}$$

The distance from point (u, v) to the origin of the centered transform



[Frequency-Domain Filtering]

- Another example of homomorphic filtering
 - PET image

