

Q.1) A)

1. LOAD GROCERIES DATASET AS TRANSACTIONS.

```
> setwd("C:\\Users\\user\\Desktop\\23")
> getwd()
[1] "C:/Users/user/Desktop/23"
> mba_data<-read.csv("C:\\Users\\user\\Desktop\\23\\groceries.csv")
> trans <- split(mba_data$Products, mba_data$Customer_Id,"transactions")
> head(trans)
$`1`
[1] "bread" "butter" "eggs" "milk"

$`2`
[1] "beer" "bread" "cheese" "chips" "mayo" "soda"

$`3`
[1] "bread" "butter" "eggs" "milk" "oranges"

$`4`
[1] "bread" "butter" "eggs" "milk" "soda"

$`5`
[1] "buns" "chips" "beer" "mustard" "pickels" "soda"

$`6`
[1] "bread" "butter" "chocolate" "eggs" "milk"

> library(arules)
Loading required package: Matrix

Attaching package: 'arules'

The following objects are masked from 'package:base':

    abbreviate, write
```

2. APPLY APRIORI ALGORITHM :

```
> rules = apriori(trans, parameter=list(support=0.7, confidence=0.8))
Apriori




Parameter specification:
 confidence minval  sxmax  arem   aval originals support minlen maxlen
    0.8         0.1   1 none FALSE     TRUE       5   0.7     1    10
 target ext
 rules TRUE

Algorithmic control:
 filter tree heap memopt load sort verbose
  0.1 TRUE TRUE  FALSE TRUE   2    TRUE

Absolute minimum support count: 10

set item appearances ...[0 item(s)] done [0.00s].
set transactions ...[15 item(s), 15 transaction(s)] done [0.00s].
sorting and recoding items ... [1 item(s)] done [0.00s].
creating transaction tree ... done [0.00s].
checking subsets of size 1 done [0.00s].
writing ... [1 rule(s)] done [0.00s].
creating s4 object ... done [0.00s].
warning message:
In asMethod(object) : removing duplicated items in transactions
> inspect(rules)
   lhs rhs support confidence coverage lift count
[1] {} => {bread} 0.8      0.8      1      1      12
```

Q.2) A) PENTAHO :



Q.2) B)

Create table sales(sid,ssname,salesregion) with 3 partition using list partition based on region

```
SQL> CREATE TABLE sales(sid INTEGER,ssname VARCHAR(20),salesregion VARCHAR(20))
2 PARTITION BY LIST(salesregion)
3 (PARTITION p1 VALUES('MAHARASHTRA'),
4 PARTITION p2 VALUES('GOA'),
5 PARTITION p3 VALUES('KERALA'));
```

a) Describe the structure of the table and display the partition table.

```
SQL> DESC sales;
```

Name	Null?	Type
SID		NUMBER(38)
SSNAME		VARCHAR2(20)
SALESREGION		VARCHAR2(20)

b) Insert minimum 6 records and display the content from each partition.

```
SQL> INSERT INTO sales VALUES(1,'Mango','MAHARASHTRA');
```

1 row created.

```
SQL> INSERT INTO sales VALUES(2,'Orange','GOA');
```

1 row created.

```
SQL> INSERT INTO sales VALUES(3,'Apple','GOA');
```

1 row created.

```
SQL> INSERT INTO sales VALUES(4,'Guava','MAHARASHTRA');
```

1 row created.

```
SQL> INSERT INTO sales VALUES(5,'Banana','MAHARASHTRA');
```

1 row created.

```
SQL> INSERT INTO sales VALUES(6,'Strawberry','KERALA');
```

1 row created.

```
SQL> SELECT * FROM sales;
```

SID	SSNAME	SALESREGION
1	Mango	MAHARASHTRA
4	Guava	MAHARASHTRA
5	Banana	MAHARASHTRA
2	Orange	GOA
3	Apple	GOA
6	Strawberry	KERALA

6 rows selected.

```
SQL> SELECT * FROM sales PARTITION(p1);
```

SID	SSNAME	SALESREGION
1	Mango	MAHARASHTRA
4	Guava	MAHARASHTRA
5	Banana	MAHARASHTRA

```
SQL> SELECT * FROM sales PARTITION(p2);
```

SID	SSNAME	SALESREGION
2	Orange	GOA
3	Apple	GOA

```
SQL> SELECT * FROM sales PARTITION(p3);
```

SID	SSNAME	SALESREGION
6	Strawberry	KERALA

c)Add new partition and insert 2 records and display content from each partiton.

```
SQL> ALTER TABLE sales ADD PARTITION p4 VALUES('GUJARAT');
```

Table altered.

```
SQL> INSERT INTO sales VALUES(7,'Kiwi','GUJARAT');
```

1 row created.

```
SQL> INSERT INTO sales VALUES(8,'Grapes','GUJARAT');
```

1 row created.

```
SQL> SELECT * FROM sales;
```

SID	SSNAME	SALESREGION
1	Mango	MAHARASHTRA
4	Guava	MAHARASHTRA
5	Banana	MAHARASHTRA
2	Orange	GOA
3	Apple	GOA
6	Strawberry	KERALA
7	Kiwi	GUJARAT
8	Grapes	GUJARAT

```
SQL> SELECT * FROM sales PARTITION(p1);
```

SID	SSNAME	SALESREGION
1	Mango	MAHARASHTRA
4	Guava	MAHARASHTRA
5	Banana	MAHARASHTRA

```
SQL> SELECT * FROM sales PARTITION(p2);
```

SID	SSNAME	SALESREGION
2	Orange	GOA
3	Apple	GOA

```
SQL> SELECT * FROM sales PARTITION(p3);
```

SID	SSNAME	SALESREGION
6	Strawberry	KERALA

```
SQL> SELECT * FROM sales PARTITION(p4);
```

SID	SSNAME	SALESREGION
7	Kiwi	GUJARAT
8	Grapes	GUJARAT

Q.3) A)

```
SQL> create type passenger_type as object
```

```
2 (  
3   PID number(6),  
4   PName varchar2(20),  
5   Address varchar2(20),  
6   Destination varchar2(20),  
7   Age number(6)  
8 );  
9 /
```

Type created.

```
SQL> create table passenger
```

```
2 (  
3   Passenger_dtls passenger_type  
4 );
```

Table created.

```
SQL> insert into passenger values(passenger_type('1','Aman','Ghatkopar','London','22'));
```

1 row created.

```
SQL> insert into passenger values(passenger_type('2','Aakash','Thane','Sweden','20'));
```

1 row created.

```
SQL> insert into passenger values(passenger_type('3','Deepak','Chembur','Germany','19'));
```

1 row created.

```
SQL> select * from passenger;
```

```
PASSENGER_DTLS(PID, PNAME, ADDRESS, DESTINATION, AGE)
```

```
PASSENGER_TYPE(1, 'Aman', 'Ghatkopar', 'London', 22)
```

```
PASSENGER_TYPE(2, 'Aakash', 'Thane', 'Sweden', 20)
```

```
PASSENGER_TYPE(3, 'Deepak', 'Chembur', 'Germany', 19)
```

Q.3) B)

```
SQL> create table studs(
```

```
2 id int,
```

```
3 name varchar(20),
```

```
4 department varchar(20),
```

```
5 major varchar(20),
```

```
6 joining_date date,
```

```
7 marks int );
```

Table created.

```
SQL> insert into studs values(1,'aman','science','IT',to_date('3/2/2022','dd/mm/yyyy'),95);
```

1 row created.

```
SQL> insert into studs
```

```
values(2,'prasad','science','physics',to_date('4/2/2022','dd/mm/yyyy'),92);
```

1 row created.

```
SQL> select * from studs;
```

ID	NAME	DEPARTMENT	MAJOR	JOINING_D	MARKS
1	aman	science	IT	03-FEB-22	95

2	prasad	science	physics	04-FEB-22	92
---	--------	---------	---------	-----------	----

```
SQL> select department,marks,
```

```
2 max(marks)keep(DENSE_RANK FIRST ORDER BY marks desc)
```

```
3 over(PARTITION BY department)"max"
```

```
4 from studs;
```

DEPARTMENT	MARKS	max
science	92	95
science	95	95

```
SQL> select department,marks,
```

```
2 min(marks)keep(DENSE_RANK LAST ORDER BY marks desc)
```

```
3 over(PARTITION BY department)"min"
```

```
4 from studs;
```

DEPARTMENT	MARKS	min
------------	-------	-----

science	92	92
---------	----	----

science	95	92
---------	----	----