

# **PROGRAMMING FOR PROBLEM SOLVING LAB MANUAL**

## **Simple numeric problems:**

**a. Write a program for find the max and min from the three numbers.**

```
#include<stdio.h>
void main()
{
    int a,b,c;
    printf("Enter 3 numbers");
    scanf("%d%d%d",&a,&b,&c);
    if (a<=b && a <=c)
    {
        if(b<c)
            printf("Min=%d, Max= %d",a,c);
        else
            printf("Min=%d, Max= %d",a,b);
    }

    else if( b<=a && b<=c)
```

```
{
    if(a<c)
        printf("Min=%d, Max= %d",b,c);
    else
        printf("Min=%d, Max= %d",b,a);
}

else
{
    if(a<b)
        printf("Min=%d, Max= %d",c,b);
    else
        printf("Min=%d, Max= %d",c,a);
}

}
```

**RESULT:**

**INPUT:** Enter 3 numbers 5 4 6

**OUTPUT :** Min=4, Max= 6

**b. Write the program for the simple, compound interest.**

```
#include<stdio.h>
```

```
#include<math.h>
```

```
int main()
```

```
{
```

```
    int p,t;
```

```
    float r,si,amount,ci;
```

```
    printf("Please enter principal,time and rate of  
interest");
```

```
    scanf("%d%d%f",&p,&t,&r);
```

```
    si=p*t*r/100;
```

```
//Simple Interest formula is  $p*t*r$ 
```

```
    printf("\nSimple interest = %.3f",si);
```

//Compound Interest formula is below

```
amount=p*pow((1 +r/100),t);
```

```
ci=amount-p;
```

```
printf("\nCompound interest = %.3f",ci);
```

```
}
```

## **RESULT:**

**INPUT:** Please enter principal,time and rate of interest 1000 2 12

**OUTPUT :** Simple interest = 240.000  
Compound interest = 254.400

**c. Write program that declares Class awarded for a given percentage of marks, where**

**mark <40%= Failed, 40% to <60% = Second class, 60% to <70%=First class, >=70% = Distinction. Read percentage from standard input.**

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int M1, M2, M3;
```

```
    float per;
```

```
    printf("Enter three subjects marks: ");
```

```
    scanf("%d%d%d", &M1, &M2, &M3);
```

```
    per = (M1 + M2 + M3) / 3.0;
```

```
    printf("Percentage = %.2f\n", per);
```

```
    if(per >= 70)
```

```
    {
```

```
        printf("Distinction");
```

```
    }
```

```
    else if((per>=60) && (per<= 70))
```

```
{
    printf("First class");
}
else if((per>=40) && (per<= 60))
{
    printf("Second class");
}
else if (per <= 40)
{
    printf("Failed");
}

return 0;
}
```

### **RESULT- 1:**

**INPUT:** Enter three subjects marks: 40 35 30

**OUTPUT :** Percentage = 35.00

Failed

### **RESULT- 2:**

**INPUT:** Enter three subjects marks: 78 65 90

**OUTPUT:** Percentage = 77.67

Distinction

**d. Write a program that prints a multiplication table for a given number and the number of rows in the table. For example, for a number 5 and rows = 3, the output should be:**

**5 x 1 = 5**

**5 x 2 = 10**

**5 x 3 = 15**

```
#include <stdio.h>
int main()
{
    int n, i, range;

    printf("Enter an integer: ");
    scanf("%d",&n);

    printf("Enter the range: ");
    scanf("%d", &range);

    for(i=1; i <= range; ++i)
    {
        printf("%d * %d = %d \n", n, i, n*i);
    }

    return 0;
}
```

**RESULT:**

**INPUT:**

Enter an integer: 5

Enter the range: 3

**OUTPUT :**

$$5 * 1 = 5$$

$$5 * 2 = 10$$

$$5 * 3 = 15$$

**e. Write a program that shows the binary**



**equivalent of a given positive number between 0 to 255.**

```
#include <stdio.h>
long decimalToBinary(long n);
int main() {
    long decimal;
    printf("Enter a decimal number\n");
    scanf("%ld", &decimal);
    printf("Binary number of %ld is %ld", decimal,
    decimalToBinary(decimal));
    return 0;
}

/* Function to convert a decimal number to binary
number */
long decimalToBinary(long n) {
    int remainder;
    long binary = 0, i = 1;

    while(n != 0) {
        remainder = n%2;
        n = n/2;
        binary= binary + (remainder*i);
        i = i*10;
    }
    return binary;
}
```

**RESULT:**

**INPUT:**

Enter a decimal number

211

**OUTPUT :**

Binary number of 211 is 11010011

### **Expression Evaluation:**

**a. A building has 10 floors with a floor height of 3 meters each. A ball is dropped from the top of the building. Find the time taken by the ball to reach each floor.**

**(Use the formula  $s = ut + (1/2)at^2$  where  $u$  and  $a$  are the initial velocity in m/sec (= 0) and acceleration in m/sec<sup>2</sup> (= 9.8 m/s<sup>2</sup>)).**

```
#include<stdio.h>
#include<math.h>
```

```
void main()
{
    float s=30,u=0,a=9.8,t,temp;    // s = 10*3 = 30
```

```
    /* s = ut+(1/2)at^2
       s = 0*t + (0.5)*a*t^2    */
```

```
    temp=(0.5)*a;
```

```
    /* s = 0 + temp*t ^2
       s/temp = t ^2
       sqrt(s/temp) = t    */
```

```
    t=u*t+sqrt(s/temp);
    printf("Time taken by the ball to reach each floor is
```

```
=%f ",t);  
  
    return 0;  
}
```

**RESULT:**

**OUTPUT:**

Time taken by the ball to reach each floor is =  
2.474358

**b. Write a C program, which takes two integer operands and one operator from the user, performs the operation and then prints the result. (Consider the operators +,-,\*, /, % and use Switch Statement)**

```
#include <stdio.h>
```

```
void main()
```

```
{
```

```
    int a, b, c;
```

```
    char ch;
```

```
    printf("Enter your operator(+, -, /, *, %)\n");
```

```
    scanf("%c", &ch);
```

```
    printf("Enter the values of a and b\n");
```

```
    scanf("%d%d", &a, &b);
```

```
    switch(ch)
```

```
{
```

```
        case '+': c = a + b;
```

```
            printf("addition of two numbers is %d", c);
```

```
            break;
```

```
        case '-': c = a - b;
```

```

        printf("subtraction of two numbers is %d",
c);
        break;
    case '*': c = a * b;
        printf("multiplication of two numbers is
%d", c);
        break;
    case '/': c = a / b;
        printf("remainder of two numbers is %d",
c);
        break;
    case '%': c = a % b;
        printf("quotient of two numbers is %d", c);
        break;
    default: printf("Invalid operator");
        break;
}

}

```

## RESULT:

## INPUT:

Enter you operator(+, -, /, \*, %)

+

Enter the values of a and b

1 3

## OUTPUT:

addition of two numbers is 4

**c. Write a program that finds if a given number is a prime number**

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int n, i, c = 0;
```

```
    printf("Enter any number n:");
```

```
    scanf("%d", &n);
```

```
    for (i = 1; i <= n; i++)
```

```
    {
```

```
        if (n % i == 0)
```

```
        {
```

```
            c++;
```

```
        }
```

```
    }
```

```
    if (c == 2)
```

```
    {
```

```
        printf("The given no is a Prime number");
```

```
    }
```

```
    else
```

```
{  
    printf("The given no is not a Prime number");  
}  
return 0;  
}
```

**RESULT:**

**INPUT:**

Enter any number n: 7

**OUTPUT:**

The given no is a Prime number



**d. Write a C program to find the sum of individual digits of a positive integer and test given number is palindrome.**

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
    int n,x,r,sum=0,k=0;
```

```
    printf("\nEnter The Number:");
```

```
    scanf("%d",&n);
```

```
    x=n;
```

```
    while(n!=0)
```

```
    {
```

```
        r=n%10;
```

```
        sum=sum+r;
```

```
        k=k*10+r;
```

```
        n=n/10;
```

```
    }
```

```
    printf("sum of%d is %d",x,sum);
```

```
    if(x==k)
```

```
    {
```

```
        printf("\n %d is a Palindrome Number",x);
    }
else
{
    printf("\n %d is not a Palindrome Number",x);
}
}
```

## **RESULT:**

## **INPUT:**

Enter The Number: 121

## **OUTPUT:**

**sum of 121 is 4**

121 is a Palindrome Number

4

121 is a Palindrome Number

**e. A Fibonacci sequence is defined as follows: the first and second terms in the sequence are 0 and 1. Subsequent terms are found by adding the preceding two terms in the sequence. Write a C program to generate the first n terms of the sequence.**

```
#include <stdio.h>
int main()
{
    int i,n,a=0,b=1,c;
    printf("Enter n value:");
    scanf("%d",&n);
    printf("\n%d\t%d\t",a,b);
    for(i=3;i<=n;i++)
    {
        c=a+b;
        printf("%d\t",c);
        a=b;
        b=c;
    }
}
```

```
return 0;  
}
```

**RESULT:**

**INPUT:**

Enter n value 5

**OUTPUT:**

0 1 1 2 3

**f. Write a C program to generate all the prime numbers between 1 and n, where n is a value supplied by the user.**

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
    int n, i, j, count;
```

```
    printf("Enter any number\n");
```

```
    scanf("%d", &n);
```

```
    printf("The prime numbers between 1 to %d\n",n);
```

```
    for(i = 1; i <= n; i++)
```

```
    {
```

```
        count = 0;
```

```
        for(j = 1; j <=i; j++)
```

```
            if(i % j == 0)
```

```
            {
```

```
                count++;
```

```
    }  
    if(count == 2)  
    {  
        printf("%d\t", i);  
    }  
}  
}
```

## **RESULT:**

## **INPUT:**

Enter any number  
10

## **OUTPUT:**

The prime numbers between 1 to 10  
2    3    5    7

**g. Write a C program to find the roots of a Quadratic equation.**

```
#include<stdio.h>
#include<math.h>

int main()
{
    int a,b,c,d,real,imaginary;
    float r1,r2;

    printf("enter values of a,b,c");
    scanf("%d%d%d",&a,&b,&c);

    d=(b*b)-(4*a*c);

    if(d==0)
    {
        printf("\n roots are equal ");
        r1=-b/(2*a);
        r2=-b/(2*a);
        printf("\n the value of root1 is =%f",r1);
        printf("\n the value of root2 is =%f",r2);
    }
}
```

```

else if(d>0)
{
    printf("roots are distinct:");
    r1=(-b+sqrt(d))/(2*a);
    r2=(-b-sqrt(d))/(2*a);
    printf("\n the value of root1 is  =%f",r1);
    printf("\n the value of root2 is  =%f",r2);
}
else
{
    realPart = -b/(2*a);
    imaginaryPart = sqrt(-determinant)/(2*a);
    printf("root1 = %f+%f and root2 = %f-%f", real,
imaginary, real, imaginary);
    //printf("\n roots are imaginary");
}
return 0;
}

```

**RESULT:**

**INPUT:**

enter the values of a,b,c 1 6 9

**OUTPUT:**

roots are equal

the value of root1 is =-3.0000



the value of root2 is =-3.0000

**h. Write a C program to calculate the following, where x is a fractional value.**

$$1-x/2 +x^2/4-x^3/6$$

```
#include<stdio.h>
```

```
#include<math.h>
```

```
int main()
```

```
{
```

```
    float  sum=1;
```

```
    int   x,k=1,i;
```

```
    printf("Enter x value:");
```

```
    scanf("%d",&x);
```

```
    for(i=1;i<=3;i++)
```

```
    {
```

```
        k=-k;
```

```
        sum=sum+(k*pow(x,i))/(i*2);
```

```
    }
```

```
    printf("sum of the series=%f",sum);
```

```
    return 0;  
}
```

**RESULT:**

**INPUT:**

Enter x value: 4

**OUTPUT:**

sum of the series= -7.666

**i. Write a C program to read in two numbers, x and n, and then compute the sum of this geometric progression:**

**$1+x+x^2+x^3+\dots+x^n$ .**

**(For example: if n is 3 and x is 5, then the program computes  $1+5+25+125$ ).**

```
#include <stdio.h>
```

```
#include <math.h>
```

```
void main()
```

```
{
```

```
    int n, x, i, sum = 0;
```

```
    printf("Enter the limit\n");
```

```
    scanf("%d", &n);
```

```
    printf("Enter the value of x\n");
```

```
    scanf("%d", &x);
```

```
    if(x < 0 || n < 0)
```

```
    {
```

```
        printf("illegal value");
```

```
    }
```

```
    else
```

```
{  
    for(i = 0; i <= n; i++)  
        sum=sum + pow(x, i);  
}  
printf("sum=%d", sum);  
}
```

## **RESULT:**

## **INPUT:**

Enter the limit

3

Enter the value of x

5

## **OUTPUT:**

sum=156

## **Arrays and Pointers and Functions:**

**a. Write a C program to find the minimum, maximum and average in an array of integers.**

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a[50];
```

```
    int i, max, min, n;
```

```
    printf("Enter size of the array: ");
```

```
    scanf("%d", &n);
```

```
    printf("Enter elements in the array: ");
```

```
    for(i=0; i<n; i++)
```

```
    {
```

```
        scanf("%d", &a[i]);
```

```
    }
```

```
    max = a[0];
```

```
    min = a[0];
```

```
for(i=1; i<n; i++)
{
    if(a[i] > max)
    {
        max = a[i];
    }

    if(a[i] < min)
    {
        min = a[i];
    }
}
printf("Maximum element = %d\n", max);
printf("Minimum element = %d", min);

return 0;
}
```

## **RESULT:**

## **INPUT:**

Enter size of the array: 5

Enter elements in the array: 1 2 3 4 5

## **OUTPUT:**

Maximum element = 5

Minimum element = 1

**b. Write a functions to compute mean, variance,**

## **Standard Deviation, sorting of n elements in single dimension array.**

```
#include<stdio.h>
#include<math.h>

void main()
{
float x[10], mean, variance,dev;
float sum1=0, sum2=0;
int n,i;
printf("Enter the number of integers:");
scanf("%d", &n);

printf("\nEnter the integers:");
for(i=0;i<=n-1;i++)
{
    scanf("%f", &x[i]);
}

//to find mean
for(i=0;i<=n-1;i++)
{
    sum1 = sum1 + x[i];
}

mean = sum1 /n;
printf("\nmean = %f", mean);
```

```
//to find variance
for(i=0;i<=n-1;i++)
{
    sum2 = sum2 + (x[i] - mean) * (x[i] - mean);
}
variance = sum2/n;
printf("\nvariance = %f", variance);

//to find deviation
dev = sqrt(variance);
printf("\ndeivation = %f", dev);

}
```

**RESULT:**

**INPUT:**

Enter the number of integers:5

Enter the integers:1 2 3 4 5

**OUTPUT:**

mean = 3.000000

variance = 2.000000



deviation = 1.414214

- c. Write a C program that uses functions to perform the following:**
- i. Addition of Two Matrices**
  - ii. Multiplication of Two Matrices**
  - iii. Transpose of a matrix with memory dynamically allocated for the new matrix as row and column counts may not be same.**

i. Addition of Two Matrices:

```
# include <stdio.h>
# include <conio.h>
void main ( )
{
int i, j, a[3][3], b[3][3], sum[3][3];
    clrscr ( ) ;
printf ("Enter the elements of 1st array .\n") ;
    for (i=1;i<=3;i++)
```

```
{
    for (j=1;j<=3;j++)
    {
        scanf ("%d", &a[i][j]) ;
    }
}
printf ("Elements of 1st array are: \n") ;
for (i=1;i<=3;i++)
{
    for (j=1;j<=3;j++)
    {
        printf ("%d\t", a[i][j]) ;
    }
    printf ("\n") ;
}
printf ("Enter the elements of 2nd array .\n") ;
for (i=1;i<=3;i++)
{
    for (j=1;j<=3;j++)
    {
        scanf ("%d", &b[i][j]) ;
    }
}
printf ("Elements of 2nd array are: \n") ;
for (i=1;i<=3;i++)
{
    for (j=1;j<=3;j++)
    {
```

```

        printf ("%d\t", b[i][j]) ;
    }
    printf ("\n") ;
}
printf ("The sum of both the matrices are: \n") ;
for (i=1;i<=3;i++)
{
    for (j=1;j<=3;j++)
    {
        sum[i][j] = a[i][j] + b[i][j];
        printf ("%d\t", sum[i][j]) ;
    }
    printf ("\n") ;
}
getch ( ) ;
}

```

-----OR-----

```

#include<stdio.h>
int read(int x[10][10],int m,int n);
int add(int a[10][10],int b[10][10],int c[10][10],int
m,int n);
int write(int x[10][10],int m,int n);

int main()
{
    int a[10][10],b[10][10],c[10][10],r1,r2,c1,c2;
    printf("\nEnter rows and columns of matrix 1:\n");
}

```

```
scanf("%d%d",&r1,&c1);
printf("\nEnter rows and columns of matrix2:\n");
scanf("%d%d",&r2,&c2);
```

```
if((r1==r2)&&(c1==c2))
{
    printf("\nEnter elements of matrix1:\n");
    read(a,r1,c1);
    printf("\nEnter elements of matrix2:\n");
    read(b,r2,c2);
    printf("after adding a&b matrices\n");

    add(a,b,c,r1,c1);
    write(c,r1,c1);
}
else
    printf("\n Addition is not possible\n");
}
```

```
int read(int x[10][10],int m,int n)
{
    int i,j;
    for(i=0;i<m;i++)
        for(j=0;j<n;j++)
            scanf("%d",&x[i][j]);
}
```

```
int add(int a[10][10],int b[10][10],int c[10][10],int
```

```

m,int n)
{
    int i,j;
    for(i=0;i<m;i++)
        for(j=0;j<n;j++)
            c[i][j]=a[i][j]+b[i][j];
}

int write(int c[10][10],int m,int n)
{
    int i,j;
    for(i=0;i<m;i++)
    {
        printf("\n");
        for(j=0;j<n;j++)
            printf("\t%d",c[i][j]);
    }
}

```

**RESULT:**

**INPUT:**

Enter rows and columns of matrix1

2 2

Enter rows and columns of matrix2

2 2

Enter elements of matrix1

1 2

3 4

Enter elements of matrix2

1 2

3 4

## **OUTPUT:**

after adding a&b matrices

2 4

6 8

## **ii. Multiplication of two matrices**

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
    int a[10][10],b[10][10],c[10][10],i,j,k,r1,c1,r2,c2;
```

```
    int sum=0;
```

```
clrscr();
```

```
printf("Enter number of rows and columns of first  
matrix (MAX 10)\n");
```

```
scanf("%d%d",&r1,&c1);
```

```
printf("Enter number of rows and columns of  
second matrix MAX 10)\n");
```

```
scanf("%d%d",&r2,&c2);
```

```
if(r2==c1)
```

```
{
```

```
printf("\n Enter First Matrix:");
```

```
for(i=0; i<r1; i++)
```

```
{
```

```
for(j=0; j<c1; j++)
```

```
scanf("%d",&a[i][j]);
```

```
}
```

```
printf("\n Enter Second Matrix: ");
```

```
for(i=0; i<r2; i++)
```

```
{
```

```
for(j=0; j<c2; j++)
```

```
scanf("%d",&b[i][j]);
```

```
}
```

```
printf("The First Matrix Is: \n");
```

```
//print the first matrix
```

```
for(i=0; i<r1; i++)
{
    for(j=0; j<c1; j++)
        printf(" %d ",a[i][j]);
    printf("\n");
}
```

```
printf("The Second Matrix Is:\n");
// print the second matrix
for(i=0; i<r2; i++)
{
    for(j=0; j<c2; j++)
        printf(" %d ",b[i][j]);
    printf("\n");
}
```

```
printf("Multiplication of the Matrices:\n");
```

```
for(i=0; i<r1; i++)
{
    for(j=0; j<c2; j++)
    {
        c[i][j]=0;
        for(k=0; k<r1; k++)
            c[i][j]+=a[i][k]*b[k][j];
        printf("%d ",c[i][j]);
    }
}
```



```

        printf("\n");
    }

}
else
{
    printf("Matrix Multiplication is Not Possible");
}
getch();
}

```

-----OR-----

```

#include<stdio.h>
int read(int x[10][10],int m,int n);
int mul(int a[10][10],int b[10][10], int c[10][10],int
r1,int c2,int r2);
int write(int x[10][10],int m,int n);

int main()
{
    int a[10][10],b[10][10],c[10][10],r1,r2,c1,c2;
    printf("\nEnter rows and columns of matrix1:\n");
    scanf("%d%d",&r1,&c1);
    printf("\nEnter rows and columns of matrix2:\n");
    scanf("%d%d",&r2,&c2);

    if(c1==r2)
    {

```

```

printf("\nEnter elements of matrix1:\n");
read(a,r1,c1);
printf("\nEnter elements of matrix2:\n");
read(b,r2,c2);
printf("After multiplying a&b matrices\n");

mul(a,b,c,r1,c2,r2);
write(c,r1,c2);
}
else
    printf("\n Multiplication is not possible\n");
}

```

```

int read(int x[10][10],int m,int n)
{
    int i,j;
    for(i=0;i<m;i++)
        for(j=0;j<n;j++)
            scanf("%d",&x[i][j]);
}

```

```

int mul(int a[10][10],int b[10][10], int c[10][10],int
r1,int c2,int r2)
{
    int i,j,k;
    for(i=0;i<r1;i++)
        for(j=0;j<c2;j++)

```

```

    {
        c[i][j]=0;
        for(k=0;k<r2;k++)
            c[i][j]=c[i][j]+a[i][k]*b[k][j];
    }
}

```

```

int write(int c[10][10],int m,int n)
{
    int i,j;
    for(i=0;i<m;i++)
    {
        printf("\n");
        for(j=0;j<n;j++)
            printf("\t%d",c[i][j]);
    }
}

```

**RESULT:**

**INPUT:**

Enter rows and columns of matrix1

2 2

Enter rows and columns of matrix2

2 2

Enter elements of matrix1

1 2

3 4

Enter elements of matrix2

1 2

3 4

## **OUTPUT:**

After multiplying a&b matrices

7 10

15 22

**iii. Transpose of a matrix with memory dynamically allocated for the new matrix as row and column counts may not be same.**

```
#include<stdio.h>
#include<malloc.h>

int main()
{
    int *a[10];
    int m,n,i,j;

    printf("\n Enter matrix order");
    scanf("%d%d",&m,&n);

    for(i=0;i<m;i++)

        a[i]=(int *)malloc(n*sizeof(int));

    printf("\n Enter matrix elements:");
    for(i=0;i<m;i++)
    for(j=0;j<n;j++)
    scanf("%d",&a[i][j]);
```

```
printf("\n The original matrix\n");
for(i=0;i<m;i++)
{
    for(j=0;j<n;j++)
        printf("%d\t",a[i][j]);
    printf("\n");
}
```

```
printf("\n The transpose of matrix\n");
for(j=0;j<n;j++)
{
    for(i=0;i<m;i++)
        printf("%d\t",a[i][j]);
    printf("\n");
}
```

```
return 0;
}
```

## **RESULT - 1:**

### **INPUT:**

Enter matrix order 2 3

Enter matrix elements: 1 2 3 4 5 6

### **OUTPUT:**

The original matrix

1      2      3

4      5      6

The transpose of matrix

1      4

2      5

3      6

**RESULT – 2:**

**INPUT:**

Enter matrix order 3 2

Enter matrix elements: 1 2 3 4 5 6

**OUTPUT:**

The original matrix

1      2

3      4

5      6

The transpose of matrix

1      3      5

2      4      6

### **RESULT – 3:**

#### **INPUT:**

Enter matrix order 2 2

Enter matrix elements:1 2 3 4

#### **OUTPUT:**

The original matrix

1      2

3      4

The transpose of matrix

1      3

2      4



**d. Write C programs that use both recursive and non-recursive functions**

- i. To find the factorial of a given integer.**
- ii. To find the GCD (greatest common divisor) of two given integers.**
- iii. To find  $x^n$**

**i. To find the factorial of a given integer using recursive function and non-recursive functions:**

```
#include <stdio.h>
```

```
int recfactorial(int );  
int nonrecfactorial(int );
```

```
void main()  
{  
    int n, a, b;  
  
    printf("Enter any number\n");  
    scanf("%d", &n);  
  
    a = recfactorial(n);  
    printf("The factorial of a given number using  
recursion is %d \n", a);  
  
    b = nonrecfactorial(n);  
    printf("The factorial of a given number using  
nonrecursion is %d ", b);  
}
```

```
int recfactorial(int x)  
{  
    int f;  
    if(x == 0)  
    {  
        return(1);  
    }  
    else
```

```
{  
    f = x * recfactorial(x - 1);  
    return(f);  
}  
}
```

```
int nonrecfactorial(int x)  
{  
    int i, f = 1;  
    for(i = 1; i <= x; i++)  
    {  
        f = f * i;  
    }  
    return(f);  
}
```

## **RESULT:**

### **INPUT:**

Enter any number

5

### **OUTPUT:**

The factorial of a given number using recursion is  
120

The factorial of a given number using  
nonrecursion is 120



**ii. To find the GCD (greatest common divisor) of two given integers using recursive function and non-recursive functions:**

```
#include <stdio.h>
int recgcd(int , int );
int nonrecgcd(int , int );

void main()
{
```

```
int a, b, c, d;
```

```
printf("Enter two numbers a, b\n");  
scanf("%d%d", &a, &b);
```

```
c = recgcd(a, b);  
printf("The gcd of two numbers using recursion is  
%d\n", c);
```

```
d = nonrecgcd(a, b);  
printf("The gcd of two numbers using nonrecursion  
is %d", d);  
}
```

```
int recgcd(int x, int y)  
{  
    if(y == 0)  
    {  
        return(x);  
    }  
    else  
    {  
        return(recgcd(y, x % y));  
    }  
}
```

```
int nonrecgcd(int x, int y)  
{
```

```

int z;
while(x % y != 0)
{
    z = x % y;
    x = y;
    y = z;
}
return(y);
}

```

## RESULT:

## INPUT:

Enter two numbers a, b    3   6

## OUTPUT:

The gcd of two numbers using recursion is 3

The gcd of two numbers using nonrecursion is 3

## iii. To find $x^n$ using recursive function and non-recursive functions:

```

#include <stdio.h>
#include<math.h>

```

```

long recpower(int, int);
long nonrecpower(int , int );

```

```

int main()

```

```

{   int p, num;
    long result1, result2;
    printf("Enter a number : ");
    scanf("%d", & num);
    printf("Enter it's power: ");
    scanf("%d", &p);

    result1 = recpower(num, p);
    printf("Recursive function result :%d^%d is %ld",
num, p, result1);

    result2 = nonrecpower(num, p);
    printf("\nNon recursive function result: %d^%d is
%ld", num, p, result2);

    return 0;
}

```

```

long recpower(int num, int p)
{
    if (p==1)
    {
        return num;
    }
else
{
    return (num * recpower(num, p - 1));
}
}

```



```
}  
    }  
    return 1;  
}  
  
long nonrecpower(int num, int p)  
{  
    long power = 1;  
    int i;  
  
    for(i=1; i<=p; i++)  
    {  
        power = power * num;  
    }  
  
    return power;  
}
```

**RESULT:**

**INPUT:**

Enter a number : 2

Enter it's power: 2

**OUTPUT:**

Recursive function result :  $2^2$  is 4

Non recursive function result :  $2^2$  is 4

**e. Write a program for reading elements using pointer into array and display the values using array.**

```
void main()  
{  
    int a[50],*p,i,n;
```

```
p=a;

printf("Enter size of array:");
scanf("%d",&n);

printf("Enter elements of array:");

for(i=0;i<n;++i)
    scanf("%d",p+i);

for(i=0;i<n;++i)
    printf("%d\t",*(p+i));

}
```

## **RESULT:**

### **INPUT:**

Enter size of array: 5

Enter elements of array:2 5 8 9 1

### **OUTPUT:**

2 5 8 9 1

**f. Write a program for display values reverse order from array using pointer.**

```
#include<stdio.h>
#define MAX 30
```

```
void main()
{
int size,i,arr[MAX];
int *ptr;
```

```
ptr=&arr[0];
```

```
printf("Enter the size of array : ");  
scanf("%d",&size);
```

```
printf("Enter %d integers into array: ",size);  
for(i=0;i<size;i++)  
{  
    scanf("%d",ptr);  
    ptr++;  
}
```

```
ptr=&arr[size-1];
```

```
printf("Elements of array in reverse order are:\n");
```

```
for(i=size-1;i>=0;i--)  
{  
    printf("\nElement%d is %d\n",i,*ptr);  
    ptr--;  
}
```

```
}
```

**RESULT:**

**INPUT:**

Enter the size of array : 5

Enter 5 integers into array: 10 20 30 40 50

## **OUTPUT:**

Elements of array in reverse order are:

Element4 is 50

Element3 is 40

Element2 is 30

Element1 is 20

Element0 is 10

**g. Write a program through pointer variable to sum of n elements from array.**

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int array[20];
```

```
    int n,i,sum=0;
```

```
    int *ptr;
```

```
    printf("\nEnter the array size:");
```

```
    scanf("%d", &n);
```

```

printf("\nEnter array elements:");
for(i=0;i<5;i++)
    scanf("%d",&array[i]);

/* array is equal to base address * array = &array[0]
*/

ptr = array;

for(i=0;i<n;i++)
{
    /*ptr refers to the value at address
    sum = sum + *ptr;
    ptr++;
}

printf("\nThe sum is: %d",sum);
}

```

**RESULT:**

**INPUT:**

Enter the array size: 5

Enter array elements:1 2 3 4 5



## **OUTPUT:**

The sum is: 15

### **Files:**

**a. Write a C program to display the contents of a file to standard output device.**

```
#include<stdio.h>
#include<string.h>
void main()
{
char ch;
char str[20];
FILE *fp;
```

```
printf("Enter the source file name");
gets(str);
```

```
fp=fopen(str,"r");

if(fp==NULL)
{
    printf("Error in opening file");
}

while((ch=getc(fp))!=EOF)
{
    putchar(ch);
}
fclose(fp);
}
```

## **RESULT:**

## **INPUT:**

hello.txt (created file with text "this is kmit")

## **OUTPUT:**

Enter the source file name

hello.txt

this is kmit

**b. Write a C program which copies one file to another, replacing all lowercase characters with their uppercase equivalents.**

```
#include <stdio.h>
#include<stdlib.h>
void main()
{
    FILE *fp,*ft;
    char ch;

    fp=fopen("w.c","r");
    ft=fopen("ww.c","w");

    if(fp==NULL)
    {
        puts("Cannot open file");
        exit(0);
    }
```

```
if(ft==NULL)
{
    puts("Cannot open file");
}

while((ch=fgetc(fp))!=EOF)
{
    if(ch>=97&&ch<=122)
        ch=ch-32;
    fputc(ch,ft);
}
fclose(fp);
fclose(ft);
}
```

## **RESULT:**

## **INPUT:**

```
//w.c created file with following c program code
#include<stdio.h>
void main()
{
    int a=10,b=20;
    printf("addition of a,b=%d",a+b);
}
```

## **OUTPUT:**

//ww.c generated by compiler with following code by

convert lowercase letters to uppercase letters

```
#INCLUDE<STDIO.H>
```

```
VOID MAIN()
```

```
{
```

```
INT A=10,B=20;
```

```
PRINTF("ADDITION OF A,B=%D",A+B); }
```

**c. Write a C program to count the number of times a character occurs in a text file. The file name and the character are supplied as command line arguments.**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <string.h>
```

```
int main(int argc, char *argv[])
```

```
{
```

```
FILE *finp = NULL;
```

```
FILE *output = NULL;
```

```
int letter; // character to be found
```

```
int ex=0; // character occurrence counter
```

```
if( argc!=4 )
```

```
{
```

```
printf( "pass correct way of command line  
arguments like inputfile outputfile character want
```

```
        to search\n");
    exit(0);
}
```

```
finp=fopen(argv[1], "r");
```

```
if( finp==NULL)
{
    perror( "fopen for the input file failed" );
    exit(0);
}
```

```
output=fopen(argv[2], "w");
```

```
if(output==NULL )
{
    perror( "fopen for the output file failed" );
    fclose( finp );
    exit(0);
}
```

```
while( (letter = fgetc(finp) )!=EOF)
{
    if( argv[3][0]==letter) /*From ASCII TABLE*/
    {
        ex++;
    }
}
```

```
    }  
}
```

```
    fprintf(output, "The search character is '%c' and it  
occurred %d times\n", argv[3][0], ex);  
    fclose(finp);  
    fclose(output);  
  
    return 0;  
}
```

## **RESULT:**

## **OUTPUT:**

```
$/a.out hi.txt hi2.txt s
```

(hi.txt file contained text: hello studentsssss.

As a result: hi2.txt got: The search character is 's'  
and it occurred 6 times )





**d. Write a C program that does the following:**

**It should first create a binary file and store 10 integers, where the file name and 10**

**values are given in the command line. (hint: convert the strings using atoi function)**

**Now the program asks for an index and a value from the user and the value at that**

**index should be changed to the new value in the file. (hint: use fseek function)**

**The program should then read all 10 values and print them back.**



**e. Write a C program to merge two files into a third file (i.e., the contents of the first file followed by those of the second are put in the third file).**

```
#include <stdio.h>
#include <stdlib.h>

void main()
{
    // Open two files to be merged
    FILE *fp1 = fopen("w.c", "r");
    FILE *fp2 = fopen("ww.c", "r");

    // Open file to store the result
    FILE *fp3 = fopen("r.c", "w");

    char c;
```

```
if (fp1 == NULL || fp2 == NULL || fp3 == NULL)
{
    puts("Could not open files");
    exit(0);
}

// Copy contents of first file to file3.txt
while ((c = fgetc(fp1)) != EOF)
    fputc(c, fp3);

// Copy contents of second file to file3.txt
while ((c = fgetc(fp2)) != EOF)
    fputc(c, fp3);

printf("Merged w.c and ww.c into r.c");
fclose(fp1);
fclose(fp2);
fclose(fp3);
}
```

## **RESULT:**

## **INPUT:**

w.c has following code  
#include<stdio.h>

```
void main()
{
int a=10,b=20;
printf("addition of a,b=%d",a+b);
}
```

ww.c has following code

```
#INCLUDE<STDIO.H>
VOID MAIN()
{
INT A=10,B=20;
PRINTF("ADDITION OF A,B=%D",A+B);
}
```

## **OUTPUT:**

Merged w.c and ww.c into r.c.

r.c has following code

```
#include<stdio.h>
void main()
{
int a=10,b=20;
printf("addition of a,b=%d",a+b);
}
#include<STDIO.H>
VOID MAIN()
{
```

```
INT A=10,B=20;  
PRINTF("ADDITION OF A,B=%D",A+B);  
}
```

### **Strings:**

**a. Write a C program to convert a Roman numeral ranging from I to L to its decimal equivalent.**

```
#include <stdio.h>
#include <string.h>
#include <stdlib.h>

void main()
{
    char rom[30];
    int a[30], l, i, k, dec;

    printf("Enter the roman number\n");
    scanf("%s", &rom);

    l = strlen(rom);
    for(i = 0; i < l; i++)
    {
        switch (rom[i])
```

```

{
    case 'T': a[i] = 1;
        break;
    case 'V': a[i] = 5;
        break;
    case 'X': a[i] = 10;
        break;
    case 'L': a[i] = 50;
        break;
    case 'C': a[i] = 100;
        break;
    case 'D': dec = dec + 500;
        break;
    case 'M': a[i] = 1000;
        break;
    default : printf("Invalid choice");
        break;
}
}

```

```

k = a[l - 1];
for(i = l - 1; i > 0; i--)
{
    if(a[i] > a[i - 1])
    {
        k = k - a[i - 1];
    }
}

```



```
        if(a[i] <= a[i - 1])
        {
            k = k + a[i - 1];
        }
    }

    printf("decimal equivalent is %d", k);
}
```

**RESULT:**

**INPUT:**

Enter the roman number  
XIV

**OUTPUT:**

decimal equivalent is 14

**b. Write a C program that converts a number**

**ranging from 1 to 50 to Roman equivalent**

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
    int a,b,e;
```

```
    printf("Input a number (between 1-50):");
```

```
    scanf("%d",&e);
```

```
    while (e==0||e>50)
```

```
    {
```

```
        printf ("ERROR: Invalid Input!");
```

```
        printf ("\nEnter the number again:");
```

```
        scanf ("%d",&e);
```

```
    }
```

```
    a = ((e/10)%10)*10;
```

```
    b = ((e/1)%10)*1;
```

```
    if (a == 10)
```

```
        printf("X");
```

```
    else if (a == 20)
```

```
        printf("XX");
```

```
    else if (a == 30)
```

```
        printf("XXX");
```

```
else if (a == 40)
    printf("XL");
else if (a == 50)
    printf("L");

if (b == 1)
    printf("I");
else if (b == 2)
    printf("II");
else if (b == 3)
    printf("III");
else if (b == 4)
    printf("IV");
else if (b == 5)
    printf("V");
else if (b == 6)
    printf("VI");
else if (b == 7)
    printf("VII");
else if (b == 8)
    printf("VIII");
else if (b == 9)
    printf("IX");
}
```

**RESULT:**

**INPUT:**

Input a number (between 1-50): 51

ERROR: Invalid Input!  
Enter the number again:50

**OUTPUT:**  
L

**c. Write a C program that uses functions to perform the following operations:**

**i. To insert a sub-string in to a given main string from a given position.**

**ii. To delete n Characters from a given position in a given string.**

**i. To insert a sub-string in to a given main string from a given position.**

```
#include <stdio.h>
#include <string.h>
```

```
void insstr(int);
```

```
char MS[20], SS[20], TS[50];
int i,j,pos;
```

```
void main()
{
    puts("Enter First String=\n");
    gets(MS);

    puts("Enter Second String=\n");
    gets(SS);
```

```
    printf("Enter the position where the item has to be
inserted=\n ");
    scanf("%d",&pos);
```

```
    insstr(pos);
}
```

```

void insstr(int pos)
{
    for(i=0;i<pos;i++)
    {
        TS[i]=MS[i];
    }

    for(j=0;SS[j]!='\0';j++)
    {
        TS[i]=SS[j];
        i++;
    }

    for(j=pos;MS[j]!='\0';j++)
    {
        TS[i]=MS[j];
        i++;
    }

    TS[i]='\0';
    printf("The final string is=\n");
    puts(TS);
}

```

**RESULT:**

**INPUT:**

Enter First String=  
sai



Enter Second String=  
ram

Enter the position where the item has to be  
inserted=  
3

## **OUTPUT:**

The final string is=  
sairam

**ii. To delete n Characters from a given position in a given string.**

```
#include<stdio.h>  
#include<string.h>
```

```
void delstr(int n,int pos);
```

```
char str[15];
```

```
int i,j;
```

```
void main()
```

```
{
```

```
    int pos,n;
```

```
    printf("Enter the string:\n");
```

```
    gets(str);
```

```
    printf("Enter the position in string from where to  
delete");
```

```
    scanf("%d", &pos);
```

```
    printf("Enter no of char to be deleted");
```

```
    scanf("%d",&n);
```

```
    delstr(n,pos);
```

```
}
```

```
void delstr(int n,int pos)
```

```
{
```

```
    i=pos;
```

```
    for(j=pos+n;str[j]!='\0';j++)
```

```
    {
```

```
    str[i]=str[j];  
    i++;  
}  
str[i]='\0';  
printf("\n string after deletion=%s",str);  
}
```

## **RESULT:**

## **INPUT:**

Enter the string:

kmitcollege

Enter the position in string from where to delete 4

Enter no of char to be deleted 7

## **OUTPUT:**

string after deletion=kmit

**d. Write a C program to determine if the given string is a palindrome or not (Spelled same in both directions with or without a meaning like madam, civic, noon, abcba, etc.)**

```
#include <stdio.h>
```

```
#include <string.h>
```

```
int main()
{
    char str[100];
    int i, len, flag;
    flag = 0;

    printf("\n Please Enter any String : ");
    gets(str);

    len = strlen(str);

    for(i = 0; i < len; i++)
    {
        if(str[i] != str[len - i - 1])
        {
            flag = 1;
            break;
        }
    }
    if(flag == 0)
    {
        printf("\n %s is a Palindrome String", str);
    }
    else
    {
        printf("\n %s is Not a Palindrome String",
str);
```

```
    }  
  
    return 0;  
}
```

**RESULT:**

**INPUT:**

Please Enter any String : MALAYALAM

**OUTPUT:**

MALAYALAM is a Palindrome String

**e. Write a C program that displays the position of a character ch in the string S or – 1 if S doesn't contain ch.**

```
#include<stdio.h>  
#include<string.h>
```

```
void main()
{
    char s[30], t[20];
    char *found;

    puts("Enter the first string: ");
    gets(s);

    puts("Enter the string to be searched: ");
    gets(t);

    found = strstr(s, t);

    if(found)
    {
        printf("Second String is found in the First String
at %d position.\n", found - s);
    }
    else
    {
        printf("-1");
    }
}
```

**RESULT - 1:**

**INPUT:**

Enter the first string:

sai ram

Enter the string to be searched:

ram

## **OUTPUT:**

Second String is found in the First String at 4 position.

## **RESULT - 2:**

## **INPUT:**

Enter the first string:

sai ram

Enter the string to be searched:

raj

## **OUTPUT: -1**

**f. Write a C program to count the lines, words and characters in a given text.**

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
    char line[81], a;
```

```
    int i,c,
```



```
end = 0,  
characters = 0,  
words = 0,  
lines = 0;
```

```
printf("TYPE ANY TEXT.\n");  
printf("GIVE ONE SPACE AFTER EACH  
WORD.\n");  
printf("WHEN COMPLETED, PRESS  
'ctrl+z'.\n\n");
```

```
while( end == 0)  
{
```

```
    /* Reading a line of text */  
    c = 0;
```

```
    while((a=getchar()) != '\n')  
        line[c++] = a;  
    line[c] = '\0';
```

```
    /* counting the words in a line */  
    if(line[0] == '\0')  
        break ;
```

```
    else
```

```
    {
```

```
        words++;
```

```
        for(i=0; line[i] != '\0';i++)
```

```
            if(line[i] == ' ' || line[i] == '\t')
```

```

                                words++;
                                }

                                /* counting lines and characters */
                                lines = lines +1;
                                characters = characters + strlen(line);
                                }

printf ("\n");
printf("Number of lines = %d\n", lines);
printf("Number of words = %d\n", words);
printf("Number of characters = %d\n", characters);
}

```

## RESULT:

### INPUT:

TYPE ANY TEXT.

GIVE ONE SPACE AFTER EACH WORD.

WHEN COMPLETED, PRESS 'ctrl+z'.

hi how r u

what r u doing

n where r u

<sup>^</sup>Z

**OUTPUT:**

Number of lines = 3

Number of words = 12

Number of characters = 35

**Miscellaneous:**

- a. Write a menu driven C program that allows a user to enter n numbers and then choose between finding the smallest, largest, sum, or average. The menu and all the choices are to be functions. Use a switch statement to determine what action to take. Display an error message if an invalid choice is entered.**

```
#include<stdio.h>
```

```
int main()
{
    int n,i,a[100];
    int ch;

    printf("Enter the size of array :");
    scanf("%d",&n);

    printf("Enter elements in to array\n");
    for(i=0;i<n;i++)
        scanf("%d",&a[i]);

    printf("\n\tMENU\n");
    printf("\n\t1.largest");
    printf("\n\t2.Smallest");
    printf("\n\t3.sum");
    printf("\n\t4.avg");
    printf("\n\n\tEnter your choice:");
    scanf("%d",&ch);

    switch(ch)
    {
        case 1: largest(a,n);
                break;
        case 2: smallest(a,n);
                break;
        case 3: sum(a,n);
                break;
```

```
        case 4:  avg(a,n);
                break;
        default: printf("\n Invalid Choice");
    }
}
```

```
int largest(int x[],int k)
{
    int t,i;
    t=x[0];
    for(i=1;i<k;i++)
    {
        if(x[i]>t)
            t=x[i];
    }
    printf("largest=%d",t);
}
```

```
int smallest(int x[],int k)
{
    int t,i;
    t=x[0];
    for(i=1;i<k;i++)
    {
        if(x[i]<t)
            t=x[i];
    }
    printf("smallest=%d",t);
}
```

```
}
```

```
int sum(int x[],int k)
{
    int i,s=0;
    for(i=0;i<k;i++)
    {
        s=s+x[i];
    }
    printf("sum=%d",s);
}
```

```
int avg(int x[],int k)
{
    int a,i,s=0;
    for(i=0;i<k;i++)
    {
        s=s+x[i];
    }
    a=s/k;
    printf("average =%d",a);
}
```

**RESULT:**

**INPUT:**

Enter the size of array : 5

Enter elements in to array

2 4 6 3 1

## MENU

- 1.largest
- 2.Smallest
- 3.sum
- 4.avg

Enter your choice: 1

## OUTPUT:

largest=6

**b. Write a C program to construct a pyramid of numbers as follows:**

1	*	1	1	*
1 2	* *	2 3	2 2	* *
1 2 3	* * *	4 5 6	3 3 3	* * *
			4 4 4 4	* *
				*

**I. Program to print half pyramid a using numbers.**

```
#include <stdio.h>
int main()
{
    int i, j, rows;
```



```
printf("Enter number of rows: ");
scanf("%d",&rows);

for(i=1; i<=rows; ++i)
{
    for(j=1; j<=i; ++j)
    {
        printf("%d ",j);
    }
    printf("\n");
}
return 0;
}
```

## **RESULT:**

## **INPUT:**

Enter number of rows: 3

## **OUTPUT:**

```
1
1 2
1 2 3
```

## II. Program to print half pyramid using \*.

```
#include <stdio.h>
int main()
{
    int i, j, rows;

    printf("Enter number of rows: ");
    scanf("%d",&rows);

    for(i=1; i<=rows; ++i)
    {
        for(j=1; j<=i; ++j)
        {
            printf("* ");
        }
        printf("\n");
    }
    return 0;
}
```

**RESULT:**

**INPUT:**

Enter number of rows: 3

**OUTPUT:**

\*

\* \*

\* \* \*

### III. Print Floyd's Triangle.

```
#include <stdio.h>
int main()
{
    int rows, i, j, number= 1;

    printf("Enter number of rows: ");
    scanf("%d",&rows);

    for(i=1; i <= rows; i++)
    {
        for(j=1; j <= i; ++j)
        {
            printf("%d ", number);
            ++number;
        }

        printf("\n");
    }

    return 0;
}
```

**RESULT:**

**INPUT:**

Enter number of rows: 3

**OUTPUT:**

1

2 3

4 5 6

#### **IV. Program to print half pyramid using numbers.**

```
#include<stdio.h>
int main()
{
    int n,i,j;

    printf("Enter size");
    scanf("%d",&n);

    for(i=1;i<=n;i++)
    {
        for(j=1;j<=i;j++)
        {
            printf("%d\t",i);
        }
        printf("\n");
    }
}
```

**RESULT:**

**INPUT:**

Enter size 4

## OUTPUT:

```
1
2 2
3 3 3
4 4 4 4
```

v. Print the following pattern.

```
#include <stdio.h>
#include <string.h>

int main()
{
    char str[]="***";
    int i,j, len;

    len = strlen(str);

    for(i=0; i<len; i++)
    {
        for(j=0; j<=i; j++)
            printf("%c\t",str[j]);
        printf("\n");
    }

    for(i=len-2; i>=0; i--)
    {
        for(j=0; j<=i; j++)
            printf("%c\t",str[j]);
        printf("\n");
    }

    return 0;
}
```



**RESULT:**

**OUTPUT:**

\*

\* \*

\* \* \*

\* \*

\*

**Sorting and Searching:**

**a. Write a C program that uses non recursive function to search for a Key value in a given list of integers using linear search method.**

```
#include<stdio.h>
```

```
int lsearch(int a[],int,int);
```

```
int main()
```

```
{
```

```
    int i,j,a[100],key,n;
```

```
    printf("Number of elements in the array\n");  
    scanf("%d",&n);
```

```
    printf("\nEnter %d elements\n",n);
```

```
    for(i=0;i<n;i++)  
        scanf("%d",&a[i]);
```

```
    printf("Element to be searched\n");  
    scanf("%d",&key);
```

```
    lsearch(a,n,key);  
}
```

```
int lsearch(int a[],int n,int key)
```

```
{
```

```
    int flag=0,i;  
    for(i=0;i<n;i++)
```

```
if(key==a[i])
{
    flag=1;
    break;
}
```

```
if(flag== 0)
    printf("key value not found");
else
    printf("key value found at %d index",i);
}
```

## **RESULT:**

## **INPUT:**

Number of elements in the array

10

Enter 10 elements

2 5 3 6 7 8 12 10 9 15

Element to be searched

8

## **OUTPUT:**

key value found at 5 index

**b. Write a C program that uses non recursive function to search for a Key value in a given sorted list of integers using binary search method.**

```
#include<stdio.h>
```

```
int bsearch(int a[],int,int);
```

```
int main()
```

```
{
```

```
    int i,a[100],key,n;
```

```
    printf("Enter Number of elements in the array:");  
    scanf("%d",&n);
```

```
    printf("\nEnter %d elements in sorted order\n",n);  
    for(i=0;i<n;i++)  
        scanf("%d",&a[i]);
```

```
    printf("Element to be searched\n");  
    scanf("%d",&key);
```

```
    bsearch(a,n,key);
```

```
}
```

```
int bsearch(int a[],int n,int key)
```

```
{
```

```
int flag=0,low=0,mid,high=n-1;
while(low<=high)
{
    mid=(low+high)/2;
    if(key==a[mid])
    {
        flag=1;
        break;
    }

    else if(key<a[mid])
        high=mid-1;

    else if(key>a[mid])
        low=mid+1;
}

if(flag==0)
    printf("key value not found");
else
    printf("key value found at %d index",mid);
}
```

**RESULT:**

**INPUT:**

Enter Number of elements in the array: 7

Enter 7 elements in sorted order

12 14 15 18 20 23 65

Element to be searched

23

**OUTPUT:**

key value found at 5 index

**c. Write a C program that implements the Bubble sort method to sort a given list of integers in ascending order.**

```
#include <stdio.h>
int main()
{
    int array[100], n, i, j, temp;

    printf("Enter number of elements\n");
    scanf("%d", &n);
```

```
printf("Enter %d integers\n", n);
for (i = 0; i < n; i++)
    scanf("%d", &array[i]);
```

```
for(i = 0; i<(n-1); i++)
{
    for(j = 0;j<n-i-1; j++)
    {
        if(array[j] > array[j+1])
        {
            temp = array[j];
            array[j] = array[j+1];
            array[j+1] =temp;
        }
    }
}
```

```
printf("Sorted list in ascending order:\n");
for ( i= 0 ; i < n ; i++ )
    printf("%d\t", array[i]);
}
```

**RESULT:**

**INPUT:**

Enter number of elements



10

Enter 10 integers

12 1 4 7 23 76 45 21 54 47

### **OUTPUT:**

Sorted list in ascending order:

1      4      7      12      21      23      45      47      54  
76

**d. Write a C program that sorts the given array of integers using selection sort in descending order.**

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a[10] = { 3,4,7,6,5,1,2,8,10,9 };
```

```
    int n = 10;
```

```
    printf("\nArray Data : ");
```

```
        for (int i = 0; i < n; i++) //Loop for displaying the  
data of array
```

```
{  
    printf(" %d ", a[i]);  
}
```

for (int i = 0; i < n; i++) //Loop for descending  
ordering

```
{  
    for (int j = 0; j < n; j++)  
    {  
        if (a[j] < a[i])  
        {  
            int tmp = a[i];  
            a[i] = a[j];  
            a[j] = tmp;  
        }  
    }  
}
```

```
printf("\n\nDescending : ");  
for (int i = 0; i < n; i++)  
{  
    printf(" %d ", a[i]);  
}
```

```
return 0;  
}
```

## **RESULT:**

## **OUTPUT:**

Array Data : 3 4 7 6 5 1 2 8 10 9

Descending : 10 9 8 7 6 5 4 3 2 1

**e. Write a C program that sorts the given array of integers using insertion sort in ascending order**

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int data[100],n,temp,i,j;
```

```
    printf("Enter number of terms(should be less than  
100): ");
```

```
    scanf("%d",&n);
```

```
    printf("Enter elements: ");
```

```

for(i=0;i<n;i++)
{
    scanf("%d",&data[i]);
}

for(i=1;i<n;i++)
{
    temp = data[i];
    j=i-1;
    while(temp<data[j] && j>=0)
/*To sort elements in descending order, change
temp<data[j] to temp>data[j] in above line.*/
    {
        data[j+1] = data[j];
        --j;
    }
    data[j+1]=temp;
}

printf("In ascending order: ");
for(i=0; i<n; i++)
    printf("%d\t",data[i]);
return 0;
}

```

**RESULT:**

**INPUT:**

Enter number of terms(should be less than 100): 5

Enter elements:

6 8 4 10 99

**OUTPUT:**

In ascending order: 4 6 8 10 99

**f. Write a C program that sorts a given array of names.**

```
#include <stdio.h>
#include <string.h>
```

```
void main()
{
```

```
    char name[10][8], tname[10][8], temp[8];
    int i, j, n;
```

```
    printf("Enter the value of n \n");
    scanf("%d", &n);
```

```
printf("Enter %d names \n",n);
```

```
for (i = 0; i < n; i++)  
{  
    scanf("%s", name[i]);  
    strcpy(tname[i], name[i]);  
}
```

```
for (i = 0; i < n - 1 ; i++)  
{  
    for (j = i + 1; j < n; j++)  
    {  
        if (strcmp(name[i], name[j]) > 0)  
        {  
            strcpy(temp, name[i]);  
            strcpy(name[i], name[j]);  
            strcpy(name[j], temp);  
        }  
    }  
}
```

```
printf("\n-----\n");  
printf("Input Names\tSorted names\n");  
printf("-----\n");
```

```
for (i = 0; i < n; i++)  
{  
    printf("%s\t\t%s\n", tname[i], name[i]);
```

```

    }

    printf("-----\n");

}

```

## RESULT:

### INPUT:

Enter the value of n

7

Enter 7 names

heap

queue

stack

object

class

program

project

### OUTPUT:

```

-----
Input Names   Sorted names
-----
heap         class

```

queue	heap
stack	object
object	program
class	project
program	queue
project	stack

---