

## ASSIGNMENT ON TYPES OF SUB QUERY.

51.WAQTD NAME OF THE EMPLOYEES EARNING SALARY MORE THAN THE SALESMAN

52.WAQTD DETAILS OF THE EMPLOYEES HIRED AFTER ALL THE CLERKS

53.WAQTD NAME AND SALARY FOR ALL THE EMPLOYEES IF THEY ARE EARNING LESS THAN ATLEST A MANAGER

54.WAQTD NAME AND HIREDATE OF EMPLOYEES HIRED BEFORE ALL THE MANAGERS

55.WAQTD NAMES OF THE EMPLOYEES HIRED AFTER ALL THE MANAGERS AND EARNING SALARY MORE THAN ALL THE CLERKS

56.WAQTD DETAILS OF THE EMPLOYEES WORKING AS CLERK AND HIRED BEFORE ATLEST A SALESMAN

57.WAQTD DETAILS OF EMPLOYEES WORKING IN ACCOUNTING OR SALES DEPT

58.WAQTD DEPARTMENT NAMES OF THE EMPLOYEES WITH NAME SMITH , KING AND MILLER

59.WAQTD DETAILS OF EMPLOYEES WORKING NEWYORK OR CHICAGO

60.WAQTD EMP NAMES IF EMPLOYEES ARE HIRED AFTER ALL THE EMPLOYEES OF DEPT 10

File Edit Search Options Help

```
SQL> SELECT ENAME
  2   FROM EMP
  3   WHERE SAL > ALL(SELECT SAL
  4                     FROM EMP
  5                     WHERE JOB = 'SALESMAN');
```

ENAME

```
-----
JONES
BLAKE
CLARK
SCOTT
KING
FORD
```

6 rows selected.

```
SQL> SELECT *
  2   FROM EMP
  3   WHERE HIREDATE > ALL(SELECT HIREDATE
  4                         FROM EMP
  5                         WHERE JOB = 'CLERK');
```

no rows selected

```
SQL> SELECT ENAME , SAL
  2   FROM EMP
  3   WHERE SAL < ANY(SELECT SAL
  4                    FROM EMP
  5                    WHERE JOB = 'MANAGER');
```

| ENAME  | SAL  |
|--------|------|
| SMITH  | 800  |
| JAMES  | 950  |
| ADAMS  | 1100 |
| WARD   | 1250 |
| MARTIN | 1250 |
| MILLER | 1300 |
| TURNER | 1500 |
| ALLEN  | 1600 |
| CLARK  | 2450 |
| BLAKE  | 2850 |

10 rows selected.

File Edit Search Options Help

```
SQL> SELECT ENAME , HIREDATE
  2 FROM EMP
  3 WHERE HIREDATE < ALL(SELECT HIREDATE
  4                        FROM EMP
  5                        WHERE JOB = 'MANAGER');
```

| ENAME | HIREDATE  |
|-------|-----------|
| SMITH | 17-DEC-80 |
| ALLEN | 20-FEB-81 |
| WARD  | 22-FEB-81 |

```
SQL> SELECT ENAME
  2 FROM EMP
  3 WHERE HIREDATE > ALL(SELECT HIREDATE
  4                        FROM EMP
  5                        WHERE JOB = 'MANAGER') AND SAL > ALL(SELECT SAL
  6                                                                FROM EMP
  7                                                                WHERE JOB = 'CLERK');
```

| ENAME  |
|--------|
| SCOTT  |
| KING   |
| TURNER |
| FORD   |

```
SQL> SELECT *
  2 FROM EMP
  3 WHERE JOB = 'CLERK' AND HIREDATE < ANY(SELECT HIREDATE
  4                                          FROM EMP
  5                                          WHERE JOB = 'SALESMAN');
```

| EMPNO | ENAME | JOB   | MGR  | HIREDATE  | SAL | COMM | DEPTNO |
|-------|-------|-------|------|-----------|-----|------|--------|
| 7369  | SMITH | CLERK | 7902 | 17-DEC-80 | 800 |      | 20     |

SQL> |

```
SQL> SELECT *
  2 FROM EMP
  3 WHERE DEPTNO IN (SELECT DEPTNO
  4                   FROM DEPT
  5                   WHERE DNAME = ANY ('ACCOUNTING','SALES'));
```

| EMPNO | ENAME  | JOB       | MGR  | HIREDATE  | SAL  | COMM | DEPTNO |
|-------|--------|-----------|------|-----------|------|------|--------|
| 7499  | ALLEN  | SALESMAN  | 7698 | 20-FEB-81 | 1600 | 300  | 30     |
| 7521  | WARD   | SALESMAN  | 7698 | 22-FEB-81 | 1250 | 500  | 30     |
| 7654  | MARTIN | SALESMAN  | 7698 | 28-SEP-81 | 1250 | 1400 | 30     |
| 7698  | BLAKE  | MANAGER   | 7839 | 01-MAY-81 | 2850 |      | 30     |
| 7782  | CLARK  | MANAGER   | 7839 | 09-JUN-81 | 2450 |      | 10     |
| 7839  | KING   | PRESIDENT |      | 17-NOV-81 | 5000 |      | 10     |
| 7844  | TURNER | SALESMAN  | 7698 | 08-SEP-81 | 1500 | 0    | 30     |
| 7900  | JAMES  | CLERK     | 7698 | 03-DEC-81 | 950  |      | 30     |
| 7934  | MILLER | CLERK     | 7782 | 23-JAN-82 | 1300 |      | 10     |

9 rows selected.

```
SQL> SELECT DNAME
  2 FROM DEPT
  3 WHERE DEPTNO IN (SELECT DEPTNO
  4                   FROM EMP
  5                   WHERE ENAME = ANY ('SMITH','KING','MILLER'));
```

DNAME

ACCOUNTING  
RESEARCH

```
SQL> SELECT *
  2 FROM EMP
  3 WHERE DEPTNO IN (SELECT DEPTNO
  4                   FROM DEPT
  5                   WHERE LOC = ANY ('NEW YORK','CHICAGO'));
```

| EMPNO | ENAME  | JOB       | MGR  | HIREDATE  | SAL  | COMM | DEPTNO |
|-------|--------|-----------|------|-----------|------|------|--------|
| 7499  | ALLEN  | SALESMAN  | 7698 | 20-FEB-81 | 1600 | 300  | 30     |
| 7521  | WARD   | SALESMAN  | 7698 | 22-FEB-81 | 1250 | 500  | 30     |
| 7654  | MARTIN | SALESMAN  | 7698 | 28-SEP-81 | 1250 | 1400 | 30     |
| 7698  | BLAKE  | MANAGER   | 7839 | 01-MAY-81 | 2850 |      | 30     |
| 7782  | CLARK  | MANAGER   | 7839 | 09-JUN-81 | 2450 |      | 10     |
| 7839  | KING   | PRESIDENT |      | 17-NOV-81 | 5000 |      | 10     |
| 7844  | TURNER | SALESMAN  | 7698 | 08-SEP-81 | 1500 | 0    | 30     |
| 7900  | JAMES  | CLERK     | 7698 | 03-DEC-81 | 950  |      | 30     |
| 7934  | MILLER | CLERK     | 7782 | 23-JAN-82 | 1300 |      | 10     |

9 rows selected.



# Oracle SQL\*Plus

File Edit Search Options Help

```
SQL> SELECT ENAME
2 FROM EMP
3 WHERE HIREDATE > ALL(SELECT HIREDATE
4 FROM EMP
5 WHERE DEPTNO = 10);
```

ENAME

-----  
SCOTT  
ADAMS

SQL>