

66 lines (50 loc) · 1.77 KB

```
83
                                                                          Raw 📮 🕹
                                                                                                   (>)
Code
         Blame
    1
           import java.util.Scanner;
    2
    3
           public class ExtendedEuclidean {
    4
               // Extended Euclidean Algorithm to find gcd and coefficients x, y
    5
    6
               public static int[] extendedEuclid(int a, int m) {
                   if (m == 0) {
    7
    8
                       return new int[] { a, 1, 0 };
    9
                   }
   10
   11
                   int[] result = extendedEuclid(m, a % m);
                   int gcd = result[0];
   12
                   int x1 = result[1];
   13
   14
                   int y1 = result[2];
   15
                   // Update x and y using the recursive results
   16
                   int x = y1;
   17
                   int y = x1 - (a / m) * y1;
   18
   19
                   return new int[] { gcd, x, y };
   20
               }
   21
   22
               // Function to find the modular inverse of a mod m
   23
               public static int modInverse(int a, int m) {
   24
                   int[] result = extendedEuclid(a, m);
   25
                   int gcd = result[0];
   26
                   int x = result[1];
   27
   28
                   // If gcd(a, m) is not 1, then the inverse does not exist
   29
   30
                   if (gcd != 1) {
                       return -1; // No modular inverse exists
   31
   32
                   } else {
                       // Ensure x is positive and return it as the modular inverse
   33
                       return (x \% m + m) \% m;
   34
   35
                   }
```

```
37
38
           public static void main(String[] args) {
39
               Scanner scanner = new Scanner(System.in);
40
               // Take input from the user
41
               System.out.print("Enter a number (a): ");
42
43
               int a = scanner.nextInt();
44
               int m = 26; // Number of letters in the alphabet
45
46
               // Calculate modular inverse
47
               int inverse = modInverse(a, m);
48
49
               if (inverse == -1) {
50
                    System.out.println("No modular inverse exists for " + a + " modulo "
51
52
               } else {
                    System.out.println("The modular inverse of " + a + " modulo " + m +
53
54
               }
55
56
               scanner.close();
57
           }
58
       }
59
60
       //Output
62
       Enter a number (a): 5
       The modular inverse of 5 modulo 26 is: 21
63
       Enter a number (a): 13
65
66
       No modular inverse exists for 13 modulo 26
```