```c
#include <stdio.h>

int main()
{
    printf("Hello C");
    return 0;
}
```

	Expected	Got	
✓	Hello C	Hello C	✓

Passed all tests! ✓

```c
#include <stdio.h>

int main()
{
    printf("I love Mangoes");
    return 0;
}
```

	Expected	Got	
✓	I love Mangoes	I love Mangoes	✓

Passed all tests! ✓

```c
#include<stdio.h>
int main()
{printf("Hello, World!");
 return 0;

}
```

	Expected	Got	
✓	Hello, World!	Hello, World!	✓

Passed all tests! ✓

```c
#include <stdio.h>
int main()
{char ch;
 scanf("%c",&ch);
 printf("%c",ch);
 return 0;
}
```

	Input	Expected	Got	
✓	c	c	c	✓

Passed all tests! ✓

```c
#include<stdio.h>
int main()
{int a,b;
 float c,d;
 scanf("%d%d",&a,&b);
 scanf("%f%f",&c,&d);
 printf("%d %d\n",a+b,a-b);
 printf("%.1f %.1f",c+d,c-d);
 return 0;
}
```

	Input	Expected	Got	
✓	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	✓
✓	20 8 8.0 4.0	28 12 12.0 4.0	28 12 12.0 4.0	✓

Passed all tests! ✓