

Edit

# MySQL cheatsheet

- Proudly sponsored by -

**Segment** Send data to any tool without having to implement a new API every time.

*ethical* ad by CodeFund

## Create / Open / Delete Database

```
CREATE DATABASE dbNameYouWant
CREATE DATABASE dbNameYouWant CHARACTER SET utf8
USE dbNameYouWant
DROP DATABASE dbNameYouWant
ALTER DATABASE dbNameYouWant CHARACTER SET utf8
```

## Repair Tables After Unclean Shutdown

```
mysqlcheck --all-databases
mysqlcheck --all-databases --fast
```

## Select

```
SELECT * FROM table
SELECT * FROM table1, table2, ...
SELECT field1, field2, ... FROM table1, table2, ...
SELECT ... FROM ... WHERE condition
SELECT ... FROM ... WHERE condition GROUPBY field
SELECT ... FROM ... WHERE condition GROUPBY field HAVING condition2
SELECT ... FROM ... WHERE condition ORDER BY field1, field2
SELECT ... FROM ... WHERE condition ORDER BY field1, field2 DESC
SELECT ... FROM ... WHERE condition LIMIT 10
SELECT DISTINCT field1 FROM ...
SELECT DISTINCT field1, field2 FROM ...
```

## Insert

## Backup Database to SQL File

```
mysqldump -u Username -p dbNameYouWant > databasename_backup.sql
```

## Restore from backup SQL File

```
mysql - u Username -p dbNameYouWant < databasename_backup.sql
```

## Browsing

```
SHOW DATABASES
SHOW TABLES
SHOW FIELDS FROM table / DESCRIBE table
SHOW CREATE TABLE table
SHOW PROCESSLIST
KILL process_number
```

## Select - Join

```
SELECT ... FROM t1 JOIN t2 ON t1.id1 = t2.id2 WHERE condition
SELECT ... FROM t1 LEFT JOIN t2 ON t1.id1 = t2.id2 WHERE condition
SELECT ... FROM t1 JOIN (t2 JOIN t3 ON ...) ON ...
```

## Conditions

```
INSERT INTO table1 (field1, field2, ...) VALUES (value1, value2, ...)
```

Delete

```
DELETE FROM table1 / TRUNCATE table1
DELETE FROM table1 WHERE condition
DELETE FROM table1, table2 FROM table1, table2 WHERE table1.id1 =
    table2.id2 AND condition
```

Create / Delete / Modify Table

Create

```
CREATE TABLE table (field1 type1, field2 type2, ...)
CREATE TABLE table (field1 type1, field2 type2, ..., INDEX (field))
CREATE TABLE table (field1 type1, field2 type2, ..., PRIMARY KEY (field1))
CREATE TABLE table (field1 type1, field2 type2, ..., PRIMARY KEY (field1,
    field2))
```

```
CREATE TABLE table1 (fk_field1 type1, field2 type2, ...,
    FOREIGN KEY (fk_field1) REFERENCES table2 (t2_fieldA))
    [ON UPDATE|ON DELETE] [CASCADE|SET NULL]
```

```
CREATE TABLE table1 (fk_field1 type1, fk_field2 type2, ...,
    FOREIGN KEY (fk_field1, fk_field2) REFERENCES table2 (t2_fieldA, t2_fieldB))
```

```
CREATE TABLE table IF NOT EXISTS (...)
```

```
CREATE TEMPORARY TABLE table (...)
```

Drop

```
DROP TABLE table
DROP TABLE IF EXISTS table
DROP TABLE table1, table2, ...
```

Alter

```
ALTER TABLE table MODIFY field1 type1
ALTER TABLE table MODIFY field1 type1 NOT NULL ...
```

```
field1 = value1
field1 <> value1
field1 LIKE 'value _ %'
field1 IS NULL
field1 IS NOT NULL
field1 IS IN (value1, value2)
field1 IS NOT IN (value1, value2)
condition1 AND condition2
condition1 OR condition2
```

Update

```
UPDATE table1 SET field1=new_value1 WHERE condition
UPDATE table1, table2 SET field1=new_value1, field2=new_value2, ... WHERE
    table1.id1 = table2.id2 AND condition
```

Keys

```
CREATE TABLE table (... , PRIMARY KEY (field1, field2))
CREATE TABLE table (... , FOREIGN KEY (field1, field2) REFERENCES table2
    (t2_field1, t2_field2))
```

Users and Privileges

```
GRANT ALL PRIVILEGES ON base.* TO 'user'@'localhost' IDENTIFIED BY 'password'
GRANT SELECT, INSERT, DELETE ON base.* TO 'user'@'localhost' IDENTIFIED BY 'password'
REVOKE ALL PRIVILEGES ON base.* FROM 'user'@'host'; -- one permission only
REVOKE ALL PRIVILEGES, GRANT OPTION FROM 'user'@'host'; -- all permissions
```

```
SET PASSWORD = PASSWORD('new_pass')
SET PASSWORD FOR 'user'@'host' = PASSWORD('new_pass')
SET PASSWORD = OLD_PASSWORD('new_pass')
```

```
DROP USER 'user'@'host'
```

Host ‘%’ indicates any host.

```
ALTER TABLE table CHANGE old_name_field1 new_name_field1 type1
ALTER TABLE table CHANGE old_name_field1 new_name_field1 type1 NOT NULL ...
ALTER TABLE table ALTER field1 SET DEFAULT ...
ALTER TABLE table ALTER field1 DROP DEFAULT
ALTER TABLE table ADD new_name_field1 type1
ALTER TABLE table ADD new_name_field1 type1 FIRST
ALTER TABLE table ADD new_name_field1 type1 AFTER another_field
ALTER TABLE table DROP field1
ALTER TABLE table ADD INDEX (field);
```

◀ | | ▶

Change field order

```
ALTER TABLE table MODIFY field1 type1 FIRST
ALTER TABLE table MODIFY field1 type1 AFTER another_field
ALTER TABLE table CHANGE old_name_field1 new_name_field1 type1 FIRST
ALTER TABLE table CHANGE old_name_field1 new_name_field1 type1 AFTER
  another_field
```

### Reset Root Password

```
$ /etc/init.d/mysql stop
```

```
$ mysqld_safe --skip-grant-tables
```

```
$ mysql # on another terminal
mysql> UPDATE mysql.user SET password=PASSWORD('new_pass') WHERE user='root'
```

◀ | | ▶

```
## Switch back to the mysqld_safe terminal and kill the process using Ctrl+C
$ /etc/init.d/mysql start
```

◀ | | ▶

Your commands may vary depending on your OS.

### Main Data Types

TINYINT (1o: -217+128) SMALLINT (2o: +-65 000) MEDIUMINT (3o: +-16 000 000) INT (4o: +- 2 000 000 000) BIGINT (8o: +-9.10^18)
Precise interval: -(2^(8*N-1)) -> (2^8*N)-1
⚠ INT(2) = "2 digits displayed" – NOT "number with 2 digits max"
FLOAT(M,D) DOUBLE(M,D) FLOAT(D=0->53)
⚠ 8,3 -> 12345,678 – NOT 12345678,123!
TIME (HH:MM) YEAR (AAAA) DATE (AAAA-MM-JJ) DATETIME (AAAA-MM-JJ HH:MM; années 1000->9999) TIMESTAMP (like DATETIME, but 1970->2038, compatible with Unix)
VARCHAR (single-line; explicit size) TEXT (multi-lines; max size=65535) BLOB (binary; max size=65535)
Variants for TEXT&BLOB: TINY (max=255), MEDIUM (max=~16000), and LONG (max=4Go). Ex: VARCHAR(32), TINYTEXT, LONGBLOB, MEDIUMTEXT
ENUM ('value1', 'value2', ...) -- (default NULL, or '' if NOT NULL)