6/5/2020 Vim cheatsheet

#### **DEVHINTS.IO**

Edit

# Vim cheatsheet

- Proudly sponsored by -

**TeamCity** Continuous Integration and Deployment server out of the box. Free forever *ethical* ad by CodeFund

Vim is a very efficient text editor. This reference was made for Vim 8.0. For shortcut notation, see :help key-notation.

#### Exiting

:qa	Close all files
:qa!	Close all files, abandon changes
: w	Save
:wq / :x	Save and close file
: q	Close file
: q!	Close file, abandon changes
ZZ	Save and quit
ZQ	Quit without checking changes

#### Exiting insert mode

Esc / <c-[></c-[>	Exit insert mode
<c -="" c=""></c>	Exit insert mode, and abort current command

#### Visual mode

#### Navigating

h j k l

<c-u> / <c< td=""><td>- D&gt; Page up/page down</td></c<></c-u>	- D> Page up/page down
Words	
Shortcut	Description
ff	
b / w	Previous/next word
ge / e	Previous/next end of word
Line	
0 (zero)	Start of line
٨	Start of line (after whitespace)
\$	End of line
Character	
fc	Go forward to character c
Fc	Go backward to character c
Document	
gg	First line

#### Editing

Arrow keys

a	Append
i	Insert
0	Next line
0	Previous line
S	Delete char and insert
S	Delete line and insert
С	Delete until end of line and insert
r	Replace one character
R	Enter Replace mode
u	Undo changes
<c -="" r=""></c>	Redo changes

#### Clipboard

Х	Delete character
dd	Delete line (Cut)

V	Enter visual mode	
V	Enter visual line mode	
<c -="" v=""></c>	Enter visual block mode	
In visual mode		
d / x	Delete selection	
S	Replace selection	
У	Yank selection (Copy)	
See Operators for other things you can do.		

Vim	cheatsheet	
VIIII	CHEALSHEEL	

G	Last line
: n	Go to line n
nG	Go to line n
Window	
ZZ	Center this line
zt	Top this line
Н	Move to top of screen
М	Move to middle of screen
L	Move to bottom of screen
Tab pages	
:tabedit [file]	Edit file in a new tab
:tabfind [file]	Open file if exists in new tab
:tabclose	Close current tab
:tabs	List all tabs
:tabfirst	Go to first tab
:tablast	Go to last tab
:tabn	Go to next tab

уу	Yank line (Copy)
р	Paste
Р	Paste before

# # Operators

### Usage

Operators let you operate in a range of text (defined by motion). These are performed in normal mode.

### Operators list

d		Delete
у		Yank (copy)

#### Examples

Combine operators with motions to use them.

6/5/2020

d	W
Operator	Motion

С	Change (delete then insert)
>	Indent right
<	Indent left
g~	Swap case
gU	Uppercase
gu	Lowercase
!	Filter through external program
See:help operator	

Vim cheatsheet

dd	(repeat the letter) Delete current line
dw	Delete to next word
db	Delete to beginning of word
2dd	Delete 2 lines
dip	Delete a text object (inside paragraph)
(in visual mode) d	Delete selection
See: :help motion.txt	<u>:</u>

# # Text objects

#### Usage

Text objects let you operate (with an operator) in or around text blocks (objects).

V i p

Operator [i]nside or [a]round Text object

#### Diff

gvimdiff file1 file2 [file3] See differencies between files, in HMI

### Text objects

p Pa	aragraph
W	Word
s s	Sentence
[ ( { < A [], (), o	r {} block
' " ` A quot	ed string
b	A block [(
B A b	lock in [{
t A XML t	ag block

### Examples

vip	Select paragraph
vipipipip	Select more
уір	Yank inner paragraph
yap	Yank paragraph (including newline)
dip	Delete inner paragraph
cip	Change inner paragraph
See Operators for other things you can do.	

# Misc

https://devhints.io/vim 3

#### Folds

zo / z0	Open
zc / zC	Close
za / zA	Toggle
ZV	Open folds for this line
zM	Close all
zR	Open all
zm	Fold more (foldlevel += 1)
zr	Fold less (foldlevel -= 1)
zx	Update folds
Uppercase ones are recursive (eg, z0 is open r	ecursively).

### Windows

z{height} <cr></cr>	Resize pane to {height} lines tall

#### Case

~	Toggle case (Case => cASE)
gU	Uppercase
gu	Lowercase
gUU	Uppercase current line (also gUgU)
guu	Lowercase current line (also gugu)
Do these in visual or normal mode.	

#### Misc

#### Navigation

Previous ( or { or <	[( [{	
Next	])	
Previous method start	[ m	
Previous method end	[ M	

### Jumping

Go back to previous location	<c -="" 0=""></c>
Go forward	<c-i></c-i>
Go to file in cursor	gf

#### Counters

<c -="" a=""></c>	Increment number
<c -="" x=""></c>	Decrement

### Tags

:tag Classname	Jump to first definition of Classname
<c -="" ]=""></c>	Jump to definition
g]	See all definitions
<c -="" t=""></c>	Go back to last tag
<c-0> <c-i></c-i></c-0>	Back/forward
:tselect Classname	Find definitions of Classname
:tjump Classname	Find definitions of Classname (auto-select 1st)

#### Marks

	Repeat last command
] p	Paste under the current indentation level
:ff=unix	Convert Windows line endings to Unix line endings

#### Command line

<c -="" r=""><c -="" w=""></c></c>	Insert current word into the command line
<c -="" r="">"</c>	Paste from " register
<c -="" x=""><c -="" f=""></c></c>	Auto-completion of path in insert mode

#### Calculator

<c-r>=128/2</c-r>	Shows the result of the division : '64'	
Do this in insert mode.		

# Spell checking

:set spell spelllang=en_us	Turn on US English spell checking
]s	Move to next misspelled word after the cursor
[s	Move to previous misspelled word before the cursor
Z=	Suggest spellings for the word under/after the cursor
zg	Add word to spell list
ZW	Mark word as bad/mispelling
zu / C-X (Insert Mode)	Suggest words for bad word under cursor from spellfile
See :help spell	

#### Vim cheatsheet

Last position of cursor in insert mode	` ^
Last change	
Last jump	
Mark this cursor position as a	ma
Jump to the cursor position a	`a
Jump to the beginning of the line with position a	'a

# Text alignment

<pre>:center [width] :right [width] :left</pre>		
See:help formatting		

# Exiting with an error

cq:cq:cquit
Works like : qa, but throws an error. Great for aborting Git commands.