A Model With Clean and Dirty Capital Stocks and and R&D in Green Innovation

Assume there are two capital sectors, each with AK production technology ($Y_i = A_i K_i,\ i\ = d, g$) and each with its own capital stock that evolves with quadratic adjustments costs and Brownian shocks as follows:

$$
\begin{aligned}
\mathrm{d}K_d/K_d &= [\alpha_d + i_d - \frac{\phi_d}{2} i_d^2]\,\mathrm{d}t + \sigma_d\,\mathrm{d}W \\
\mathrm{d}K_g/K_g &= [\alpha_g + i_g - \frac{\phi_g}{2} i_g^2]\,\mathrm{d}t + \sigma_g\,\mathrm{d}W
\end{aligned}
$$

We also assume there is R & D investment that leads to an increased arrival rate of a one time jump in Sector 2 productivity. The arrival rate is denoted as t and evolves as follows

$$
\mathrm{d}\lambda_t/\lambda_t = (\varphi i_\lambda \frac{K_d + K_g}{\lambda} - \alpha_\lambda)\,\mathrm{d}t + \sigma_\lambda\,\mathrm{d}W
$$

The key difference between the sectors is that production from Sector 1 generates emissions. As a result,the evolution of atmospheric temperature is give by the Matthews Approximation, so that temperature Y_t and cumulative carbon emissions are given by

$$
\mathrm{d}Y_t = E_t(\beta_f\,\mathrm{d}t + \varsigma\,\mathrm{d}W)
$$

where β_f is the Matthews parameter and η is the scaling factor converting Sector d output $A_d K_d$ into emissions such that

$$
E_t = \eta A_d K_d
$$

Output can be used in for consumption, investment in either capital stock, or for R&D into improving the productivity of Sector g :

$$
C = A_d K_d - i_d K_d + A_g K_g - i_g K_g - i_\lambda (K_d + K_g)
$$

We assume exponential-quadratic damages to preferences so that our utility is augmented when accounting for climate damages. Flow utility is a log function over consumption, assuming perfect substitutability over output from the two sectors so that

$$
U(C) = \delta \log(A_d K_d - i_d K_d + A_g K_g - i_g K_g - i_\lambda (K_d + K_g)) - \delta \log N_t
$$

where the $\log N_t$ follows from BBH2 as

$$
\begin{aligned}
\log N_t &= \Gamma(Y) \\
\Gamma(y) &= \gamma_1 y + \frac{\gamma_2}{2} y^2 + \frac{\gamma_3}{2} \mathbb{I}_{y \geq \bar{y}} (y - \bar{y})^2
\end{aligned}
$$

Taking these pieces together we get the HJB equation

$$
\begin{aligned}
\delta V(K_d, K_g, \lambda, Y, \log N) = \max_{i_g, i_d, i_\lambda}\ & \delta \log(A_d K_d - i_d K_d + A_g K_g - i_g K_g - i_\lambda (K_d + K_g)) - \delta \log N \\
& + \{\alpha_d + i_d - \frac{\phi_d}{2} i_d^2\} V_d K_d + \{\alpha_g + i_g - \frac{\phi_g}{2} i_g^2\} V_g K_g + \frac{\sigma_d^2 K_d^2}{2} V_{dd} + \frac{\sigma_g^2 K_g^2}{2} V_{gg} \\
& + \beta_f E_d V_Y + \frac{1}{2} \varsigma^2 E_d^2 V_{YY} + [\{\gamma_1 + \gamma_2 Y + \gamma_3 (Y - \bar{y}) \mathbf{I}\{Y_t > \bar{y}\}\} \beta_f E_d \\
& + \frac{\gamma_2 + \gamma_3 \mathbf{I}\{Y > \bar{y}\}}{2} \varsigma^2 E_d^2] V_{\log N} + \frac{\varsigma^2 E_d^2}{2} V_{\log N \log N} \\
& + (\varphi i_\lambda - \alpha_\lambda) \lambda V_\lambda + \frac{(\sigma_\lambda \lambda)^2}{2} V_{\lambda\lambda} + \lambda \left(V(K_d, K_g, \lambda, Y, \log N; A_g') - V(K_d, K_g, \lambda, Y, \log N; A_g) \right)
\end{aligned}
$$

The FOC for investment and R& D are given by

$$
\begin{aligned}
0 =& -\delta(A_dK_d - i_dK_d + A_gK_g - i_gK_g - i_\lambda\lambda)^{-1} + (1-\phi_d i_d)V_d \\
0 =& -\delta(A_dK_d - i_dK_d + A_gK_g - i_gK_g - i_\lambda\lambda)^{-1} + (1-\phi_d i_d)V_d \\
0 =& -\delta(A_dK_d - i_dK_d + A_gK_g - i_gK_g - i_\lambda\lambda)^{-1} + \varphi V_\lambda
\end{aligned}
$$

Using the fact that $\varphi V_\lambda = \delta(A_dK_d - i_dK_d + A_gK_g - i_gK_g - i_\lambda\lambda)^{-1}$, we can simplify to

$$
\begin{aligned}
i_d =& \frac{1}{\phi_d} - \frac{\varphi}{\phi_d}\frac{V_\lambda}{V_d} \\
i_g =& \frac{1}{\phi_g} - \frac{\varphi}{\phi_g}\frac{V_\lambda}{V_g} \\
i_\lambda =& \frac{1}{\lambda}\left((A_d - (\frac{1}{\phi_d} - \frac{\varphi}{\phi_d}\frac{V_\lambda}{V_d}))K_d + (A_g - (\frac{1}{\phi_g} - \frac{\varphi}{\phi_g}\frac{V_\lambda}{V_g}))K_g - \frac{\delta}{\varphi V_\lambda}\right)
\end{aligned}
$$

We can analytically simplify out $\log N_t$ to get a simplified HJB

$$
\begin{aligned}
\delta v(K_d, K_g, \lambda, Y) =& \max_{i_g, i_d, i_\lambda} \delta \log(A_dK_d - i_dK_d + A_gK_g - i_gK_g - i_\lambda\lambda) \\
&+ \{\alpha_d + i_d - \frac{\phi_d}{2}i_d^2\}v_dK_d + \{\alpha_g + i_g - \frac{\phi_g}{2}i_g^2\}v_gK_g + \frac{\sigma_d^2K_d^2}{2}v_{dd} + \frac{\sigma_g^2K_g^2}{2}v_{gg} \\
&+ \beta_f E_d v_Y + \frac{1}{2}\varsigma^2 E_d^2 v_{YY} \\
&- [\{\gamma_1 + \gamma_2 Y_t + \gamma_3(Y_t - 2)\mathbf{I}\{Y_t > 2\}\}\beta_f E_d + \frac{\gamma_2 + \gamma_3\mathbf{I}\{Y_t > 2\}}{2}\varsigma^2 E_d^2] \\
&+ (\varphi i_\lambda - \alpha_\lambda)\lambda v_\lambda + \frac{(\sigma_\lambda\lambda)^2}{2}v_{\lambda\lambda} + \lambda\left(v(K_d, K_g, \lambda, Y; A_g') - v(K_d, K_g, \lambda, Y; A_g)\right)
\end{aligned}
$$

FOC

$$
\begin{aligned}
i_d =& \frac{1}{\phi_d} - \frac{\varphi}{\phi_d}\frac{v_\lambda}{v_d} \\
i_g =& \frac{1}{\phi_g} - \frac{\varphi}{\phi_g}\frac{v_\lambda}{v_g} \\
i_\lambda =& \frac{1}{\lambda}\left((A_d - (\frac{1}{\phi_d} - \frac{\varphi}{\phi_d}\frac{v_\lambda}{v_d}))K_d + (A_g - (\frac{1}{\phi_g} - \frac{\varphi}{\phi_g}\frac{v_\lambda}{v_g}))K_g - \frac{\delta}{\varphi v_\lambda}\right)
\end{aligned}
$$

From this we can layer on different forms of uncertainty.

1 Post jump

1.1 Desired model

Replace E_d with $\eta A_d K_d$. We solve post jump HJB:

$$
\begin{aligned}
\delta v(K_d, K_g, Y; A_g') =& \max_{i_g, i_d} \delta \log(A_dK_d - i_dK_d + A_g'K_g - i_gK_g) \\
&+ \{\alpha_d + i_d - \frac{\phi_d}{2}i_d^2\}v_dK_d + \{\alpha_g + i_g - \frac{\phi_g}{2}i_g^2\}v_gK_g + \frac{\sigma_d^2K_d^2}{2}v_{dd} + \frac{\sigma_g^2K_g^2}{2}v_{gg} \\
&+ \beta_f(\eta A_dK_d)v_Y + \frac{1}{2}\varsigma^2(\eta A_dK_d)^2 v_{YY} - [\{\gamma_1 + \gamma_2 Y + \gamma_3(Y - \bar{y})\mathbf{I}\{Y > \bar{y}\}\}\beta_f(\eta A_dK_d)] \\
&- \frac{\gamma_2 + +\gamma_3\mathbf{I}\{Y > \bar{y}\}}{2}[\varsigma^2(\eta A_dK_d)^2]
\end{aligned}
$$

denote

$$mc = \delta(A_d K_d - i_d K_d + A_g' K_g - i_g K_g)^{-1}$$

FOC

$$\begin{aligned} i_d =& \frac{1}{\phi_d} - \frac{mc}{\phi_d v_d} \\ i_g =& \frac{1}{\phi_g} - \frac{mc}{\phi_g v_g} \end{aligned}$$

1.2 Transformation of state variables

$$X = [\log K, R, Y]', \quad \log K = \log(K_d + K_g), \quad R = \frac{K_g}{K_d + K_g}$$

$$\begin{aligned} \mathrm{d}(K_d + K_g) &= \left([\alpha_d + i_d - \frac{\phi_d}{2} i_d^2] K_d + [\alpha_g + i_g - \frac{\phi_g}{2} i_g^2] K_g \right) \mathrm{d}t + (\sigma_d K_d + \sigma_g K_g) \, \mathrm{d}W \\ \mathrm{d}K/K &= \left([\alpha_d + i_d - \frac{\phi_d}{2} i_d^2](1-R) + [\alpha_g + i_g - \frac{\phi_g}{2} i_g^2] R \right) \mathrm{d}t + (\sigma_d(1-R) + \sigma_g R) \, \mathrm{d}W \\ \mathrm{d}\log K &= \left([\alpha_d + i_d - \frac{\phi_d}{2} i_d^2](1-R) + [\alpha_g + i_g - \frac{\phi_g}{2} i_g^2] R - \frac{\mid \sigma_d(1-R) + \sigma_g R \mid^2}{2} \right) \mathrm{d}t \\ &+ (\sigma_d(1-R) + \sigma_g R) \, \mathrm{d}W \end{aligned}$$

$$\mathrm{d}R = \left((\alpha_d + i_d - \frac{\sigma_d^2}{2})(1-R) + (\alpha_g + i_g - \frac{\sigma_g^2}{2}) R - R\sigma_g^2 + (1-R)\sigma_d^2 \right) dt + R(1-R)(\sigma_d + \sigma_g) dW$$

$$\mathrm{d}Y = \eta A_d (1-R) K (\beta_f \, \mathrm{d}t + \varsigma \, \mathrm{d}W)$$

1.2.1 $\log K, R, Y$

$\log K \in [4., 8.5]$, $R \in [0.14, 0.99]$ and $Y \in [0., 3.]$

$$\begin{aligned} \delta v(\log K, R, Y; A_g') = & \max_{i_g, i_d} \delta \log((A_d - i_d)(1-R) + (A_g' - i_g) R) + \delta \log K \\ & + \left(\{\alpha_d + i_d - \frac{\phi_d}{2} i_d^2\}(1-R) + \{\alpha_g + i_g - \frac{\phi_g}{2} i_g^2\} R - \frac{\mid \sigma_d(1-R) + \sigma_g R \mid^2}{2} \right) v_k \\ & + \frac{\mid \sigma_d(1-R) + \sigma_g R \mid^2}{2} v_{kk} \\ & + \left((\alpha_g + i_g - \frac{\phi_g}{2} i_g^2) - R\sigma_g^2 - (\alpha + i_d - \frac{\phi_d}{2} i_d^2) + (1-R)\sigma_d^2 \right) [R(1-R)] \, v_r \\ & + \frac{1}{2} R^2 (1-R)^2 (\sigma_g^2 + \sigma_d^2) v_{rr} \\ & + \beta_f (\eta A_d (1-R) K) v_Y + \frac{1}{2} \varsigma^2 (\eta A_d (1-R) K)^2 v_{YY} \\ & - [\{\gamma_1 + \gamma_2 Y + \gamma_3 (Y - \bar{y}) \mathbb{I}\{Y > \bar{y}\}\} \beta_f (\eta A_d (1-R) K) + \frac{\gamma_2 + \gamma_3 \mathbb{I}\{Y_t > \bar{y}\}}{2} \varsigma^2 (\eta A_d (1-R) K)^2] \end{aligned}$$

FOC

$$mc = \delta((A_d - i_d)(1-R) + (A_g' - i_g)R)^{-1}$$

$$\begin{aligned} mc =& (1-\phi_d i_d)\left((v_k - Rv_r\right) & \Rightarrow i_d = \frac{1}{\phi_d}\left[1 - \frac{mc}{v_k - Rv_r}\right] \\ mc =& (1-\phi_g i_g)\left(v_k + (1-R)v_r\right) & \Rightarrow i_g = \frac{1}{\phi_g}\left[1 - \frac{mc}{v_k + (1-R)v_r}\right] \end{aligned}$$

Future plans:

- Non-zero γ_3

2 Pre jump

R& D investment, I_λ, R& D investment ratio $i_\lambda = \dfrac{I_\lambda}{K}$

Technology jump intensity :

$$\mathrm{d}\log\lambda = (-\alpha_\lambda + \varphi i_\lambda \frac{K}{\lambda} - \frac{\sigma_\lambda^2}{2})\,\mathrm{d}t + \sigma_\lambda\,\mathrm{d}W$$

State variables $\log K, R, Y, \log(\lambda)$, controls i_d, i_g and i_λ, HJB:

$$\begin{aligned} \delta v(\log K, R, Y, \log(\lambda); A_g) = \max_{i_g, i_d, i_\lambda} & \delta\log((A_d - i_d)(1-R) + (A_g - i_g)R - i_\lambda) + \delta\log K \\ & + \left(\{\alpha_d + i_d - \frac{\phi_d}{2} i_d^2\}(1-R) + \{\alpha_g + i_g - \frac{\phi_g}{2} i_g^2\}R - \frac{\mid \sigma_d(1-R) + \sigma_g R\mid^2}{2}\right) v_k \\ & + \frac{\mid \sigma_d(1-R) + \sigma_g R\mid^2}{2} v_{kk} \\ & + \left((\alpha_g + i_g - \frac{\phi_g}{2} i_g^2) - R\sigma_g^2 - (\alpha_d + i_d - \frac{\phi_d}{2} i_d^2) + (1-R)\sigma_d^2\right)\left[R(1-R)\right] v_r \\ & + \frac{1}{2} R^2 (1-R)^2 \left[\sigma_d^2 + \sigma_g^2\right] v_{rr} \\ & + \beta_f(\eta A_d(1-R)K) v_Y + \frac{1}{2}\varsigma^2(\eta A_d(1-R)K)^2 v_{YY} \\ & - \left[\{\gamma_1 + \gamma_2 Y + \gamma_3(Y - \bar{y})\mathbb{I}\{Y > \bar{y}\}\}\beta_f(\eta A_d(1-R)K) + \frac{\gamma_2 + \gamma_3\mathbb{I}\{Y > \bar{y}\}}{2}\varsigma^2(\eta A_d(1-R)K)^2\right] \\ & + (\varphi i_\lambda \frac{K}{\lambda} - \alpha_\lambda - \frac{\sigma_\lambda^2}{2}) v_\lambda + \frac{\sigma_\lambda^2}{2} v_{\lambda\lambda} + \lambda\left(v^{\text{post}}(\log K, R, Y; A_g') - v(\log K, R, Y, \log(\lambda); A_g)\right) \end{aligned}$$

FOC

$$\begin{aligned} mc =& \delta((A_d - i_d)(1-R) + (A_g - i_g)R - i_\lambda)^{-1} \\ mc =& \frac{K}{\lambda}\varphi v_\lambda \end{aligned}$$

$$\begin{aligned} mc =& (1-\phi_d i_d)\left((v_k - Rv_r\right) & \Rightarrow i_d = \frac{1}{\phi_d}\left[1 - \frac{K}{\lambda}\frac{\varphi v_\lambda}{v_k - Rv_r}\right] \\ mc =& (1-\phi_g i_g)\left(v_k + (1-R)v_l\right) & \Rightarrow i_g = \frac{1}{\phi_g}\left[1 - \frac{K}{\lambda}\frac{\varphi v_\lambda}{v_k + (1-R)v_r}\right] \end{aligned}$$

$$i_\lambda = (A_d - (\frac{1}{\phi_d} - \frac{K}{\lambda}\frac{\varphi}{\phi_d}\frac{v_\lambda}{v_k - Rv_r}))(1-R) + (A_g - (\frac{1}{\phi_g} - \frac{K}{\lambda}\frac{\varphi}{\phi_g}\frac{v_\lambda}{v_k + (1-R)v_r}))R - \frac{\lambda\delta}{K\varphi v_\lambda}$$

A State variables

$$\begin{aligned}\log(K) \in& [4, 8.5] \\ R \in& [0.01, 0.99] \\ Y \in& [0, 4] \\ \log(\lambda) \in& [-4, 0]\end{aligned}$$

B Parameters

Economy

Parameters	values
δ	0.01
$(\alpha_d, \phi_d, \sigma_d)$	(-0.02, 8, 0.016)
$(\alpha_g, \phi_g, \sigma_g)$	(-0.02, 8, 0.016)
$(\alpha_\lambda, \varphi, \sigma_\lambda)$	(0, 0.01, 0.016)
A_d	0.12
(A_g, A_g')	(0.10, 0.15)

Temperature and damage

Parameters	values
β_f	1.86 / 1000
ς	1.2 * 1.86 / 1000
γ_1	0.00017675
γ_2	2 * 0.0022
γ_3	$\frac{1}{3}\frac{m-1}{19}, m = 1, 2, \dots, 20$
$\bar{y}$	2

η are determined as follows:

- Initial capital: $K_0 = 85/0.115 \approx 739$
- $K_{d,0} = K_0 \times \frac{2}{3} \approx 493$
- Choose η such that $10 = \eta \times 0.12 \times 493 \Rightarrow \eta \approx 0.17$