Peach Fuzzer
Hosted Trial Guide

1. Preface

This document supports the user through a trial of using Peach Fuzzer to test several different real-world applications. It shows how Peach Fuzzer should be configured for each application, what monitors are useful for each scenario, and has examples of test runs that show the types of faults that Peach Fuzzer can find and the information it gathers for those faults. This should give the user an overview of the capabilities of Peach Fuzzer and set expectations for what the user will need to do to use Peach Fuzzer to test their own software.

1.1. Goals

After reading this document, you should be able to accomplish the following:

1. Access your trial instance of Peach Fuzzer

2. Run tests against several target applications with Peach Fuzzer

3. View the results of a test run to see the vulnerabilities that were found and the data was gathered

4. Understand how Peach Fuzzer is configured to test various applications based on the nature of the application

5. Understand why the configurations have the specific settings and Monitors that they do and how those settings relate to the specifics of the application they are testing

6. (Optional) Create a new configuration to test one of the existing applications that exist on your trial instance

1.2. Non-Goals

This document is NOT intended to be comprehensive documentation for how to configure Peach Fuzzer or a full demonstration of every feature that Peach Fuzzer offers. It is also not meant to help the user install, configure, or troubleshoot Peach Fuzzer for testing their own applications. Users needing assistance with any of those things should consult the Peach Fuzzer User Guide or contact support for assistance.

1.3. Target Applications

The applications being tested in the trial are all free and open source where possible. In many cases, the source was forked from the original version and contrived security vulnerabilities were intentionally introduced into the code in order to better demonstrate the features of Peach Fuzzer. Therefore, the vulnerabilities found by Peach Fuzzer on the trial instance should not be assumed to be present in the publicly available versions of those applications. In addition, Peach Tech has not done a comprehensive test of those applications so we cannot guarantee that additional vulnerabilities are not present in those applications' original source code.

2. Configurations

Each pit available in the trial has at least one configuration. In some cases there will be two; a basic configuration and an advanced configuration.

> In protocols where both a client and server are present and being tested, the client and server are considered separate protocols for purposes of this document. It is therefore possible that both the client and the server will each have a basic and advanced configuration.

2.1. Basic Configuration

This configuration shows how a user would typically set up Peach Fuzzer to test an application that they either can't compile or can't re-compile with additional compiler or linker options. The applications used in these configurations have typically been compiled with debug and no optimizations e.g. `gcc -g main.cpp` or similar. The GDB Monitor is used in most cases to detect faults.

2.2. Advanced Configuration

This configuration shows how a user would typically set up Peach Fuzzer to test an application that they have recompiled with various compiler options such as Address Sanitizer (the advanced configurations used in the trial are all compiled this way unless indicated otherwise) and various optimization levels e. g. `gcc -g -O1 -fsanitize=address main.cpp` or similar.

With ASan in use, the GDB Monitor is generally not advised since ASan will terminate the program without sending a signal (e.g. SIGSEGV, SIGABRT, etc.) that the debugger will detect. The Process Monitor is therefore used instead, as it will recognize that ASan has terminated the process for some reason and can gather information from the ASan output in the report for the fault on that particular iteration.

3. Accessing your trial instance

You should have received the following for your trial instance:

- The URL to access the instance
- The login/password for your trial instance

If you do not have this information, please contact support@peach.tech for assistance.

3.1. Logging in to your trial instance

To log in to your trial instance, follow these steps:

1. Enter the URL into your web browser. It should be something similar to https://mycompany.demo.peach.tech

2. When prompted, enter your credentials.

3. Click "Accept" to accept the license agreement.

4. If prompted a second time for credentials, enter the same credentials you used in step 2.

5. You should now see a screen similar to what is pictured below

4. Sample Configurations

The following are sample configurations for several different protocols as well as file types that Peach Fuzzer can fuzz. Each sample will already be present and configured on your trial instance. In addition, a test run for each sample is already present on the trial instance so that you can easily view the test results and see the types of faults that Peach Fuzzer can find. You can run the sample configurations with the supplied seed values in this guide. Each section below has instructions for how to set up the sample configuration, including a brief explanation of why Peach Fuzzer has been configured this way for this particular application. It is strongly recommended that you use the supplied values in each section for the **Seed** and **Stop Test Case** (and **Start Test Case** if indicated). These values have been selected to guarantee that you can create a test run that will find faults in the target applications within a few minutes.

4.1. Viewing the Sample Job Results

Your trial instance already has test runs for each available sample configuration. These can be viewed from the Jobs page. Any additional test runs you perform will be available on the Jobs page. To view the results:

1. From the Home page, click the Jobs tab.

2. Click the job you wish to view from the list of available jobs.

Jobs

Here is a comprehensive list of the fuzzing jobs on this computer.

For any entry, you can perform the following actions:

- Click the icon to view the report generated for the fuzzing session.
- Click the ✖ icon to delete the job.

Name	Status	Start Time	Stop Time	Test Cases	Total Faults	Actions
Example-JPG-Advanced	Stopped	6/25/18 5:23 PM	6/25/18 5:23 PM	46	1	
Example-JPG-Basic	Stopped	6/25/18 5:20 PM	6/25/18 5:21 PM	46	1	
Example-PNG-Advanced	Stopped	6/25/18 5:19 PM	6/25/18 5:19 PM	11	1	
Example-PNG-Basic	Stopped	6/25/18 5:19 PM	6/25/18 5:19 PM	11	1	
Example-MODBUS-TCP Slave	Stopped	6/25/18 5:17 PM	6/25/18 5:17 PM	30	1	
Example-MODBUS-TCP Master	Stopped	6/25/18 5:14 PM	6/25/18 5:15 PM	50	3	
Example-SNMPv3 Server-Advanced	Stopped	6/25/18 5:11 PM	6/25/18 5:12 PM	10	5	
Example-SNMPv3 Server-Basic	Stopped	6/25/18 5:06 PM	6/25/18 5:10 PM	10	5	
Example-HTTP Server-Advanced	Stopped	6/25/18 5:04 PM	6/25/18 5:05 PM	30	2	

3. The results of the selected job will now be displayed. You can see the overall results which will indicate the parameters with which the job was run and the faults that were found. You can examine the faults individually or download a report that summarizes all of the findings in this job run.

4.2. Running the Samples

To run the pre-configured examples:

1. Click **Library**

2. Under **Configurations**, click the name of the sample configuration that you wish to run

Configurations

The Configurations section contains existing Peach Pit configurations. Selecting an existing configuration allows editing the configuration and starting a new fuzzing job.

Image			
Example-JPG-Advanced	Example-PNG-Advanced		
Example-JPG-Basic	Example-PNG-Basic		

Net			
Example-DICOM Net Provider	Example-DNP3 Slave-Basic	Example-HTTP Server-Basic	Example-SNMPv3 Server-Advanced
Example-DNP3 Master-Advanced	Example-HL7 Net TCP MLLP Receiver	Example-MODBUS-TCP Master	Example-SNMPv3 Server-Basic
Example-DNP3 Master-Basic	Example-HTTP Server-Advanced	Example-MODBUS-TCP Slave	
Example-DNP3 Slave-Advanced			

> ℹ️ Your trial instance may not have every Configuration pictured here. The exact Configurations available will depend on what Pits are included with your trial license.

3. Enter the appropriate values for **Seed** and **Stop Test Case**.

4. Enter the appropriate value for **Start Test Case** if specified. Otherwise, leave the default of **1**.

4.3. HTTP-Server

This configuration will test an application using HTTP. It has two versions, a basic configuration and an advanced configuration. The basic configuration is compiled only with the Debug option. The advanced configuration is compiled with Address Sanitizer, Debug, and Optimization Level 1 options.

4.3.1. Running the test

To run the pre-configured basic test:

1. Click **Example-HTTP_Server-Basic**.

2. Enter a seed value of **46122**.

3. Enter a Stop Test Case value of **30**.

4. Click **Start**.

To run the pre-configured advanced test:

1. Click **Example-HTTP_Server-Advanced**.

2. Enter a seed value of **46122**.

3. Enter a Stop Test Case value of **30**

4. Click **Start**.

4.3.2. Configuring the test

These steps will create the same configuration as is in use in the HTTP_Server configuration that is already present on the trial instance. The steps are the same for both the basic and advanced configuration except where indicated. To create the configuration:

1. Click Library and then click **HTTP_Server**.

2. Enter a name when prompted and optionally a description, then click **Submit**.

Configuring Variables

The first thing you need to configure are the variables that control how Peach Fuzzer will test the application. Both the Basic and Advanced configuration will use the same variables with the same values. Follow these steps to create a working configuration on your trial instance:

1. Click **Configure Variables**.

2. Configure your variables as appropriate for your application. The following should be used for Mongoose running on the trial instance:

   a. Target IPv4 Address: set to **127.0.0.1**

   b. Target Port: set to 4040 as Mongoose will also use to this port.

   c. HTTP Host Header: set to **peachapisec** as Mongoose has been configured to use this host name.

   d. Under **Advanced Configuration**, leave all the defaults as they are acceptable for Mongoose.

   e. Under System Defines, do NOT change any of the values present. These values normally do not require changing.

3. Once all the settings have the desired values, click **Save**.

Configuring Agents

An Agent runs either in-process of Peach Fuzzer or can be installed and run on a remote machine. For this configuration, only a single local agent is required.

1. Click **Monitoring**.

2. Click **Add Agent**.

3. Enter a name. Leave the **Location** setting to the default **local://**.

4. Click **Save**.

Monitoring

The Monitoring data entry screen defines one or more Agents and one or more Monitors for the Pit.

Agents are host processes for monitors and publishers. Local agents can reside on the same machine as Peach, and can control the test environment through monitors and publishers. Remote agents reside on the test target, and can provide remote monitors and publishers.

Saved successfully.

[Save] [+ Add Agent]

∨ local:// (local)   [∧] [∨] [✕]

Name | local |
             Friendly name for your agent

Location | local:// |
             URL for the agent. Leave blank for a local agent. For remote agents use the `tcp`
             scheme. The default agent port is `9001` . Example: `tcp://192.168.48.2:9001`

For more detailed instructions, see Adding an agent.

Configuring the monitors for basic

The basic configuration is targeting Mongoose compiled with Debug enabled. You will therefore want the following monitors:

- **Gdb Monitor**. This will allow Peach Fuzzer to launch Mongoose from within GDB so that GDB attaches to Mongoose. Peach Fuzzer will monitor GDB and attempt to analyze any crashes that GDB detects based on receiving signals from the application being tested.

- **Network Capture monitor**. Since HTTP is a network protocol, this monitor will allow Peach Fuzzer to capture the actual data that was sent and received as a pcap. This will help determine what may have caused a fault and could also be useful in trying to create a repro or test case that can aid in creating a fix for the application. Any configuration that is fuzzing a network protocol should typically have this monitor.

To add and configure the monitors:

1. Click **Add Monitor**. In the pop-up, scroll down and select **Gdb**. Click **Ok**.

2. Under **Executable**, enter **/var/targets/mongoose/restful_server** which is the location of Mongoose's launcher. This will allow the monitor to launch the application when fuzzing starts. Do not change any of the other settings for this monitor.

3. Under **Arguments**, enter **-p 4040**.

4. Click **Save**.

5. Click **Add Monitor**. In the pop-up, scroll down and select **Network Capture** under the **Data Collection** section. Click **Ok**.

6. Under **Device**, enter **lo** (for loopback, since Mongoose is listening on the loopback interface)

7. Under **Filter**, enter **port ##TargetPort##** to capture all traffic going to or from the port you specified when you configured the variables in the previous section.

8. Click **Save**.

Configuring the monitors for advanced

The advanced configuration is targeting Mongoose compiled with Debug, Address Sanitizer (ASan), and Optimization level 1. You will therefore want the following monitors:

- **Process Monitor**. This will allow Peach Fuzzer to launch Mongoose. Because Mongoose is compiled with ASan, the Process Monitor will detect the program exited due to an error and gather the output from ASan about the nature of the crash.

  > ⚠️ Do not use the GDB Monitor for applications that are compiled with ASan. It is not compatible with ASan.

- **Network Capture monitor**. Since HTTP is a network protocol, this monitor will allow Peach Fuzzer to capture the actual data that was sent and received as a pcap. This will help determine what may have caused a fault and could also be useful in trying to create a repro or test case that can aid in creating a fix for the application. Any configuration that is fuzzing a network protocol should typically have this monitor.

To add and configure the monitors:

1. Click **Add Monitor**. In the pop-up, scroll down and select **Process**. Click **Ok**.

2. Under **Executable**, enter **/var/targets/advanced/mongoose/restful_server** which is the location of Mongoose's launcher. This will allow the monitor to launch the application when fuzzing starts.

3. Under **Arguments**, enter **-p 4040**.

4. Do not change any of the other settings for this monitor.

5. Click **Save**.

6. Click **Add Monitor**. In the pop-up, scroll down and select **Network Capture** under the **Data Collection** section. Click **Ok**.

7. Under **Device**, enter **lo** (for loopback, since Mongoose is listening on the loopback interface)

8. Under **Filter**, enter **port ##TargetPort##** to capture all traffic going to or from the port you specified when you configured the variables in the previous section.

9. Click **Save**.

Testing your configuration

You should always test your configuration to ensure that Peach Fuzzer is able to fuzz your application. This will run some control iterations to ensure that your application responds as expected to normal input.

1. Click **Test**

2. Click **Begin Test**

3. Once testing is complete, you will see the results. Correct any errors in your Variables or Monitoring if the test is not successful.

4. Once the test has passed, click **Continue**.

You can now fuzz the application.

Follow the steps under Running the test to start testing the application.

4.4. SNMP-Server

This configuration will test an application using SNMP. It has two versions, a basic configuration and an advanced configuration. The basic configuration is compiled only with the Debug option. The advanced configuration is compiled with Address Sanitizer, Debug, and Optimization Level 1 options.

4.4.1. Running the test

To run the pre-configured basic test:

1. Click **Example-SNMPv3_Server-Basic**.

2. Enter a seed value of **47918**.

3. Enter a Stop Test Case value of **10**.

4. Click **Start**.

To run the pre-configured advanced test:

1. Click **Example-SNMPv3_Server-Advanced**.

2. Enter a seed value of **47918**.

3. Enter a Stop Test Case value of **10**

4. Click **Start**.

4.4.2. Configuring the test

These steps will create the same configuration as is in use in the SNMPv3_Server configuration that is already present on the trial instance. The steps are the same for both the basic and advanced configuration except where indicated. To create the configuration:

1. Click Library and then click **SNMPv3_Server**.

2. Enter a name when prompted and optionally a description, then click **Submit**.

Configuring Variables

The first thing you need to configure are the variables that control how Peach Fuzzer will test the application. Both the Basic and Advanced configuration will use the same variables with the same values. Follow these steps to create a working configuration on your trial instance:

1. Click **Configure Variables**.

2. Configure your variables as appropriate for your application. The following should be used for osnmpd running on the trial instance:

    a. Target IPv4 Address: set to **127.0.0.1**

    b. Target Port: set to **161** as osnmpd will also use to this port.

    c. Source Port: set to **162** as osnmpd is configured to listen for messages from this port.

    d. Under **Advanced Configuration**, leave all the defaults as they are acceptable for osnmpd.

    e. Under System Defines, do NOT change any of the values present. These values normally do not require changing.

3. Once all the settings have the desired values, click **Save**.

Configuring Agents

An Agent runs either in-process of Peach Fuzzer or can be installed and run on a remote machine. For this configuration, only a single local agent is required.

1. Click **Monitoring**.

2. Click **Add Agent**.

3. Enter a name. Leave the **Location** setting to the default **local://**.

4. Click **Save**.

Monitoring

The Monitoring data entry screen defines one or more Agents and one or more Monitors for the Pit.

Agents are host processes for monitors and publishers. Local agents can reside on the same machine as Peach, and can control the test environment through monitors and publishers. Remote agents reside on the test target, and can provide remote monitors and publishers.

Saved successfully.   🖫 Save   ➕ Add Agent

⌄   local:// (local)   [⌃] [⌄] [✖]

Name   local

                  Friendly name for your agent

Location   local://

                  URL for the agent. Leave blank for a local agent. For remote agents use the `tcp`
                  scheme. The default agent port is `9001` . Example: `tcp://192.168.48.2:9001`

For more detailed instructions, see Adding an agent.

Configuring the monitors for basic

The basic configuration is targeting osnmpd compiled with Debug enabled. You will therefore want the following monitors:

- **Gdb Monitor**. This will allow Peach Fuzzer to launch osnmpd from within GDB so that GDB attaches to osnmpd. Peach Fuzzer will monitor GDB and attempt to analyze any crashes that GDB detects based on receiving signals from the application being tested.

- **RunCommand Monitor** In this case, osnmpd takes a long time to load. It is therefore necessary to add a means to delay starting the test run until the application has fully loaded. To do this, the RunCommand Monitor can be used to run the bash "sleep" command. Peach Fuzzer must wait both at the start of each session and the start of each iteration in case a fault was found and the target had to be restarted. As a result, two monitors will be added with the same sleep command, one set to **OnStart** and the other set to **OnIterationStart**.

- **Network Capture monitor**. Since SNMP is a network protocol, this monitor will allow Peach Fuzzer to capture the actual data that was sent and received as a pcap. This will help determine what may have caused a fault and could also be useful in trying to create a repro or test case that can aid in creating a fix for the application. Any configuration that is fuzzing a network protocol should typically have this monitor.

- **Syslog Monitor** The application writes entries to the syslog, which may be useful to capture for debugging purposes. In some cases, may also be useful to trigger a fault if a particular syslog message is seen.

To add and configure the monitors:

1. Click **Add Monitor**. In the pop-up, scroll down and select **Gdb**. Click **Ok**.

2. Under **Executable**, enter **/usr/local/bin/snmpd** which is the location of osnmpd's launcher. This will allow the monitor to launch the application when fuzzing starts. Do not change any of the other settings for this monitor.

3. Under **Arguments**, enter **-fd**.

4. Click **Save**.

5. Click **Add Monitor**. In the pop-up, scroll down and select **RunCommand**.

6. Under **Command**, enter **/bin/bash**.

7. Under **Arguments**, enter **-c "sleep 1"**. This will call the bash "sleep" command to sleep for 1 second.

8. Under **When To Trigger**, set **When** to **OnStart** so that this will execute when the test session starts.

9. Click **Save**

10. Click **Add Monitor**. In the pop-up, scroll down and select **RunCommand**.

11. The previous RunCommand monitor will have automatically used the name "Run Command" when it was created unless it was changed. You will need to give this RunCommand Monitor a different name. Here, **Run Command On Iteration Start** is used.

12. Under **Command**, enter **/bin/bash**.

13. Under **Arguments**, enter **-c "sleep 1"**. This will call the bash "sleep" command to sleep for 1 second.

14. Under **When To Trigger**, set **When** to **OnIterationStart** so that this executes when each iteration starts. This is important because if a fault is found, Peach Fuzzer will re-start the target application and therefore needs to delay running the next iteration to give the target application enough time to load.

15. Click **Save**

16. Click **Add Monitor**. In the pop-up, scroll down and select **Network Capture** under the **Data Collection** section. Click **Ok**.

17. Under **Device**, enter **lo** (for loopback, since osnmpd is listening on the loopback interface)

18. Under **Filter**, enter **port ##TargetPort## or port ##SourcePort##** to capture all traffic going to or from the port you specified when you configured the variables in the previous section.

19. Click **Save**.

20. Click **Add Monitor**. In the pop-up, scroll down and select **Syslog**. Click **Ok**.

21. Leave the default values for **Interface** and **Port**.

22. Click **Save**

Configuring the monitors for advanced

The advanced configuration is targeting osnmpd compiled with Debug, Address Sanitizer (ASan), and Optimization level 1. You will therefore want the following monitors:

- **Process Monitor**. This will allow Peach Fuzzer to launch osnmpd. Because osnmpd is compiled with ASan, the Process Monitor will detect the program exited due to an error and gather the output from ASan about the nature of the crash.

⚠️ Do not use the GDB Monitor for applications that are compiled with ASan. It is not compatible with ASan.

- **Network Capture monitor**. Since SNMP is a network protocol, this monitor will allow Peach Fuzzer to capture the actual data that was sent and received as a pcap. This will help determine what may have caused a fault and could also be useful in trying to create a repro or test case that can aid in creating a fix for the application. Any configuration that is fuzzing a network protocol should typically have this monitor.

- **Syslog Monitor** The application writes entries to the syslog, which may be useful to capture for debugging purposes. In some cases, may also be useful to trigger a fault if a particular syslog message is seen.

To add and configure the monitors:

1. Click **Add Monitor**. In the pop-up, scroll down and select **Process**. Click **Ok**.

2. Under **Executable**, enter **/var/targets/advanced/osnmpd/bin/snmpd** which is the location of osnmpd's launcher. This will allow the monitor to launch the application when fuzzing starts.

3. Under **Arguments**, enter **-fd**.

4. Do not change any of the other settings for this monitor.

5. Click **Save**.

6. Click **Add Monitor**. In the pop-up, scroll down and select **Network Capture** under the **Data Collection** section. Click **Ok**.

7. Under **Device**, enter **lo** (for loopback, since osnmpd is listening on the loopback interface)

8. Under **Filter**, enter **port ##TargetPort## or port ##SourcePort##** to capture all traffic going to or from the port you specified when you configured the variables in the previous section.

9. Click **Save**.

10. Click **Add Monitor**. In the pop-up, scroll down and select **Syslog**. Click **Ok**.

11. Leave the default values for **Interface** and **Port**.

12. Click **Save**

Testing your configuration

You should always test your configuration to ensure that Peach Fuzzer is able to fuzz your application. This will run some control iterations to ensure that your application responds as expected to normal input.

1. Click **Test**

2. Click **Begin Test**

3. Once testing is complete, you will see the results. Correct any errors in your Variables or Monitoring if the test is not successful.

4. Once the test has passed, click **Continue**.

You can now fuzz the application.

Follow the steps under Running the test to start testing the application.

Appendix A: Common Tasks

This section includes more detailed instructions on how to perform the more frequent tasks in this document.

A.1. Adding an agent

An Agent runs either in-process of Peach Fuzzer or can be installed and run on a remote machine.

> ℹ️ It is typically not necessary to configure multiple agents for the same machine. A single agent is capable of running multiple different monitors.

A.1.1. Add a local agent

To add a local agent, follow these steps:

1. Click Monitoring

2. Click Add Agent

3. Enter a name for the agent e.g. `Local`. Leave the default value of `local://` for the agent's location.

Monitoring

The Monitoring data entry screen defines one or more Agents and one or more Monitors for the Pit.

Agents are host processes for monitors and publishers. Local agents can reside on the same machine as Peach, and can control the test environment through monitors and publishers. Remote agents reside on the test target, and can provide remote monitors and publishers.

Save **+ Add Agent**

❯ local:// (local)

➡ **Name** local

Friendly name for your agent

Location local://

URL for the agent. Leave blank for a local agent. For remote agents use the `tcp` scheme. The default agent port is `9001`. Example: `tcp://192.168.48.2:9001`

4. Click Save

Monitoring

The Monitoring data entry screen defines one or more Agents and one or more Monitors for the Pit.

Agents are host processes for monitors and publishers. Local agents can reside on the same machine as Peach, and can control the test environment through monitors and publishers. Remote agents reside on the test target, and can provide remote monitors and publishers.

Saved successfully.

➡ **Save** **+ Add Agent**

❯ local:// (local)

Name local

Friendly name for your agent

Location local://

URL for the agent. Leave blank for a local agent. For remote agents use the `tcp` scheme. The default agent port is `9001`. Example: `tcp://192.168.48.2:9001`

A.1.2. Add a remote agent

Assume you have peachagent running on a host with the IP address 192.168.17.145. To add a remote agent to this host, follow these steps:

1. Click Monitoring

2. Click Add Agent

Monitoring

The Monitoring data entry screen defines one or more Agents and one or more Monitors for the Pit.

Agents are host processes for monitors and publishers. Local agents can reside on the same machine as Peach, and can control the test environment through monitors and publishers. Remote agents reside on the test target, and can provide remote monitors and publishers.

3. Enter a name for the agent e.g. `Remote`. Use `tcp://192.168.17.145` to indicate the agent is running on the remote host.

4. Click Save

A.2. Using variables

Peach Fuzzer supports using variables for things such as parameters for monitors and values for other variables. All variables are surrounded by double hash marks e.g. ##. It is generally recommended to use variables whenever possible.

Variables are defined under the **Variables** section of a configuration.

A variable is referred to by its **Key** value in this section. For example, this shows a variable called `TargetPort` that has a value of **20000**.

Figure 1. The TargetPort variable is shown here.

This variable could be used anywhere the Target Port is needed, such as an argument passed to the command of a process monitor or a PCAP expression on a Network Capture Monitor. To use the `TargetPort` variable elsewhere in the configuration, reference it as **##TargetPort##**.

Figure 2. The TargetPort variable is used here to set a Network Capture Monitor to capture all traffic for this configuration. In this example, traffic to and from port 20000 will be captured.

If the vale of a variable changes, it will automatically be applied everywhere the next time the configuration is run.

A.3. Examining faults

Each job represents a single test run using a specific configuration. A job will show information on the duration of the job, the settings used to run that job, and the faults that were found. When you run a test on a configuration, a new job is created and you will see all the relevant information for that job. If you wish to view the information on a previous job, you can select a specific job from the Jobs page.

1. First, navigate to the Jobs page by clicking on the Jobs tab

or by clicking on the Jobs icon

2. Next, select the job you wish to view.

Jobs

Here is a comprehensive list of the fuzzing jobs on this computer.

For any entry, you can perform the following actions:

- Click the 🅟 icon to view the report generated for the fuzzing session.
- Click the ✖ icon to delete the job.

⇕ Name	⇕ Status	⇟ Start Time	⇕ Stop Time	⇕ Test Cases	⇕ Total Faults	Actions
Example-JPG-Advanced	Stopped	6/25/18 5:23 PM	6/25/18 5:23 PM	46	1	🅟 ✖
Example-JPG-Basic	Stopped	6/25/18 5:20 PM	6/25/18 5:21 PM	46	1	🅟 ✖
Example-PNG-Advanced	Stopped	6/25/18 5:19 PM	6/25/18 5:19 PM	11	1	🅟 ✖
Example-PNG-Basic	Stopped	6/25/18 5:19 PM	6/25/18 5:19 PM	11	1	🅟 ✖
Example-MODBUS-TCP Slave	Stopped	6/25/18 5:17 PM	6/25/18 5:17 PM	30	1	🅟 ✖
Example-MODBUS-TCP Master	Stopped	6/25/18 5:14 PM	6/25/18 5:15 PM	50	3	🅟 ✖
Example-SNMPv3 Server-Advanced	Stopped	6/25/18 5:11 PM	6/25/18 5:12 PM	10	5	🅟 ✖
Example-SNMPv3 Server-Basic	Stopped	6/25/18 5:06 PM	6/25/18 5:10 PM	10	5	🅟 ✖
Example-HTTP Server-Advanced	Stopped	6/25/18 5:04 PM	6/25/18 5:05 PM	30	2	🅟 ✖

3. The job you selected will now be displayed. Select a fault to view more information.

Example-SNMPv3 Server-Advanced

This job has completed. 🅟 Click here to view the final report.

6/25/18 5:11PM	00h 01m 06s
Start Time	Running Time
545	47918
Test Cases/Hour	Seed
10	5
Test Cases Executed	Total Faults

✎ Edit Configuration   **↶ Replay Job**

Recent Faults

⇟ #	⇕ When	⇕ Monitor	⇕ Risk	⇕ Major Bucket	⇕ Minor Bucket	Download
9	6/25/18 5:12 PM	Process	heap use after free	1D70A0F1	AE468585	Download
8	6/25/18 5:11 PM	Process	heap-use-after-free	A6468B29	AE468585	Download
7	6/25/18 5:11 PM	Process	heap-use-after-free	98430BA7	AE468585	Download
6	6/25/18 5:11 PM	Process	heap-use-after-free	38C77DA7	AE468585	Download
3	6/25/18 5:11 PM	Process	heap-use-after-free	F204B8C6	AE468585	Download

4. The selected fault will contain detailed information about the type of fault, how it was discovered, and the information collected from the various Monitors that were running when the fault

occurred.

PEACH FUZZER

Home / Jobs / Example-SNMPv3 Server-Advanced / Faults / Test Case: 9

- Dashboard
- Faults (5)
- Metrics
- Help

Test Case: 9

Fault Details

Test Case	9
Assets Archive	Download all fault assets
Reproducible	Yes
Title	heap-use-after-free on address 0x61400000fe40 at pc 0x7f917b1ee935 bp 0x7ffe998a5260 sp 0x7ffe9
When	6/25/18 5:12 PM
Source	Process
Risk	heap-use-after-free
Major Bucket	1D70A0F1
Minor Bucket	AE468585

Tested Fields

Field	Mut:
SNMP:MessageV3.Message.Value.msgGlobalData.Value.msgId.Value	Data
SNMP:MessageV3.Message.Value.msgData.Value.data.Choice.GetRequest-PDU.PDU.Value	Data
SNMP:MessageV3.Message.Value.msgGlobalData.Value.msgId.length	Num
SNMP:MessageV3.Message.Value.msgVersion	Data

Description

```
==3938==ERROR: AddressSanitizer: heap-use-after-free on address 0x61400000fe40 at pc 0x
READ of size 100 at 0x61400000fe40 thread T0
    #0 0x7f917b1ee934 in __asan_memcpy (/usr/lib/x86_64-linux-gnu/libasan.so.2+0x8c934)
    #1 0x416bea in memcpy /usr/include/x86_64-linux-gnu/bits/string3.h:53
    #2 0x416bea in handle_request snmp-agent/agent-incoming.c:215

0x61400000fe40 is located 0 bytes inside of 400-byte region [0x61400000fe40,0x61400000f
freed by thread T0 here:
    #0 0x7f917b1fa2ca in __interceptor_free (/usr/lib/x86_64-linux-gnu/libasan.so.2+0x9
    #1 0x416bda in handle_request snmp-agent/agent-incoming.c:214
    #2 0x202315901525c92  (<unknown module>)

previously allocated by thread T0 here:
    #0 0x7f917b1fa602 in malloc (/usr/lib/x86_64-linux-gnu/libasan.so.2+0x98602)
    #1 0x416bcf in handle_request snmp-agent/agent-incoming.c:212
    #2 0x202315901525c92  (<unknown module>)

SUMMARY: AddressSanitizer: heap-use-after-free ??:0 __asan_memcpy
Shadow bytes around the buggy address:
  0x0c287fff9f70: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
  0x0c287fff9f80: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
  0x0c287fff9f90: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
  0x0c287fff9fa0: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
  0x0c287fff9fb0: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
=>0x0c287fff9fc0: fa fa fa fa fa fa fa fa[fd]fd fd fd fd fd fd fd
  0x0c287fff9fd0: fd fd fd fd fd fd fd fd fd fd fd fd fd fd fd fd
  0x0c287fff9fe0: fd fd fd fd fd fd fd fd fd fd fd fd fd fd fd fd
  0x0c287fff9ff0: fd fd fd fd fd fd fd fd fd fd fa fa fa fa fa fa
  0x0c287fffa000: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
```

Fault Assets

Test Case I/O

Name	
#1 - TX - Initial.GetRequest	
#2 - RX - Initial.Report	
#3 - TX - Initial.GetRequest2	

Monitoring Assets

local

Process (Process)

Name	
description.txt	2.6
stderr.log	2.6

Other Assets

Name	
fault.json	

Original Fault Assets

5. You can download all the captured data by clicking **Download all fault assets**.

A.4. Downloading the final report

Each job contains a final report detailing an overview of all the findings from that job. You can access this report several different ways:

- From the Jobs page, click the **Report** icon for any job in the list to download the report for that job

- If you are already viewing a job, click the link at the top of the page

Example-SNMPv3 Server-Advanced

This job has completed. 📄 Click here to view the final report.

6/25/18 5:11PM Start Time	**00h 01m 06s** Running Time
545 Test Cases/Hour	**47918** Seed
10 Test Cases Executed	**5** Total Faults

✏ Edit Configuration   ↩ Replay Job

Recent Faults

▾ #	⇕ When	⇕ Monitor	⇕ Risk	⇕ Major Bucket	⇕ Minor Bucket	Download
9	6/25/18 5:12 PM	Process	heap-use-after-free	1D70A0F1	AE468585	Download