

# Scalability Problems In Shared Memory

José Alves, Rui Brito

Universidade do Minho

Braga, March 2013

# Index

- 1 Memory Bandwidth and Computational Intensity
- 2 Measure Task Granularity
- 3 Measure Programs Without Synchronization
- 4 Measure Loads Per Task
- 5 Conclusion

The OpenFoam Computational Fluid Dynamics (CFD) software package

- Highly Modular
- By scientists, for scientists
- Fluid dynamics problems, involving chemical reactions, turbulence and heat transfer
- Has many other applications

### Memory Bandwidth

$Mem\_bandwidth = ((PAPI\_LLC\_TCM) \times 64 \times 1 \times 10^{-9}) / exec\_time$   
 $measured\_mem\_bandwidth = (3826100 \times 64 \times 1 \times 10^{-9}) / 0.942194 =$   
 $0.2599 GB/s$   
 $System\_memory\_avail\_bandwidth = 14.8473 GB/s$

### Instructions per cycle

$Total\ Instructions = 211932871$   $Number\ of\ cycles = 1548$   
 $Instruction\ per\ cycle = 136907$

As seen in the December presentation, conv-diff has some locality problems (has it can also be seen by the high number of L1 misses (14037146))

# Scalability Problems In Shared Memory

## Memory Bandwidth and Computational Intensity

- The OpenFoam Computational Fluid Dynamics (CFD) software package
- Highly Modular
    - By scientists, for scientists
    - Fluid dynamics problems, involving chemical reactions, turbulence and heat transfer
    - Has many other applications

### Memory Bandwidth

```
Mem_bandwidth = ((PAPV_LLC_TCM) * 64 * 1 * 10^-9) / mem_time
measured_mem_bandwidth = (3826100 * 64 * 1 * 10^-9) / 0.942194 =
0.2509GB/s
System_memory_avail_bandwidth = 14.8473GB/s
```

### Instructions per cycle

```
Total Instructions = 211032871 Number of cycles = 1548
Instruction per cycle = 136907
```

As seen in the Decamber presentation, conv-diff has some locality problems (has it can also be seen by the high number of L1 misses (14937146)).

## Beat

Vender peixe, basicamente

1. Com alta modularidade entende-se que é composto por várias bibliotecas, e cada função da biblioteca pode ser aplicada a uma grande variedade de tipos de dados. E ser resolvido com solvers e esquemas diferentes




Figure : Roofline for rMBP and conv\_diff

## Task Granularity

In `conv_diff`:

- Only two parallel pieces of code run in parallel
- Large chunks of code
- Thread creation overhead is thus minimized

conv\_diff is unsuitable for this sort of optimization:

### Excessive task synchronization

- Reduction can't be used because values are updated in an array of pointers
- Synchronization must be forced on attributions

## Loads Per Task

- Slight improvement using dynamic and guided scheduling
- Workload distribution also isn't the biggest problem






Figure : Scalability of the parallel region (original implementation)




Figure : Total execution time (original implementation)




Figure : Scalability of the parallel region (without atomic directive)




Figure : Total execution time (without atomic directive)

## Conclusion

- Bad data locality hinders the entire application performance
- Implementation either AoS or SoA is expected to improve performance dramatically
- High chance that locality problem hides other problems
- Maybe what is not a problem now will prove to be so in the near future

# Scalability Problems In Shared Memory

José Alves, Rui Brito

Universidade do Minho

Braga, March 2013

– ? –