Name of Student: Pushkar Sane			
Roll Number: 45		Lab Assignment Number: 9	
Title of Lab Assignment: To implement continuous deployment using Ansible/chef.			
DOP: 28-03-2024		DOS: 03-04-2024	
CO Mapped: CO5	PO Mapped: PO1, PO2, PO PSO1, PSO2	D3, PO5,	Signature:

#### Practical No. 9

Aim: To implement continuous deployment using Ansible/chef.

#### Introduction:

In the world of software development, continuous integration and continuous delivery (CI/CD) pipelines have become essential for efficient and rapid code delivery. CI/CD pipelines automate the process of building, testing, and deploying software, enabling faster product delivery to customers while minimizing manual intervention. In this blog,we will explore the stages of a CI/CD pipeline and demonstrate how to set up these stages using Ansible Playbook.

### Goal of this ansible playbook:

The goal of the Ansible playbook mentioned in this blog is to automate the stages of the CI/CD pipeline using the principles of continuous integration and continuous delivery. By leveraging Ansible, we aim to achieve the following:

- 1. Install Required Software:
  - The playbook will ensure that the necessary software, such as openjdk-8-jdk, git, maven, tomcat9, and tomcat9-admin, is installed on all relevant hosts.
- 2. Continuous Download and Continuous Build:
  - The playbook will download the development code from a specified Git repository, create an artifact from the code, and fetch the artifact to the Ansible controller machine.
- 3. Continuous Deployment and Continuous Testing:
  - The playbook will deploy the artifact into the Tomcat server on the QA server, download Selenium scripts from a specified Git repository, execute the Selenium scripts, and perform continuous testing.
- 4. Continuous Delivery:
  - Finally, the playbook will deploy the artifact into the Tomcat server on the production server, enabling continuous delivery of the application.

By automating these stages with Ansible, we can achieve faster and more reliable software delivery, reduce manual intervention, and ensure consistent deployments across different environments.

### CI/CD stages

A typical CI/CD pipeline includes the following stages. These stages make up the development lifecycle and workflow from source code to production:

#### Source:

- 1. Triggered when a developer commits code changes to a source code repository
- 2. Common triggers include scheduled or user-initiated workflows
- 3. Popular repository tools like GitHub and SVN are used

#### **Build:**

- 1. Creation and compilation of source code
- 2. Compiler gathers code features and dependencies, establishes links, and compiles into a new build
- 3. Quick detection and resolution of issues or conflicts in the build

#### Test:

- 1. Automated testing to validate code accuracy and ensure quality
- 2. Functional and unit testing for new features and functions
- 3. Integration and regression testing to ensure stability of existing features
- 4. Feedback loop for issue analysis and rectification in subsequent builds

#### **Deliver:**


- 1. Approval of codebase from testing stage
- 2. Delivery to a runtime environment for integration, quality assurance, and pre production
- 3. Functional and performance testing conducted on the application

#### Deploy:

- 1. Deployment of code changes to the production environment
- 2. Orchestration of software releases by DevOps teams
- 3. Flexibility to schedule code deployments or target specific user groups
- 4. Rollback mechanism in case of issues

These above stages are created by using Ansible

### **Setting Up the Ansible Environment**



# **Installing Ansible**

- Update the apt repository sudo apt-get update
- Install software-properties-common sudo apt-get install -y software-properties-common
- 3. Add the latest version of Ansible to apt repository sudo apt-add-repository ppa:ansible/ansible
- Install Ansible sudo apt-get install -y ansible
- 5. Update your ansible inventory hosts sudo vim /etc/ansible/host

[webserver] 172.31.30.86

[appserver] 172.31.92.137

[dbserver]

172.31.86.213

To check the version of Ansible ansible –version

### Steps:

Step 1: To perform and install the ansible we need a linux server so to work on the linux server we will download the "Ubuntu 22.04" either from the command prompt or from the Microsoft store.

# Command prompt:


Run Command = wsl -install -d Ubuntu-22.04

```
prasadg@Prasad-Lappy: - X + v
Microsoft Windows [Version 10.0.22631.3374]
(c) Microsoft Corporation. All rights reserved.
C:\Users\prasa>wsl --install -d Ubuntu-22.04
Installing: Ubuntu 22.04 LTS
Ubuntu 22.04 LTS has been installed.
Launching Ubuntu 22.84 LTS...
Installing, this may take a few minutes...
Please create a default UNIX user account. The username does not need to match your Windows username.
For more information visit: https://aka.ms/wslusers
Enter new UNIX username: Prasad1520
adduser: Please enter a username matching the regular expression configured via the NAME_REGEX[_SYSTEM] configuration variable. Use the '--force-badname'
option to relax this check or reconfigure NAME_REGEX.
Enter new UNIX username: prasadg
New password:
Retype new password:
passwd: password updated successfully
Installation successful!
To run a command as administrator (user "root"), use "sudo <command>".
 See "man sudo_root" for details.
Welcome to Ubuntu 22.04.3 LTS (GNU/Linux 5.15.146.1-microsoft-standard-WSL2 x86_64)
 * Documentation: https://help.ubuntu.com
 * Management: https://landscape.canonical.com
 * Support:
                     https://ubuntu.com/advantage
This message is shown once a day. To disable it please create the
/home/prasadg/.hushlogin file.
```

#### Through Microsoft store:

Open the Microsoft store and search for unbuntu and then click on install.

Name: Pushkar Sane MCA / A Roll No. 45



Step 2: Once the installation is successful, open the ubuntu command line and perform below commands.

- 1. apt update (used to update the list of available packages)
- 2. sudo!! (re-run the previous command with sudo privileges)

```
This message is shown once a day. To disable it please create the //home/prasadg/.hushlogin file.

prasadg@Prasad-lappy:=$ pat update
Reading package lists... Done
E: Could not open lock file /var/lib/apt/lists/lock - open (13: Permission denied)
E: Unable to lock directory /var/lib/apt/lists/
W: Problem unlinking the file /var/cache/apt/pkgcache.bin - RemoveCaches (13: Permission denied)
W: Problem unlinking the file /var/cache/apt/pkgcache.bin - RemoveCaches (13: Permission denied)
W: Problem unlinking the file /var/cache/apt/srcpkgcache.bin - RemoveCaches (13: Permission denied)
prasadg@Prasad-lappy:=$ sudo !!
sudo apt update
[sudo] password for prasadg:
Hit:1 http://archive.ubuntu.com/ubuntu jammy-security InRelease
[sudo] password for prasadg:
Hit:1 http://archive.ubuntu.com/ubuntu jammy-security/main and64 Packages [1303 kB]
Get:3 http://archive.ubuntu.com/ubuntu jammy-backports InRelease [109 kB]
Get:4 http://security.ubuntu.com/ubuntu jammy-security/main Translation-en [233 kB]
Get:5 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [271 kB]
Get:8 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [271 kB]
Get:9 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:10 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:10 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:11 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:11 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:11 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:12 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:13 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:13 http://security.ubuntu.com/ubuntu jammy-security/restricted Translation-en [171 kB]
Get:15 http://security.ubuntu.com/ubuntu jammy-
```

Step 3: We need to install the python before installing ansible as it is one of the pre-requisites.

Command: sudo apt install python3 (Installation)
Command: python3 —version (To Check the version)

```
prasadg@Prasad-Lappy:~$ sudo apt install python3
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
python3 is already the newest version (3.10.6-1~22.04).
python3 set to manually installed.
0 upgraded, 0 newly installed, 0 to remove and 98 not upgraded.
prasadg@Prasad-Lappy:~$ python3 --version
Python 3.10.12
prasadg@Prasad-Lappy:~$ |
```

Step4: Use below command to update the ansible packages available in linux

```
prasadg@Prasad-Lappy: - X + v
                                                                                                                                                                                                                                                                                                                                   0 X
   orasadg@Prasad-Lappy:~$
sudo apt update 66 sudo apt install software-properties-common 66 sudo add-apt-repository --ves --update pna:ansible/ansible
ansible/ansible
 Hit:1 http://security.ubuntu.com/ubuntu jammy-security InRelease
Hit:2 http://archive.ubuntu.com/ubuntu jammy InRelease
Hit:3 http://archive.ubuntu.com/ubuntu jammy-updates InRelease
Hit:4 http://archive.ubuntu.com/ubuntu jammy-backports InRelease
  Reading package lists... Done
 Reading package lists... Done
Reading state information... Done
98 packages can be upgraded. Run 'apt list --upgradable' to see them.
Reading package lists... Done
 Reualing Machage (1963... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
python3-software-properties
 The following packages will be upgraded:
python3-software-properties software-properties-common
2 upgraded, θ newly installed, θ to remove and 96 not upgraded.
Need to get 42.9 kB of archives.
 After this operation, 0 B of additional disk space will be used.
 Do you want to continue? [Y/n] Y
Get:1 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 software-properties-common all 0.99.22.9 [14.1 k8]
Get:2 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 python3-software-properties all 0.99.22.9 [28.8 kB]
  Fetched 42.9 kB in 1s (51.6 kB/s)
Fetched 42.9 kB in 1s (51.6 kB/s)
(Reading database ... 24208 files and directories currently installed.)
Preparing to unpack .../software-properties-common_0.99.22.9_all.deb ...
Unpacking software-properties-common (0.99.22.9) over (0.99.22.8) ...
Preparing to unpack .../python3-software-properties_0.99.22.9_all.deb ...
Unpacking python3-software-properties (0.99.22.9) over (0.99.22.8) ...
Setting up python3-software-properties (0.99.22.9) ...
Setting up software-properties-common (0.99.22.9) ...
Processing triggers for man-db (2.10.2-1) ...
Processing triggers for dbus (1.12.20-2ubuntu#.1) ...
Repository: 'deb https://ppa.launchpadcontent.net/ansible/ansible/ubuntu/ jammy main'
Description:
  Ansible is a radically simple IT automation platform that makes your applications and systems easier to deploy. Avoid mriting scripts or custom code to depl
  oy and update your applications- automate in a language that approaches plain English, using SSH, with no agents to install on remote systems.
  http://ansible.com/
  If you face any issues while installing Ansible PPA, file an issue here:
```

# Step 5: Install ansible with below commands.

```
rasadg@Prasad-Lappy:~$
                                                             y:-$ sudo ant install ansible
      Reading package lists... Done
    Building dependency tree... Done
    Reading state information... Done
     The following additional packages will be installed:
         ansible-core python-babel-localedata python3-babel python3-bcrypt python3-certifi python3-chardet python3-idna python3-jinja2 python3-jmespath python3-kerberos python3-markupsafe python3-nacl python3-ntlm-auth python3-packaging python3-paramiko python3-requests python3-requests-kerberos python3-requests-ntlm python3-resolvelib python3-tz python3-unlib3 python3-minrm python3-xmltodict sshpass
     Suggested packages:
python-jinja2-doc python-macl-doc python3-gssapi python3-invoke python3-openssl python3-socks python-requests-doc
      The following NEW packages will be installed:
         ansible ansible-core python-babel-localedata python3-babel python3-bcrypt python3-certifi python3-chardet python3-idna python3-jinja2 python3-jmespath
         python3-kerberos python3-markupsafe python3-nacl python3-ntlm-auth python3-packaging python3-paramiko python3-requests python3-requests-kerberos python3-requests-ntlm python3-resolvelib python3-tz python3-wilib3 python3-wiltodict sshpass
   0 upgraded, 25 newly installed, 0 to remove and 96 not upgraded.
Need to get 23.6 MB of archives.
After this operation, 225 MB of additional disk space will be used.
After this operation, 225 MB of additional disk space will be used.

Do you want to continue? [Y/n] Y

Get:1 http://archive.ubuntu.com/ubuntu jammy/main amd64 python-babel-localedata all 2.8.0+dfsg.1-7 [4982 kB]

Get:2 https://ppa.launchpadcontent.net/ansible/ansible/ubuntu jammy/main amd64 ansible-core all 2.16.5-1ppa-jammy [10.5 MB]

Get:3 https://ppa.launchpadcontent.net/ansible/ansible/ubuntu jammy/main amd64 ansible all 9.4.0-1ppa-jammy [10.5 MB]

Get:4 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 python3-ta all 2022.1-1ubuntu0.22.04.1 [30.7 kB]

Get:5 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-babel all 2.8.0+dfsg.1-7 [85.1 kB]

Get:6 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-markupsafe amd64 2.0.1-2build1 [12.7 kB]

Get:8 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-packaging all 21.3-1 [30.7 kB]

Get:9 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-resolvelib all 0.8.1-1 [23.6 kB]

Get:10 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-resolvelib all 0.8.1-1 [23.6 kB]

Get:11 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-certifi all 2020.6.20-1 [150 kB]

Get:11 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-chardet all 4.0.0-1 [98.0 kB]

Get:12 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-idna all 3.3-1 [49.3 kB]

Get:13 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-jespath all 0.10-1 [21.7 kB]

Get:14 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-macpath all 0.10-1 [21.7 kB]

Get:15 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-macpath all 0.10-1 [21.7 kB]

Get:16 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-macpath all 0.10-1 [21.7 kB]

Get:16 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-macpath all 0.10-1 [21.7 kB]

Get:16 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-macpath all 0.10-1 [21.7 kB]

Get:16 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-macpath all 0.10-1 [21.7 kB]

Get:16 http://archive.ubu
    Get:17 http://archive.ubuntu.com/ubuntu jammy/main amd64 python3-bcrypt amd64 3.2.0-1build1 [32.7 kB]
Get:18 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 python3-paramiko all 2.9.3-0ubuntu1.2 [134 kB]
    Get:19 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 python3-urllib3 all 1.26.5-1-explubuntu8.1 [98.2 k8]
   Get:20 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 python3-requests all 2.25.1+dfsg-Zubuntu0.1 [48.8 kB]
Get:21 http://archive.ubuntu.com/ubuntu jammy/universe amd64 python3-requests-kerberos all 0.12.0-2 [11.9 kB]
Get:22 http://archive.ubuntu.com/ubuntu jammy/universe amd64 python3-requests-ntlm all 1.1.0-1.1 [6160 B]
```


Step 6: Check the ansible version.


```
prasadg@Prasad-Lappy: ~
prasadg@Prasad-Lappy:~$ ansible --version
ansible [core 2.16.5]
  config file = /etc/ansible/ansible.cfg
  configured module search path = ['/home/prasadg/.ansible/plugins/modules', '/usr
/share/ansible/plugins/modules']
  ansible python module location = /usr/lib/python3/dist-packages/ansible
  ansible collection location = /home/prasadg/.ansible/collections:/usr/share/ansi
ble/collections
  executable location = /usr/bin/ansible
  python version = 3.10.12 (main, Jun 11 2023, 05:26:28) [GCC 11.4.0] (/usr/bin/py
thon3)
  jinja version = 3.0.3
  libyaml = True
prasadg@Prasad-Lappy:~$
```

Step 7: Create a new directory and follow the below steps to create new files.


```
X
          prasadg@Prasad-Lappy: ~
 prasadg@Prasad-Lappy:~$ mkdir tuts
prasadg@Prasad-Lappy:*$ cd tuts/
prasadg@Prasad-Lappy:~/tuts$ mkdir -p ansible1
prasadg@Prasad-Lappy:~/tuts$ cd ansbile1/
 -bash: cd: ansbile1/: No such file or directory
prasadg@Prasad-Lappy:~/tuts$ cd ansible1/
prasadg@Prasad-Lappy:~/tuts/ansible1$ vi inventory
prasadg@Prasad-Lappy:~/tuts/ansible1$ ls
inventory playbooks
prasadg@Prasad-Lappy:~/tuts/ansiblel$ mkdir files
prasadg@Prasad-Lappy:~/tuts/ansiblel$ cd
 prasadg@Prasad-Lappy:~$ ls -la
total 44
drwxr-x--- 7 prasadg prasadg 4096 Mar 31 10:12
drwxr-xr-x 3 root root 4096 Mar 31 09:49
drwxr-xr-x 3 prasadg prasadg 4096 Mar 31 10:03
-rw-r---- 1 prasadg prasadg 220 Mar 31 09:49 .bash_lc
-rw-r---- 1 prasadg prasadg 3771 Mar 31 09:49 .bashrc
drwx----- 2 prasadg prasadg 4096 Mar 31 09:49 .cache
-rw-r---- 1 prasadg prasadg 0 Mar 31 09:49 .motd_sh
                                                                                         .bash_logout
                                                         0 Mar 31 09:49 .motd_shown
 -rw-r--r-- 1 prasadg prasadg 807 Mar 31 09:49 .profile
 -rw-r--r-- 1 prasadg prasadg
                                                          0 Mar 31 09:50 .sudo_as_admin_successful
-rw------ 1 prasadg prasadg 954 Mar 31 10:09 .viminfo
drwxr-xr-x 3 prasadg prasadg 4096 Mar 31 10:12 .vscode-remote-containers
drwxr-xr-x 5 prasadg prasadg 4096 Mar 31 10:12 .vscode-server
drwxr-xr-x 3 prasadg prasadg 4096 Mar 31 10:06 tuts
prasadg@Prasad-Lappy:-$ ls -lh /etc/ansible.cfg
ls: cannot access '/etc/ansible.cfg': No such file or directory
```

Step 8: To create a playbook and other files we will use vscode. Open the vscode and install the extension for WSL.






Click on "Connect to WSL using Distro" then select the name of your ubuntu server.



Step 10: Once connected click on the open folder. And select the directory which we created earlier.




Step 11: Create a folder name Inventory and create a file named "Inventory.ini" Code:

[webservers]
web1.example.com
web2.example.com

[dbservers]
one.example.com
two.example.com
three.example.com

Step 12: Create a ansible configuration file with below command \$ ansible-config init > ansible.cfg



# Step 13: Create a Ansible Playbook with .yml extension

--- - name: Update web servers

hosts: webservers remote\_user: root

### tasks:

- name: Ensure apache is at the latest version

ansible.builtin.yum:

name: httpd state: latest

- name: Write the apache config file

ansible.builtin.template:

src: /srv/httpd.j2

dest: /etc/httpd.conf

- name: Update db servers

hosts: databases remote\_user: root

# tasks:

- name: Ensure postgresql is at the latest version

ansible.builtin.yum: name: postgresql

state: latest

- name: Ensure that postgresql is started

ansible.builtin.service:

name: postgresql

state: started

Name: Pushkar Sane MCA / A Roll No. 45

Conclusion: In this practical we learned about the Ansible tool and how to create a playbook in it.