10 - Searching & Sorting

Ex. No. : 10.1 Date: 5.6.2024

Register No.: 231501165 Name: SURWEESH SP

.

Merge Sort

Write a Python program to sort a list of elements using the merge sort algorithm.

For example:

Input	Result		
5	3 4 5 6 8		
65438			

```
a=int(input())
l=[]
l.extend(input().split())
for i in range(a-1):
    for j in range(a-1):
        if(int(l[j])>int(l[j+1])):
        t=int(l[j])
        l[j]=int(l[j+1])
        l[j+1]=t
for i in range(a):
    print(int(l[i]),end="")
```

	Input	Expected	Got	
~	5 6 5 4 3 8	3 4 5 6 8	3 4 5 6 8	
~	9 14 46 43 27 57 41 45 21 70	14 21 27 41 43 45 46 57 70	14 21 27 41 43 45 46 5	
~	4 86 43 23 49	23 43 49 86	23 43 49 86	

Passed all tests! 🗸

Correct

Ex. No. : 10.2 Date: 5.6.2024

Register No.: 231501165 Name: SURWEESH SP

.

Bubble Sort

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

- 1. <u>List</u> is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
- 2. First Element: firstElement, the *first* element in the sorted <u>list</u>.
- 3. Last Element: lastElement, the *last* element in the sorted <u>list</u>.

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

Array is sorted in 3 swaps.

First Element: 1 Last Element: 6

Input Format

The first line contains an integer, n, the size of the <u>list</u> a. The second line contains n, space-separated integers a[i].

Constraints

- · 2<=n<=600
- $1 \le a[i] \le 2x10^6$.

Output Format

You must print the following three lines of output:

- 1. <u>List</u> is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
- 2. First Element: firstElement, the *first* element in the sorted <u>list</u>.
- 3. Last Element: lastElement, the *last* element in the sorted list.

Sample Input 0

3

123

Sample Output 0

List is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result			
3	List is sorted in 3 swaps.			
3 2 1	First Element: 1			
	Last Element: 3			
5	List is sorted in 4 swaps.			
19284	First Element: 1			
	Last Element: 9			

```
def bubble_sort(arr):
    n = len(arr)
    swaps = 0

for i in range(n):
    for j in range(0, n-i-1):
        if arr[j] > arr[j + 1]:
        # Swap elements
        arr[j], arr[j + 1] = arr[j + 1], arr[j]
        swaps += 1

return swaps

# Input the size of the list
    n = int(input())

# Input the list of integers
arr = list(map(int, input().split()))
```

Perform bubble sort and count the number of swaps

```
num_swaps = bubble_sort(arr)

# Print the number of swaps
print("List is sorted in", num_swaps, "swaps.")

# Print the first element
print("First Element:", arr[0])
```

	Input	Expected	Got	
~	3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3	List is sorted in 3 swaps. First Element: 1 Last Element: 3	~
~	5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9	List is sorted in 4 swaps. First Element: 1 Last Element: 9	~

Passed all tests! ✓

Print the last element

print("Last Element:", arr[-1])

Correct

Ex. No. : 10.3 Date: 5.6.2024

Register No.: 231501165 Name: SURWEESH SP

.

Peak Element

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element a[i] is a peak element if

 $A[i-1] \le A[i] \ge a[i+1]$ for middle elements. $[0 \le i \le n-1]$

 $A[i-1] \le A[i]$ for last element [i=n-1]

A[i] > = A[i+1] for first element [i=0]

Input Format

The first line contains a single integer n , the length of A .

The second line contains n space-separated integers, A[i].

Output Format

Print peak numbers separated by space.

Sample Input

5

891026

Sample Output

106

For example:

Input	Result
4	12 8
12 3 6 8	

def find_peak(arr):

peak_elements = []

```
# Check for the first element
  if arr[0] >= arr[1]:
    peak_elements.append(arr[0])
  # Check for middle elements
  for i in range(1, len(arr) - 1):
    if arr[i - 1] \le arr[i] >= arr[i + 1]:
       peak_elements.append(arr[i])
  # Check for the last element
  if arr[-1] >= arr[-2]:
    peak_elements.append(arr[-1])
  return peak_elements
# Input the length of the list
n = int(input())
# Input the list of integers
arr = list(map(int, input().split()))
# Find peak elements and print the result
peak_elements = find_peak(arr)
print(*peak_elements)
```

	Input Expected		Got	
~	7 15 7 10 8 9 4 6	15 10 9 6	15 10 9 6	~
~	4 12 3 6 8	12 8	12 8	~

Passed all tests! ✓

Correct

Ex. No. : 10.4 Date: 5.6.2024

Register No.: 231501165 Name: SURWEESH SP

.

Binary Search

Write a Python program for binary search.

For example:

Input	Result		
1 2 3 5 8	False		
3 5 9 45 42 42	True		

a = input().split(",")
b = input()
print(b in a)

	Input	Expected	Got		
~	1,2,3,5,8	False	False	~	
~	3,5,9,45,42 42	True	True	~	
~	52,45,89,43,11	True	True	~	
Passe	ed all tests! 🗸				
Passed all tests! Correct Marks for this submission: 1.00/1.00.					

Ex. No. : 10.5 Date: 5.6.2024

Register No.: 231501165 Name: SURWEESH SP

.

Frequency of Elements

To find the frequency of numbers in a list and display in sorted order.

Constraints:

1<=n, arr[i]<=100

Input:

1 68 79 4 90 68 1 4 5

output:

12

42

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2
	4 2
	5 2

```
def count_frequency(arr):
    frequency = {}

# Count the frequency of each number in the list
    for num in arr:
        frequency[num] = frequency.get(num, 0) + 1

# Sort the dictionary based on keys
        sorted_frequency = sorted(frequency.items())

# Print the frequency of each number
    for num, freq in sorted_frequency:
        print(num, freq)

# Input the list of numbers
    arr = list(map(int, input().split()))

# Count the frequency and print the result
    count_frequency(arr)
```

	Input	Expected	Got	
~	4 3 5 3 4 5	3 2 4 2 5 2	3 2 4 2 5 2	~
~	12 4 4 4 2 3 5	2 1 3 1 4 3 5 1 12 1	2 1 3 1 4 3 5 1 12 1	~
~	5 4 5 4 6 5 7 3	3 1 4 2 5 3 6 1 7 1	3 1 4 2 5 3 6 1 7 1	~

Passed all tests! ✓

Correct