

VIAVI

Cable Id : Cable
Location A : Loc A
Job ID : 12

Fiber Id/Number : Fiber 24
Location B : Loc B
Technician Id :

SmartOTDR (S/N 92589)

E100AS (S/N 92589)

Calibration Date : 29/09/2025

Date : 26/11/2025 14:41 (UTC+0)

Test Setup


OTDR Laser Pw Range Acq Time IOR Scatter Coefficient
EXPERT 1310nm 30ns 5km 10.0s 1.46750(G652 G657) -79.0 dB
Alarms

Thresholds

None


Summary

Filename Laser nm Link Loss dB Link ORL dB Fiber End Km Direction Avg Loss dB/Km Event Alarms
24 f 09 no kusmi gp to olt .sor 1310 0.700 38.04 1.493 Loc A -> Loc B 0.469 4



A : 0.000km 0.316 dB
B : 0.659km 0.149 dB

A-B : 0.659km 0.254 dB/Km

0.168 dB

Event	Distance	Loss	Reflect.	Slope	Section	T. Loss
	Km	dB	dB	dB/km	Km	dB
1	0.726	0.159		0.600	0.726	0.269
2	0.925	-0.272		0.267	0.199	0.481
3	1.004	0.316			0.079	0.223
4	1.493	>-16.48	0.328	0.488		0.700