R PROGRAMMING

LAB EXPERIMENTS RECORD

Data Warehousing & Data Mining (DWDM) Lab

20 Experiments | Complete with Aim, Program, Output & Result

TABLE OF CONTENTS

Exp No.	Experiment Title	Page
1	ADDITION	3
2	SUBTRACTION	5
3	MULTIPLICATION	7
4	DIVISION	9
5	ODD OR EVEN	11
6	MEAN, MEDIAN, MODE	13
7	SUMMARY	15
8	GREATEST AMONG THREE NUMBERS	17
9	IQR (INTERQUARTILE RANGE)	19
10	QUANTILE	21
11	MID RANGE	23
12	Z-SCORE NORMALIZATION	25
13	MIN, MAX, MEAN, MINMAX NORMALIZATION	27
14	BAR PLOT AND HORIZONTAL BAR	29
15	BOX PLOT	31
16	HISTOGRAM	33
17	CORRELATION ANALYSIS	35
18	SCATTER PLOT	37
19	LINEAR REGRESSION	39
20	MULTIPLE REGRESSION	41

EXPERIMENT - 1

ADDITION


AIM:

To prove the program for addition using R-tool.

PROGRAM:

```
num1 <- as.integer(readline(prompt = "enter the first number: "))
num2 <- as.integer(readline(prompt = "enter the second number: "))
num3 <- num1 + num2
print(paste("Result of Addition:", num3))
```

OUTPUT:



RESULT:

Thus, the basic program for addition is executed successfully.

— ✦ —

EXPERIMENT - 2

SUBTRACTION


AIM:

To prove the program for subtraction using R-tool.

PROGRAM:

```
num1 <- as.integer(readline(prompt = "enter the first number: "))
num2 <- as.integer(readline(prompt = "enter the second number: "))
num3 <- num1 - num2
print(paste("Result of Subtraction:", num3))
```

OUTPUT:



RESULT:

Thus, the basic program for subtraction is executed successfully.

— ✦ —

EXPERIMENT - 3

MULTIPLICATION


AIM:

To prove the program for multiplication using R-tool.

PROGRAM:

```
num1 <- as.integer(readline(prompt = "enter the first number: "))
num2 <- as.integer(readline(prompt = "enter the second number: "))
num3 <- num1 * num2
print(paste("Result of Multiplication:", num3))
```

OUTPUT:



RESULT:

Thus, the basic program for multiplication is executed successfully.

— ✦ —

EXPERIMENT - 4

DIVISION


AIM:

To prove the program for division using R-tool.

PROGRAM:

```
num1 <- as.integer(readline(prompt = "enter the first number: "))
num2 <- as.integer(readline(prompt = "enter the second number: "))
num3 <- num1 / num2
print(paste("Result of Division:", num3))
```

OUTPUT:



RESULT:

Thus, the basic program for division is executed successfully.

— ✦ —

EXPERIMENT - 5

ODD OR EVEN


AIM:

To write the program to check whether a number is odd or even using R-tool.

PROGRAM:

```
num <- as.integer(readline(prompt = "enter a number: "))
if ((num %% 2) == 0) {
  print("number is even")
} else {
  print("number is odd")
}
```

OUTPUT:



RESULT:

Thus, the program for odd or even was executed successfully.

— ✦ —

EXPERIMENT - 6

MEAN, MEDIAN, MODE


AIM:

To write the program for mean, median and mode using R-tool.

PROGRAM:

```
names <- c("siri", "mahi", "chiru")
age <- c(23, 24, 25)
marks <- c(88, 78, 25)
df <- data.frame(names, age, marks)
cat("--- MEAN ---\n"); print(mean(df$age))
cat("--- MEDIAN ---\n"); print(median(df$age))
cat("--- MODE ---\n"); print(mode(df$age))
write.csv(df, "datafr.csv", row.names = FALSE)
```

OUTPUT:



RESULT:

Thus, the central tendency measures (mean, median, mode) are executed successfully.

— ✦ —

EXPERIMENT - 7

SUMMARY


AIM:

To write the program for summary statistics using R-tool.

PROGRAM:

```
names <- c("siri", "mahi", "chiru")
age <- c(23, 24, 25)
marks <- c(88, 78, 25)
df <- data.frame(names, age, marks)
cat("--- SUMMARY OF AGE ---\n")
print(summary(df$age))
write.csv(df, "datafr.csv", row.names = FALSE)
```

OUTPUT:



RESULT:

Thus, the central tendency and measure of dispersion (summary) is executed successfully.

— ✦ —

EXPERIMENT - 8

GREATEST AMONG THREE NUMBERS


AIM:

To write the program for the greatest among three numbers using R-tool.

PROGRAM:

```
x <- as.integer(readline(prompt = "Enter first number : "))
y <- as.integer(readline(prompt = "Enter second number : "))
z <- as.integer(readline(prompt = "Enter third number : "))
if (x > y && x > z) {
  print(paste("Greatest is :", x))
} else if (y > z) {
  print(paste("Greatest is :", y))
} else {
  print(paste("Greatest is :", z))
}
```

OUTPUT:



RESULT:

Thus, the greatest among three numbers was executed successfully.

—✦—

EXPERIMENT - 9

IQR (INTERQUARTILE RANGE)


AIM:

To write the program for central tendency and data dispersion measures (IQR) using R-tool.

PROGRAM:

```
names <- c("siri", "mahi", "chiru")
age <- c(23, 24, 25)
marks <- c(88, 78, 25)
df <- data.frame(names, age, marks)
cat("--- IQR OF AGE ---\n")
print(IQR(df$age))
write.csv(df, "datafr.csv", row.names = FALSE)
```

OUTPUT:



RESULT:

Thus, the program for central tendency and data dispersion measures (IQR) was executed successfully.

— ✦ —

EXPERIMENT - 10

QUANTILE


AIM:

To write the program for central tendency and data dispersion measures (Quantile) using R-tool.

PROGRAM:

```
names <- c("siri", "mahi", "chiru")
age <- c(23, 24, 25)
marks <- c(88, 78, 25)
df <- data.frame(names, age, marks)
cat("--- QUANTILE OF AGE ---\n")
print(quantile(df$age))
write.csv(df, "datafr.csv", row.names = FALSE)
```

OUTPUT:



RESULT:

Thus, the program for central tendency and data dispersion measures (Quantile) was executed successfully.

— ✦ —

EXPERIMENT - 11

MID RANGE


AIM:

To write the program for central tendency and data dispersion measures (Mid Range) using R-tool.

PROGRAM:

```
names <- c("siri", "mahi", "chiru")
age <- c(23, 24, 25)
marks <- c(88, 78, 25)
df <- data.frame(names, age, marks)
mid_range <- (max(df$age) + min(df$age)) / 2
cat("--- MID RANGE OF AGE ---\n")
print(paste("Mid Range:", mid_range))
write.csv(df, "datafr.csv", row.names = FALSE)
```

OUTPUT:



RESULT:

Thus, the program for central tendency and data dispersion measures (Mid Range) was executed successfully.

—✦—

EXPERIMENT - 12

Z-SCORE NORMALIZATION


AIM:

To write the program for Z-score normalization using R-tool.

PROGRAM:

```
diabetest1 <- read.csv("diabetes.csv")
A <- c(diabetest1$Age)
Mean <- mean(A)
Std <- sd(A)
Zscore <- (A - Mean) / Std
cat("Mean of Age:", Mean, "\n")
cat("Standard Deviation:", Std, "\n")
print(Zscore)
```

OUTPUT:



RESULT:

Thus, the Z-score normalization using R-tool was executed successfully.

— ✦ —

EXPERIMENT - 13

MIN, MAX, MEAN, MINMAX NORMALIZATION


AIM:

To write the program for the minimum, maximum, mean and min-max normalization using R-tool.

PROGRAM:

```
diabetest1 <- read.csv("diabetes.csv")
A <- c(diabetest1$Age)
Mean <- mean(A); cat("MEAN:", Mean, "\n")
Minimum <- min(diabetest1$Age); cat("MINIMUM:", Minimum, "\n")
Maximum <- max(diabetest1$Age); cat("MAXIMUM:", Maximum, "\n")
MinMax <- (A - Minimum) / (Maximum - Minimum)
cat("--- MINMAX NORMALIZATION ---\n"); print(MinMax)
```

OUTPUT:



RESULT:

Thus, the program for min, max, mean and min-max normalization was executed successfully.

— ✦ —

EXPERIMENT - 14

BAR PLOT AND HORIZONTAL BAR


AIM:

To draw the bar plot and horizontal bar using R-tool.

PROGRAM:

```
a <- c(55, 67, 89, 80, 90)
barplot(a, main = "Vertical Bar Plot", col = "steelblue",
        xlab = "Index", ylab = "Values")
barplot(a, horiz = TRUE, main = "Horizontal Bar Plot",
        col = "salmon", xlab = "Values", ylab = "Index")
```

OUTPUT:



RESULT:

Thus, the bar plot and horizontal bar plot were executed successfully.

— ✦ —

EXPERIMENT - 15

BOX PLOT


AIM:

To draw the histogram and box plot using R-tool.

PROGRAM:

```
names <- c("siri", "chru", "loki")
age <- c(23, 24, 25)
marks <- c(88, 78, 25)
df <- data.frame(names, age, marks)
hist(df$age, main = "Histogram of Age", col = "lightblue", xlab = "Age")
boxplot(df$age, main = "Box Plot of Age", col = "gold", ylab = "Age")
```

OUTPUT:



RESULT:

Thus, the histogram and box plot were executed successfully.

— ✦ —

EXPERIMENT - 16

HISTOGRAM


AIM:

To draw the histogram plot using R-tool.

PROGRAM:

```
a <- c(55, 67, 89, 80, 90)
hist(a, main = "Histogram Plot", col = "lightgreen",
     xlab = "Values", ylab = "Frequency")
```

OUTPUT:



RESULT:

Thus, the histogram plot was executed successfully.

— ✦ —

EXPERIMENT - 17

CORRELATION ANALYSIS


AIM:

To write the program for correlation analysis (Chi-Square Test) using R-tool.

PROGRAM:

```
diabetest1 <- read.csv("diabetes.csv")
tab <- table(diabetest1$Age, diabetest1$Insulin)
cat("--- CONTINGENCY TABLE ---\n"); print(tab)
cat("--- CHI-SQUARE TEST ---\n")
print(chisq.test(tab))
```

OUTPUT:



RESULT:

Thus, the correlation analysis (Chi-Square Test) was executed successfully.

— ✦ —

EXPERIMENT - 18

SCATTER PLOT


AIM:

To draw the scatter plot using R-tool.

PROGRAM:

```
set.seed(9)
x <- rnorm(1000)
y <- rnorm(1000)
smoothScatter(y - x, main = "Smooth Scatter Plot (y - x)")
smoothScatter(x, y, main = "Smooth Scatter Plot (x vs y)")
```

OUTPUT:



RESULT:

Thus, the scatter plot was executed successfully.

— ✦ —

EXPERIMENT - 19

LINEAR REGRESSION


AIM:

To write the program for linear regression using R-tool.

PROGRAM:

```
diabetes <- read.csv("diabetes.csv")
Relation <- lm(diabetes$BloodPressure ~ diabetes$Age)
print(summary(Relation))
plot(diabetes$Age, diabetes$BloodPressure, col = "darkgreen", pch = 16,
     main = "Linear Regression Analysis",
     xlab = "Age", ylab = "BloodPressure")
abline(lm(diabetes$BloodPressure ~ diabetes$Age), col = "red", lwd = 2)
```

OUTPUT:



RESULT:

Thus, the linear regression program was executed successfully.

— ✦ —

EXPERIMENT - 20

MULTIPLE REGRESSION


AIM:

To write the program for multiple regression using R-tool.

PROGRAM:

```
diabetes <- read.csv("diabetes.csv")
Input <- diabetes[, c("Age", "BloodPressure", "Glucose")]
Model <- lm(Age ~ BloodPressure + Glucose, data = Input)
print(Model)
A <- coef(Model)[1]; print(A)
xBloodPressure <- coef(Model)[2]
yGlucose <- coef(Model)[3]
print(xBloodPressure); print(yGlucose)
y <- A + xBloodPressure + yGlucose; print(y)
```

OUTPUT:



RESULT:

Thus, the multiple regression program was executed successfully.

— ✦ —