



NumPy Joining Array

[< Previous](#)[Next >](#)

Joining NumPy Arrays

Joining means putting contents of two or more arrays in a single array.

In SQL we join tables based on a key, whereas in NumPy we join arrays by axes.

We pass a sequence of arrays that we want to join to the `concatenate()` function, along with the axis. If axis is not explicitly passed, it is taken as 0.

Example

Join two arrays

```
import numpy as np

arr1 = np.array([1, 2, 3])

arr2 = np.array([4, 5, 6])

arr = np.concatenate((arr1, arr2))

print(arr)
```

[Try it Yourself »](#)

Example

Join two 2-D arrays along rows (axis=1):

```
import numpy as np

arr1 = np.array([[1, 2], [3, 4]])

arr2 = np.array([[5, 6], [7, 8]])

arr = np.concatenate((arr1, arr2), axis=1)

print(arr)
```

[Try it Yourself »](#)

Joining Arrays Using Stack Functions

Stacking is same as concatenation, the only difference is that stacking is done along a new axis.

We can concatenate two 1-D arrays along the second axis which would result in putting them one over the other, ie. stacking.

We pass a sequence of arrays that we want to join to the `stack()` method along with the axis. If axis is not explicitly passed it is taken as 0.

Example

```
import numpy as np

arr1 = np.array([1, 2, 3])

arr2 = np.array([4, 5, 6])

arr = np.stack((arr1, arr2), axis=1)

print(arr)
```

Stacking Along Rows

NumPy provides a helper function: `hstack()` to stack along rows.

Example

```
import numpy as np

arr1 = np.array([1, 2, 3])

arr2 = np.array([4, 5, 6])

arr = np.hstack((arr1, arr2))

print(arr)
```

Stacking Along Columns

NumPy provides a helper function: `vstack()` to stack along columns.

Example

```
import numpy as np

arr1 = np.array([1, 2, 3])

arr2 = np.array([4, 5, 6])

arr = np.vstack((arr1, arr2))
```

```
print(arr)
```

[Try it Yourself »](#)

Stacking Along Height (depth)

NumPy provides a helper function: `dstack()` to stack along height, which is the same as depth.

Example

```
import numpy as np

arr1 = np.array([1, 2, 3])

arr2 = np.array([4, 5, 6])

arr = np.dstack((arr1, arr2))

print(arr)
```

[Try it Yourself »](#)

Test Yourself With Exercises

Exercise:

Use a correct NumPy method to join two arrays into a single array.

```
arr1 = np.array([1, 2, 3])
```

```
arr2 = np.array([4, 5, 6])
```

```
arr = np.          ((arr1, arr2))
```

[Submit Answer »](#)

[Start the Exercise](#)


[◀ Previous](#)

[Next ▶](#)



NEW

We just launched
W3Schools videos



[Explore now](#)

COLOR PICKER





Get certified
by completing
a Python
course today!



Get started

CODE GAME



Play Game



Report Error

Spaces

Pro

Get Certified

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
Angular Reference
jQuery Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

Get Certified

HTML Certificate
CSS Certificate

JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

