







HTML CSS







Python Scope

Previous

Next >

A variable is only available from inside the region it is created. This is called **scope**.

Local Scope

A variable created inside a function belongs to the *local scope* of that function, and can only be used inside that function.

Example

A variable created inside a function is available inside that function:

```
def myfunc():
    x = 300
    print(x)

myfunc()
```

Try it Yourself »

Function Inside Function

As explained in the example above, the variable x is not available outside the function, but it is available for any function inside the function:

Example

The local variable can be accessed from a function within the function:

```
def myfunc():
    x = 300
    def myinnerfunc():
        print(x)
    myinnerfunc()

myfunc()
```

Try it Yourself »

ADVERTISEMENT

Global Scope

A variable created in the main body of the Python code is a global variable and belongs to the global scope.

Global variables are available from within any scope, global and local.

Example

A variable created outside of a function is global and can be used by anyone:

```
x = 300

def myfunc():
   print(x)
```

```
myfunc()
print(x)

Try it Yourself »
```

Naming Variables

If you operate with the same variable name inside and outside of a function, Python will treat them as two separate variables, one available in the global scope (outside the function) and one available in the local scope (inside the function):

Example

The function will print the local x, and then the code will print the global x:

```
x = 300

def myfunc():
    x = 200
    print(x)

myfunc()

print(x)
```

Try it Yourself »

Global Keyword

If you need to create a global variable, but are stuck in the local scope, you can use the global keyword.

The global keyword makes the variable global.

Example

If you use the global keyword, the variable belongs to the global scope:

```
def myfunc():
    global x
    x = 300

myfunc()

print(x)
```

Try it Yourself »

Also, use the global keyword if you want to make a change to a global variable inside a function.

Example

To change the value of a global variable inside a function, refer to the variable by using the global keyword:

```
x = 300

def myfunc():
    global x
    x = 200

myfunc()

print(x)
```

Try it Yourself »

Previous

Next >



NEW

We just launched W3Schools videos



Explore now

COLOR PICKER









Get certified by completing a Python course today!



Get started

CODE GAME



Play Game

ADVERTISEMENT

ADVERTISEMENT

Report Error

Spaces

Pro

Get Certified

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
c++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference

Angular Reference jQuery Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

FORUM | ABOUT

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.

