



# NumPy Set Operations

[< Previous](#)[Next >](#)

## What is a Set

A set in mathematics is a collection of unique elements.

Sets are used for operations involving frequent intersection, union and difference operations.

## Create Sets in NumPy

We can use NumPy's `unique()` method to find unique elements from any array. E.g. create a set array, but remember that the set arrays should only be 1-D arrays.

## Example

Convert following array with repeated elements to a set:

```
import numpy as np

arr = np.array([1, 1, 1, 2, 3, 4, 5, 5, 6, 7])

x = np.unique(arr)

print(x)
```

## Finding Union

To find the unique values of two arrays, use the `union1d()` method.

### Example

Find union of the following two set arrays:

```
import numpy as np

arr1 = np.array([1, 2, 3, 4])
arr2 = np.array([3, 4, 5, 6])

newarr = np.union1d(arr1, arr2)

print(newarr)
```

Try it Yourself »

---

## Finding Intersection

To find only the values that are present in both arrays, use the `intersect1d()` method.

### Example

Find intersection of the following two set arrays:

```
import numpy as np

arr1 = np.array([1, 2, 3, 4])
arr2 = np.array([3, 4, 5, 6])

newarr = np.intersect1d(arr1, arr2, assume_unique=True)
```

```
print(newarr)
```

[Try it Yourself »](#)

**Note:** the `intersect1d()` method takes an optional argument `assume_unique`, which if set to True can speed up computation. It should always be set to True when dealing with sets.

---

## Finding Difference

To find only the values in the first set that is NOT present in the seconds set, use the `setdiff1d()` method.

### Example

Find the difference of the set1 from set2:

```
import numpy as np

set1 = np.array([1, 2, 3, 4])
set2 = np.array([3, 4, 5, 6])

newarr = np.setdiff1d(set1, set2, assume_unique=True)

print(newarr)
```

[Try it Yourself »](#)

**Note:** the `setdiff1d()` method takes an optional argument `assume_unique`, which if set to True can speed up computation. It should always be set to True when dealing with sets.

---

# Finding Symmetric Difference

To find only the values that are NOT present in BOTH sets, use the `setxor1d()` method.

## Example

Find the symmetric difference of the set1 and set2:

```
import numpy as np

set1 = np.array([1, 2, 3, 4])
set2 = np.array([3, 4, 5, 6])

newarr = np.setxor1d(set1, set2, assume_unique=True)

print(newarr)
```


Try it Yourself »

**Note:** the `setxor1d()` method takes an optional argument `assume_unique`, which if set to True can speed up computation. It should always be set to True when dealing with sets.

[< Previous](#)[Next >](#)


NEW

We just launched  
W3Schools videos



Explore now

COLOR PICKER



Get certified  
by completing  
a Python  
course today!



Get started

CODE GAME



[Play Game](#)



[Report Error](#)

[Spaces](#)

[Pro](#)

[Get Certified](#)

## Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

## Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)

[SQL Reference](#)  
[Python Reference](#)  
[W3.CSS Reference](#)  
[Bootstrap Reference](#)  
[PHP Reference](#)  
[HTML Colors](#)  
[Java Reference](#)  
[Angular Reference](#)  
[jQuery Reference](#)

## Top Examples

[HTML Examples](#)  
[CSS Examples](#)  
[JavaScript Examples](#)  
[How To Examples](#)  
[SQL Examples](#)  
[Python Examples](#)  
[W3.CSS Examples](#)  
[Bootstrap Examples](#)  
[PHP Examples](#)  
[Java Examples](#)  
[XML Examples](#)  
[jQuery Examples](#)

## Get Certified

[HTML Certificate](#)  
[CSS Certificate](#)  
[JavaScript Certificate](#)  
[Front End Certificate](#)  
[SQL Certificate](#)  
[Python Certificate](#)  
[PHP Certificate](#)  
[jQuery Certificate](#)  
[Java Certificate](#)  
[C++ Certificate](#)  
[C# Certificate](#)  
[XML Certificate](#)

---

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie](#) and [privacy policy](#).

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.

