



NumPy Filter Array

[< Previous](#)[Next >](#)

Filtering Arrays

Getting some elements out of an existing array and creating a new array out of them is called *filtering*.

In NumPy, you filter an array using a *boolean index list*.

A *boolean index list* is a list of booleans corresponding to indexes in the array.

If the value at an index is **True** that element is contained in the filtered array, if the value at that index is **False** that element is excluded from the filtered array.

Example

Create an array from the elements on index 0 and 2:

```
import numpy as np

arr = np.array([41, 42, 43, 44])

x = [True, False, True, False]

newarr = arr[x]
```

```
print(newarr)
```

Try it Yourself »

The example above will return `[41, 43]`, why?

Because the new array contains only the values where the filter array had the value `True`, in this case, index 0 and 2.

Creating the Filter Array

In the example above we hard-coded the `True` and `False` values, but the common use is to create a filter array based on conditions.

Example

Create a filter array that will return only values higher than 42:

```
import numpy as np

arr = np.array([41, 42, 43, 44])

# Create an empty list
filter_arr = []

# go through each element in arr
for element in arr:
    # if the element is higher than 42, set the value to True, otherwise
    False:
    if element > 42:
        filter_arr.append(True)
    else:
        filter_arr.append(False)

newarr = arr[filter_arr]

print(filter_arr)
print(newarr)
```

ADVERTISEMENT

Example

Create a filter array that will return only even elements from the original array:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6, 7])

# Create an empty list
filter_arr = []

# go through each element in arr
for element in arr:
    # if the element is completely divisible by 2, set the value to True,
    # otherwise False
    if element % 2 == 0:
        filter_arr.append(True)
    else:
        filter_arr.append(False)

newarr = arr[filter_arr]

print(filter_arr)
print(newarr)
```

Creating Filter Directly From Array

The above example is quite a common task in NumPy and NumPy provides a nice way to tackle it.

We can directly substitute the array instead of the iterable variable in our condition and it will work just as we expect it to.

Example

Create a filter array that will return only values higher than 42:

```
import numpy as np

arr = np.array([41, 42, 43, 44])

filter_arr = arr > 42

newarr = arr[filter_arr]

print(filter_arr)
print(newarr)
```

Try it Yourself »

Example

Create a filter array that will return only even elements from the original array:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6, 7])

filter_arr = arr % 2 == 0

newarr = arr[filter_arr]
```

```
print(filter_arr)
print(newarr)
```

Try it Yourself »

◀ Previous


Next ▶



ADVERTISEMENT

NEW

We just launched
W3Schools videos



Explore now

COLOR PICKER



Get certified
by completing
a Python
course today!



Get started

CODE GAME



[Play Game](#)

ADVERTISEMENT

ADVERTISEMENT



[Report Error](#)

[Spaces](#)

[Pro](#)

[Get Certified](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)

[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

